
**Gas cylinders — Cylinder valves with
integrated pressure regulators —
Specification and type testing**

*Bouteilles à gaz — Robinets de bouteilles avec détendeur intégré —
Spécifications et essais de type*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 22435:2007](#)

<https://standards.iteh.ai/catalog/standards/iso/e0c0c274-8001-480d-9323-4f4583377297/iso-22435-2007>



Reference number
ISO 22435:2007(E)

© ISO 2007

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 22435:2007](#)

<https://standards.iteh.ai/catalog/standards/iso/e0c0c274-8001-480d-9323-4f4583377297/iso-22435-2007>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

| | |
|--|-----------|
| Foreword | v |
| Introduction | vi |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions. | 2 |
| 4 Symbols and terminology | 4 |
| 5 Design requirements | 4 |
| 5.1 General | 4 |
| 5.2 Description | 5 |
| 5.3 Materials | 5 |
| 5.4 Pressure indicators | 6 |
| 5.5 Filling connection | 6 |
| 5.6 Cylinder connection | 6 |
| 5.7 Outlet connection | 6 |
| 5.8 Outlet pressure for acetylene | 7 |
| 5.9 Flow control valve (flow controller) | 7 |
| 5.10 Pressure adjusting device | 7 |
| 5.11 Filtration | 7 |
| 5.12 Main shut-off valve | 7 |
| 5.13 Flow and pressure performance for regulators without flow metering devices | 7 |
| 5.14 Pressure relief valve | 8 |
| 5.15 Leakage | 8 |
| 5.16 Mechanical strength | 8 |
| 5.17 Resistance to ignition | 9 |
| 5.18 Requirement for VIPR with flow metering devices | 9 |
| 5.19 Constructional requirements | 9 |
| 5.20 Valve operating device | 9 |
| 6 Test methods | 10 |
| 6.1 General | 10 |
| 6.2 Documentation | 11 |
| 6.3 Number of test samples | 11 |
| 6.4 Test sequence | 12 |
| 6.5 Test method for mechanical strength | 13 |
| 6.6 Test methods for flow and pressure performance for regulators without flow metering devices | 13 |
| 6.7 Test method for relief valve | 21 |
| 6.8 Pressure retention of the low-pressure side of the pressure regulator | 21 |
| 6.9 Test method for flowmeter mechanical strength | 22 |
| 6.10 Test method for accuracy of VIPR with flowmeter | 22 |
| 6.11 Test method for accuracy of VIPR with flowmeter and with fixed orifices | 22 |
| 6.12 Test methods for leakage | 22 |
| 6.13 Test method for operating and loosening torques | 23 |
| 6.14 Test method for endurance of the main shut-off mechanism | 23 |
| 6.15 Test method for endurance of the non-return valve | 25 |
| 6.16 Test method for ignition | 25 |
| 6.17 Test method for resistance to acetylene decomposition | 26 |
| 6.18 Test method for flame resistance of the valve operating device | 26 |
| 7 Marking | 29 |

| | | |
|---|---------------------------|-----------|
| 8 | Instructions | 29 |
| Annex A (normative) Valve impact test | 30 | |
| Annex B (informative) Endurance test | 32 | |
| Bibliography | 36 | |

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 22435:2007](#)

<https://standards.iteh.ai/catalog/standards/iso/e0c0c274-8001-480d-9323-4f4583377297/iso-22435-2007>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22435 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

iTeh Standards
[**\(https://standards.iteh.ai\)**](https://standards.iteh.ai)
Document Preview

[ISO 22435:2007](#)

<https://standards.iteh.ai/catalog/standards/iso/e0c0c274-8001-480d-9323-4f4583377297/iso-22435-2007>

Introduction

Cylinder valves with integrated pressure regulators are used to reduce the high cylinder pressure to a lower pressure suitable for use.

These functions cover a wide range of inlet and outlet pressures and flows which require specific design characteristics. It is important that the operating characteristics of these valves be specified and tested in a defined manner.

Such valves are more complicated than conventional cylinder valves yet subject to the same environmental and transportation conditions. These conditions should be borne in mind at the design and development stage.

This International Standard pays particular attention to

- suitability of materials,
- safety (mechanical strength, safe relief of excess pressure and resistance to ignition),
- gas-specificity,
- cleanliness,
- testing,
- identification, and
- information supplied.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 22435:2007](#)

<https://standards.iteh.ai/catalog/standards/iso/e0c0c274-8001-480d-9323-4f4583377297/iso-22435-2007>

Gas cylinders — Cylinder valves with integrated pressure regulators — Specification and type testing

1 Scope

This International Standard applies to cylinder valves with integrated pressure regulators (VIPR) intended to be fitted to gas cylinders that convey compressed, liquefied or dissolved gases.

This International Standard is not intended for medical applications (see ISO 10524-3). Further, additional specific requirements for valves fitted with safety valves and bursting discs (see EN 14513) and for valves fitted with residual pressure valves (see ISO 15996) are not covered by this International Standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2503:1998, *Gas welding equipment — Pressure regulators for gas cylinders used in welding, cutting and allied processes up to 300 bar*

ISO 3253, *Gas welding equipment — Hose connections for equipment for welding, cutting and allied processes*

<https://standards.iteh.ai>

[Document Preview](https://standards.iteh.ai)

[http://ISO 5145, Cylinder valve outlets for gases and gas mixtures — Selection and dimensioning](https://standards.iteh.ai)

ISO 5171, *Pressure gauges used in welding, cutting and allied processes*

ISO 7289, *Quick-action couplings with shut-off valves for gas welding, cutting and allied processes*

ISO 7291:1999, *Gas welding equipment — Pressure regulators for manifold systems used in welding, cutting and allied processes up to 300 bar*

ISO/TR 7470, *Valve outlets for gas cylinders — List of provisions which are either standardized or in use*

ISO 9090, *Gas tightness of equipment for gas welding and allied processes*

ISO 10156, *Gases and gas mixtures — Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets*

ISO 10920, *Gas cylinders — 25E taper thread for connection of valves to gas cylinders — Specification*

ISO 11114-1, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 1: Metallic materials*

ISO 11114-2, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 2: Non-metallic materials*

ISO 11114-3, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 3: Autogenous ignition test in oxygen atmosphere*

ISO 11117, *Gas cylinders — Valve protection caps and valve guards for industrial and medical gas cylinders — Design, construction and tests*

ISO 13341, *Transportable gas cylinders — Fitting of valves to gas cylinders*

ISO 15001, *Anaesthetic and respiratory equipment — Compatibility with oxygen*

ISO 15996, *Gas cylinders — Residual pressure valves — General requirements and type testing*

EN 13918, *Gas welding equipment — Integrated flowmeter regulators used on cylinders for welding, cutting and allied processes — Classification, specification and tests*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 adjustable pressure regulator
device that has been provided with a means of operator adjustment of the delivery pressure under normal use

3.2 closure pressure
 P_4
stabilized outlet pressure, one minute after cessation of the flow, from a pressure regulator by which the flow has been set to a standard discharge

3.3 cylinder valve with integrated pressure regulator
VIPR

device intended to be permanently fitted to a gas cylinder connection and comprising a shut-off valve system and pressure reduction system

3.4 filling port
point on the device through which the cylinder is filled

3.5 flow characteristic
variation of the outlet pressure in relation to the rate of flow from zero to maximum capacity flow of the pressure regulator with the inlet pressure remaining constant

3.6 flow gauge
device that measures pressure and that is calibrated in units of flow

3.7 flowmeter
device that measures and indicates the flow of a specific gas or gas mixture

3.8 hysteresis
lagging of the outlet pressure (effect) when the flow (cause) is varied so that at a constant inlet pressure the values of outlet pressure measured with increasing flow do not coincide with the values of outlet pressure measured with decreasing flow

3.9**maximum discharge flow** Q_{\max} maximum flow which is delivered by the pressure regulator at the rated outlet pressure, p_2 , and at the test inlet pressure, p_3 **3.10****orifice**

restriction of known cross-section that delivers a constant flow of gas when supplied with gas at a constant upstream pressure

3.11**pre-set pressure regulator**

pressure regulator that has not been provided with a means of operator adjustment of the delivery pressure under normal use

3.12**pressure characteristic**

variation of the outlet pressure with inlet pressure under specific initial flow conditions

3.13**pressure regulator**

device for regulation of a generally variable inlet pressure to an outlet pressure as constant as possible

3.14**main shut-off mechanism**

shut-off valve between the gas cylinder and the regulating mechanism of the device

3.15**rated outlet pressure** P_2 downstream pressure for the standard discharge, Q_1 , specified in the instructions for use**3.16****pressure relief valve**[ISO 22435:2007](#)

device designed to release excess pressure from the outlet side of the pressure regulator at a pre-set value

3.17**secondary operating mechanism**

means of setting the outlet discharge flow between zero and maximum

3.18**standard discharge** Q_1 flowrate, specified in the instructions for use for which the pressure regulator is designed to maintain a rated outlet pressure, p_2 , at test inlet pressure, p_3 **3.19****test inlet pressure** p_3 inlet pressure at which the standard discharge of the pressure regulator, Q_1 , is measured and which is twice the rated outlet pressure, p_2 , plus 100 kPa, i.e. $p_3 = (2 p_2 + 100 \text{ kPa})$ **3.20****test outlet pressure** p_5 highest or lowest value of the outlet pressure resulting from a variation in the inlet pressure between p_1 and p_3 at previously adjusted conditions p_1, p_2, Q_1

3.21**valve test pressure** p_{vt} for compressed gases, $p_{vt} = 1,2 \times p_w$;for liquefied gases and dissolved gases under pressure (e.g. acetylene), p_{vt} is at least equal to the minimum test pressure of the cylinder quoted in the relevant transportation regulation for that gas or gas group**3.22****working pressure** p_w

settled pressure, at a uniform temperature of 15 °C, for a full gas cylinder

NOTE 1 For compressed gases, p_w in this International Standard corresponds to p_1 in ISO 2503.

NOTE 2 This definition applies only to compressed gases and not to liquefied gases and dissolved gases (acetylene).

4 Symbols and terminology

The symbols used for the physical characteristics are given in Table 1.

Table 1 — Notations, symbols and designations

| Symbol | Designation |
|------------|--|
| p_w | Working pressure |
| p_{vt} | Valve test pressure |
| p_1 | Inlet pressure |
| p_2 | Rated outlet pressure |
| p_3 | Test inlet pressure, $(2 p_2 + 100)$ kPa |
| p_4 | Closure pressure |
| p_{4max} | Maximum closure pressure |
| p_5 | Test outlet pressure |
| Q_1 | Standard discharge |
| Q_{max} | Maximum discharge |
| Q_{RV} | Discharge of the relief valve |
| R | Coefficient of pressure increase upon closure, $(p_4 - p_2)/p_2$ |
| i | Irregularity coefficient, $(p_5 - p_2)/p_2$ |

5 Design requirements**5.1 General**

VIPR shall operate satisfactorily over a range of service temperatures, from – 20 °C to + 65 °C. The range may be extended for short periods (e.g. during filling). Where higher or lower service temperatures are required for longer periods, the purchaser shall specify accordingly.

VIPR shall be capable of withstanding the mechanical stresses or chemical attack they may experience during intended service, e.g. during storage, valving into cylinders, filling processes, transportation and end use of the cylinder.

5.2 Description

This International Standard does not prescribe the components that the VIPR shall comprise.

A cylinder valve with integrated pressure regulator typically comprises

- a body,
- an inlet connection to the cylinder,
- a main shut-off mechanism (to isolate the device from the high pressure gas in the cylinder),
- a filling connection (it may be fitted with a non-return valve or an isolating valve),
- the pressure regulating mechanism(s),
- a pressure relief valve on the low pressure side of the regulating mechanism(s) and
- an outlet connection (for the end user).

A VIPR can also be fitted with

- a secondary operating mechanism to set the outlet flow,

NOTE Some devices can have both mechanisms, some others can have only one.

- a pressure relief device to protect the cylinder,
- a siphon tube,
- a screwed plug or cap on the outlet and/or the filling connection,
- an excess flow limiting device,
- a means of preventing the ingress of atmospheric air,
- a residual pressure retaining device (see ISO 15996),
- pressure indicator(s) on the high and/or low pressure sides of devices,
- a flow control device,
- a flow indicator (e.g. flowmeter or flow gauge) and
- filter(s).

5.3 Materials

Metallic and non-metallic materials in contact with the gas shall be chemically and/or physically compatible with the gas (see ISO 11114-1 and ISO 11114-2).

Because of the risk of forming explosive acetylides, VIPR for acetylene may be manufactured from copper-based alloys only if the copper content does not exceed 70 % (by mass). The manufacturer shall not use any procedure resulting in copper enrichment of the surface. For the same reasons, silver content of alloys shall be limited for acetylene VIPR. The acceptable limit varies between 43 % (by mass) and 50 % (by mass), but in no case exceeds 50 % (by mass).

Ignition resistance in oxygen or other highly oxydising gases (see ISO 10156) of non-metallic materials and lubricants shall have been established by an appropriate test procedure (see ISO 11114-3). Where, during the filling of gas mixtures containing oxygen (even if the final mixture is less oxydising than air), there is the possibility that high pressure oxygen comes into contact with such material, the purchaser shall specify accordingly.

Non-metallic sealing material for use with air, oxygen and oxygen-enriched gases shall be capable of withstanding an ageing sensitivity test.

5.4 Pressure indicators

Devices other than pressure gauges may be used to indicate pressure or flow. Pressure indicators shall be of the fail-safe type, i.e. the operator shall not be injured in case of failure.

If pressure gauges are used, they shall comply with the safety features of ISO 5171. This applies also to pressure gauges used to indicate flow.

5.5 Filling connection

The filling connection shall be designed to handle the intended service conditions. It shall comply with ISO 5145, the relevant national standards (see ISO/TR 7470) or be a proprietary connection. If the filling connection is separate to the outlet connection and is not equipped with a non-return valve or isolating valve, it shall be provided with a pressure-tight device, e.g. a valve pressure plug or a cap which can be operated or removed only by the use of a special tool. Where applicable, such a device shall be designed to vent gas before becoming disengaged.

If the filling connection is made through the outlet connection, it shall be designed so that it does not interfere with a gas withdrawal connection made in accordance with the relevant national or International Standard.

The filling connection non-return valve, if fitted, shall comply with the requirements of 5.15 after testing as described in 6.15.

5.6 Cylinder connection

[ISO 22435:2007](#)

<https://standards.iteh.ai/catalog/standards/iso/e0c0c274-8001-480d-9323-4f4583377297/iso-22435-2007>

The connection to the cylinder shall be in accordance with international or national standards, (e.g. 25E, see ISO 10920).

If other connectors are used, evidence shall be provided by the manufacturer that an equivalent mechanical strength is achieved.

5.7 Outlet connection

The connection shall be either

- a) a proprietary fitting; if a quick connection is used, it shall comply with the endurance tests of ISO 7289 or
- b) a welding hose connection (e.g. ISO 3253 for a threaded connection or ISO 7289 for a quick connection or other regional or national standards) or
- c) a high pressure cylinder valve outlet connection (e.g. ISO 5145).

If a residual pressure valve is fitted to the outlet connection, it shall be designed so that it does not interfere with a gas withdrawal connection made in accordance with the relevant standard.