



SLOVENSKI STANDARD SIST ISO 15673:2011

01-maj-2011

Smernice za poenostavljeno projektiranje armirano betonskih konstrukcij stavb

Guidelines for the simplified design of structural reinforced concrete for buildings

Lignes directrices pour la conception simplifiée du béton armé pour les structures de bâtiments

(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ISO 15673:2005**

<https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011>

ICS:

91.080.40 Betonske konstrukcije Concrete structures

SIST ISO 15673:2011

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 15673:2011

<https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011>

INTERNATIONAL STANDARD

ISO
15673

First edition
2005-07-15

Guidelines for the simplified design of structural reinforced concrete for buildings

*Lignes directrices pour la conception simplifiée du béton armé pour
les structures de bâtiments*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 15673:2011](https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011)

[https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-
ec987cbcf833/sist-iso-15673-2011](https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011)



Reference number
ISO 15673:2005(E)

© ISO 2005

ISO 15673:2005(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 15673:2011

<https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Symbols and abbreviated terms	12
4.1 Symbols	12
4.2 Abbreviated terms	17
5 Design and construction procedure	18
5.1 Procedure	18
5.2 Design documentation	20
6 General provisions	20
6.1 Limitations	20
6.2 Limit states	22
6.3 Ultimate limit state design format	22
6.4 Serviceability limit state design format	24
7 Specific provisions	24
7.1 Structural systems and layout	24
7.2 Actions (loads)	29
7.3 General reinforced concrete requirements	31
7.4 Floor system	69
7.5 Solid slabs supported on girders, beams, joists or structural concrete walls	79
7.6 Girders, beams and joists	106
7.7 Columns	131
7.8 Lateral force resistance	143
7.9 Structural concrete walls	157
7.10 Foundations	165
Annex A (normative) Equivalent equations for material factors	168

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15673 was prepared by Technical Committee ISO/TC 71, *Concrete, reinforced concrete and pre-stressed concrete*, Subcommittee SC 5, *Simplified design standard for concrete structures*.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 15673:2011](https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011)

<https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011>

Introduction

The aim of this International Standard is to provide rules for the design and construction of low-rise concrete structures of small floor area to be built in the less developed areas of the world. The document is developed for countries that do not have existing national standards. This document shall not be used in place of a national standard unless specifically considered and accepted by the national standard body or other appropriate regulatory organization. The design rules are based in simplified worldwide-accepted strength models. The document is self-contained; therefore actions (loads) and simplified analysis procedures are included, as well as minimum acceptable construction practice guidelines.

The minimum dimensional provisions contained in this document are intended to account for undesirable side effects that will require more sophisticated analysis and design procedures. Material and construction provisions are aimed at site-mixed concrete as well as ready-mixed concrete, and steel of the minimum available strength grades.

The earthquake-resistance provisions are included to account for the fact that numerous underdeveloped regions of the world occur in earthquake-prone areas. The earthquake resistance is based upon the employment of structural concrete walls (shear walls) that limit the lateral deformations of the structure and provide for its lateral strength.

The document contains provisions that can be modified by the national standards body due to local design and construction requirements and practices. The specifications that can be modified are indicated using ["boxed values"]. The authorities in each member country are expected to review the "boxed values" and may substitute alternative definitive values for these elements for use in the national application of the document.

A great effort was made to include self-explanatory tables, graphics, and design aids to simplify the use of the document and provide foolproof procedures. Notwithstanding, the economic implications of the conservatism inherent in approximate procedures as a substitution to sound and experienced engineering should be a matter of concern to the designer who employs the document, and to the owner who hires him.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 15673:2011

<https://standards.iteh.ai/catalog/standards/sist/64f84012-14a0-4289-ad65-ec987cbcf833/sist-iso-15673-2011>

Guidelines for the simplified design of structural reinforced concrete for buildings

1 Scope

This International Standard applies to the planning, design and construction of structural reinforced concrete structures to be used in new low-rise buildings with restricted occupancy, number of stories, and area. The purpose of this International Standard is to provide a registered civil engineer or architect with sufficient information to design the reinforced-concrete structural framing of a low-rise building that complies with these limitations; see 6.1. The rules of design as set forth in the present document are simplifications of the more elaborate requirements.

This document may be used as an alternative to the development of a national concrete building code, or equivalent document, in countries where no national design codes themselves are available, or as an alternative to the national concrete building code in countries where it is specifically considered and accepted by the national standard body or other appropriate regulatory organization.

Although the provisions contained in this document were established to produce, when properly employed, a reinforced concrete structure with an appropriate margin of safety, this International Standard is not a substitute for sound and experienced engineering. In order for the resulting structure designed in accordance with these provisions to attain the intended margin of safety, the document must be used as a whole, and alternative procedures should be employed only when explicitly permitted by the provisions. The minimum dimensional provisions as prescribed in the document replace in most cases, more elaborate procedures such as those prescribed in the national building code, and an eventual economic impact is realized from the simplicity of the procedures prescribed.

The professional performing the structural design in accordance with this International Standard should meet the legal requirements for structural designers in the country of adoption and have training and a minimum of appropriate knowledge of structural mechanics, statics, strength of materials, structural analysis, and reinforced concrete design and construction.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 679, *Methods of testing cements — Determination of strength*

ISO 680, *Cement — Test methods — Chemical analysis*

ISO 863, *Cement — Test methods — Pozzolanicity test for pozzolanic cements*

ISO 2103, *Loads due to use and occupancy in residential and public buildings*

ISO 2633, *Determination of imposed floor loads in production buildings and warehouses*

ISO 3010, *Basis for design of structures — Seismic actions on structures*

ISO/TR 3956, *Principles of structural fire-engineering design with special regard to the connection between real fire exposure and the heating conditions of the standard fire-resistance test (ISO 834)*

ISO 15673:2005(E)

ISO 4354, *Wind actions on structures*

ISO 4355, *Bases for design of structures — Determination of snow loads on roofs*

ISO 6274, *Concrete — Sieve analysis of aggregates*

ISO 6782, *Aggregates for concrete — Determination of bulk density*

ISO 6783, *Coarse aggregates for concrete — Determination of particle density and water absorption — Hydrostatic balance method*

ISO 6935-1, *Steel for the reinforcement of concrete — Part 1: Plain bars*

ISO 6935-2, *Steel for the reinforcement of concrete — Part 2: Ribbed bars*

ISO 6935-3:1992, (as amended in 2000), *Steel for the reinforcement of concrete — Part 3: Welded fabric*

ISO 7033, *Fine and coarse aggregates for concrete — Determination of the particle mass-per-volume and water absorption — Pycnometer method*

ISO 9194, *Bases for design of structures — Actions due to the self-weight of structures, non-structural elements and stored materials — Density*

ISO 9597, *Cements — Test methods — Determination of setting time and soundness*

ISO 10144, *Certification scheme for steel bars and wires for the reinforcement of concrete structures*

STANDARD PREVIEW
(standards.iteh.ai)

3 Terms and definitions

SIST ISO 15673:2011

For the purposes of this document, the following terms and definitions apply.

https://standards.iteh.ai/catalog/standards/sist/15673-2011/iso-15673-2011
ec987cbcf833/sist-iso-15673-2011

3.1**acceleration of gravity**

g

acceleration produced by gravity at the surface of earth

NOTE For the purposes of this International Standard, its value can be approximated as $g \approx [10] \text{ m/s}^2$.

3.2**admixture**

material other than water, aggregate, or hydraulic cement, used as an ingredient of concrete and added to concrete before or during its mixing to modify its properties

3.3**aggregate**

granular material, such as sand, gravel, crushed stone, and iron blast-furnace slag, used in conjunction with a cementing medium to form a hydraulic cement concrete or mortar

3.4**anchorage**

device used to anchor a non-structural element to the structural framing

3.5**bar diameter, nominal**

approximate diameter of a steel reinforcing bar, often used as a class designation

NOTE The nominal diameter for deformed bars is usually taken as the diameter of a plain bar having the same area.

3.6**base of structure**

level at which earthquake motions are assumed to be imparted to a building

NOTE This level does not necessarily coincide with the ground level.

3.7**beam**

horizontal, or nearly horizontal, structural member supported at one (such as a cantilever) or more points, but not throughout its length, transversely supporting a load, and subjected primarily to flexure

3.8**bearing capacity of the soil**

maximum permissible stress on the foundation soil that provides adequate safety against bearing failure of the soil, or settlement of the foundation of such magnitude as to impair the structure

NOTE The value of the bearing capacity of the soil is defined at the working stress level.

3.9**bending moment**

product of a force and the distance to a particular axis, producing bending effects in a structural element

3.10**boundary element**

portion along a wall edge strengthened by longitudinal and transverse reinforcement

NOTE A boundary element does not necessarily require an increase in thickness of the wall.

3.11**building**

structure, usually enclosed by walls and a roof, constructed to provide support or shelter intended for occupancy

3.12**caisson**

foundation pile of large diameter, built partly or totally above ground and sunk below ground usually by digging out the soil inside

3.13**cement**

material as specified in the corresponding referenced International Standards, which, when mixed with water, has hardening properties, used either in concrete or by itself

3.14**column**

vertical member used primarily to support axial compressive loads

3.15**collector element**

element that serves to transmit the inertia forces within the diaphragm to members of the lateral-force resisting system

3.16**combined footing**

footing that transmits to the supporting soil the load carried by several columns or structural concrete walls

3.17**compression reinforcement**

reinforcement provided to resist compression stresses induced by flexural moments acting on the member section

ISO 15673:2005(E)**3.18****concrete**

mixture of Portland cement and any other hydraulic cement, fine aggregate, coarse aggregate, and water, with or without admixtures

3.19**concrete mix design**

choice and proportioning of the ingredients of concrete

3.20**confinement hook**

hook on a stirrup, hoop, or crosstie having a bend of not less than 135° with a six-diameter (but not less than 75 mm) extension that engages the longitudinal reinforcement and projects into the interior of the stirrup or hoop

3.21**confinement stirrup****tie**

closed stirrup, tie or continuously wound spiral

NOTE A closed stirrup or tie can be made up of several reinforcement elements, each having a confinement hook at both ends. A continuously wound spiral should have a confinement hook at both ends.

3.22**corrosion**

gradual removal or weakening of metal from its surface that requires the presence of humidity and oxygen, and is helped by the presence of other materials

3.23**cover**

〈concrete〉 thickness of concrete between the surface of any reinforcing bar and the nearest face of the concrete member

3.24**crosstie**

continuous reinforcing bar having a 135° hook at one end and a hook of not less than 90° at least a six-diameter extension at the other end

NOTE The hooks normally engage peripheral longitudinal bars. The 90° hooks of two successive crossties engaging the same longitudinal bars are normally alternated end for end.

3.25**curing**

keeping the concrete damp for a period of time, usually several days, starting from the moment it is cast, in order to provide the cement with enough water to harden and attain the intended strength

NOTE Appropriate curing will greatly reduce shrinkage, increase strength of concrete, and normally reduces surface cracking. Curing time will depend on the temperature and the relative humidity of the surrounding air, the amount of wind, the direct sunlight exposure, the type of concrete mix employed, and other factors.

3.26**curtain wall**

wall that is part of the façade or enclosure of the building

3.27**deformed reinforcement**

steel reinforcement that has deformations in its surface to increase its bond to the concrete

NOTE The following steel reinforcement are normally considered deformed reinforcement under this International Standard: deformed reinforcing bars, deformed wire, welded plain wire fabric, and welded deformed wire fabric conforming to the appropriate International Standards.

3.28**depth of member***h*

vertical size of a cross-section of a horizontal structural element

3.29**design load combination**

combination of factored loads and forces as specified in this International Standard

3.30**design strength**product of the nominal strength multiplied by a strength reduction factor, ϕ **3.31****development length**

length of embedded reinforcement required to develop the design strength of reinforcement at a critical section

3.32**development length**

〈bar with a standard hook〉 the shortest distance between the critical section (where the strength of the bar is to be developed) and a tangent to the outer edge of the 90° or 180° hook

3.33**differential settlement**

movement of the foundation of different parts of a structure by different amounts

3.34**effective depth of section***d*

distance measured from the extreme compression fibre to the centroid of tension reinforcement

3.35**embedment length**

length of embedded reinforcement provided beyond a critical section

3.36**essential facility**

building or other structure that is intended to remain operational in the event of extreme environmental loading from wind, snow, or earthquakes

3.37**factored load****factored force**

specified nominal load or force multiplied by the load factors specified in this International Standard

3.38**fire protection of reinforcement**

amount of concrete cover necessary to insulate the reinforcement against the effects of the high temperatures produced by fire

NOTE

The concrete cover is a function of the number of hours of exposure to the fire.

3.39**flange**

top or bottom part of an I-shaped section separated by the web

3.40**flexural**

pertaining to the flexure bending moment

ISO 15673:2005(E)**3.41****flexural reinforcement**

reinforcement provided to resist the tensile stresses induced by flexural moments acting on the member section

3.42**floor system**

structural elements that comprise the floor of a story in a building

NOTE

The floor system includes the beams and girders, the joists (if employed), and the slab that spans between them.

3.43**footing**

portion of the foundation that transmits loads directly to the soil

NOTE

The footing is often the widened part of a column, a structural concrete wall or several columns, in a combined footing.

3.44**formwork**

temporary construction to contain concrete in a plastic state while it is cast and setting and which forms the final shape of the element as the concrete hardens

3.45**foundation**

any part of the structure that serves to transmit loads to the underlying soil, or to contain it

3.46**foundation beam**

beam that rests on the foundation soil and spans between footings, used either to support walls or to limit differential settlement of the foundation

3.47**foundation mat**

continuous slab laid over the ground as part of the foundation and that transmits to the underlying soil the loads from the structure

3.48**girder**

main horizontal support beam, usually supporting other beams

3.49**gravity load**

load that acts downward and is caused by the acceleration of gravity, g , acting on the mass of the elements that causes the dead and live loads

3.50**hook**

bend at the end of a reinforcing bar

NOTE

Hooks are classified by the angle that the bend forms with the bar as 90°, 135° or 180° hooks.

3.51**joist**

T-shaped beam used in parallel series to directly support floor and ceiling loads, and are supported in turn by larger girders, beams, or bearing structural concrete walls

3.52**lap splice**

splice between two reinforcing bars obtained by overlapping them for a specified length

3.53**lateral-force resisting system**

that portion of the structure composed of members proportioned to resist loads related to earthquake effects

3.54**lightweight aggregate concrete**

concrete made with coarse granular material that weighs less than the granular material used in normal-weight aggregates

NOTE This type of concrete is not covered in this International Standard.

3.55**limit state**

condition beyond which a structure or member becomes unfit for service and is judged either to be no longer useful for its intended function (serviceability limit state) or to be unsafe (strength limit state)

3.56**live load**

load produced by environmental factors or the use and occupancy of the building and do not include construction or environmental loads

EXAMPLE Wind load, snow load, rain load, earthquake load, flood load, or dead load (without load factors).

3.57**load effect**

force and deformation produced in structural members by the applied loads

3.58**load factor**

factor that accounts for deviations of the actual load from the nominal load, for uncertainties in the analysis that transforms the load into a load effect and for the probability that more than one extreme load will occur simultaneously

3.59**load**

force or other action that results from the weight of all building materials, occupants and their possessions, environmental effects, differential movement, and restrained dimensional changes

3.60**longitudinal reinforcement**

reinforcement that is laid parallel to the longitudinal axis of the element, generally to account for flexural effects

3.61**mass**

quantity of matter in a body

3.62**mesh wire**

welded-wire fabric reinforcement

3.63**modulus of elasticity**

ratio of the normal stress to the corresponding strain for tensile or compressive stresses below the proportional limit of the material