
**Acoustics — Determination and
application of measurement
uncertainties in building acoustics —
Part 1:
Sound insulation**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
*Acoustique — Détermination et application des incertitudes de
mesure dans l'acoustique des bâtiments —
Partie 1: Isolation acoustique*

ISO 12999-1:2014

<https://standards.iteh.ai/catalog/standards/sist/18d5531c-5a86-4208-856d-51ed65aa3d80/iso-12999-1-2014>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12999-1:2014

<https://standards.iteh.ai/catalog/standards/sist/18d5531c-5a86-4208-856d-51ed65aa3d80/iso-12999-1-2014>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Detailed uncertainty budget	3
5 Uncertainty determination by inter-laboratory measurements	3
5.1 General.....	3
5.2 Measurement situations.....	3
5.3 Measurement conditions.....	4
5.4 Number of participating laboratories.....	4
5.5 Stating the test results of inter-laboratory measurements.....	4
5.6 Choice of test specimen.....	4
5.7 Laboratories with outlying measurement results.....	5
5.8 Verification of laboratory results by results of inter-laboratory tests.....	5
6 Uncertainties associated with single-number values	7
7 Standard uncertainties for typical measurands	7
7.1 General.....	7
7.2 Airborne sound insulation.....	7
7.3 Impact sound insulation.....	8
7.4 Reduction of transmitted impact noise by floor coverings.....	9
8 Application of the uncertainties	10
Annex A (informative) Example of handling uncertainties in building acoustics	12
Annex B (informative) Example for the calculation of the uncertainty of single number values	15
Annex C (informative) Detailed uncertainty budget	18
Bibliography	20

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*.

This first edition of ISO 12999-1 cancels and replaces ISO 140-2:1991, which has been technically revised. It also incorporates the Technical Corrigendum ISO 140-2:1991/Cor 1:1993.

ISO 12999 consists of the following parts, under the general title *Acoustics — Determination and application of measurement uncertainties in building acoustics*:

— *Part 1: Sound insulation*

A part 2 dealing with sound absorption is under preparation.

Introduction

An assessment of uncertainties that is comprehensible and close to reality is indispensable for many questions in building acoustics. Whether a requirement is met, a laboratory delivers correct results or the acoustic properties of a product are better than the same properties of some other product can be decided only by adequately assessing the uncertainties associated with the quantities under consideration.

Uncertainties should preferably be determined following the principles of ISO/IEC Guide 98-3. This Guide specifies a detailed procedure for the uncertainty evaluation that is based upon a complete mathematical model of the measurement procedure. At the current knowledge, it seems to be impossible to formulate these models for the different quantities in building acoustics. Therefore, only the principles of such an uncertainty assessment are explained.

To come to uncertainties all the same, the concept of reproducibility and repeatability is incorporated which is the traditional way of uncertainty determination in building acoustics. This concept offers the possibility to state the uncertainty of a method and of measurements carried out according to the method, based on the results of inter-laboratory measurements.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 12999-1:2014](https://standards.iteh.ai/catalog/standards/sist/18d5531c-5a86-4208-856d-51ed65aa3d80/iso-12999-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/18d5531c-5a86-4208-856d-51ed65aa3d80/iso-12999-1-2014>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12999-1:2014

<https://standards.iteh.ai/catalog/standards/sist/18d5531c-5a86-4208-856d-51ed65aa3d80/iso-12999-1-2014>

Acoustics — Determination and application of measurement uncertainties in building acoustics —

Part 1: Sound insulation

1 Scope

This part of ISO 12999 specifies procedures for assessing the measurement uncertainty of sound insulation in building acoustics. It provides for

- a detailed uncertainty assessment;
- a determination of uncertainties by inter-laboratory tests;
- an application of uncertainties.

Furthermore, typical uncertainties are given for quantities determined according to ISO 10140, ISO 140-4, ISO 140-5, ISO 140-7 and ISO 717 (all parts).

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 140-4, *Acoustics — Measurement of sound insulation in buildings and of building elements — Part 4: Field measurements of airborne sound insulation between rooms*

ISO 140-5, *Acoustics — Measurement of sound insulation in buildings and of building elements — Part 5: Field measurements of airborne sound insulation of façade elements and façades*

ISO 140-7, *Acoustics — Measurement of sound insulation in buildings and of building elements — Part 7: Field measurements of impact sound insulation of floors*

ISO 717 (all parts), *Acoustics — Rating of sound insulation in buildings and of building elements*

ISO 5725-1:1994, *Accuracy (trueness and precision) of measurement methods and results — Part 1: General principles and definitions*

ISO 5725-2:1994, *Accuracy (trueness and precision) of measurement methods and results — Part 2: Basic method for the determination of repeatability and reproducibility of a standard measurement method*

ISO 10140 (all parts), *Acoustics — Laboratory measurement of sound insulation of building elements*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE Whenever applicable, they are equivalent to those given in ISO 5725-1, in the ISO/IEC Guide 98-3^[1] and in ISO/IEC Guide 99^[2]

3.1 measurand

particular quantity subject to measurement, e.g. the airborne sound insulation of a particular window pane determined in accordance with ISO 10140

3.2 measurement result

value attributed to a measurand, obtained by following the complete set of instructions given in a measurement procedure

Note 1 to entry: The measurement result may be a frequency band level or a single number value determined according to the rating procedures of ISO 717 (all parts).

3.3 uncertainty

parameter, associated with the result of a measurement, that characterizes the dispersion of the values that can reasonably be attributed to the measurand

3.4 standard uncertainty

u
uncertainty of the result of a measurement expressed as a standard deviation

3.5 combined standard uncertainty

u_c
standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities, equal to the positive square root of a sum of terms, the terms being the variances or covariances of these other quantities weighted according to how the measurement result varies with changes in these quantities

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12999-1:2014

3.6 expanded uncertainty

<https://standards.iteh.ai/catalog/standards/sist/18d5531c-5a86-4208-856d-51ed65aa3d80/iso-12999-1-2014>

U
quantity defining an interval about the result of a measurement that may be expected to encompass a large fraction of the distribution of values that can reasonably be attributed to the measurand

3.7 coverage factor

k
numerical factor used as a multiplier of the combined standard uncertainty in order to obtain an expanded uncertainty

3.8 repeatability condition

condition of measurement that includes the same measurement procedure, same operators, same measuring system, same location (laboratory or usual building), and replicate measurements on the same object over a short period of time

3.9 repeatability standard deviation

σ_r
standard deviation of measurement results obtained under repeatability conditions

3.10 reproducibility condition

condition of measurement that includes different locations (laboratories or usual buildings), operators, measuring systems, and replicate measurements on the same or similar objects

3.11 reproducibility standard deviation

σ_R
standard deviation of measurement results obtained under reproducibility conditions

3.12 *in-situ* condition

condition of measurement that includes the same location (laboratory or usual building), and replicate measurements on the same object by different operators using different measuring systems

3.13 *in-situ* standard deviation

σ_{situ}
standard deviation of measurement results obtained under *in-situ* conditions

4 Detailed uncertainty budget

The derivation of a detailed uncertainty budget is desirable to find out which uncertainty contributions are the most important ones and how these contributions can be reduced. Furthermore, such a budget reflects the individual sound fields during the measurement. Consequently, the uncertainty is valid for an individual measurement result and not for a whole family of results. [Annex C](#) gives provisions on the derivation of such uncertainty budgets.

5 Uncertainty determination by inter-laboratory measurements

5.1 General

Standard deviations determined by inter-laboratory measurements may serve as an estimate for the standard uncertainty. The general concept and the procedure for determining these standard deviations are given in ISO 5725-1 and ISO 5725-2, respectively. As many operators and laboratories as possible should participate in such inter-laboratory measurements in order to obtain reliable results.

5.2 Measurement situations

In building acoustics, three different measurement situations are to be distinguished.

- a) Situation A is that a building element is characterized by laboratory measurements. In this case, the measurand is defined by the relevant part of ISO 10140, including all additional requirements e.g. for the measurement equipment and especially for the test facilities. Therefore, all measurement results that are obtained in another test facility or building also comply with this definition. The standard uncertainty, thus, is the standard deviation of reproducibility as determined by inter-laboratory measurements.
- b) Situation B is described by the case that different measurement teams come to the same location to carry out measurements. The location may be a usual building or a test facility. The measurand, thus, is a property of one particular element in one particular test facility or the property of a building. The main difference to situation A is that many aspects of the airborne and structure-borne sound fields involved remain constant since the physical construction is unchanged. The standard uncertainty obtained for this situation is called *in situ* standard deviation.
- c) Situation C applies to the case when the measurement is simply repeated in the same location by the same operator using the same equipment. The location may be a usual building or a test facility. The standard uncertainty is the standard deviation of repeatability as determined by inter-laboratory measurements.

5.3 Measurement conditions

The acoustical measurement conditions for determining the different standard deviations shall correspond to the conditions given in the standardized measurement procedures. The test specimen shall not be remounted between repeated measurements.

Each laboratory shall use its normal measurement procedure when participating in an inter-laboratory measurement. No deviations from the test procedure laid down shall occur but repeating the measurements several times, the parameters left open in the measurement procedure shall be represented as well as possible. In particular, the set of microphone positions and source positions over which averaging is carried out for one measurement shall be selected anew, more or less randomly, for each repeated measurement. This is necessary to obtain a mean value and a standard deviation of repeatability that represent the situation correctly.

Before the inter-laboratory measurement is started, each participating laboratory shall report the exact details of its test procedure.

Additional requirements for carrying out inter-laboratory measurements for the test specimen chosen shall be laid down in detail. This refers in particular to the following items:

- quantities being measured and reported, rules for rounding numbers;
- number of repeated measurements required;
- calibration of the measurement equipment;
- mounting and sealing conditions of the test specimen, and curing time where appropriate.

5.4 Number of participating laboratories

The number of laboratories, p , shall, from a statistical point of view, be at least eight, but is preferable to exceed this number in order to reduce the number of replicate measurements required. The number, n , of measurements in each laboratory should be so chosen that $p(n - 1) \geq 35$. In addition, at least five test results are needed for each laboratory. If the number n of measurements is different among the participating laboratories, a mean number of measurements shall be calculated and used (see ISO 5725-2). The measurement results obtained shall not be pre-selected in any way by the participating laboratories before they are reported.

5.5 Stating the test results of inter-laboratory measurements

In order to simplify the evaluation of measurement results reported, it is strongly desirable to supply forms for filling in by the participants. For the statistical analysis, it is important to report special observations and/or any irregularities observed during the test.

5.6 Choice of test specimen

5.6.1 General

The kind of test specimen used for an inter-laboratory measurement depends not only on the quantity being tested (i.e. airborne sound reduction index, normalized impact sound pressure level) but specifically on the mounting and measurement conditions for which the standard deviation of repeatability and reproducibility are being obtained (e.g. walls, floors, windows). Effects influencing the measurement result, like ageing or a strong dependence on humidity or temperature, shall also be considered.

The choice of test specimen also depends on practical considerations. In general, three different approaches (see 5.6.2 to 5.6.4) depending on the type of measurement method and/or on the type of specimen can be appropriate.

5.6.2 Use of single test specimen — Same material circulated among participants

For checking the measurement procedure and the facilities in different laboratories, ideally, the same test specimen should be used by all participants in the inter-laboratory measurement and checked again by the first laboratory at the end of the inter-laboratory measurement.

In building acoustics, this procedure is often not feasible due to the long period of time required, the risk of damage or change of the test specimen and different sizes of test openings. However, the variability resulting from the use of more than one test specimen is avoided and the standard deviation of reproducibility thus obtained is characteristic for the test facility and measurement procedure alone.

5.6.3 Use of several test specimens taken from a production lot — Nominally identical material exchangeable among participants

In contrast to the procedure described in 5.6.2, all participants of the inter-laboratory measurement receive nominally identical test specimens, i.e. coming from the same production lot or of identical design and constructed by one manufacturer. This enables testing in parallel and reduces the risk of damage or of change due to the influence of time. However, the variability among the test specimens due to their heterogeneity is then inseparable from the variability of the measurement procedure, and forms an inherent part of the reproducibility standard deviation. For this reason it can be advantageous to check all test specimens for homogeneity with more precision at one laboratory before the inter-laboratory measurement and possibly also after its completion.

5.6.4 Use of several test specimens constructed *in situ* — Nominally identical material not exchangeable among participants

When the test specimens cannot be prefabricated and readily transported, they shall be constructed *in situ* by each participant according to close specifications. In this case, the variability among the test specimens due to their heterogeneity is even larger than for test specimens according to 5.6.3.

5.7 Laboratories with outlying measurement results

ISO 5725-2 provides statistical methods to test whether a result of a laboratory is an outlier in a statistical sense. If a result turns out to be an outlier, it is necessary to investigate what are the reasons for the discrepancy. A result shall be disqualified only in the case that an error has occurred, e.g. a wrong microphone sensitivity was used. Whenever the measurement procedure described in the standard has been applied correctly and all the requirements for the test facility, the measurement equipment and the mounting of the specimen are fulfilled, the measurement result shall be considered to be in conformity with the definition of the measurand. Such results shall not be disqualified even if they are outliers.

5.8 Verification of laboratory results by results of inter-laboratory tests

A laboratory x that has not taken part in an inter-laboratory test can verify the proper operation of its own test procedure using the test results and the test specimen from an inter-laboratory test. It is further recommended that a laboratory verify the proper operation of its own test procedure from time to time, especially whenever changes in the test procedure itself, the test facility or the instrumentation are made.

Laboratory x carries out n_x repeated measurements. The standard deviation of these measurements shall be smaller than the values given in Table 1.

Table 1 — Maximum standard deviation of repeatability

Frequency	Maximum standard deviation of repeatability
Hz	dB
50	4,0
63	3,5