



SLOVENSKI STANDARD

SIST ETS 300 540 E2:2003

01-december-2003

8][JhUb]WW] b]hYY_ca i b]_UWg]g]ghYa 'fUhU&LÉJ]X]_]bU fLc j Ub'UdfYbcgU
[c j cfbYghcf]hj YdfY_ ; GA 'Uj bY[U_cdYbg_Y[Ua cV]bY[Uca fYy'UfD@A BŁfl; GA
\$' ') \$Ł

Digital cellular telecommunications system (Phase 2) (GSM); Transmission planning aspects of the speech service in the GSM Public Land Mobile Network (PLMN) system (GSM 03.50)

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 540 E2:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cbbc0ae500/sist-ets-300-540-e2-2003>

Ta slovenski standard je istoveten z: **ETS 300 540 Edition 2**

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST ETS 300 540 E2:2003

en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST ETS 300 540 E2:2003
<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cbbc0ae500/sist-ets-300-540-e2-2003>



**EUROPEAN
TELECOMMUNICATION
STANDARD**

ETS 300 540

January 1996

Second Edition

Source: ETSI TC-SMG

Reference: RE/SMG-020350P

ICS: 33.060.50

Key words: Digital cellular telecommunications system, Global System Mobile communications (GSM)



**Digital cellular telecommunications system (Phase 2);
Transmission planning aspects of the speech service in the
GSM Public Land Mobile Network (PLMN) system
(GSM 03.50)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Page 2

ETS 300 540: January 1996 (GSM 03.50 Version 4.2.0)

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 540 E2:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cbbc0ae500/sist-ets-300-540-e2-2003>

Contents

Foreword	7
1 General.....	9
1.1 Scope.....	9
1.2 Normative references	9
1.3 Definitions and abbreviations.....	11
1.4 Introduction	12
2 Network configurations.....	12
2.1 General	12
2.2 Model of the PLMN	12
2.3 Interfaces	12
2.4 Configurations of Connections.....	13
2.4.1 General Configurations of Connections	13
2.4.2 Reference configurations to illustrate delay and echo control issues.....	13
2.5 4-wire circuits in the PLMN	14
3 Transmission performance	14
3.1 Overall Loss/Loundness ratings	14
3.1.1 Connections with handset MSs	15
3.1.2 Connections with handsfree MSs using loudspeakers.....	15
3.1.3 Connections with headset MSs	16
3.2 Stability Loss.....	16
3.3 Delay	16
3.3.1 General.....	16
3.3.2 Sources of delay.....	17
3.3.2.1 Elements of the PLMN that cause delay.....	17
3.3.2.2 Elements of the PSTN that cause delay.....	17
3.3.3 Effects of delay.....	17
3.3.4 Allocation of delay to the PLMN	18
3.3.4.1 Allocation of delay to the PLMN when using a full rate system	18
3.3.4.2 Allocation of delay to the PLMN when using a half rate system	18
3.3.5 Delay of various network configurations.....	18
3.3.5.1 National and international connections with no echo control in the PSTN (reference configurations A)	18
3.3.5.2 National and international connections with echo control in the PSTN (reference configurations B)	18
3.3.5.3 Connections where re-routing leads to a significant increase in transmission path length (reference configurations C)	18
3.3.6 Delay related requirements on the MS	19
3.3.6.1 Full rate MS	19
3.3.6.2 Half rate MS.....	19
3.4 Echo.....	19
3.4.1 General.....	19
3.4.2 Electrical echo control in the PLMN (Reference configurations A)	19
3.4.3 Acoustic echo control in the PLMN	20
3.4.3.1 Acoustic echo control in a handsfree MS	20
3.4.3.2 Acoustic echo control in a handset MS	20
3.4.3.3 Acoustic echo control in a headset MS	20
3.4.4 Interaction between tandem echo control devices (reference configurations B & C)	20
3.5 Clipping	20
3.5.1 General.....	20
3.5.2 Properties of voice switches in the PLMN	21

3.5.3	Problems of tandem voice switching	21
3.6	Idle channel noise	21
3.6.1	Sending.....	21
3.6.2	Receiving	21
3.7	Noise contrast	22
3.7.1	General.....	22
3.7.2	Elements of a PLMN which can cause noise contrast impairment.....	22
3.7.3	Reduction of noise contrast	22
3.7.3.1	Reduction of noise contrast by limiting the noise received by the microphone.....	22
3.7.3.1.1	Headset MS.....	23
3.7.3.1.2	Handset MS.....	23
3.7.3.1.3	Handsfree MS	23
3.7.3.2	Reduction of noise contrast by insertion of comfort noise ..	23
3.7.4	Consequence of the introduction of high comfort noise levels on other voice-operated devices.....	23
3.8	Sensitivity/frequency characteristics	23
3.8.1	Headset and Handset MSs.....	23
3.8.1.1	Sending	23
3.8.1.2	Receiving	24
3.8.2	Handsfree MS	24
3.9	Distortion	24
3.9.1	Sending.....	24
3.9.2	Receiving	25
3.10	Sidetone	26
3.10.1	Sidetone loss	26
3.10.2	Sidetone distortion	26
3.11	Out-of-band signals	26
3.11.1	Discrimination against out-of-band input signals	26
3.11.2	Spurious out-of-band signals	27
3.12	Requirements for information tones	27
3.13	Crosstalk	27
3.13.1	Near and far end crosstalk.....	27
3.13.2	Go/return crosstalk	27
	https://standards.ieee.org/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cbhc0ae500/sist-ets-300-540-e2-2003	
Annex A (informative):	Considerations on the Acoustic Interface of the Mobile Station	37
A.1	Handsfree MS.....	37
A.2	Handset MS	37
A.3	Headset MS	37
A.4	Inter-reaction with DTX.....	37
Annex B (normative):	Transmission requirements testing.....	38
B.1	Loudness ratings	38
B.1.1	Sending Loudness Rating (SLR).....	38
B.1.2	Receiving Loudness Rating (RLR)	38
B.2	Idle Channel Noise	38
B.2.1	Sending	38
B.2.2	Receiving.....	38
B.3	Sensitivity/frequency Characteristics	38
B.3.1	Sending	38
B.3.2	Receiving.....	39
B.4	Distortion.....	39
B.4.1	Sending	39
B.4.2	Receiving.....	39

B.5	Variation of gain with input level	39
B.5.1	Sending.....	39
B.5.2	Receiving	40
B.6	Sidetone	40
B.6.1	Talker sidetone (STMR).....	40
B.6.2	Listener sidetone (LSTR).....	40
B.7	Sidetone distortion.....	41
B.8	Out-of-band signals.....	41
B.8.1	Discrimination against out-of-band input signal	41
B.8.2	Spurious out-of-band signals	41
B.9	Acoustic echo loss.....	41
Annex C (normative): MS delay requirement definition		42
C.1	Full rate MS delay requirement definition.....	42
C.2	Half rate MS delay requirement definition	42
History.....		44

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 540 E2:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26ccbc0ae500/sist-ets-300-540-e2-2003>

Page 6

ETS 300 540: January 1996 (GSM 03.50 Version 4.2.0)

Blank page

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST ETS 300 540 E2:2003

<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cbbc0ae500/sist-ets-300-540-e2-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS describes the transmission planning aspects pertaining to the speech service within the digital cellular telecommunications system (Phase 2). This ETS corresponds to GSM Technical Specification (GSM-TS) GSM 03.50 version 4.2.0.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI/PNE rules.

Reference is made within this ETS to GSM-TSs (NOTE).

NOTE: TC-SMG has produced documents which give the technical specifications for the implementation of the European digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TSs). These TSs may have subsequently become I-ETSSs (Phase 1), or ETSSs (Phase 2), whilst others may become ETSI Technical Reports (ETRs). GSM-TSs are, for editorial reasons, still referred to in current GSM ETSSs.

Transposition dates	
Date of adoption of this ETS:	31 January 1996
Date of latest announcement of this ETS (doa):	30 April 1996
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 October 1996
Date of withdrawal of any conflicting National Standard (dow):	31 October 1996

*SIST ETS 300 540 E2:2003
<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cb0ae500/sist-ets-300-540-e2-2003>*

Page 8

ETS 300 540: January 1996 (GSM 03.50 Version 4.2.0)

Blank page

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST ETS 300 540 E2:2003

<https://standards.iteh.ai/catalog/standards/sist/927e7c32-a89d-4595-bab5-26cbbc0ae500/sist-ets-300-540-e2-2003>

1 General

1.1 Scope

This European Telecommunication Standard (ETS) is concerned with the transmission planning aspects pertaining to the speech service in the pan-European PLMN system. Due to technical and economic factors, there cannot be full compliance with the general characteristics of international telephone connections and circuits recommended by CCITT.

This ETS gives guidance as to the precautions, measures and minimum requirements needed for successful interworking of the PLMN with the national and international PSTN. The Recommendation identifies a number of routing and network configurations. The objective is to reach a quality as close as possible to CCITT standards in order to safeguard the performance seen by PSTN customers.

1.2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies. Unless otherwise stated, all references to CCITT Recommendations are from the Blue Book (1989).

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunication system (Phase 2); Abbreviations and acronyms".
- [2] GSM 03.04 (ETS 300 524): "European digital cellular telecommunication system (Phase 2); Signalling requirements relating to routing of calls to mobile subscribers".
iTels STANDARD PREVIEW
(standards.itech.ai)
SIST ETS 300 540 E2:2003
- [3] GSM 06.01 (ETS 300 580-1): "European digital cellular telecommunication system (Phase 2); Full rate speech processing functions".
- [4] <https://standards.itech.ai/catalogs/gsm/037/e702c80145951115-3mcPhase2FullRateSpeechTranscoding>
GSM 06.10 (ETS 300 580-2): "European digital cellular telecommunication system (Phase 2); Full rate speech transcoding".
- [5] GSM 06.11 (ETS 300 580-3): "European digital cellular telecommunication system (Phase 2); Substitution and muting of lost frames for full rate speech channels".
- [6] GSM 06.12 (ETS 300 580-4): "European digital cellular telecommunication system (Phase 2); Comfort noise aspect for full rate speech traffic channels".
- [7] GSM 06.31 (ETS 300 580-5): "European digital cellular telecommunication system (Phase 2); Discontinuous Transmission (DTX) for full rate speech traffic channel".
- [8] GSM 06.32 (ETS 300 580-6): "European digital cellular telecommunication system (Phase 2); Voice Activity Detection (VAD)".
- [9] GSM 06.02 (ETS 300 581-1): "European digital cellular telecommunication system (Phase 2); Half rate speech processing functions".
- [10] GSM 06.20 (ETS 300 581-2): "European digital cellular telecommunication system (Phase 2); Half rate speech transcoding".
- [11] GSM 06.21 (ETS 300 581-3): "European digital cellular telecommunication system (Phase 2); Substitution and muting of lost frames for half rate speech traffic channels".
- [12] GSM 06.22 (ETS 300 581-4): "European digital cellular telecommunication system (Phase 2); Comfort noise aspects for half rate speech traffic channels".

Page 10

ETS 300 540: January 1996 (GSM 03.50 Version 4.2.0)

- [13] GSM 06.41 (ETSI 300 581-5): "European digital cellular telecommunication system (Phase 2); Discontinuous Transmission (DTX) for half rate speech traffic channels".
- [14] GSM 06.42 (ETSI 300 581-6): "European digital cellular telecommunication system (Phase 2); Voice Activity Detection (VAD) for half rate speech traffic channels".
- [15] ETSI 300 085 (1990): "Integrated Services Digital Network (ISDN); 3,1 kHz telephony teleservice; Attachment requirements for handset terminals".
- [16] CCITT Recommendation G.103: "Hypothetical reference connections".
- [17] CCITT recommendation G.111: "Loudness ratings (LRs) in an international connections".
- [18] CCITT Recommendation G.113: "Transmission impairments".
- [19] CCITT Recommendation G.114: "Mean one-way propagation time".
- [20] CCITT Recommendation G.121: "Loudness ratings (LRs) of national systems".
- [21] CCITT Recommendation G.122: "Influence of national systems on stability, talker echo, and listener echo in international connections".
- [22] CCITT Recommendation G.131: "Stability and echo".
- [23] CCITT Recommendation G.165: "Echo cancellers".
- [24] CCITT Recommendation G.223: "Assumptions for the calculation of noise on hypothetical reference circuits for telephony".

The STANDARD PREVIEW

- [25] CCITT Recommendation G.703: "Physical/electrical characteristics of hierarchical digital interfaces".
SIST ETS 300 540 E2:2003
http://telec.technion.ac.il/standards/sist/927e7c32-a89d-4595-bab5-26ccbc0ae500/sist-ets-300-540-e2-2003
- [26] CCITT Recommendation G.711: "Pulse code modulation (PCM) of voice frequencies".
- [27] CCITT Recommendations G.712: "Transmission performance characteristics of pulse code modulation".
- [28] CCITT Recommendations G.714: "Separate performance characteristics for the send and receive sides of PCM channels applicable to 4-wire voice frequency interfaces".
- [29] CCITT Recommendations M.1020: "Characteristics of special quality".
- [30] CCITT Recommendations M.1025: "Characteristics of special quality international leased circuits with basic bandwidth conditioning".
- [31] CCITT Recommendations M.1030: "Characteristics of ordinary quality international leased circuits forming part of private switched telephone networks".
- [32] CCITT Recommendations M.1040: "Characteristics of ordinary quality international leased circuits".
- [33] CCITT Recommendation O.132 (1988), "Specification for a quantizing distortion measuring apparatus using a sinusoidal test signal."
- [34] CCITT Recommendation P.11: "Effect of transmission impairments".

- [35] CCITT Recommendation P.34: "Transmission characteristics of hands-free telephones".
- [36] CCITT Recommendation P.38: "Transmission characteristics of operator telephone systems (OTS)".
- [37] CCITT Recommendation P.50: "Artificial voices".
- [38] CCITT Recommendation P.51 (1988), "Artificial mouths and artificial ears."
- [39] CCITT Recommendation P.64 (1988), "Determination of sensitivity/frequency characteristics of local telephone systems to permit calculation of their loudness ratings."
- [40] CCITT Recommendation P.76 (1988), "Determination of loudness ratings; fundamental principles."
- [41] CCITT Recommendation P.79 (1988), "Calculation of loudness ratings."
- [42] CCITT Recommendation Q.35: "Technical characteristics of tones for the telephone service".
- [43] CCITT Recommendation Q.551: "Transmission characteristics of digital exchanges".
- [44] CCITT Blue Book (1988), Volume V, Supplement 13, "Noise spectra."
- [45] ISO 3-1973, "Preferred numbers - series of preferred numbers."

iTel STANDARD PREVIEW (standards.iteh.ai)

1.3 Definitions and abbreviations

[SIST ETS 300 540 E2:2003](#)

In addition to those below, the definitions and abbreviations used in this specification are listed in GSM 01.04.

<https://standards.iteh.ai/catalog/standards/itst/027-7-22-a891-4595-bc15-26ccbc0ae500/sist-ets-300-540-e2-2003>

ADC	Analogue to Digital Converter
ADPCM	Adaptive Differential Pulse Code Modulation
AEC	Acoustic Echo Control
BSC'	Base Station Controller (excluding transmission systems)
BTS'	Base Transceiver Station (excluding transmission systems)
DAC	Digital to Analogue Converter
DMR	Digital Mobile Radio
DSI	Digital Speech Interpolation
EEC	Electric Echo Control
EL	Echo Loss
ERP	Ear Reference Point
FDM	Frequency Division Multiplex
LSTR	Listener Sidetone Rating
MRP	Mouth Reference Point
OLR	Overall Loudness Rating
PCM	Pulse Code Modulation
POI	Point of Interconnection (with PSTN)
RLR	Receiver Loudness Rating
SLR	Send Loudness Rating
STMR	Sidetone Masking Rating
UPCMI	13-bit Uniform PCM Interface