
**Information technology —
Telecommunications and information
exchange between systems — Private
Integrated Services Network —
Inter-exchange signalling protocol —
Wireless terminal call handling additional
network features**

iTeh STANDARD PREVIEW

(standards.iteh.ai)

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseau privé à intégration de
services — Protocole de signalement d'interéchange — Caractéristiques
de réseau additionnelles pour le traitement d'appel de terminal sans fil*

<https://standards.iteh.ai/catalog/standards/sist/635691fa-56aa-4c67-9297-b9685e87a6b2/iso-iec-15431-2003>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 15431:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003>

© ISO/IEC 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Foreword	vi
Introduction	vii
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions	2
4.1 External definitions	2
4.2 Other definitions	3
4.2.1 Alternative identifier	3
4.2.2 Home data base (HDB)	3
4.2.3 Home PINX	3
4.2.4 Rerouteing PINX	3
4.2.5 Visitor data base (VDB)	3
4.2.6 Visitor PINX	3
4.2.7 WTMI-detect PINX	3
5 Symbols and abbreviated terms	4
6 Signalling protocol for the support of ANF-WTMI	4
6.1 ANF-WTMI description	4
6.2 ANF-WTMI operational requirements	5
6.2.1 Requirements on the Rerouteing PINX	5
6.2.2 Requirements on the WTMI-detect PINX	5
6.2.3 Requirements on the Home PINX	5
6.2.4 Requirements on the Visitor PINX	5
6.2.5 Requirements on a Transit PINX	5
6.3 ANF-WTMI coding requirements	6
6.3.1 Operations	6
6.3.2 Information elements	8
6.3.3 Messages	9
6.4 ANF-WTMI state definitions	9
6.4.1 States at the Rerouteing PINX	9
6.4.2 States at the WTMI-detect PINX	9
6.4.3 States at the Home PINX	9
6.4.4 States at the Visitor PINX	9
6.5 ANF-WTMI signalling procedures for invocation and operation	9
6.5.1 Actions at the Rerouteing PINX	9
6.5.2 Actions at the WTMI-detect PINX	10
6.5.3 Actions at the Home PINX	11
6.5.4 Actions at the Visitor PINX	12
6.5.5 Actions at a Transit PINX	12
6.5.6 Actions at an Originating PINX	12
6.6 ANF-WTMI impact of interworking with public ISDNs	12
6.7 ANF-WTMI impact of interworking with non-ISDNs	13
6.8 Protocol interactions between ANF-WTMI and other supplementary services and ANFs	13

6.8.1	Interaction with Calling Name Identification Presentation (SS-CNIP)	13
6.8.2	Interaction with Connected Name Identification Presentation (SS-CONP)	13
6.8.3	Interaction with Call Completion to Busy Subscriber (SS-CCBS)	13
6.8.4	Interaction with Call Completion on No Reply (SS-CCNR)	13
6.8.5	Interaction with Call Transfer (SS-CT)	13
6.8.6	Interaction with Call Forwarding Unconditional (SS-CFU)	13
6.8.7	Interaction with Call Forwarding Busy (SS-CFB)	13
6.8.8	Interaction with Call Forwarding No Reply (SS-CFNR)	13
6.8.9	Interaction with Call Deflection (SS-CD)	13
6.8.10	Interaction with Path Replacement (ANF-PR)	13
6.8.11	Interaction with Call Offer (SS-CO)	13
6.8.12	Interaction with Call Intrusion (SS-CI)	14
6.8.13	Interaction with Do Not Disturb (SS-DND)	14
6.8.14	Interaction with Do Not Disturb Override (SS-DNDO)	14
6.8.15	Interaction with Advice Of Charge (SS-AOC)	14
6.8.16	Interaction with Recall (SS-RE)	14
6.8.17	Interaction with Call Interception (ANF-CINT)	14
6.8.18	Interaction with Transit Counter (ANF-TC)	14
6.8.19	Interaction with Route Restriction Class (ANF-RRC)	14
6.8.20	Interaction with Message Waiting Indication (SS-MWI)	15
6.8.21	Interaction with Wireless Terminal Location Registration (SS-WTLR)	15
6.8.22	Interaction with Wireless Terminal Information (ANF-WTINFO)	15
6.8.23	Interaction with Wireless Terminal Outgoing Call (ANF-WTMO)	15
6.8.24	Interaction with Wireless Terminal Authentication of the Terminal (SS-WTAT)	15
6.8.25	Interaction with Wireless Terminal Authentication of the Network (SS-WTAN)	15
6.9	ANF-WTMI parameter values (timers)	16
6.9.1	Timer T1	16
6.9.2	Timer T2	16
7	Signalling protocol for the support of ANF-WTMO	16
7.1	ANF-WTMO description	16
7.2	ANF-WTMO operational requirements	16
7.2.1	Requirements on the Originating PINX	16
7.2.2	Requirements on the Home PINX	16
7.2.3	Requirements on a Transit PINX	16
7.3	ANF-WTMO coding requirements	16
7.3.1	Operations	16
7.3.2	Information elements	16
7.3.3	Messages	16
7.4	ANF-WTMO state definitions	17
7.4.1	States at the Originating PINX	17
7.4.2	States at the Home PINX	17
7.5	ANF-WTMO signalling procedures	17
7.5.1	Actions at the Originating PINX	17
7.5.2	Actions at the Home PINX	17
7.5.3	Actions at the Transit PINX	18
7.6	ANF-WTMO impact of interworking with public ISDNs	18
7.7	ANF-WTMO impact of interworking with non-ISDNs	18
7.8	Protocol interactions between ANF-WTMO and other supplementary services and ANFs	18
7.8.1	Interaction with Calling Name Identification Presentation (SS-CNIP)	18
7.8.2	Interaction with Connected Name Identification Presentation (SS-CONP)	18

7.8.3	Interaction with Call Completion to Busy Subscriber (SS-CCBS)	18
7.8.4	Interaction with Call Completion on No Reply (SS-CCNR)	18
7.8.5	Interaction with Call Transfer (SS-CT)	18
7.8.6	Interaction with Call Diversion (SS-CFU, SS-CFB, SS-CFNR, SS-CD)	18
7.8.7	Interaction with Path Replacement (ANF-PR)	19
7.8.8	Interaction with Call Offer (SS-CO)	19
7.8.9	Interaction with Call Intrusion (SS-CI)	19
7.8.10	Interaction with Do Not Disturb (SS-DND)	19
7.8.11	Interaction with Do Not Disturb Override (SS-DNDO)	19
7.8.12	Interaction with Advice of Charge (SS-AOC)	19
7.8.13	Interaction with Recall (SS-RE)	19
7.8.14	Interaction with Call Interception (ANF-CINT)	19
7.8.15	Interaction with Transit Counter (ANF-TC)	19
7.8.16	Interaction with Route Restriction Class (ANF-RRC)	19
7.8.17	Interaction with Message Waiting Indication (SS-MWI)	19
7.8.18	Interaction with Wireless Terminal Location Registration (SS-WTLR)	19
7.8.19	Interaction with Wireless Terminal Information (ANF-WTINFO)	19
7.8.20	Interaction with Wireless Terminal Incoming Call (ANF-WTMI)	19
7.8.21	Interaction with Wireless Terminal Authentication of the Terminal (SS-WTAT)	19
7.8.22	Interaction with Wireless Terminal Authentication of the Network (SS-WTAN)	20
7.9	Parameter values (timers)	20
7.9.1	Timers at the Originating PINX	20
7.9.2	Timers at the Home PINX	20
Annexes		
A	Protocol Implementation Conformance Statement (PICS) proforma	21
B	Imported ASN.1 definitions	31
C	Examples of Message Sequences	32
D	Specification and Description Language (SDL) representation of procedures	37
E	ASN.1 definitions according to ITU-T Recs. X.208 / X.209	45

iteh STANDARD PREVIEW
(standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 15431 was prepared by ECMA (as ECMA-304) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, Information technology, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 15431:1999), which has been technically revised.

Introduction

This International Standard is one of a series of Standards defining Wireless Terminal Mobility (WTM) services and signalling protocols applicable to Private Integrated Services Networks (PISNs). The series uses ISDN concepts as developed by ITU-T and conforms to the framework of International Standards for Open Systems Interconnection as defined by ISO/IEC.

This International Standard specifies the signalling protocol for use at the Q reference point in support of the Wireless Terminal Call Handling additional network feature. The protocol defined in this International Standard forms part of the PSS1 protocol (informally known as QSIG).

This International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 15431:2003](https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003)

<https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 15431:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003>

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Wireless terminal call handling additional network features

1 Scope

This International Standard specifies the signalling protocol for the support of the Wireless terminal call handling additional network features (ANF-WTMI and ANF-WTMO) at the Q reference point between Private Integrated services Network eXchanges (PINX) connected together within a Private Integrated Services Network (PISN).

ANF-WTMI is a feature that directs incoming calls to a WTMI user within the PISN regardless of the WTMI user's geographical location within the PISN, provided that the WTMI user's location is known. Roaming outside the PISN is outside the scope of this edition of this International Standard.

ANF-WTMO permits the PISN to process call requests from a WTMO user at the home location, if required.

The Q reference point is defined in ISO/IEC 11579-1.

Service specifications are produced in three stages and according to the method specified in ITU-T Rec. I.130. This International Standard contains the stage 3 specification for the Q reference point and satisfies the requirements identified by the stage 1 and stage 2 specifications in ISO/IEC 15430.

The signalling protocol for ANF-WTMI and ANF-WTMO operates on top of the signalling protocol for basic circuit switched call control, as specified in ISO/IEC 11572, and uses certain aspects of the generic procedures for the control of supplementary services specified in ISO/IEC 11582.

This International Standard also specifies additional signalling protocol requirements for the support of interactions at the Q reference point between ANF-WTMI / ANF-WTMO and other supplementary services and ANFs.

This International Standard is applicable to PINXs which can interconnect to form a PISN.

2 Conformance

In order to conform to this International Standard, a PINX shall satisfy the requirements identified in the Protocol Implementation Conformance Statement (PICS) proforma in annex A.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11571:1998, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Networks - Addressing*

ISO/IEC 11572:2000, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit mode bearer services - Inter-exchange signalling procedures and protocol*

ISO/IEC 11574:2000, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Circuit-mode 64 kbit/s bearer services - Service description, functional capabilities and information flows*

ISO/IEC 11579-1:1994, *Information technology - Telecommunications and information exchange between systems - Private integrated services network - Part 1: Reference configuration for PISN Exchanges (PINX)*

ISO/IEC 11582:2002, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Generic functional protocol for the support of supplementary services - Inter-exchange signalling procedures and protocol*

- ISO/IEC 13241:1997, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Route Restriction Class additional network feature*
- ISO/IEC 13868:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Name identification supplementary services*
- ISO/IEC 13873:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Call Diversion supplementary services*
- ISO/IEC 13874:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Path Replacement additional network feature*
- ISO/IEC 14843:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Call Offer supplementary service*
- ISO/IEC 14844:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Do Not Disturb and Do Not Disturb Override supplementary services*
- ISO/IEC 14846:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Call Intrusion supplementary service*
- ISO/IEC 15050:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Advice Of Charge supplementary services*
- ISO/IEC 15054:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Call Interception additional network feature*
- ISO/IEC 15056:1997, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Transit counter additional network feature*
- ISO/IEC 15430:1999, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Specification, functional model and information flows - Wireless terminal call handling additional network features* <https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b0685e87a6b2/iso-iec-15431-2003>
- ISO/IEC 15506:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Message Waiting Indication supplementary service*
- ITU-T Rec. I.112:1993, *Vocabulary of terms for ISDNs*
- ITU-T Rec. I.130:1988, *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN (Blue Book)*
- ITU-T Rec. I.210:1993, *Principles of telecommunication services supported by an ISDN and the means to describe them*
- ITU-T Rec. Q.850:1993, *Use of cause and location in the digital subscriber Signalling System No. 1 and the Signalling System No. 7 ISDN user part*
- ITU-T Rec. Q.950:2000, *Supplementary services protocols, structure and general principles*
- ITU-T Rec. Z.100:1999, *Specification and description language (SDL)*

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1 External definitions

This International Standard uses the following terms defined in other documents:

- Additional Network Feature (ANF) (ISO/IEC 11582)
- Application Protocol Data Unit (APDU) (ISO/IEC 11582)
- Basic service (ITU-T Rec. I.210)
- Call, Basic call (ISO/IEC 11582)
- Call independent (ISO/IEC 11582)
- Call independent signalling connection (ISO/IEC 11582)

– Call related	(ISO/IEC 11582)
– Complete number	(ISO/IEC 11571)
– Co-ordination function	(ISO/IEC 11582)
– End PINX	(ISO/IEC 11582)
– Incoming Gateway PINX	(ISO/IEC 11572)
– Incoming WTM call	(ISO/IEC 15430)
– Interpretation APDU	(ISO/IEC 11582)
– Network Facility Extension (NFE)	(ISO/IEC 11582)
– Originating PINX	(ISO/IEC 11572)
– Private Integrated Services Network (PISN)	(ISO/IEC 11579-1)
– Private Integrated services Network eXchange (PINX)	(ISO/IEC 11579-1)
– PISN number	(ISO/IEC 11571)
– Signalling	(ITU-T Rec. I.112)
– Supplementary service	(ITU-T Rec. I.210)
– Supplementary Service Control Entity	(ISO/IEC 11582)
– Subsequent PINX	(ISO/IEC 11572)
– Terminating PINX	(ISO/IEC 11572)
– Transit PINX	(ISO/IEC 11572)
– User	(ISO/IEC 11574)
– WTMI user	(ISO/IEC 15430)
– WTMO user	(ISO/IEC 15430)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003>

<https://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003>

4.2 Other definitions

4.2.1 Alternative identifier

An identifier, other than the PISN number, which identifies the WTMI user uniquely.

4.2.2 Home data base (HDB)

The data base in which the current location and all associated parameters of a wireless terminal are stored.

4.2.3 Home PINX

The PINX which has direct access to the HDB entry for a particular WTMI or WTMO user.

4.2.4 Rerouteing PINX

The PINX which executes the rerouteing of the incoming WTM call to the current Visitor PINX.

NOTE - In case of rerouteing, the Rerouteing PINX is either the Originating PINX or the Incoming Gateway PINX. In case of forward switching, the Rerouteing PINX is the WTMI-detect PINX.

4.2.5 Visitor data base (VDB)

The data base in which all relevant parameters concerning a wireless terminal are stored for as long as it is located in an area controlled by this data base.

4.2.6 Visitor PINX

The PINX which has direct access to the VDB entry for a particular WTMI or WTMO user.

4.2.7 WTMI-detect PINX

The PINX which detects that an incoming call is to a WTMI user.

NOTE - The WTMI-detect PINX is either the Home PINX, a Transit PINX, the Incoming Gateway PINX or the Originating PINX.

5 Symbols and abbreviated terms

ANF	Additional Network Feature
ANF-CINT	Call Interception additional network feature
ANF-PR	Path Replacement additional network feature
ANF-RRC	Route Restriction Class additional network feature
ANF-TC	Transit counter additional network feature
(ANF-)WTMI	Wireless Terminal Incoming Call (additional network feature)
(ANF-)WTMO	Wireless Terminal Outgoing Call (additional network feature)
APDU	Application Protocol Data Unit
ASN.1	Abstract Syntax Notation no. 1
HDB	Home Data Base
ISDN	Integrated Services Digital Network
NFE	Network Facility Extension
PICS	Protocol Implementation Conformance Statement
PINX	Private Integrated services Network eXchange
PISN	Private Integrated Services Network
SDL	Specification and Description Language
SS-AOC	Advice Of Charge supplementary services
SS-CD	Call Deflection supplementary service
SS-CFB	Call Forwarding Busy supplementary service
SS-CFNR	Call Forwarding No Reply supplementary service
SS-CFU	Call Forwarding Unconditional supplementary service
SS-CI	Call Intrusion supplementary service
SS-CNIP	Calling Name Identification Presentation supplementary service
SS-CO	Call Offer supplementary service
SS-DNDO	Do Not Disturb Override supplementary service
SS-MWI	Message Waiting Indication supplementary service
VDB	Visitor Data Base
WTM	Wireless Terminal Mobility

6 Signalling protocol for the support of ANF-WTMI

6.1 ANF-WTMI description

ANF-WTMI enables calls to be directed to a WTMI user within the PISN. As there is no predetermined PINX for the connection of a WTMI user to the PISN, the directing of such calls requires that information regarding the location of the user is available.

6.2 ANF-WTMI operational requirements

6.2.1 Requirements on the Rerouting PINX

ISO/IEC 11572 protocol control procedures for call establishment at the outgoing side of an inter-PINX link shall apply to the establishment of the connection to the Visitor PINX. ISO/IEC 11572 protocol control procedures for call clearing shall apply to the release of the connection to the WTMI-detect PINX.

Generic procedures for the call related control of supplementary services, as specified in ISO/IEC 11582 for an End PINX, shall apply.

6.2.2 Requirements on the WTMI-detect PINX

ISO/IEC 11572 protocol control procedures for call establishment at the incoming side of an inter-PINX link shall apply to the establishment of the connection from the Originating or Incoming Gateway PINX. ISO/IEC 11572 protocol control procedures for call clearing shall apply to the release of the connection to the Rerouting PINX.

Generic procedures for the call related control of supplementary services, as specified in ISO/IEC 11582 for an End PINX, shall apply.

Generic procedures for the call independent control (connection oriented) of supplementary services, as specified in ISO/IEC 11582 for an Originating PINX, shall apply.

6.2.3 Requirements on the Home PINX

Generic procedures for the call independent control (connection oriented) of supplementary services, as specified in ISO/IEC 11582 for a Terminating PINX, shall apply.

6.2.4 Requirements on the Visitor PINX

ISO/IEC 11572 protocol control procedures for call establishment at the incoming side of an inter-PINX link shall apply to the establishment of the connection from the Rerouting PINX.

Generic procedures for the call related control of supplementary services, as specified in ISO/IEC 11582 for an End PINX, shall apply.

6.2.5 Requirements on a Transit PINX

Basic call procedures for call establishment and call clearing at a Transit PINX, as specified in ISO/IEC 11572, shall apply.

Generic procedures for the call related control and call independent control (connection oriented) of supplementary services, as specified in ISO/IEC 11582 for a Transit PINX, shall apply.

iteh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 15431:2003](http://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003)

<http://standards.iteh.ai/catalog/standards/sist/855b391a-36aa-4c07-9257-b9685e87a6b2/iso-iec-15431-2003>

6.3 ANF-WTMI coding requirements

6.3.1 Operations

The operations defined in Abstract Syntax Notation number 1 (ASN.1) in table 1 shall apply. The notation is in accordance with ITU-T Rec. X.680 and X.690. The ITU-T Rec. X.208 and X.209 superseded version is in annex E.

Table 1 - Operations in support of call handling additional network features

Wireless-Terminal-Call-Handling-Operations-asn1-97 { iso (1) standard (0) pss1-wtm-call-handling (15431) operations-asn1-97 (1)}	
DEFINITIONS EXPLICIT TAGS ::=	
BEGIN	
IMPORTS	OPERATION, ERROR FROM Remote-Operations-Information-Objects { joint-iso-itu-t remote-operations (4) informationObjects(5) version1(0)}
	EXTENSION, Extension{} FROM Manufacturer-specific-service-extension-class-asn1-97 { iso (1) standard (0) pss1-generic-procedures (11582) msi-class-asn1-97 (11) }
	PSS1InformationElement FROM PSS1-generic-parameters-definition-asn1-97 { iso (1) standard (0) pss1-generic-procedures (11582) pss1-generic-parameters-asn1-97 (17) }
	Name FROM Name-Operations-asn1-97 { iso (1) standard (0) pss1-name (13868) name-operations-asn1-97 (1) }
	basicServiceNotProvided, invalidServedUserNr, notAvailable FROM General-Error-List { ccitt (0) recommendation (0) q 950 general-error-list (1) }
	Address, PartyNumber, PartySubaddress, PresentedNumberScreened FROM Addressing-Data-Elements-asn1-97 { iso (1) standard (0) pss1-generic-procedures (11582) addressing-data-elements-asn1-97 (20) };
-- Operations for ANF-WTMI: --	
WTMCH-Operations OPERATION ::= {wtmiEnquiry wtmiDivert wtmiInform wtmoCall}	
wtmiEnquiry	OPERATION ::= { -- Sent from the WTMI-detect PINX to the Home PINX. ARGUMENT EnquiryArg RESULT EnquiryRes ERRORS { invalidServedUserNr locationNotKnown notAvailable basicServiceNotProvided unspecified } CODE local: 54}

Table 1 - Operations in support of call handling additional network features (continued)

wtmiDivert	OPERATION ::= { -- Sent from the WTMI-detect PINX to the Rerouteing PINX. ARGUMENT DivertArg RESULT DummyRes ERRORS { notAvailable unspecified } CODE local: 55}
wtmiInform	OPERATION ::= { -- Sent from the Rerouteing PINX to the Visitor PINX. ARGUMENT InformArg RETURN RESULT FALSE ALWAYS RESPONDS FALSE CODE local: 56}
EnquiryArg ::=	SEQUENCE { pismNumber PartyNumber, -- The PISN number of the WTMI user qSIGInfoElement PSS1InformationElement, -- The basic call information elements Bearer capability, High layer compatibility, -- Low layer compatibility can be embedded in the qSIGInfoElement -- in accordance with clause 6.5.2.1. argExtension WtmiExtension OPTIONAL }
DivertArg ::=	SEQUENCE { visitPINX PartyNumber, -- The PISN number of the Visitor PINX, -- always a Complete Number. callingNumber PresentedNumberScreened, wtmIdentity WtmIdentity, -- The PISN number (always a Complete Number) -- and/or an alternative identifier of the WTMI user. qSIGInfoElement PSS1InformationElement, -- The basic call information elements Bearer capability, High layer compatibility, -- Low layer compatibility, and Progress indicator -- can be embedded in the qSIGInfoElement in accordance with clause 6.5.2.1. callingUserSub [1] PartySubaddress OPTIONAL, callingName [2] Name OPTIONAL, wtmUserSub [3] PartySubaddress OPTIONAL, argExtension WtmiExtension OPTIONAL }
InformArg ::=	SEQUENCE { wtmIdentity WtmIdentity, -- The PISN number (always a Complete Number) -- and/or an alternative identifier of the WTMI user. argExtension WtmiExtension OPTIONAL }
EnquiryRes ::=	CHOICE { currLocation [1] IMPLICIT CurrLocation, cfuActivated [2] IMPLICIT CfuActivated }
CurrLocation ::=	SEQUENCE { visitPINX PartyNumber, -- The PISN number of the Visitor PINX, -- always a Complete Number. wtmIdentity WtmIdentity, -- The PISN number (always a Complete Number) -- and/or an alternative identifier of the WTMI user argExtension WtmiExtension OPTIONAL }