

**SLOVENSKI STANDARD****SIST EN 4612-012:2011****01-december-2011**

**Aeronavtika - Eno- in večžilni električni kabli za splošne namene - Družina XLETFE  
- Oplaščeni ali zaslonjeni in oplaščeni - 012. del: Ponikljani baker - Obratovalne  
temperature med –65 °C in 150 °C - Dvojno ekstrudirana izolacija za zunanjo  
uporabo s plaščem in zaslonom (opletom) - Možnost UV-laserskega tiskanja -  
Standard za izdelek**

Aerospace series - Cables, electrical, for general purpose, single and multicore assembly  
- XLETFE Family - Jacketed or screened and jacketed - Part 012: Nickel plated copper -  
Operating temperatures, between –65 °C and 150 °C - Dual extruded wall for open  
applications, with jacket and screen (braid) - UV laser printable - Product standard

Luft- und Raumfahrt - Ein- und mehrdrige elektrische Leitungen für allgemeine  
Verwendung - XLETFE Familie 7c743b588604/sist-en-4612-012-2011 Mit Mantel oder geschirmt und Mantel - Teil 012: Kupfer  
vernickelt - Betriebstemperaturen zwischen –65 °C und 150 °C - Doppelt extrudierte  
Isolierung für externe Verwendung, mit Mantel und Schirm (Geflecht) - UV-Laser  
bedruckbar - Produktnorm

Série aérospatiale - Câbles, électriques, d'usage général, mono et multiconducteurs -  
Famille XLETFE - Gainés ou blindés et gainés - Partie 012: Cuivre nickelé -  
Températures de fonctionnement comprises entre – 65 °C et 150 °C - Fil double isolé  
pour applications externes, gainé et blindé (tressé) - Marquable au laser UV - Norme de  
produit

**Ta slovenski standard je istoveten z: EN 4612-012:2011**

**ICS:**

49.060      Letalska in vesoljska      Aerospace electric  
                  električna oprema in sistemi      equipment and systems

**SIST EN 4612-012:2011****en**

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 4612:2011

<https://standards.iteh.ai/catalog/standards/sist/e585a314-e51f-4841-b22f-7c743bb88b04/sist-en-4612-012-2011>

**EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM**

**EN 4612-012**

October 2011

ICS 49.060

English Version

Aerospace series - Cables, electrical, for general purpose,  
single and multicore assembly - XLETFE Family - Jacketed or  
screened and jacketed - Part 012: Nickel plated copper -  
Operating temperatures, between - 65 °C and 150 °C - Dual  
extruded wall for open applications, with jacket and screen  
(braid) - UV laser printable - Product standard

Série aérospatiale - Câbles, électriques, d'usage général,  
mono et multiconducteurs - Famille XLETFE - Gainés ou  
blindés et gainés - Partie 012: Cuivre nickelé -  
Températures de fonctionnement comprises entre - 65 °C  
et 150 °C - Fil double isolé pour applications externes,  
gainé et blindé (tressé) - Marquable au laser UV - Norme  
de produit

Luft- und Raumfahrt - Ein- und mehradrig elektrische  
Leitungen für allgemeine Verwendung - XLETFE Familie -  
Mit Mantel oder geschirmt und Mantel - Teil 012: Kupfer  
vernickelt - Betriebstemperaturen zwischen - 65 °C und 150  
°C - Doppelt extrudierte Isolierung für externe Verwendung,  
mit Mantel und Schirm (Geflecht) - UV-Laser bedruckbar -  
Produktnorm

**ITEH STANDARD PREVIEW**

**(standards.iteh.ai)**

This European Standard was approved by CEN on 20 August 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

[SIST EN 4612-012-2011](http://www.cen-cenelec.eu/7674358888004/sist-en-4612-012-2011)

[7674358888004/sist-en-4612-012-2011](http://www.cen-cenelec.eu/7674358888004/sist-en-4612-012-2011)

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

## Contents

	Page
<b>Foreword.....</b>	<b>3</b>
<b>1 Scope .....</b>	<b>4</b>
<b>2 Normative references .....</b>	<b>4</b>
<b>3 Terms, definitions and symbols.....</b>	<b>4</b>
<b>4 Materials and construction .....</b>	<b>5</b>
<b>5 Required characteristics.....</b>	<b>7</b>
<b>6 Quality assurance .....</b>	<b>10</b>
<b>7 Designation .....</b>	<b>11</b>
<b>8 Identification and marking .....</b>	<b>11</b>
<b>9 Packaging, labelling and delivery lengths .....</b>	<b>11</b>
<b>10 Technical specification .....</b>	<b>11</b>
<b>Annex A (normative) Formulae for calculating braid details .....</b>	<b>12</b>
<b>A.1 The filling factor <math>K_f</math> is given by the following formula.....</b>	<b>12</b>
<b>A.2 Lay factor.....</b>	<b>12</b>
<b>A.3 Coverage.....</b>	<b>12</b>

SIST EN 4612-012:2011

https://standards.iteh.ai/catalog/standards/sist/e585a314-e51f-4841-b22f  
7c743bb88b04/sist-en-4612-012-2011

## Foreword

This document (EN 4612-012:2011) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2012, and conflicting national standards shall be withdrawn at the latest by April 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## The STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 4612-012:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/e585a314-e51f-4841-b22f-7c743bb88b04/sist-en-4612-012-2011>

## 1 Scope

This European Standard specifies the characteristics of UV laser printable jacket, nickel plated copper conductor, electrical cables Crosslinked Ethylene Tetra Fluoro Ethylene co-polymer (XLETFE) family for use in the on-board electrical systems of aircraft at operating temperatures between – 65 °C and 150 °C, operating at voltages not exceeding 600 V r.m.s and frequencies not exceeding 2 000 Hz. These cables are suitable for airframe use without additional protection. In case of conflict between this standard and other referenced documents the requirements of this standard shall take precedence.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2083, *Aerospace series — Copper and copper alloys conductors for electrical cables — Product standard*

EN 2235, *Aerospace series — Single and multicore electrical cables, screened and jacketed*

EN 3475-100 (all parts), *Aerospace series — Cables, electrical, aircraft use — Test methods — Part 100: General*

EN 4611-007, *Aerospace series — Cables, electrical, for general purpose, single and multicore assembly — XLETFE Family — Part 007: Nickel plated copper — Operating temperatures between – 65 °C and 150 °C — Dual extruded wall for open applications — UV laser printable — Product standard<sup>1)</sup>*

EN 4612-002, *Aerospace series — Cables, electrical, for general purpose, single and multicore assembly — XLETFE Family — Jacketed or screened and jacketed — Part 002: General*

EN 9133, *Aerospace series Quality management systems — Qualification procedure for aerospace standard parts*

## 3 Terms, definitions and symbols

For the purposes of this document, the terms, definitions and symbols given in EN 3475-100 apply.

---

1) Published as ASD-STAN Prestandard at the date of publication of this standard ([www.asd-stan.org](http://www.asd-stan.org)).

## 4 Materials and construction

### 4.1 Materials

These cables shall consist of the following:

- cores according to EN 4611-007;
- number of cores 1 (one) to 4 (four).

2 (two) core to 4 (four) core shall be twisted together according to EN 2235.

Filler cores shall not be permitted.

Screen:

- nickel plated copper stranded woven screen;
- for dimensions of strands, see Table 1;
- material according to EN 2083, tests according to EN 3475-100;
- construction according to EN 2235.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

Outer jacket:

- XLETFE;
- it shall be possible to mark the jacket by UV laser printing.  
SIST EN 4612-012:2011  
<https://standards.iteh.ai/catalog/standards/sist/c58/a314-e51f-4841-b22f-7c743bb88b04/sist-en-4612-012-2011>

### 4.2 Construction

See Table 1.

Table 1 — Multicore screened and jacketed

Number of cores	Code for nominal section	AWG <sup>a</sup>	Linear resistance at 20 °C Ω/km max.	Screen strands nominal diameter mm	Jacket thickness mm min.	External diameter mm max.	Mass kg/km max.
1	001 <sup>b</sup>	26	160,0	0,10	0,15	1,98	7,89
	002 <sup>b</sup>	24	114,0			2,11	9,54
	004	22	60,0			2,26	11,76
	006	20	33,2			2,47	15,30
	010	18	21,1	0,13	0,18	2,77	19,79
	012	16	15,3			3,05	25,10
	020	14	10,9			3,40	33,04
	030	12	6,8			3,91	46,60
2	001 <sup>b</sup>	26	164,8	0,10	0,15	3,02	13,30
	002 <sup>b</sup>	24	117,4			3,28	16,80
	004	22	61,8			3,65	20,90
	006	20	34,2	0,13	0,18	4,10	28,10
	010	18	21,7			4,66	36,60
	012	16	15,8			5,25	47,40
	020	14	11,2			5,92	61,61
	030	12	7,0			6,83	90,70
3	001 <sup>b</sup>	26	164,8	0,10	0,15	3,17	17,20
	002 <sup>b</sup>	24	117,4			3,47	22,10
	004	22	61,8			3,88	27,90
	006	20	34,2	0,13	0,18	4,36	38,10
	010	18	21,7			4,97	50,40
	012	16	15,8			5,60	65,90
	020	14	11,2			6,31	85,72
	030	12	7,0			7,47	129,00
4	001 <sup>b</sup>	26	164,8	0,10	0,15	3,48	21,30
	002 <sup>b</sup>	24	117,4			3,79	27,60
	004	22	61,8			4,23	35,00
	006	20	34,2	0,13	0,18	4,76	48,40
	010	18	21,7			5,45	64,30
	012	16	15,8			6,15	84,60
	020	14	11,2			7,01	111,46
	030	12	7,0			8,24	167,00

<sup>a</sup> AWG = Closest American Wire Gage.<sup>b</sup> Nickel plated copper alloy component conductor.

### 4.3 Colour coding of cores and jacket

See EN 4612-002.

## 5 Required characteristics

According to EN 2235 and EN 3475-100.

See Table 2.

**Table 2**

EN 3475-	Test	Details
201	Visual examination	Applicable
202	Mass	Applicable; see Table 1.
203	Dimensions	Applicable; see Table 1.
–	Lay Factor	Less than 3 in accordance with Annex A (normative).
–	Screen coverage, see EN 2235.	Applicable not less than 85 % in accordance with Annex A (normative).
301	Ohmic resistance per unit length <i>iTech STANDARD PREVIEW</i>	Applicable; see Table 1.
302	Voltage proof test <i>(standards.iteh.ai)</i>	Applicable
303	Insulation resistance <i>SIST EN 4612-012:2011</i> <a href="https://standards.iteh.ai/catalog/standards/sist/e585a314-e51f-4841-b22f-7c743bb88b04/sist-en-4612-012">https://standards.iteh.ai/catalog/standards/sist/e585a314-e51f-4841-b22f-7c743bb88b04/sist-en-4612-012</a> <i>(95±2) °C, 1 MΩ.km minimum</i>	Applicable <i>(20±2) °C, 500 MΩ.km minimum</i> <i>(95±2) °C, 1 MΩ.km minimum</i>
304	Surface resistance	Not applicable
305	Overload resistance	Not applicable
401	Accelerated ageing	Applicable Temperature (200 ± 3) °C
402	Shrinkage and delamination	Applicable Temperature (150 ± 5) °C Maximum shrinkage at each end of cable: Jacket: 2 mm on size 001 to 010 3 mm on size 012 to 050 Cores: 0,80 mm on size 001 to 006 1,00 mm on size 010 to 012 1,20 mm on size 020 to 030

continued