

**Aeronautika - Kabli, električni, za splošne namene, eno- in večžilni - Družina XLETFE - Oplaščeni ali zaslonjeni in oplaščeni - 008. del: Posrebreni baker - Obratovalne temperature med –65 °C in 150 °C - Enojno ekstrudirana izolacija za zunanjo uporabo, s plaščem in zaslonom (pletenica) - Možnost UV-laserskega tiskanja - Standard za izdelek**

Aerospace series - Cables, electrical, for general purpose, single and multicore assembly  
XLETFE Family jacketed or screened and jacketed - Part 008: Silver plated copper -  
Operating temperatures, between -65 °C and 150 °C - single extruded wall for open  
applications, with jacket and screen (braid) - UV laser printable - Product standard

Luft- und Raumfahrt - Ein- und mehrdrige elektrische Leitungen für allgemeine Verwendung - XLETFE Familie - Mit Mantel oder geschirmt und Mantel - Teil 008: Kupfer versilbert - Betriebstemperaturen zwischen –65 °C und 150 °C - Einfach extrudierte Isolierung für externe Verwendung, mit Mantel und Schirm (Geflecht) - UV-Laser bedruckbar - Produktnorm

Série aérospatiale -Câbles, électriques, d'usage général, mono et multiconducteurs - Famille XLETFE - Gainés ou blindés et gainés - Partie 008 : Cuivre argenté - Températures de fonctionnement comprises entre – 65 °C et 150 °C - Fil simple isolé pour applications externes, gainé et blindé (tressé) - Marquable au laser UV - Norme de produit

**Ta slovenski standard je istoveten z: EN 4612-008:2011**

**ICS:**

49.060      Letalska in vesoljska      Aerospace electric  
                  električna oprema in sistemi      equipment and systems

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 4612-008:2011

<https://standards.iteh.ai/catalog/standards/sist/8d83ffec-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008-2011>

**EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM**

**EN 4612-008**

October 2011

ICS 49.060

English Version

Aerospace series - Cables, electrical, for general purpose,  
single and multicore assembly XLETFE Family jacketed or  
screened and jacketed - Part 008: Silver plated copper -  
Operating temperatures, between - 65 °C and 150 °C - single  
extruded wall for open applications, with jacket and screen  
(braid) - UV laser printable - Product standard

Série aérospatiale - Câbles, électriques, d'usage général,  
mono et multiconducteurs - Famille XLETFE - Gainés ou  
blindés et gainés - Partie 008: Cuivre argenté -  
Températures de fonctionnement comprises entre - 65 °C  
et 150 °C - Fil simple isolé pour applications externes,  
gainé et blindé (tressé) - Marquable au laser UV - Norme  
de produit

Luft- und Raumfahrt - Ein- und mehradrig elektrische  
Leitungen für allgemeine Verwendung - XLETFE Familie -  
Mit Mantel oder geschirmt und Mantel - Teil 008: Kupfer  
versilbert - Betriebstemperaturen zwischen - 65 °C und 150  
°C - Einfach extrudierte Isolierung für externe Verwendung,  
mit Mantel und Schirm (Geflecht) - UV-Laser bedruckbar -  
Produktnorm

**ITEH STANDARD PREVIEW**  
**(standards.iteh.ai)**

This European Standard was approved by CEN on 20 August 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

## Contents

	Page
<b>Foreword.....</b>	<b>3</b>
<b>1 Scope .....</b>	<b>4</b>
<b>2 Normative references .....</b>	<b>4</b>
<b>3 Terms, definitions and symbols.....</b>	<b>4</b>
<b>4 Materials and construction .....</b>	<b>5</b>
<b>5 Required characteristics.....</b>	<b>7</b>
<b>6 Quality assurance .....</b>	<b>10</b>
<b>7 Designation .....</b>	<b>11</b>
<b>8 Identification and marking .....</b>	<b>11</b>
<b>9 Packaging, labelling and delivery lengths .....</b>	<b>11</b>
<b>10 Technical specification .....</b>	<b>11</b>
<b>Annex A (normative) Formulae for calculating braid details.....</b>	<b>12</b>
<b>A.1 The filling factor <math>K_f</math> is given by the following formula.....</b>	<b>12</b>
<b>A.2 Lay factor.....</b>	<b>12</b>
<b>A.3 Coverage.....</b>	<b>12</b>

SIST EN 4612-008:2011

https://standards.iteh.ai/catalog/standards/sist/8d83ffec-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008-2011

## Foreword

This document (EN 4612-008:2011) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2012, and conflicting national standards shall be withdrawn at the latest by April 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## The STANDARD PREVIEW (standards.iteh.ai)

SIST EN 4612-008:2011

<https://standards.iteh.ai/catalog/standards/sist/8d83ffec-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008-2011>

## 1 Scope

This European Standard specifies the characteristics of UV laser printable jacket, silver plated copper conductor, electrical cables Crosslinked Ethylene Tetra Fluoro Ethylene co-polymer (XLETFE) family for use in the on-board electrical systems of aircraft at operating temperatures between – 65 °C and 150 °C, operating at voltages not exceeding 600 V r.m.s and frequencies not exceeding 2 000 Hz. These cables are suitable for airframe use without additional protection when the jacket is present. When the jacket is stripped back the cores may need additional protection. In case of conflict between this standard and other referenced documents the requirements of this standard shall take precedence.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2083, Aerospace series — Copper and copper alloys conductors for electrical cables — Product standard

EN 2235, Aerospace series — Single and multicore electrical cables, screened and jacketed

EN 3475-100 (all parts), Aerospace series — Cables, electrical, aircraft use — Test methods — Part 100: General

EN 4611-002, Aerospace series — Cables, electrical, for general purpose, single and multicore assembly — XLETFE Family — Part 002: General<sup>1)</sup>

EN 4611-005, Aerospace series — Cables, electrical, for general purpose, single and multicore assembly — XLETFE Family — Part 005: Silver plated copper — Operating temperatures, between – 65 °C and 150 °C — Single extruded wall for enclosed applications — SIST EN 4612-008:2011 — Product standard<sup>1)</sup>  
<https://standards.iteh.ai/catalog/standards/sist/8d83ffec-4c30-4c02-9aa7>

EN 4612-002, Aerospace series — Cables electrical, for general purpose, single and multicore assembly — XLETFE Family — Jacketed or screened and jacketed — Part 002: General

EN 9133, Aerospace series — Quality management systems — Qualification procedure for aerospace standard parts

## 3 Terms, definitions and symbols

For the purposes of this document, the terms, definitions and symbols given in EN 3475-100 apply.

---

1) Published as ASD-STAN Prestandard at the date of publication of this standard ([www.asd-stan.org](http://www.asd-stan.org)).

## 4 Materials and construction

### 4.1 Materials

These cables shall consist of the following:

- cores according to EN 4611-005;
- number of cores 1 (one) to 4 (four).

2 (two) core to 4 (four) core shall be twisted together according to EN 2235.

Filler cores shall not be permitted.

Screen:

- silver plated copper stranded woven screen;
- for dimensions of strands, see Table 1;
- material according to EN 2083, tests according to EN 3475-100;
- construction according to EN 2235.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

Outer jacket:

- XLETFE;
- it shall be possible to mark the jacket by UV laser printing; <https://standards.iteh.ai/standard/standards/standards/ffec-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008-2011>
- minimum thickness single core and 2 (two) core shall be 0,13 mm;
- minimum thickness 3 (three) core and 4 (four) core shall be 0,15 mm.

### 4.2 Construction

See Table 1.

Table 1 — Multicore screened and jacketed

Number of cores	Code for nominal section	AWG <sup>a</sup>	Linear resistance at 20 °C Ω/km max.	Screen strands nominal diameter mm	External diameter mm max.	Mass kg/km max.
1	001 <sup>b</sup>	26	149,0	0,10	1,72	6,54
	002 <sup>b</sup>	24	106,0		1,81	7,40
	004	22	55,3		1,98	9,66
	006	20	31,0		2,25	13,30
	010	18	19,6	0,13	2,49	18,92
	012	16	14,9		2,72	21,85
	020	14	10,2		3,19	30,18
	030	12	6,4		3,64	42,08
2	001 <sup>b</sup>	26	153,5	0,10	2,54	10,43
	002 <sup>b</sup>	24	109,2		2,72	12,53
	004	22	57,0		3,06	16,96
	006	20	32,0		3,60	24,09
	010	18	20,2	0,13	4,08	32,34
	012	16	15,4		4,54	39,12
	020	14	10,5		5,48	55,96
	030	12	6,6		6,44	83,55
3	001 <sup>b</sup>	26	153,5	0,10	2,67	14,16
	002 <sup>b</sup>	24	109,2		2,87	16,92
	004	22	57,0		3,23	22,56
	006	20	32,0		3,82	32,72
	010	18	20,2	0,13	4,33	44,56
	012	16	15,4		4,83	54,43
	020	14	10,5		5,91	79,79
	030	12	6,6		6,88	118,73
4	001 <sup>b</sup>	26	153,5	0,10	2,88	17,38
	002 <sup>b</sup>	24	109,2		3,10	21,15
	002	22	57,0		3,51	28,30
	004	20	32,0		4,17	41,54
	006	18	20,2	0,13	4,75	56,99
	010	16	15,4		5,30	69,99
	012	14	10,5		6,50	103,10
	020	12	6,6		7,59	154,41

<sup>a</sup> AWG = Closest American Wire Gage.<sup>b</sup> Silver plated copper alloy component conductor.

### 4.3 Colour coding of cores and jacket

See EN 4611-002.

## 5 Required characteristics

According to EN 2235 and EN 3475-100.

See Table 2.

**Table 2**

EN 3475-	Test	Details
201	Visual examination	Applicable
202	Mass	Applicable; see Table 1.
203	Dimensions	Applicable; see Table 1.
–	Lay Factor	Less than 3 in accordance with Annex A (normative).
–	Screen coverage, see EN 2235.	Applicable not less than 85 % in accordance with Annex A (normative).
301	Ohmic resistance per unit length <i>iTech STANDARD PREVIEW</i> <a href="https://standards.iteh.ai/catalog/standards/sist/8d83ffcc-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008">https://standards.iteh.ai/catalog/standards/sist/8d83ffcc-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008</a>	Applicable; see Table 1.
302	Voltage proof test <i>(standards.iteh.ai)</i>	Applicable
303	Insulation resistance  <i>SIST EN 4612-008:2011</i> <a href="https://standards.iteh.ai/catalog/standards/sist/8d83ffcc-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008">https://standards.iteh.ai/catalog/standards/sist/8d83ffcc-4c30-4c02-9aa7-fa17fdc5953f/sist-en-4612-008</a>	Applicable  (20 ± 2) °C, 500 MΩ.km minimum (95 ± 2) °C, 1 MΩ.km minimum
304	Surface resistance	Applicable 12 500 MΩ.mm minimum
305	Overload resistance	Not applicable
401	Accelerated ageing	Applicable Temperature (200 ± 3) °C
402	Shrinkage and delamination	Applicable Temperature (150 ± 5) °C Maximum shrinkage at each end of cable: Jacket: 2 mm on size 001 to 010 3 mm on size 012 to 030 Cores: 0,80 mm on size 001 to 006 1,00 mm on size 010 to 012 1,20 mm on size 020 to 030

continued