

SLOVENSKI STANDARD SIST EN 12512:2002

01-julij-2002

@'gYbY'_cbglfi _W]'Y'!'DfYg_i gb]'dcghcd_]'!'7]_`] bc'dfYg_i ýUb'Y'gdc'Yj 'n a Y\ Ubg_]a |'j Ynb]a |'gfYXghj |

Timber structures - Test methods - Cyclic testing of joints made with mechanical fasteners

Holzbauwerke - Prüfverfahren - Zyklische Prüfungen von Anschlüssen mit mechanischen Verbindungsmitteln **iTeh STANDARD PREVIEW**

Structures en bois - Méthodes d'essai - Essais cycliques d'assemblages réalisés par organes mécaniques

SIST EN 12512:2002

https://standards.iteh.ai/catalog/standards/sist/82e23cd2-e11c-40ad-8ca0-

Ta slovenski standard je istoveten z: EN 12512-2001

ICS:

21.060.01 Vezni elementi na splošno Fasteners in general 91.080.20 Lesene konstrukcije Timber structures

SIST EN 12512:2002 en

SIST EN 12512:2002

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 12512:2002

https://standards.iteh.ai/catalog/standards/sist/82e23cd2-e11c-40ad-8ca0-384618804f92/sist-en-12512-2002

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 12512

November 2001

ICS 21.060.01; 91.080.20

English version

Timber structures - Test methods - Cyclic testing of joints made with mechanical fasteners

Structures en bois - Méthodes d'essai - Essais cycliques d'assemblages réalisés par organes mécaniques

Holzbauwerke - Prüfverfahren - Zyklische Prüfungen von Anschlüssen mit mechanischen Verbindungsmitteln

This European Standard was approved by CEN on 5 October 2001.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

SIST EN 12512:2002

https://standards.iteh.ai/catalog/standards/sist/82e23cd2-e11c-40ad-8ca0-384618804f92/sist-en-12512-2002



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

		page
Forew	word	3
Introd	duction	4
1 Sc	cope	5
	ormative references	
	erms and definitions	
	ymbols and abbreviations	
•	equirements	
	est methods	
6.1	Principles	
6.2	Apparatus	
6.3	Preparation of the specimens	
6.3.1	Conditioning	
6.3.2	Test laboratory	11
6.3.3	Test laboratory Moisture content	11
6.4	Procedures	11
6.4.1	Procedures	11
6.4.2	Complete procedure	11
6.4.3	Short procedureSIST EN 12512:2002	12
7 Re	esults	<u>a01</u>
	20461000482111 12512 2002	13

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 124 "Timber structures", the secretariat of which is held by DS.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2002, and conflicting national standards shall be withdrawn at the latest by May 2002.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 12512:2002</u> https://standards.iteh.ai/catalog/standards/sist/82e23cd2-e11c-40ad-8ca0-384618804f92/sist-en-12512-2002

Introduction

Developments in the field of load-bearing engineered timber structures in seismic regions require that joints made with mechanical fasteners be tested to obtain information about their ductility, dissipation of energy and impairment of strength under cyclic loading.

This standard lays down general principles, which should be followed in order to achieve comparability of results from investigations carried out in different laboratories.

For different purposes two different testing procedures are considered: a general one, when the determination of the complete cyclic load-slip performance is required (complete procedure), and a particular one when only the determination of the main performances at a pre-determined ductility level is required (short procedure).

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 12512:2002</u> https://standards.iteh.ai/catalog/standards/sist/82e23cd2-e11c-40ad-8ca0-384618804f92/sist-en-12512-2002

1 Scope

This European Standard specifies a test method for determining the ductility, impairment of strength and energy dissipation properties of joints made with mechanical fasteners under cyclic loading.

NOTE This standard is written, for uniformity, in terms of direct axial loads and their effects only. The standard is, however, also appropriate to the determination of the moment resisting properties of joints.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 26891, Timber structures - Joints made with mechanical fasteners - General principles for the determination of strength and deformation characteristics (ISO 6891:1983).

3 Terms and definitions iTeh STANDARD PREVIEW

For the purposes of this European Standard, the following terms and definitions apply:

3.1

cyclic load

SIST EN 12512:2002

alternative load in compression and tension log/standards/sist/82e23cd2-e11c-40ad-8ca0-384618804f92/sist-en-12512-2002

3.2

maximum load

maximum joint load reached during test, F_{max} , see Figure 2

3.3

yield load

load corresponding to the entry into the plastic range. When the load-slip curve presents two well-defined linear parts, the yield values are determined by the intersection between these two lines (see Figure 1 a)). When the load-slip curve does not present two well defined linear parts, the yield values are determined by the intersection of the following two lines: the first line will be determined as that drawn through the point on the load slip curve corresponding to 0,1 F_{max} and the point on the load-slip curve corresponding to 0,4 F_{max} ; the second line is the tangent having an inclination of 1/6 of the first line (see Figure 1 b))

3.4

ultimate load

joint load corresponding to

- a) failure; or
- b) 80 % of the maximum load for a slip of less than 30 mm; or
- c) a joint slip of 30 mm whichever occurs first in the test, see Figure 2

3.5

yield slip

joint slip corresponding to the yield load, see Figures 1 a) and 1 b)

3.6

ultimate slip

joint slip corresponding to the ultimate load, see Figure 2

3.7

ductility

ability of the joint to undergo large amplitude slip in the plastic range without a substantial reduction of strength. It is measured by the ratio between ultimate slip and yield slip,

$$D = V_u/V_v$$
.

NOTE The above definitions are intended with reference to envelop load-slip cycle loops curves, but they may also be used for monotonic load-slip curves.

3.8


impairment of strength

reduction in the load when attaining a given joint slip from the first to the third cycle of the same amplitude, see Figure 3: The impairment of strength is measured as ΔF where $\Delta F = I\Delta F_cI$ in the compression side and $\Delta F = I\Delta F_tI$ in the tension side


3.9 iTeh STANDARD PREVIEW

dissipation of energy

property of a joint which, for the purposes of this European Standard, is measured as the equivalent viscous damping ratio by hysteresis. It is a non-dimensional parameter expressing the hysteresis damping properties of the joint and is measured as the ratio between the dissipated energy in one half cycle and the available potential energy multiplied by 2π , see Figure 4: The equivalent viscous damping ratio is defined as $v_{eq} = E_d/(2\pi E_p)$ 38461880492/sist-en-12512-2002



a) Definition of yield values for a load-slip curve with two well-defined linear parts



b) Definition of yield values for a load-slip curve without two well-defined linear parts

Key

F Load

F_{max} Maximum load

 $F_{\rm v.}$ Yield load

V Slip

v_{y,} Yield slip

Figure 1 - Definition of yield values for a load-sup curve