



SLOVENSKI STANDARD SIST ETS 300 110 E1:2003

01-december-2003

Digitalno omrežje z integriranimi storitvami (ISDN) – Kategorija nosilne vodovne storitve za prenosno hitrost 64 kbit/s in 8 kHz za strukturirane signale, ki se uporabljajo za prenos zvokovnih podatkov s 3,1 kHz – Opis storitve

Integrated Services Digital Network (ISDN); Circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer; Service description

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 110 E1:2003](https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-0c6616a1b17b/sist-ets-300-110-e1-2003)

Ta slovenski standard je istoveten z: <https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-0c6616a1b17b/sist-ets-300-110-e1-2003> **ETS 300 110 Edition 1**

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST ETS 300 110 E1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 110 E1:2003

<https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 110

August 1992

Source: ETSI TC-NA

Reference: DE/NA-012237

ICS: 33.080

Key words: ISDN, bearer service

**Integrated Services Digital Network (ISDN);
Circuit-mode 64 kbit/s 8 kHz structured bearer
service category usable for 3,1 kHz audio
information transfer
Service description**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1992. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 110 E1:2003](https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003>

Contents

Foreword	5
1 Scope	7
2 Normative references	8
3 Definitions	8
4 Symbols and abbreviations	9
5 Description	9
6 Procedures	10
6.1 Provision and withdrawal	10
6.2 Normal procedures	11
6.2.1 Originating the call (call establishment).....	11
6.2.2 Indications during call establishment.....	11
6.2.3 Terminating the call	11
6.3 Exceptional procedures	11
6.3.1 Situations at the calling user side	11
6.3.2 Situations at the called user side.....	12
6.3.3 Situations due to network conditions.....	12
6.3.4 Retention of call information.....	12
7 Intercommunication considerations.....	12
7.1 Interworking with non-ISDNs	12
7.2 Interworking with private ISDNs.....	12
8 Interaction with other supplementary services	13
9 Static description of the service using attributes	13
9.1 Low layer attributes	13
9.1.1 Information transfer attributes	13
9.1.2 Access attributes.....	14
9.2 High layer attributes	14
9.3 General attributes	14
10 Dynamic description	14
Annex A (informative): Bibliography	15
History.....	16

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 110 E1:2003](https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Network Aspects (NA) Technical Committee of the European Telecommunications Standards Institute (ETSI).

In accordance with CCITT Recommendation I.130 [1], the following three level structure is used to describe the supplementary telecommunications services by European public telecommunications operators under the pan-European Integrated Services Digital Network (ISDN):

- Stage 1: is an overall service description, from the user's standpoint;
- Stage 2: identifies the functional capabilities and information flows needed to support the service described in stage 1; and
- Stage 3: defines the signalling system protocols and switching functions needed to implement the service described in stage 1.

This ETS details the stage 1 aspects (overall service description) for the circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer. The stage 2 and 3 aspects are detailed in a general form in documents CCITT Recommendation Q.71 (an ETSI version is currently under development) and ETS 300 102 (1990), respectively.

The circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer corresponds to the service which is currently offered in the Public Switched Telephone Network (PSTN). This bearer service category provides for the transfer of speech and of 3,1 kHz bandwidth audio information such as voice band data via modems, facsimile groups 1, 2 and 3 information.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 110 E1:2003](https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 110 E1:2003](https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/ebf73d85-111e-4d2d-90cb-6c661b81b17b/sist-ets-300-110-e1-2003>

1 Scope

This standard defines the stage one of the circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators. Stage one is an overall service description from the user's point of view (see CCITT Recommendation I.130 [1]), but does not deal with the details of the human interface itself.

This standard defines the interworking requirements of private ISDNs with the public ISDN.

In addition this standard specifies the base functionality where the service is provided to the user via a private ISDN.

This standard does not specify the additional requirements where the service is provided to the user via a telecommunications network that is not an ISDN but does include interworking requirements of other networks with the public ISDN.

Charging principles are outside the scope of this standard.

The values of the general attributes are outside the scope of this standard.

The circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer corresponds to the service which is currently offered in the Public Switched Telephone Network (PSTN). This bearer service category provides for the transfer of speech and of 3,1 kHz bandwidth audio information such as voice band data via modems, facsimile groups 1, 2 and 3 information.

The digital signal at the coincident S and T reference point (see CCITT Recommendation I.411 [2]) conforms to CCITT Recommendation G.711 [3] (A-law).

The circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer is intended to support speech and 3,1 kHz bandwidth audio information transfer between reference points. Each of these reference points can be either an S or coincident S and T reference points.

NOTE: Network operators can also provide information transfer with the same attributes where the reference point is T.

This standard is applicable to the stage two and stage three standards for the ISDN circuit-mode 64 kbit/s 8 kHz structured bearer service category usable for 3,1 kHz audio information transfer. The terms "stage two" and "stage three" are also defined in CCITT Recommendation I.130 [1]. Where the text indicates the status of a requirement (i.e. as strict command or prohibition, as authorisation leaving freedom, or as a capability or possibility), this shall be reflected in the text of the relevant stage two and stage three standards.

Furthermore, conformance to this standard is met by conforming to the stage three standards with the field of application appropriate to the equipment being implemented. Therefore no method of testing is provided for this standard.