



SLOVENSKI STANDARD

SIST EN 14363:2016

01-maj-2016

Nadomešča:

SIST EN 14363:2005

SIST EN 15686:2011

SIST EN 15687:2011

Železniške naprave - Preskušanje in simuliranje vozniških karakteristik pri prevzemu železniških vozil - Preskušanje obnašanja med vožnjo in mirovanjem

Railway applications - Testing and Simulation for the acceptance of running characteristics of railway vehicles - Running Behaviour and stationary tests

(standards.iteh.ai)

Bahnanwendungen - Zulassungsprozess bezüglich der fahrtechnischen Eigenschaften von Eisenbahnfahrzeugen - Prüfung des Fahrverhaltens und stationäre Versuche

<https://standards.iteh.ai/catalog/standards/sist/544e8592-0758-4514-8e42-18bf882eac/sist-en-14363-2016>

Applications ferroviaires - Essais en vue de l'homologation du comportement dynamique des véhicules ferroviaires - Essais en ligne et à poste fixe

Ta slovenski standard je istoveten z: EN 14363:2016

ICS:

45.060.01 Železniška vozila na splošno Railway rolling stock in general

SIST EN 14363:2016

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 14363:2016

<https://standards.iteh.ai/catalog/standards/sist/544e8592-0758-4514-8e42-18bf882eac/sist-en-14363-2016>

EUROPEAN STANDARD

EN 14363

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2016

ICS 45.060.01

Supersedes EN 14363:2005, EN 15686:2010, EN
15687:2010

English Version

Railway applications - Testing and Simulation for the acceptance of running characteristics of railway vehicles - Running Behaviour and stationary tests

Applications ferroviaires - Essais et simulations en vue
de l'homologation des caractéristiques dynamiques des
véhicules ferroviaires - Comportement dynamique et
essais stationnaires

Bahnanwendungen - Versuche und Simulationen für
die Zulassung der fahrtechnischen Eigenschaften von
Eisenbahnfahrzeugen - Fahrverhalten und stationäre
Versuche

This European Standard was approved by CEN on 19 September 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

(standards.iteh.ai)

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

<https://standards.iteh.ai/catalog/standards/sist/544e8592-0758-4514-8e42-18168877a2c1/sist-en-14363-2016>

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword.....	6
Introduction	7
1 Scope.....	9
2 Normative references.....	11
3 Terms and definitions	12
4 Deviations from requirements.....	14
5 Test requirements	15
5.1 Measuring uncertainty.....	15
5.2 Test extent	15
5.2.1 General.....	15
5.2.2 Fault modes	15
5.3 Test vehicle.....	16
5.3.1 Selection and status of the vehicle.....	16
5.3.2 Loading conditions	16
5.3.3 Distribution of static wheel forces.....	17
5.4 Assessment of test result.....	17
5.5 Documentation of test.....	18
6 First stages assessment.....	19
6.1 Safety against derailment on twisted track.....	19
6.1.1 General.....	19
6.1.2 Signal processing.....	20
6.1.3 Rail test conditions.....	20
6.1.4 Vehicle test conditions	21
6.1.5 Test methods	23
6.2 Safety against derailment under longitudinal compressive forces in S-shaped curves.....	37
6.3 Evaluation of the torsional coefficient of a vehicle body	37
6.4 Determination of displacement characteristics	38
6.5 Loading of the diverging branch of a switch.....	38
6.6 Running safety in curved crossings for vehicles with small wheels.....	38
7 Second stage – dynamic performance assessment	39
7.1 General.....	39
7.2 Choice of measuring method.....	40
7.2.1 General.....	40
7.2.2 Base conditions for the use of the simplified measuring method and measurement of axle box forces.....	41
7.2.3 Simplifications for separate stability testing.....	42
7.3 Performing on-track tests	42
7.3.1 General.....	42
7.3.2 Test zones and track sections.....	48
7.3.3 Extent of tests	49
7.3.4 Test operation	50
7.4 Measured quantities and measuring points.....	50
7.5 Assessment quantities and limit values.....	52
7.5.1 General.....	52
7.5.2 Running safety.....	57

7.5.3	Track loading	58
7.5.4	Ride characteristics	58
7.6	Test evaluation	58
7.6.1	Overview	58
7.6.2	Recording the measuring signals.....	59
7.6.3	Statistical evaluation in test zones.....	60
7.6.4	Evaluation of test results in transition curves	67
7.6.5	Verification of stability	67
7.7	Documentation	67
7.7.1	General	67
7.7.2	Description of the vehicle design and status of the tested vehicle	68
7.7.3	Additional information for future extension of acceptance.....	68
7.7.4	Description of the test routes.....	68
7.7.5	Description of data capture	68
7.7.6	Description of evaluation	68
7.7.7	Test results (including additional information for model validation)	69
7.7.8	Deficiencies in reaching the target test conditions	70
7.7.9	Infrastructure conditions more severe than the target test conditions.....	70
Annex A (informative) Information on safety against derailment		71
A.1	Factors influencing the safety against derailment of vehicles running on twisted track.....	71
A.2	Evaluation and limit value for safety against derailment.....	72
A.3	Friction conditions during testing on special track	73
A.4	Special conditions for vehicles with air springs.....	75
A.5	Test twist conditions for articulated vehicles.....	76
A.6	Test twist conditions for vehicles with more than two suspension levels.....	82
A.7	Calculation of the shim sizes (test method 1).....	83
A.8	Performing and evaluating a twist test for a two-axle vehicle (test method 2).....	84
A.9	Performing and evaluation of a twist test for a vehicle with two bogies with two axles (test method 2).....	87
Annex B (informative) Computer simulations designed to examine whether the vehicle has an acceptable resistance to flange climbing derailment at low speed		95
B.1	General requirement.....	95
B.2	Computer output.....	95
B.3	Track input.....	95
B.4	Body-bogie yaw torque.....	96
B.5	Performance requirement	96
Annex C (informative) Tests for determination of the torsional coefficient of a vehicle body		98
C.1	Force-deflection measurement directly at the vehicle body	98
C.2	Force-deflection measurement at the contact points between wheel and rail after blocking of the suspension(s) between wheelset (bogie frame) and vehicle body.....	99
Annex D (informative) Determination of displacement characteristics for application with EN 15273		100

EN 14363:2016 (E)

D.1	Introduction	100
D.2	Determination of displacement characteristics	100
Annex E (informative) Assessment of the behaviour of vehicles with small wheels in curved crossings.....		106
E.1	Purpose.....	106
E.2	Area of application.....	106
E.3	Description of the crossing geometry.....	106
E.4	Test conditions.....	109
Annex F (informative) Test specification for assessment of vehicle behaviour in switches and crossings		112
F.1	Introduction	112
F.2	Definitions	112
F.3	Test conditions.....	112
F.4	Assessment of the test results	113
F.5	Documentation.....	113
Annex G (normative) Coordinate system for measured quantities		116
Annex H (informative) Operational parameters		117
Annex I (informative) Position of the different wheelsets during test.....		119
Annex J (informative) Additional track loading assessment quantities		120
J.1	General.....	120
J.2	Maximum lateral force	120
J.3	Combination of lateral and vertical forces.....	120
Annex K (informative) Evaluation and background of the rail surface damage quantity		122
Annex L (informative) Typical maximum estimated values of ride characteristics.....		124
Annex M (normative) Track geometric quality – Selection of test tracks.....		125
M.1	Basis of evaluation	125
M.2	Assessment quantities for track geometric quality.....	125
M.3	Different measuring systems.....	126
M.4	Target test conditions.....	127
M.5	Reporting	128
Annex N (informative) Background of track quality description.....		129
Annex O (normative) Rail profile measurement		130
O.1	General.....	130
O.2	Manual measurements.....	130
O.3	Automatic measurements	130
Annex P (normative) Requirements for evaluation of equivalent conicity		131
Annex Q (informative) Radial steering index		132

Q.1	Introduction.....	132
Q.2	Calculation of radial steering index.....	133
Annex R (normative) Statistical evaluation		136
R.1	Objectives and principles of statistical analysis.....	136
R.2	Determination of the percentiles for each track section.....	137
R.3	Preparation of the random samples	137
R.4	One-dimensional analysis for estimated maximum values	138
R.5	Two-dimensional analysis for estimated values.....	138
R.6	Multiple regression analysis for estimated values.....	139
R.7	Statistical evaluation for the overturning criterion.....	141
R.8	Regression assumptions	142
Annex S (informative) Running behaviour of special vehicles.....		144
S.1	General	144
S.2	Vehicle design and classification	144
S.3	Use of the simplified measuring method	145
S.4	Test conditions	145
S.5	Specific limit value	145
Annex T (informative) Simulation of on-track tests		146
T.1	Introduction.....	146
T.2	Fields of application.....	146
T.3	Validation	148
T.4	Input	162
T.5	Output.....	165
T.6	Documentation	166
T.7	Examples for model validation according to Method 1	166
Annex U (informative) Extension of acceptance.....		174
U.1	General	174
U.2	Determination of the safety factor	180
U.3	Dispensation.....	180
U.4	Check for base conditions for simplified method	181
U.5	Requirements depending on the initial approval.....	181
Annex V (normative) Symbols.....		183
Annex W (informative) List with the main technical changes compared to EN 14363:2005, EN 15686:2010 and EN 15687:2010.....		187
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC.....		190
Bibliography		193

EN 14363:2016 (E)**European foreword**

This document (EN 14363:2016) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2016, and conflicting national standards shall be withdrawn at the latest by September 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14363:2005, EN 15686:2010 [4], EN 15687:2010 [5].

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

It is not necessary to require further assessment of vehicles which have been already assessed under the conditions of previous standards in this field. Test results achieved under the conditions of the previous standards remain valid and can be used for the extension of acceptance of a vehicle or vehicle design according to this standard.

SIST EN 14363:2016

<https://standards.iteh.ai/catalog/standards/sist/544e8592-0758-4514-8e42-186cc8200c/sist-en-14363-2016>

Prior to the first issue of this standard, national procedures were applied for vehicle acceptance, for example in Germany or UK. The underlying principles that were applied in these earlier standards are also incorporated in this standard. The fundamentals have not been changed but the formulation of the requirements has been made consistent. Therefore it is considered that also vehicles that were previously approved utilizing these earlier requirements have an equal status compared to vehicles that are approved according to this standard. This applies to the infrastructure and operating conditions that were considered in the earlier approval. This includes also a use as reference vehicle for extension of acceptance.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Acceptable running characteristics of a railway vehicle (hereafter called vehicle) are essential for a safe and economic operation of a railway system. They are related to:

- the vehicle,
- the operating conditions,
- the characteristics of the infrastructure (track layout design and track quality) and
- the contact conditions of the wheel/rail interface.

The objective is to quantify the vehicle's performance under known representative conditions of operation and infrastructure.

This standard describes methods to assess the vehicle performance in the following areas:

- safety against derailment on twisted track (see 6.1);
- running safety under longitudinal compressive forces in s-shaped curves (see 6.2);
- evaluation of the torsional coefficient (see 6.3);
- determination of displacement characteristics (see 6.4);
- loading of the diverging branch of a switch (see 6.5);
- running safety in curved crossings (see 6.6);
- running safety, track loading and ride characteristics (see Clause 7).

The vehicle performance is assessed in two stages. Usually in the first stage the basic characteristics and low speed behaviour are investigated before first runs on the line under controlled operating conditions. In the second stage the running behaviour is assessed. The assessment of a vehicle according to the elements listed above can be performed either by physical testing, numerical simulation, calculation or comparison with a known solution (dispensation). Details about the requirements relating to the choice of the appropriate assessment method are given in this document.

The operational envelope (speed and cant deficiency) that the vehicle has been assessed for needs to be documented.

The establishment of this document was based on existing rules, practices and procedures. The following principles were applied:

- the railway system requires comprehensive technical rules in order to ensure an acceptable interaction of vehicle and track;
- the performance of new railway vehicles has to be evaluated and assessed before putting them into service;
- it is of particular importance that the existing level of safety and reliability is not compromised even when changes in design or operating conditions are demanded, e.g. by the introduction of higher speeds, higher vertical wheel forces, modification of the suspension, etc.
- it is possible to demonstrate compliance with the requirements of this standard by comparison of relevant parameters or by simulation if changes are made to the design or to the operating conditions;
- as the combination of all the target test conditions described is not always achievable, the compliance against the missing target test conditions can be demonstrated by other means.

Requirements on running safety under longitudinal compressive forces in S-shaped curves of certain vehicles are given in EN 15839, while EN 16235 specifies a method to get dispensation from on-track

EN 14363:2016 (E)

testing for vehicles equipped with established and standardized running gear, if certain conditions are fulfilled.

The informative Annexes A, B, C, D, E, F; Q, S, T and U contain requirements that have to be fulfilled when the annex is applied.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 14363:2016

<https://standards.iteh.ai/catalog/standards/sist/544e8592-0758-4514-8e42-18bf882eac/sist-en-14363-2016>

1 Scope

This European Standard defines the process for assessment of the running characteristics of railway vehicles for the European network of standard gauge tracks (nominally 1 435 mm).

In addition to the assessment of the running characteristics of vehicles for acceptance processes, this standard also defines quantities and dependencies that are not directly used for acceptance purposes. This information is for example intended for the validation of simulation models. It can also be used to define operating conditions outside the reference conditions to be used for the approval.

The assessment of running characteristics applies to vehicles which:

- are newly developed;
- have had relevant design modifications; or
- have changes in their operating conditions.

The assessment process is based on specified target test conditions (see 3.1) given in this document.

Experience over many years has demonstrated that vehicles complying with this standard can be operated safely on infrastructure with conditions more severe than the target test conditions, if the current general operating rules are applied. As an example it is generally current practice to restrict cant deficiency in curves below a certain radius. It may be necessary to adapt these operating rules, if a deterioration of the infrastructure conditions is observed. These operating rules are defined on a national basis. The procedure to evaluate these operating rules is out of the scope of this standard.

NOTE 1 There are margins included in the specified limit values and the statistical evaluation. They cannot be quantified, but they explain why vehicles can also be operated at full speed and cant deficiency in many cases outside of the target test conditions.

This standard also enables the demonstration of compliance against the target test conditions for the case that their combination is not achievable during tests. It is also possible to carry out the assessment of a vehicle for limited test conditions such as test zones 1 and 2 or reduced speed or reduced cant deficiency. In this case the approval of the vehicle shall be restricted accordingly.

NOTE 2 National regulations sometimes allow the increase or decrease of the values for speed, curve radius and cant deficiency for local operation based on safety considerations taking into account the local characteristics of the infrastructure (track layout, track structure, track geometrical quality and contact conditions). These local characteristics can be different from those included in the assessment for the vehicle acceptance.

NOTE 3 The methods of this standard can also be applied to gather information about the compatibility between the vehicle and infrastructure with conditions more severe than the target test conditions. The results of such investigations can be used to determine safe operating rules for such infrastructure conditions.

Where testing the vehicle demonstrates that the performance of a vehicle complies with the requirements of this standard when operating at maximum speed and maximum cant deficiency under infrastructure conditions that are more severe than the target test conditions, the obtained results are accepted and there is no need to carry out additional tests to fulfil the requirements defined in this standard.

This standard addresses four aspects:

1) Vehicles

The assessment of the running characteristics applies principally to all railway vehicles. The document contains acceptance criteria for all types of vehicles with nominal static vertical wheelset forces up to 225 kN (of the highest loaded wheelset of the vehicle in the assessed load configuration specified in 5.3.2). In addition for freight vehicles with nominal static vertical wheelset forces up to 250 kN the

EN 14363:2016 (E)

acceptance criteria are defined. The acceptance criteria given in this document apply to vehicles designed to operate on standard gauge tracks.

2) Infrastructure

In the acceptance process the range of curve radii is defined, for which the vehicle is assessed. A vehicle accepted according to the requirements of this standard is able to be operated on all standard gauge tracks complying with EN 13803-1 and EN 13803-2.

EN 14363 also gives guidance about the handling of geometric track quality associated with the assessment.

3) Conditions of the wheel rail interface

This standard contains requirements relating to the necessary range of equivalent conicity to be included in the assessment as target test conditions.

In some national systems, either parts or all, equivalent conicities are significantly higher than the target test conditions of this standard. These cases are outside the scope of this standard. Nevertheless the methodology defined in this standard for the proof of running stability can also be used for higher equivalent conicities.

NOTE 4 In these cases running safety is demonstrated by application of existing national requirements for high equivalent conicities during stability testing. Experience shows, that it is not necessary to include the maximum occurring values of equivalent conicity in such national requirements.

4) Operating conditions

iTeh STANDARD PREVIEW
(standards.iteh.ai)

The document requires the specification of the combination of admissible speed and admissible cant deficiency as well as the loading conditions for each type of vehicle.

NOTE 5 Recommended values of cant deficiencies for broad international approval are given in informative Annex H.

This standard is not directly applicable to:

- railways with different track layout, e.g. tramways, metros and underground railways;
- railways with non-standard gauge tracks;

but assessment can be conducted by analogy with this document, e.g. the test procedures described in this standard can be applied also to vehicles operated in networks with other track gauges (e.g. 1 524 mm and 1 668 mm). The related limit values and test conditions could be different. They are specified nationally taking into account track design and operating conditions.

The strength of the vehicle and mounted parts, passengers and train crew vibration exposure, comfort, load security and effects of cross wind are out of the scope of this standard.

This document includes the assessment of track loading quantities, the quantification of track deterioration or track fatigue is out of the scope of this standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13803-1, *Railway applications — Track — Track alignment design parameters — Track gauges 1435 mm and wider — Part 1: Plain line*

EN 13803-2, *Railway applications — Track alignment design parameters — Track gauges 1 435 mm and wider — Part 2: Switches and crossings and comparable alignment design situations with abrupt changes of curvature*

EN 13848-1, *Railway applications — Track — Track geometry quality — Part 1: Characterisation of track geometry*

EN 13848-2, *Railway applications — Track — Track geometry quality — Part 2: Measuring systems — Track recording vehicles*

EN 13848-5:2008+A1:2010, *Railway applications — Track — Track geometry quality — Part 5: Geometric quality levels — Plain line*

EN 14033-1, *Railway applications — Track — Railbound construction and maintenance machines — Part 1: Technical requirements for running*

EN 15273-1, *Railway applications — Gauges — Part 1: General — Common rules for infrastructure and rolling stock*

EN 15273-2, *Railway applications — Gauges — Part 2: Rolling stock gauge*

EN 15302:2008+A1:2010, *Railway applications — Method for determining the equivalent conicity*

EN 15663:2009, *Railway applications — Definition of vehicle reference masses*

EN 15746-1, *Railway applications — Track — Road-rail machines and associated equipment — Part 1: Technical requirements for running and working*

EN 15839 *Railway applications — Testing for the acceptance of running characteristics of railway vehicles — Freight wagons — Testing of running safety under longitudinal compressive forces*

EN 15954-1, *Railway applications — Track — Trailers and associated equipment — Part 1: Technical requirements for running and working*

EN 15955-1, *Railway applications — Track — Demountable machines and associated equipment — Part 1: Technical requirements for running and working*

EN 16235, *Railway application — Testing for the acceptance of running characteristics of railway vehicles — Freight wagons — Conditions for dispensation of freight wagons with defined characteristics from on-track tests according to EN 14363*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

- 3.1 target test conditions**
conditions specified in this standard for the performance of on-track tests
- 3.2 bogie yaw resistance**
torque around the vertical axis between bogie and vehicle body required to rotate a bogie while supporting a vehicle body
- 3.3 unsprung mass**
mass of a wheelset including all components that are attached to it and which are not suspended by the primary suspension or the wheelset guidance, e.g. brake discs, gear wheels, bearings, axle boxes plus half of the primary suspension mass, half the mass of suspension links and if applicable the unsuspended part of the traction equipment
- Note 1 to entry: Sometimes it will be necessary to regard different wheelsets of a running gear separately.
- Note 2 to entry: Sometimes it will be necessary to include or exclude parts which are separately suspended with regard to the problem in question, e.g. magnetic brakes.
- 3.4 primary suspended mass**
mass between primary and secondary suspension of a running gear with two vertical suspension stages, i. e. the bogie frame together with all components attached to it, e.g. braking equipment, antennas, pipes and cables plus half of the primary and secondary suspension mass, half the mass of suspension links and traction rods and if applicable the primary suspended part of the traction equipment
- Note 1 to entry: Sometimes it will be necessary to include or exclude parts which are separately suspended with regard to the problem in question, e.g. magnetic brakes.
- 3.5 secondary suspended mass**
mass supported by the secondary suspension of a running gear, i. e. the mass of the relevant part of a vehicle body with all components attached to it, e.g. upper bolster or adapter beam plus half of the secondary suspension mass, half the mass of suspension links and traction rods and if applicable the secondary suspended part of the traction equipment
- 3.6 bogie mass**
mass of the bogie which rotates against the vehicle body around the vertical axis during the entrance into curves
- Note 1 to entry: In most cases this mass is similar to the sum of the unsprung masses and the primary suspended mass of a running gear with two or more wheelsets.
- 3.7 yaw moment of inertia of whole running gear**
moment of inertia of the mass of the running gear which rotates against the vehicle body around the vertical axis during the entrance into curves

3.8**displacement characteristics**

combination of lateral and roll displacements of a vehicle when subjected to cant excess or deficiency

3.9**running behaviour**

behaviour of a vehicle or running gear with regard to the interaction between vehicle and track covering the specific terms running safety, track loading and ride characteristics

3.10**running characteristics**

characteristics of a vehicle or running gear with regard to running behaviour, safety against derailment in twisted track and under longitudinal compressive forces in S-shaped curves, torsional coefficient of a vehicle body, displacement characteristics, loading of the diverging branch of a switch and running safety in curved crossings

3.11**equivalent conicity** **$\tan \gamma_e$**

is equal to the tangent of the cone angle $\tan \gamma_e$ of a wheelset with coned wheels whose lateral movement has the same kinematic wavelength as the given wheelset and is the relevant parameter of contact geometry on straight track and on large radius curves

Note 1 to entry: See also EN 15302.

3.12**radial steering index** **q_E**

ratio between curve radius R_c negotiable without longitudinal creepage and the actual curve radius R of the track section and it describes the radial steering capability of a free wheelset in a track section as the relevant parameter of contact geometry on small and very small radius curves

3.13**operation envelope**

given by the combinations of speed and cant deficiency for which the vehicle is intended to be operated

Note 1 to entry: See informative Annex H.

3.14**conventional technology vehicle**

vehicles which are operated under normal operating conditions and correspond completely or in those construction parts which are relevant to the running behaviour to the proven state of the art

ITh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 14363:2016

http://standards.iteh.ai/catalog/standards/sist/14363-2016/en-14363-2016