

9`Y_fca U[bYfbUnXfi y`^j cghfØ A7L]b`nUXYj Yj`nj Yn]`n`fUX]`g_]a`gdY_fca`fØFAŁ!
 BUdfUj Y`fUh_Y[UXcgY[UfGF8 gŁ!`HY b] bY`UfU`hf]gh_Y]b`dfYg_i`yYj UbY
 a YtcXY`nUfUX]`g_c`cdfYa c`j`ZY_j Yb bYa`cVa c`f`cX`8) `A<n`Xc`%\$\$\$`A<n`n
 a c`c`Xc`) \$\$`a K`!`%`XY.`DUfUa Yf]`nUfY[i`UrcfbY`bUa YbY

Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices;
 Technical characteristics and test methods for radio equipment to be used in the 25 MHz
 to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1:
 Parameters intended for regulatory purposes

Ta slovenski standard je istoveten z: EN 300 220-1 V1.2.1.2007 - +!%%

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

DSIST EN 300 220-1:2007 - - en

EN 300 220-1 V1.2.1 (1997-11)

European Standard (Telecommunications series)

**Electromagnetic compatibility and
Radio spectrum Matters (ERM);
Short range devices;
Technical characteristics and test methods for radio
equipment to be used in the 25 MHz to 1 000 MHz frequency
range with power levels ranging up to 500 mW;
Part 1: Parameters intended for regulatory purposes**



European Telecommunications Standards Institute

Reference

REN/ERM-RP08-0107-1 (21c90ioo.PDF)
formerly REN/RES-08-0107-1

Keywords

Radio, testing, SRD

ETSI Secretariat

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

X.400

c= fr; a=atlas; p=etsi; s=secretariat

Internet

secretariat@etsi.fr
<http://www.etsi.fr>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

Contents

Intellectual Property Rights.....	7
Foreword	7
1 Scope.....	8
2 Normative references	9
3 Definitions, symbols and abbreviations.....	9
3.1 Definitions	9
3.2 Symbols	10
3.3 Abbreviations.....	10
4 General	11
4.1 Presentation of equipment for testing purposes	11
4.1.1 Choice of model for type testing	11
4.1.2 Definitions of Switching Range (SR), alignment range and operational frequency range.....	11
4.1.2.1 Definition of SR.....	11
4.1.2.2 Definition of alignment range.....	11
4.1.2.3 Definition of operating frequency range.....	12
4.1.3 Definition of the categories of the alignment range (AR0, AR1, AR2 and AR3).....	12
4.1.4 Testing of equipment of category AR0	12
4.1.5 Testing of equipment of category AR1	12
4.1.6 Testing of equipment of category AR2	12
4.1.7 Testing of equipment of category AR3	12
4.1.8 Testing of equipment capable of being aligned to operate with more than one frequency separation.....	13
4.1.9 Number of samples for testing.....	13
4.1.10 Testing of a family of equipment with a total operating range in excess of each equipment's alignments range.....	14
4.1.11 Testing of equipment with alternative power levels	14
4.1.12 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)....	14
4.1.12.1 Equipment with an internal permanent or temporary antenna connector.....	14
4.1.12.2 Equipment with a temporary antenna connector.....	14
4.2 Mechanical and electrical design	15
4.2.1 General.....	15
4.2.2 Controls.....	15
4.2.3 Transmitter shut-off facility.....	15
4.2.4 Marking.....	15
4.2.4.1 Equipment identification.....	15
4.2.4.2 Regulatory marking	15
4.2.5 Receiver mute or squelch	15
4.3 Declarations by the applicant.....	15
4.4 Auxiliary test equipment.....	15
4.5 Interpretation of the measurement results	16
5 Test conditions, power sources and ambient temperatures.....	16
5.1 Normal and extreme test conditions.....	16
5.2 Test power source	16
5.2.1 External test power source	16
5.2.2 Internal test power source.....	16
5.3 Normal test conditions	17
5.3.1 Normal temperature and humidity.....	17
5.3.2 Normal test power source.....	17
5.3.2.1 Mains voltage	17
5.3.2.2 Regulated lead-acid battery power sources.....	17
5.3.2.3 Other power sources	17
5.4 Extreme test conditions.....	17
5.4.1 Extreme temperatures.....	17

5.4.1.1	Procedure for tests at extreme temperatures	17
5.4.1.1.1	Procedure for equipment designed for continuous operation	18
5.4.1.1.2	Procedure for equipment designed for intermittent operation	18
5.4.1.2	Extrem temperature ranges	18
5.4.2	Extreme test source voltages	18
5.4.2.1	Mains voltage	18
5.4.2.2	Regulated lead-acid battery power sources	18
5.4.2.3	Power sources using other types of batteries	19
5.4.2.4	Other power sources	19
6	General conditions	19
6.1	Normal test signals and test modulation	19
6.1.1	Normal test signals for analogue speech	19
6.1.2	Normal test signals for data	19
6.2	Artificial antenna	20
6.3	Test fixture	20
6.4	Test sites and general arrangements for radiated measurements	20
6.5	Modes of operation of the transmitter	21
6.6	Measuring receiver	21
7	Measurement uncertainty	21
8	Methods of measurement and limits for transmitter parameters	21
8.1	Frequency error	22
8.1.1	Definition	22
8.1.2	Method of measurement	22
8.1.3	Limits	22
8.2	Carrier power (conducted)	23
8.2.1	Definition	23
8.2.2	Method of measurement	23
8.2.3	Limits	23
8.3	Effective radiated power (radiated)	23
8.3.1	Definition	23
8.3.2	Methods of measurement	24
8.3.3	Limits	24
8.4	Response of the transmitter to modulation frequencies	25
8.4.1	Frequency deviation	25
8.4.1.1	Definition	25
8.4.1.2	Analogue signals within the audio bandwidth	25
8.4.1.2.1	Method of measurement	25
8.4.1.2.2	Limits	25
8.4.1.3	Analogue signals above the audio bandwidth	26
8.4.1.3.1	Method of measurement	26
8.4.1.3.2	Limits	26
8.4.2	Modulation depth	27
8.4.2.1	Definition	27
8.4.2.2	Analogue signals within the audio bandwidth	27
8.4.2.2.1	Method of measurement	27
8.4.2.2.2	Limits	28
8.4.2.3	Analogue signals above the audio bandwidth	28
8.4.2.3.1	Method of measurement	28
8.4.2.3.2	Limits	28
8.5	Adjacent channel power	29
8.5.1	Definition	29
8.5.2	Method of measurement	29
8.5.2.1	Method of measurement using a power measuring receiver	29
8.5.3	Limits	30
8.6	Range of modulation bandwidth for wide band equipment (> 25 kHz)	31
8.6.1	Definition	31
8.6.2	Method of measurement	31
8.6.3	Limits	31

8.7	Spurious emissions.....	31
8.7.1	Definition	32
8.7.2	Method of measuring the power level in a specified load, subclause 8.7.1 a) i)	32
8.7.3	Method of measuring the effective radiated power, subclause 8.7.1 a) ii)	32
8.7.4	Method of measuring the effective radiated power, subclause 8.7.1 b).....	33
8.7.5	Limits	33
8.8	Frequency stability under low voltage conditions.....	34
8.8.1	Definition	34
8.8.2	Method of measurement.....	34
8.8.3	Limits	34
8.9	Duty Cycle	34
8.9.1	Definitions.....	34
8.9.2	Duty cycle classes	34
9	Methods of measurement and limits for receiver parameters	35
9.1	Spurious radiation	35
9.1.1	Definition	35
9.1.2	Method of measuring the power level in a specified load, subclause 9.1.1 a) i)	35
9.1.3	Method of measuring the effective radiated power, subclause 9.1.1 a) ii)	35
9.1.4	Method of measuring the effective radiated power, subclause 9.1.1 b).....	36
9.1.5	Limits	36
9.2	Spurious response rejection and blocking/desensitization	36
9.2.1	Method of measurement.....	36
9.2.2	Performance criteria for electromagnetic compatibility	37
Annex A (normative): Radiated measurements		38
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	38
A.1.1	Outdoor test site	38
A.1.1.1	Standard position.....	39
A.1.2	Test antenna	39
A.1.3	Substitution antenna.....	39
A.1.4	Optional additional indoor site.....	40
A.2	Guidance on the use of radiation test sites.....	41
A.2.1	Measuring distance	41
A.2.2	Test antenna	41
A.2.3	Substitution antenna.....	41
A.2.4	Artificial antenna	41
A.2.5	Auxiliary cables	41
A.3	Further optional alternative indoor test site using an anechoic chamber.....	41
A.3.1	Example of the construction of a shielded anechoic chamber.....	42
A.3.2	Influence of parasitic reflections in anechoic chambers.....	42
A.3.3	Calibration of the shielded RF anechoic chamber.....	42
Annex B (normative): Specifications for adjacent channel power measurement arrangements		45
B.1	Power measuring receiver specification	45
B.1.1	IF filter.....	45
B.1.2	Variable attenuator.....	46
B.1.3	Rms value indicator	46
B.1.4	Oscillator and amplifier	46

Annex C (normative):	Technical performance of the spectrum analyser	47
Annex D (normative):	Graphic representation of the selection of equipment and frequencies for testing	48
D.1	Tests on a single sample.....	48
D.2	Tests and samples needed when the switching range is a subset of the alignment range.....	49
D.3	Tests and samples for a family of equipment where the alignment range is a subset of the total operating frequency range.....	49
D.3.1	Test scenario 1	50
D.3.2	Test scenario 2	50
Annex E (normative):	Subclauses of this EN relevant for compliance with the essential requirements of relevant EC Council Directives.....	52
History		53