

SLOVENSKI STANDARD SIST EN 13032-4:2015

01-september-2015

Svetloba in razsvetljava - Merjenje in podajanje fotometričnih podatkov sijalk in svetil - 4. del: LED-sijalke, moduli in svetila

Light and lighting - Measurement and presentation of photometric data of lamps and luminaires - Part 4: LED lamps, modules and luminaires

Licht und Beleuchtung - Messung und Darstellung photometrischer Daten von Lampen und Leuchten - Teil 4: LED-Lampen - Module und - Leuchten

Lumière et éclairage - Mesure et présentation des données photométriques des lampes et des luminaires - Partie 4: Lampes, modules et luminaires LED

https://standards.iteh.ai/catalog/standards/sist/4a7eea8f-d9d8-4012-80ff-

Ta slovenski standard je istoveten z: EN 13032-4-2015

ICS:

17.180.20 Barve in merjenje svetlobe Colours and measurement of

light

91.160.01 Razsvetljava na splošno Lighting in general

SIST EN 13032-4:2015 en,fr,de

SIST EN 13032-4:2015

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 13032-4

June 2015

ICS 17.180.20; 29.140.99

English Version

Light and lighting - Light and lighting - Measurement and presentation of photometric data of lamps and luminaires - Part 4: LED lamps, modules and luminaires

Lumière et éclairage - Mesure et présentation des données photométriques des lampes et des luminaires - Partie 4: Lampes, modules et luminaires LED Licht und Beleuchtung - Messung und Darstellung photometrischer Daten von Lampen und Leuchten - Teil 4: LED-Lampen, -Module und -Leuchten

This European Standard was approved by CEN on 19 March 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovakia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

9ad171b7d48d/sist-en-13032-4-2015



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

COII	lents	Page
Forew	ord	5
Introd	uction	6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Laboratory requirements	
4.1	General	
4.1.1	Standard Test Conditions	17
4.1.2	Tolerance Interval	18
4.2	Laboratory and Environmental Conditions	
4.2.1	Test Room	
4.2.2	Ambient Temperature	18
4.2.3	Surface Temperature (t _p -Point Temperature)	19
4.2.4	Air Movement	
4.2.5	Operating Position	20
4.3	Electrical Test Conditions and Electrical Equipment	20
4.3.1	Test Voltage and Test Current	20
4.3.2	Electrical Measurements	21
4.3.3	Electrical Power Supply (standards.iteh.ai)	
4.4	Stabilization before Measurement	
4.4.1	General <u>SIST EN-13032-42015</u>	23
4.4.2 4.4.3	LED Lamps and LED Luminaires in the literature of the lateral lateralateral lateral lateral lateral lateral lateral lateral lateral la	23
4.4.3 4.5	LED Modules9ad171b7d48d/sixt-on-19032-4-2015 Photometric and Colorimetric Measurement Instruments	∠ა იი
4.5 4.5.1	General	
4.5.1 4.5.2	Spectral Responsivity Requirements for Photometers	
4.5.3	Integrating Sphere (all Types)	
4.5.4	Goniophotometer (all Types)	
4.5.5	Luminance Meters	
	Preparation, mounting and operating conditions	
5 5.1	Ageing	
5.1 5.2	Test device	
5.2 5.3	Mounting	_
5.3.1	Operating orientation	
5.3.2	Coordinate system	
5.3.3	Photometric Centre	
5.4	Operating conditions of the LED devices	
5.4.1	General	
5.4.2	LED lamps	
5.4.3	LED modules	
5.4.4	LED luminaires	31
6	Measurement of photometric quantities	31
6.1	General	31
6.2	Measurement of total luminous flux	
6.3	Partial Luminous Flux	
6.4	Luminous efficacy	
6.5	Luminous intensity distribution and data presentation	
6.5.1	General	34

6.5.2 6.5.3	LED-lamps and LED-modules LED-luminaires	
6.6	Centre beam intensity and beam angles	
6.7	Luminance Measurements	
7	Measurement of colour quantities	.35
7.1	Colorimetric Measurements	
7.1.1 7.1.2	General aspects Correlated Colour Temperature (white LED light sources)	
7.1.3	Colour Rendering Indices (white LED light sources)	
7.1.4	Angular Colour Uniformity	.37
8	Measurement Uncertainties	
8.1 8.2	General Guidance for Measurement uncertainty budgets	
8.2.1	Common parameters to all measurements	
8.2.2	Luminous flux	.38
8.2.3 8.2.4	Luminous intensity and luminance Colour quantities	
8.2.5	Electrical power	
8.2.6	Luminous efficacy	40
9	Presentation of test results	
9.1 9.1.1	Test reportIntroduction	
9.1.1 9.1.2		
9.1.3	General information Information on the device(s) under test.R.D.P.R.E.V.E.W.	
9.1.4 9.1.5	Information on the test procedure Photometric and/or colorimetric data rds.iten.ai)	42
	A (informative) Guidance on the Application of this standard	
A.1	Generalhttps://standards.itch.ai/catalog/standards/cist/4a7cca8f-d9d8-4012-80ff	
	Tolerance Interval 9ad171b7d48d/sist-en-13032-4-2015	
A.2		
	B (informative) Stray light — Screening against stray light in a goniophotometer	
C.1	Correction factors	
	Measurement correction factors	
C.1.1	Service conversion factors	
C.2	Sensitivity coefficients	
C.3	Typical Sensitivity coefficients and tolerance intervals	
C.3.1	General	
C.3.2	Ambient temperature	
C.3.3	Measurement of a LED module at Performance Temperature	.47
C.3.4	Air movement	.50
C.3.5	Test voltage	.50
C.3.6	Spectral mismatch of photometer	.51
C.3.7	Model for Luminous Intensity Distribution	.52
Annex	D (informative) Guidance on calculating measurement uncertainties	.54
D.1	General	.54

D.2	Uncertainty budget	54
D.3	Example of measurement uncertainties	55
	E (informative) Guidance for determining rated values of photometric quantities of LED luminaires	61
E.1	Introduction	61
E.2	Rating and tolerance of LED-luminaire data	61
Bibliog	ıraphy	64

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

This document (EN 13032-4:2015) has been prepared by Technical Committee CEN/TC 169 "Light and Lighting", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2015, and conflicting national standards shall be withdrawn at the latest by December 2015.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This standard was developed in collaboration with CIE TC2.71, which developed CIE S 025, to produce two technically-harmonized standards at CEN and CIE level.

Acknowledgement is given to CIE for their support in the preparation of this standard.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

Introduction

This standard provides requirements to perform reproducible photometric and colorimetric measurements on LED lamps, LED modules and LED luminaires (LED devices). It also provides advice for the reporting of the data.

The availability of reliable and accurate photometric data for LED devices is a basic requirement for designing good lighting systems and evaluating performance of products. By obtaining these data through measurements in specific normalized measuring conditions the consistency of the data should be ensured between different laboratories (within the limits of the declared measurement uncertainty) and comparison of different products on the same basis is possible.

This standard aims in particular to cover measurement methods for testing the compliance of LED devices with the photometric and colorimetric requirements of LED performance standards (see Clause 2) issued by IEC/TC 34/CLC/TC 34 "Lamps and related equipment" and/or relevant European regulations.

LED devices offer a large variety of configurations in respect to geometry and/or colour. For each configuration the photometric and colorimetric performances are considered individually.

iTeh STANDARD PREVIEW (standards.iteh.ai)

1 Scope

This European Standard specifies the requirements for measurement of electrical, photometric, and colorimetric quantities of LED lamps, LED modules and LED luminaires, for operation with AC or DC supply voltages, possibly with associated LED control gear. LED light engines are assimilated to LED modules and handled accordingly. Photometric and colorimetric quantities covered in this standard include total luminous flux, luminous efficacy, partial luminous flux, luminous intensity distribution, centre-beam intensity, luminance and luminance distribution, chromaticity coordinates, correlated colour temperature (CCT), colour rendering index (CRI), and angular colour uniformity.

This European Standard does not cover LED packages and products based on OLEDs (organic LEDs).

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN ISO 11664-1:2011, Colorimetry - Part 1: CIE standard colorimetric observers (ISO 11664-1:2007)

EN ISO 11664-2:2011, Colorimetry - Part 2: CIE standard illuminants (ISO 11664-2:2007)

EN ISO 11664-3:2013, Colorimetry - Part 3: CIE tristimulus values (ISO 11664-3:2012)

EN 12665, Light and lighting - Basic terms and criteria for specifying lighting requirements

EN 13032-1:2004+A1:2012, Light and lighting Measurement and presentation of photometric data of lamps and luminaires - Part 1: Measurement and file format

SIST EN 13032-4:2015

EN 61341:2011, Method of measurement of centre beam intensity and beam angle(s) of reflector lamps (IEC/TR 61341:2010) 9ad171b7d48d/sist-en-13032-4-2015

EN 62504:2014. General lighting -Light emitting diode products and related equipment-Terms and definitions (IEC 62504:2014)

prEN 62717:2014, LED modules for general lighting - Performance requirements (IEC 62717:2014)

ISO/IEC Guide 98-3:2008, Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)

ISO/IEC Guide 98-4:2012, Uncertainty of measurement — Part 4: Role of measurement uncertainty in conformity assessment

ISO/IEC Guide 99:2007, International vocabulary of metrology — Basic and general concepts and associated terms (VIM)

CIE/DIS 024/E:2013, Light Emitting Diodes (LEDs) and LED Assemblies – Terms and Definitions

CIE 13.3, Method of Measuring and Specifying Colour Rendering of Light Sources

CIE 15, Colorimetry

CIE 84:1989. Measurement of Luminous Flux

CIE 198:2011, Determination of Measurement Uncertainties in Photometry

CIE 198:2011-SP1, Determination of Measurement Uncertainties in Photometry – Supplement 1: Modules and Examples for the Determination of Measurement Uncertainties

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12665, EN 13032-1 and the following apply.

3.1

electric light source

primary light source that transforms electrical energy into optical radiation

[SOURCE: CIE/DIS 024/E:2013, 3.3]

3.2

light-emitting diode

LED

solid state device embodying a p-n junction, emitting incoherent optical radiation when excited by an electric current

Note 1 to entry: This definition is independent from the existence of enclosure(s) and of terminals.

Note 2 to entry: The output is a function of its physical construction, material used and exciting current. The optical emission may be in the ultraviolet, visible, or infrared wavelength regions.

Note 3 to entry: "LED" term represents the LED die (or chip) or LED package. It is also used as a generic term representing the technology.

(standards.iteh.ai)

Note 4 to entry: "LED" term should not be used for reporting product performance (like luminous flux, colour rendering, lifetime...) instead use for example "luminous flux of the LED module".4:2015

https://standards.iteh.ai/catalog/standards/sist/4a7eea8f-d9d8-4012-80ff-

[SOURCE: EN 62504:2014, 3.24] 9ad171b7d48d/sist-en-13032-4-2015

3.3

LED package

single electrical component encapsulating principally one or more LED dies, possibly including optical elements and thermal, mechanical, and electrical interfaces

Note 1 to entry: The component does not include the control unit of the control gear, does not include a cap, and is not connected directly to the supply voltage.

Note 2 to entry: A LED package is a discrete component and part of the LED module or LED lamp.

[SOURCE: EN 62504:2014, 3.20]

3.4

LED light source

electric light source based on LED technology

Note 1 to entry: A luminaire may include LED light sources but is not considered itself as a light source.

Note 2 to entry: LED light source(s) for a LED luminaire represent(s) one or more LED lamp(s) or LED module(s).

[SOURCE: EN 62504:2014, 3.16]

3.5

LED lamp

LED light source provided with (a) cap(s) incorporating one or more LED module(s) and possibly including one or more of the following: electrical, optical, mechanical, and thermal components, interfaces and control gear

A LED lamp may be integrated (LEDi lamp) or semi-integrated (LEDsi lamp) or non-integrated Note 1 to entry:

(LEDni lamp).

Single and double-capped lamps are included. Note 2 to entry:

Note 3 to entry: A LED lamp is designed so that it can be replaced by an ordinary person (as defined in IEC 60050-

18-03, 826)

[SOURCE: EN 62504:2014, 3.15]

3.6

integrated LED lamp (LEDi lamp)

LED lamp, incorporating control gear, and any additional elements necessary for stable operation of the light source, designed for direct connection to the supply voltage

In some documents the term self-ballasted LED lamp is still used. Note 1 to entry:

[SOURCE: EN 62504:2014, 3.15.1 modified by note1,added]

3.7

semi-integrated LED lamp (LEDsi lamp) ARD PREVIEW

LED lamp which carries the control unit of the control gear, and is operated by the separated power supply of the control gear standards.iteh.ai)

Note 1 to entry: In some documents the term semi-self-ballasted LED lamp is still used.

[SOURCE: EN 62504:2014, 3.15.4 modified by note 1, added] and added and solution an

3.8

non-integrated LED lamp (LEDni lamp)

LED lamp which needs a separate control gear to operate

Note 1 to entry: In some documents the term non-self-ballasted LED lamp is still used.

[SOURCE: EN 62504:2014, 3.15.2 modified by note1, added]

3.9

retrofit LED lamp

LED lamp, intended as a replacement of a non-LED lamp without requiring any internal modification of the **luminaire**

[SOURCE: EN 62504:2014, 3.15.3]

3.10

LED module

LED light source having no cap, incorporating one or more LED package(s) on a printed circuit board, and possibly including one or more of the following: electrical, optical, mechanical, and thermal components, interfaces and control gear

A LED module may be integrated (LEDi module) or semi-integrated (LEDsi module) or non-integrated Note 1 to entry: (LEDni module).

Note 2 to entry: The LED module is usually designed to be part of a LED lamp or LED luminaire.

[SOURCE: EN 62504:2014, 3.19]

3.11

integrated LED module (LEDi module)

LED module, incorporating control gear and any additional elements necessary for stable operation of the light source, designed for direct connection to the supply voltage

In some documents the term self-ballasted LED module is still used. Note 1 to entry:

[SOURCE: EN 62504:2014, 3.19.4 modified by note 1,added]

3.12

semi-integrated LED module (LEDsi module)

LED module which carries the control unit of the control gear, and is operated by the separated power supply of the control gear iTeh STANDARD PREVIEW

In some documents the term semi-self-ballasted LED module is used. Note 1 to entry:

[SOURCE: EN 62504:2014, 3.19.6 modified by note 1 added]

https://standards.iteh.ai/catalog/standards/sist/4a7eea8f-d9d8-4012-80ff-

non-integrated LED module (LEDni module)

LED module which needs a separate control circuitry or control gear to operate

Note 1 to entry: In some documents the term non-self-ballasted LED module is used.

One or more LED packages on a printed circuit board or substrate in a geometric structure are Note 2 to entry: regarded as LED array. No further components are included like electrical, optical, mechanical and thermal components.

[SOURCE: EN 62504:2014, 3.19.5 modified by note 1, added]

integral LED module

LED module, generally designed to form a non-replaceable part of a luminaire

[SOURCE: EN 62504:2014, 3.19.3]

3.15

control gear for LED module

LED control gear

unit inserted between the electrical supply and one or more LED modules which serves to supply the LED module(s) with its (their) rated voltage or rated current. The unit may consist of one or more separate components and may include means for dimming, correcting the power factor and suppressing radio interference, and further control functions

Note 1 to entry: The control gear consists of a power supply and a control unit.

Note 2 to entry: The control gear may be partly or totally integrated in the LED module.

Note 3 to entry: When no confusion is expected like used in a LED standard, "control gear" may also be used.

Note 4 to entry: Both terms "controlgear" or "control gear" are acceptable.

[SOURCE: EN 62504:2014, 3.6.1, modified, Note 4 to entry added]

3.16

LED light engine

integrated assembly or set consisting of LED module(s) and LED control gear for direct connection to the electrical supply system

Note 1 to entry: A LED light engine typically shall have defined electrical, mechanical, thermal and control interfaces, and specific photometric properties.

TANDARD PREVIEW Note 2 to entry: A LED light engine may incorporate a heat sink or not.

standards.iteh.ai)

ISOURCE: CIE/DIS 024/E:2013. 3.131

SIST EN 13032-4:2015 3.17

https://standards.iteh.ai/catalog/standards/sist/4a7eea8f-d9d8-4012-80ff-**LED** luminaire

luminaire designed to incorporate one or more LED light source(s)

Note 1 to entry: The LED light sources(s) may be an integral part of a LED luminaire

[SOURCE: EN 62504:2014, 3.17 modified by note1, added]

3.18

LED device

generic term to designate LED lamps, LED modules, LED light engines or LED luminaires for the purpose of this standard

3.19

beam angle

the angle between two lines in a plane through the optical beam axis, such that these lines pass through the centre of the front face of the device and through points at which the luminous intensity is 50 % of the centre beam intensity, where the centre beam intensity is the value of luminous intensity measured on the optical beam axis

Note 1 to entry: Beam angle is expressed in degrees (°)

This angle is a full angle measure, not a half angle measure. Note 2 to entry:

Note 3 to entry: The optical beam axis is the axis about which the luminous intensity distribution is substantially symmetrical.

[SOURCE: EN 62504:2014, 3.4 modified by note 3, added]

3.20

tuneable LED devices

device with independent channels where the spectra of the emitted light can be deliberately modified

Note 1 to entry: This means chromaticity coordinates are changeable.

Note 2 to entry: For devices with independent channels and changeable chromaticity coordinates the colorimetric figures are usually determined for the gamut corners, for changeable correlated colour temperature devices the minimum and maximum correlated colour temperature and for any additional setup (defined by applicant).

3.21

type test

conformity test on one or more LED product(s) representative of the production

[SOURCE: EN 62504:2014, 3.41]

3.22

type test sample

one or more LED product(s) submitted by the manufacturer or responsible vendor for the purpose of the type test

[SOURCE: EN 62504:2014, 3.42]

3.23

applicant

the responsible person who commissions a test NDARD PREVIEW

Note 1 to entry: The applicant can be for example a manufacturer, responsible vendor, customer or regulator.

Note 2 to entry: The applicant will normally provide all information required to correctly perform the test.

3.24

https://standards.iteh.ai/catalog/standards/sist/4a7eea8f-d9d8-4012-80ff-

9ad171b7d48d/sist-en-13032-4-2015

device under test

DUT

LED device submitted for testing

Note 1 to entry: A DUT (device under test) is not a type test sample unless it is declared so.

3.25

supply voltage (for a LED device)

voltage applied to the complete unit of LED light source or LED luminaire

[SOURCE: EN 62504:2014, 3.37]

3.26

supply power (for a LED device)

electrical power consumed by the light source(s), control gear and any control circuit in the device which includes any parasitic power when the light source is turned on

3.27

rated value

value of a quantity used for specification purposes under standard test conditions as declared by the manufacturer or responsible vendor

Note 1 to entry: The standard test conditions are given in the relevant standard

[SOURCE: EN 62504:2014, 3.33]

3.28

initial values

photometric and electrical characteristics measured at the end of the ageing period and stabilisation time

Note 1 to entry: Ageing period can be specified as zero

[SOURCE: prEN 62717:2014, 3.4]

3.29

ageing (for a LED source)

preconditioning period of LED light source before initial values are taken

Note 1 to entry: In some documents the term seasoning is used.

[SOURCE: EN 62504:2014, 3.1 modified by note 1, added]

3.30

stabilisation time (for a LED device)

time that is required for the LED light source or LED luminaire to obtain stable photometric output and electric power with constant electrical input

[SOURCE: EN 62504:2014, 3.35]

3.31

ambient temperature

iTeh STANDARD PREVIEW

temperature of air or another medium in the vicinity of the device under test

Note 1 to entry: Ambient temperature is expressed in degrees Celsius (°C).

SIST EN 13032-4:2015

[SOURCE: EN 62504)2014;a3,38:11.imodified]bg/standards/sist/4a7eea8f-d9d8-4012-80ff-

9ad171b7d48d/sist-en-13032-4-2015

3.32

ambient performance temperature

ambient temperature related to the performance of the LED light source or LED luminaire

Note 1 to entry: Ambient performance temperature is expressed in degrees Celsius (°C).

[SOURCE: EN 62504:2014, 3.38.2]

3 33

rated maximum temperature (of a component)

t

highest permissible safety related temperature which may occur on the outer surface of the component (LED module or control gear) (at the indicated position, if marked) under normal operating conditions and at the rated voltage/current/power or the maximum of the rated voltage/current/power range

Note 1 to entry: Rated maximum temperature is expressed in degrees Celsius (°C).

[SOURCE: EN 62504:2014, 3.38.9]