
**Motorcycles — Test and analysis
procedures for research evaluation of
rider crash protective devices fitted to
motorcycles —**

Part 6:
Full-scale impact-test procedures

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Motorcycles — Méthodes d'essai et d'analyse de l'évaluation par la
recherche des dispositifs, montés sur les motocycles, visant à la
protection des motocyclistes contre les collisions —*

<https://standards.iteh.ai/catalog/standards/sist/8adfb9a-f10b-4628-b03e-21a0b8094e59/iso-13232-6-2005>
Partie 6: Méthodes d'essai de choc en vraie grandeur



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 13232-6:2005](https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005)

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction.....	vi
1 Scope	1
2 Normative references	2
3 Definitions	2
4 Requirements.....	3
4.1 Opposing vehicle.....	3
4.2 Motorcycle.....	4
4.3 Dummy and instrumentation.....	4
4.4 Photographic equipment	5
4.5 Impact conditions	5
4.6 Additional test and analysis procedures for inflatable/triggered protective device	8
4.7 Test safety	8
5 Impact test methods.....	8
5.1 Impact conditions.....	8
5.2 Vehicle set up.....	8
5.3 Dummy set up.....	9
5.4 Stationary MC support	13
5.5 Camera set up	13
5.6 Pre-test measurements	14
5.7 Temperature soaking	14
6 Documentation and reporting	14
Annex A (normative) Procedure to set dummy joint tensions	15
Annex B (normative) Procedure for dummy pre-mount preparation.....	22
Annex C (normative) Procedure for positioning the dummy on the motorcycle	23
Annex D (normative) Procedure to install the helmet on the dummy and position the dummy head	27
Annex E (informative) Outline of additional general test and analysis procedures for inflatable/triggered protective devices	29
Annex F (informative) Rationale for ISO 13232-6	33

ITeH STANDARD PREVIEW
(standards.iteh.ai)

ISO 13232-6:2005

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

Figures

Figure 1 — Motorcycle overall length measurement bump 11

Figure 2 — Head impactor target point and line-of-motion centre for sensor, data acquisition, and post processing verification..... 12

Figure A.1 — Typical weight hanger 16

Figure A.2 — Weight set..... 17

Figure A.3 — Typical lower arm clamping fixture 18

Figure C.1 — An example torso inclinometer 26

Figure D.1 — Template of the helmet alignment tool 28

Figure F.1 — Effect of joint tension on maximum head acceleration in car side 90° impact 44

Figure F.2 — HyGe sled test results comparing arm joint tension effects on trajectory 47

Tables

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Table 1 — OV contact point relative tolerances for the seven required impact configurations described in ISO 13232-2 6

Table 2 — OV contact point tolerances for other impact configurations 7

Table 3 — OV ride heights 9

Table 4 — Impactor characteristics for systems verification 10

Table A.1 — Arm joint initial adjustments 19

Table A.2 — Arm joint tension adjustments 20

Table A.3 — Leg joint tension adjustments 21

Table B.1 — Dummy limb pre-mount positions 22

Table F.1 — EC, Japan and US vehicle data 34

Table F.2 — Hybrid III dummy response sensitivity to temperature changes, based on Seiffert and Leyer, 1976 ... 41

Table F.3 — Dummy limb weights, distances used for joint tension calculations 48

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

ISO 13232-6 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 22, *Motorcycles*.

This second edition cancels and replaces the first version (ISO 13232-6:1996), which has been technically revised.

ISO 13232 consists of the following parts under the general title *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles*:

- *Part 1: Definitions, symbols and general considerations*
- *Part 2: Definition of impact conditions in relation to accident data*
- *Part 3: Motorcyclist anthropometric impact dummy*
- *Part 4: Variables to be measured, instrumentation and measurement procedures*
- *Part 5: Injury indices and risk/benefit analysis*
- *Part 6: Full-scale impact-test procedures*
- *Part 7: Standardized procedures for performing computer simulations of motorcycle impact tests*
- *Part 8: Documentation and reports*

Introduction

ISO 13232 has been prepared on the basis of existing technology. Its purpose is to define common research methods and a means for making an overall evaluation of the effect that devices which are fitted to motorcycles and intended for the crash protection of riders, have on injuries, when assessed over a range of impact conditions which are based on accident data.

It is intended that all of the methods and recommendations contained in ISO 13232 should be used in all basic feasibility research. However, researchers should also consider variations in the specified conditions (for example, rider size) when evaluating the overall feasibility of any protective device. In addition, researchers may wish to vary or extend elements of the methodology in order to research issues which are of particular interest to them. In all such cases which go beyond the basic research, if reference is to be made to ISO 13232, a clear explanation of how the used procedures differ from the basic methodology should be provided.

ISO 13232 was prepared by ISO/TC 22/SC 22 at the request of the United Nations Economic Commission for Europe Group for Road Vehicle General Safety (UN/ECE/TRANS/SCI/WP29/GRSG), based on original working documents submitted by the International Motorcycle Manufacturers Association (IMMA), and comprising eight interrelated parts.

This revision of ISO 13232 incorporates extensive technical amendments throughout all the parts, resulting from extensive experience with the standard and the development of improved research methods.

In order to apply ISO 13232 properly, it is strongly recommended that all eight parts be used together, particularly if the results are to be published.

[ISO 13232-6:2005](https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005)

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles —

Part 6: Full-scale impact-test procedures

1 Scope

This part of ISO 13232 specifies minimum requirements for:

- paired comparison tests;
- the preparation of the dummy, motorcycle and opposing vehicle;
- the repeatability and reproducibility of impact test conditions within and between test sites;
- the minimization of variation in secondary test variables;
- realistic and representative impact conditions for full-scale impact tests;
- a means to verify analytical evaluations of proposed rider crash protective devices fitted to motorcycles, such as computer simulation.

ISO 13232 specifies the minimum requirements for research into the feasibility of protective devices fitted to motorcycles, which are intended to protect the rider in the event of a collision.

ISO 13232 is applicable to impact tests involving:

- two-wheeled motorcycles;
- the specified type of opposing vehicle;
- either a stationary and a moving vehicle or two moving vehicles;
- for any moving vehicle, a steady speed and straight-line motion immediately prior to impact;
- one helmeted dummy in a normal seating position on an upright motorcycle;
- the measurement of the potential for specified types of injury by body region;
- evaluation of the results of paired impact tests (i.e. comparisons between motorcycles fitted and not fitted with the proposed devices);
- evaluation of inflatable/triggered protective device.

ISO 13232-6 does not apply to testing for regulatory or legislative purposes.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13232-1, *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles — Part 1: Definitions, symbols, and general considerations*

ISO 13232-2, *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles — Part 2: Definition of impact conditions in relation to accident data*

ISO 13232-3, *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles — Part 3: Motorcyclist anthropometric impact dummy*

ISO 13232-4, *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles — Part 4: Variables to be measured, instrumentation, and measurement procedures*

ISO 13232-7, *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles — Part 7: Standard procedures for performing computer simulations of motorcycle impact tests*

ISO 13232-8, *Motorcycles — Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles — Part 8: Documentation and reports*

49 CFR Part 572, subpart E: 1993, Anthropomorphic test dummies, United States of America Code of Federal Regulations issued by the National Highway Traffic Safety Administration (NHTSA), Washington, D.C

SAE Engineering aid 23: 1986, User's manual for the 50th percentile Hybrid III test dummy, Disassembly and assembly, p. 5-20. Warrendale, Pennsylvania, USA

E/ECE/TRANS/505 Rev. 1/Add. 21/Reg. 22/Rev. 3: 1992, Uniform provisions concerning the approval of protective helmets and of their visors for drivers and passengers of motorcycles and mopeds, Genève, Switzerland

3 Definitions

The following terms are defined in ISO 13232-1. For the purposes of this part of ISO 13232, those definitions apply. Additional definitions which could apply to this part of ISO 13232 are also listed in ISO 13232-1:

- baseline MC;
- kerb mass;
- dummy K index;
- dummy preparation areas;
- dummy S index;
- group of tests;
- head hook;

- hexagonal key tool;
- knee centre line index;
- lower arm clamping fixture;
- modified MC;
- motorcycle K point;
- motorcycle S point;
- multiple paired comparison;
- overall height;
- overall length of the MC;
- pivot;
- rotate;
- secondary test variables;
- single paired comparison;
- structural element of the MC;
- suppression
- upper torso reference line;
- weight hanger.

STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

4 Requirements

4.1 Opposing vehicle

For all test series except those intended for international comparison purposes, the opposing vehicle (OV) for all tests in a given test series shall be a single make, model, year and version of any four door saloon having a kerb mass not less than 1238 kg and not greater than 1450 kg, and having an overall height not less than 137 cm and not greater than 147 cm.

For all test series which are intended for international comparison purposes, the involved research organizations shall together select a single make, model, year and version of a four door saloon, which meets the aforementioned kerb mass and overall height specifications. The involved research organizations may also select, for tests in other regions, local versions that are similar to the selected version, which are or shall be made to be structurally equivalent to the selected version, with full explanation given in the test report. The involved research organizations shall also together select the OV ride height values for the selected version, as described in 5.2.1, to be used in all tests for international comparison purposes.

The OV shall be in sound, unmodified mechanical condition, except for modifications to the local versions of the selected OV for international comparison tests, as may be required by this clause. The allowable test mass for all OV's shall be 80 kg \pm 20 kg more than the kerb mass of the selected vehicle.

NOTE The specified OV's are to be used until ISO 13232 is amended to incorporate updated OV alternatives, and/or a moving deformable barrier.

The OV shall be set up following the procedures described in 5.2.1.

4.2 Motorcycle

The motorcycle (MC) shall be set up following the procedures described in 5.2.2.

4.3 Dummy and instrumentation

4.3.1 Motorcyclist anthropometric impact dummy

The motorcyclist impact dummy used shall meet all of the requirements described in ISO 13232-3.

Prior to use in impact testing the dummy head, thorax, and knees shall be tested to conform to the calibration requirements and procedures as described in paragraphs 572.32, 572.34, and 572.35 of U.S. 49 CFR Part 572, using the test conditions and instrumentation described in paragraphs 572.36 of U.S. 49 CFR Part 572. The neck shall be tested to conform to the requirements of 3-4.3.6. The number of full-scale tests between calibrations shall not exceed ten. The number of full-scale tests since the last calibration shall be documented according to ISO 13232-8.

All frangible components shall be new and not previously used either in full-scale or component testing.

4.3.2 Instrumentation

iTeh STANDARD PREVIEW

(standards.iteh.ai)

The dummy shall be equipped with the instrumentation described in ISO 13232-4.

4.3.3 Sensor, data acquisition, and post processing systems verification

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e->

Prior to each impact test, the operation of the head sensors and data acquisition and post processing systems shall be verified by applying an impact to the unhelmeted head of the dummy, as described in 5.3.1. The resulting time histories shall be included in the documentation of test results. Between the time of such verification test and the full-scale impact test, none of the sensors, data acquisition or post processing hardware, or gains, scale factors or ranges shall be changed in any way.

4.3.4 Joint tensions

The dummy joint tensions shall be adjusted, as described in 5.3.2, according to the procedures described in Annex A.

4.3.5 Clothing

The dummy shall be fitted with long sleeved close fitting thermal knit underwear. The underwear shall have holes cut in it to accommodate the lower arm pre-mount positioning procedure, described in Table B.1, and the upper torso angle measurement procedure, if performed as described in C.2.4.2. The dummy feet shall be fitted with leather racing type boots which shall have the following dimensions:

2,0 cm ± 0,5 cm heel height;

1,0 kg ± 0,3 kg mass per boot.

The same boot make, model, and size shall be used for all tests within a paired comparison, as described in 4.5.4.4.

Gloves may also be used to protect the hands if the gloves do not affect the flexibility of the hands and fingers.

4.3.6 Position on motorcycle

The dummy shall be positioned on the motorcycle, as described in 5.3.4 and 5.3.5.

4.3.7 Helmet

The dummy shall be fitted with a Bieffe model B12R¹⁾ helmet according to the procedures described in Annex D. The helmet shall be new (i.e., the helmet shall not be used for more than one test) and shall meet the following specifications:

- size designation, either small (56 cm) or medium (58 cm);
- certified to ECE Reg 22-03 on a 57 cm headform.

The same helmet make, model, and specifications shall be used for all tests within a paired comparison, as described in 4.5.4.4. Helmets from the same production lot should be used for all tests within a paired comparison²⁾.

4.4 Photographic equipment

High speed cameras having the capabilities given in ISO 13232-4 shall be used. The cameras used for pre-test and pre-impact photographs may be remotely triggered.

Photographic targets shall be placed on the MC, OV, and ground at the locations described in 4.3 of ISO 13232-4, and on the dummy at the locations described in 5.3.6 of this part of ISO 13232.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.5 Impact conditions

In order to do an overall evaluation of the feasibility of a given protective device according to ISO 13232, paired comparison tests using at least the seven full-scale impact configurations defined in 4.3.1 of ISO 13232-2 shall be done. The protective device shall also be evaluated in the remaining 193 impact configurations defined in Table B.1 of ISO 13232-2, and this evaluation should be done by computer simulation according to ISO 13232-7.

The impact condition shall be selected as described in 5.1.

The impact test shall be performed such that it meets the following requirements.

4.5.1 Pre-test measurement

The static measurements which are required to determine impact conditions shall be performed as defined in 5.6 of this part of ISO 13232.

4.5.2 Post-test measurement

Measurements of impact conditions at the time immediately preceding first MC/OV contact shall be performed as described in 5.3 of ISO 13232-4. The measurements shall be used to determine accuracy of impact conditions, as described in 4.5.4 of this part of ISO 13232.

When comparing the pre-test set up photographs with the pre-impact photographs, the positions of the dummy helmet centroid point and of the dummy joint locations, with respect to the motorcycle, shall agree to within ± 3 cm.

1) Bieffe, model B12R is a product supplied by Bieffe Helmets S.r.l., Lucca, Italy. This information is given for the convenience of users of ISO 13232 and does not constitute an endorsement by ISO of the product named.

2) Helmets purchased in EU countries are marked with a serial number related to the production lot number. Users who choose to use such helmets should contact Bieffe to determine the relationship between serial numbers and lot numbers.

4.5.3 Vehicle speed control

The MC and OV shall be free wheeling at the time of impact, and thereafter, except:

- if the OV impact speed is zero, then the OV parking brake, adjusted to the manufacturer's specification, shall be fully applied during the entire impact test;
- if the OV impact speed is non-zero, then between 0,5 s and 1,0 s after impact, the OV shall be decelerated to a stop with braking equivalent to a brake pedal force of at least 400 N.

4.5.4 Paired comparisons

4.5.4.1 Required relative tolerances

The difference between two tests in a single paired comparison or among all members of a group of tests in a multiple paired comparison shall not be greater than the following values:

- relative heading angle: 3°;
- OV impact speed: 5% of the target speed;
- MC impact speed: 5% of the target speed;
- MC roll angle: 5°;
- OV contact point: see Table 1 for the seven required impact configurations described in ISO 13232-2.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Table 1 — OV contact point relative tolerances for the seven required impact configurations described in ISO 13232-2

OV contact location	Relative heading angle deg	OV/MC speeds m/s	OV contact point relative tolerance cm
Front	90	9,8/0	5
Front	135	6,7/13,4	10
Front corner	180	0/13,4	3
Side	90	0/13,4	5
Side	135	6,7/13,4	15
Side	90	6,7/13,4	15
Side	45	6,7/13,4	15

4.5.4.2 Recommended OV contact point relative tolerances for other impact configurations

For the other 193 impact configurations described in ISO 13232-2, the OV contact point relative tolerance should be as described in Table 2.

Table 2 — OV contact point tolerances for other impact configurations

OV contact location	Relative heading angle deg	OV contact point relative tolerance cm	
		For zero OV or MC speed	All other speed combinations
Front or rear	all	5	10
Front corner or rear corner	all	3	6
Side front, side middle, or side rear	90	5	15
Side front, side middle, or side rear	45, or 135	5	15

4.5.4.3 Required absolute tolerances

For a given impact condition and for each impact condition variable, the difference between the target condition and each of the tests in a single or multiple paired comparison, shall be less than or equal to the values specified in 4.5.4.1 and 4.5.4.2.

4.5.4.4 Number of tests

For paired comparison impact tests, at least one test with the protective device fitted to the MC and at least one test without the protective device fitted to the MC shall be done.

Multiple runs may be performed provided that the same number of multiple runs are performed and documented for both the baseline MC and the modified MC.

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

4.5.5 Ambient conditions

The air temperature of the area used for long term storage of the dummy should be between 13° C and 30° C. Beginning at least 3 hours before the planned time of impact, the air temperature in each of the dummy preparation areas shall be measured and documented while the dummy is in each area.

If the temperature measured in each of the dummy preparation areas is between 13° C and 30° C, then no additional temperature soaking procedures shall be used.

If the temperature in any of the dummy preparation areas is outside this range, and the total exposure time to the out of range temperature exceeds the time given by the equation below, where first area is the soak area and the second area is the out of range area, then the dummy shall be soaked following the temperature soaking procedure given in 5.7.

$$t = \tau \ln [(T_2 - T_1)/(T_2 - T_0)]$$

where

t is the total exposure time required to reach the limit of the temperature range, in hours;

T_1 is the air temperature in the first area, in degrees Celsius;

T_2 is the air temperature in the second area, in degrees Celsius;

T_0 is the critical temperature, in degrees Celsius: 13° C for moving to or from temperatures colder than the required range; 30° C for moving to or from temperatures warmer than the required range;

τ is 2.9, the dummy thorax thermal time constant, in hours.

Any further exposure to out of range temperatures shall be treated as described in 5.7.

The wind velocity at the point and time of impact shall be no greater than 4,2 m/s. The test surface shall be substantially level with a maximum gradient of 2%.

4.6 Additional test and analysis procedures for inflatable/triggered protective device

If an inflatable/triggered protective device (i.e., airbag) is being evaluated, additional test and analysis methods should be used that are consistent with those outlined in Annex F.

4.7 Test safety

When performing tests using ISO 13232 procedures, specifications, and requirements, safety must always be a primary goal. At no time should safety practices and procedures be compromised in order to comply with the requirements of this Standard.

Users of this Standard are requested to report to the relevant ISO working group any test personnel injuries or near injuries encountered during the implementation of ISO 13232 so that the incident may be analysed and ISO 13232 modified as required, in order to prevent future accidents and possible injuries.

5 Impact test methods

5.1 Impact conditions

iTeh STANDARD PREVIEW

From the list of required and other, permissible impact configurations given in 4.3 of ISO 13232-2, select the impact configuration to be tested and specify the impact conditions using the variables described in ISO 13232-2.

5.2 Vehicle set up

<https://standards.iteh.ai/catalog/standards/sist/fladfb9a-fl0b-4628-b03e-21a0b8094e59/iso-13232-6-2005>

5.2.1 Opposing vehicle

Remove the battery cable and fuel. Weigh the vehicle. Weigh the brake actuator system and the portion of the guidance system mounted on the OV. Add this mass to the measured OV mass and compare the total mass to the allowable test mass given in 4.1. Add or remove ballast or components as necessary to attain the allowable test mass. Install the brake actuator and guidance systems in the OV.

Leave the steering wheel and steering system free to steer. Put the transmission in neutral gear. Completely close all doors, windows, the bonnet, and the boot lid.

For the first OV in a test series, measure and adjust the ride height as specified in Table 3. For subsequent OV's in a test series, measure and adjust the ride height to be within the tolerances as specified in Table 3. Adjust the ride height by adjusting any of the tyre pressures to between 138 kPa and 276 kPa, or by adding spring spacers and/or compressors.

Table 3 — OV ride heights

OV contact location	OV ride height measurement location	Height above ground cm	Tolerance compared to first OV in test series cm
Front and front corner	Lowest point of bonnet at forward end of bonnet centreline	Measure for first OV in test series ^a	1
Side	Highest point of front door	Measure for first OV in test series ^a	1
Rear	Lowest point of boot lid at rearward end of boot lid centreline	Measure for first OV in test series ^a	1

^a To be measured for first OV in a test series, after vehicle's x and y body axes have been levelled to be 90 degrees \pm 5 degrees from the gravitational vertical axis.

5.2.2 Motorcycle

Remove the fuel. If the MC is equipped with a rear wheel adjuster to accommodate a chain or belt, adjust the rear wheel to the most forward position. Remove the chain or belt, if present. Set the tyre pressures to the vehicle manufacturer's recommendations. Set the suspension ride height and damping settings to the vehicle manufacturer's recommendations, or to the mid-range point, in the absence of a recommendation. Weigh the MC. Put the MC in neutral gear.

For impact configurations in which the overall MC length measurement is required (e.g., 143-9,8/0 in ISO 13232-2), place the dummy on the motorcycle in a riding position which approximates that to be used in the full-scale impact tests, with the hands on the hand grips and the feet on the foot rests. Ballast the motorcycle to simulate the mass of any additional equipment related to the conduct of the test. Place a bump, like the one shown in Figure 1, approximately 1,5 m in front of the MC, such that the bump is perpendicular to the MC longitudinal centre line. Roll the laden MC a total distance of at least 3 m, perpendicularly across the bump. Place a target on the intended MC contact point and document the MC overall length as specified in clause 6. Remove the dummy from the MC.

For impact configurations in which the MC is moving, install the MC in the guidance system, such that:

- the steering system is free to steer after release from the guidance system and prior to impact, except for interaction with the dummy's hands;
- the front wheel is pointed in the straight ahead direction;
- the front and rear facing MC upper and lower centre line targets form a vertical line with respect to gravity.

For impact configurations where the MC is stationary, construct two wooden support stands with a nominally square cross section; a maximum length and width of 50 mm; and of suitable height to support the MC in a vertical position. Use metal shims having a maximum outside diameter of 25 mm and a maximum thickness of 2 mm, on top of each support stand to level the MC on the stands.

5.3 Dummy set up

5.3.1 Sensor, data acquisition, and post processing systems verification

Mark the dummy head skin with the impactor target point and line-of-motion centre as indicated in Figure 2. Seat the dummy on a rigid, flat, horizontal surface with the thoracic spine box, upper arms, and lower legs in a vertical orientation. Adjust the neck adjustment joint so that with the helmet alignment tool (shown in Figure D.1) fitted to the front of the head, the helmet alignment tool upper edge is horizontal, $\pm 2^\circ$ with respect to gravity. Pitch the