



Designation: D 2079 – 92 (Reapproved 1998)

Standard Test Method for Nonvolatile Matter (Solids) in Fatty Quaternary Ammonium Chlorides¹

This standard is issued under the fixed designation D 2079; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This method was prepared jointly by the American Society for Testing and Materials and the American Oil Chemists' Society.

1. Scope

1.1 This method covers the determination of nonvolatile matter (solids) in fatty quaternary ammonium chlorides.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Summary of Test Method

2.1 Volatile matter is evaporated under heat and vacuum and the nonvolatile matter determined.

3. Apparatus

3.1 *Vacuum Oven*, with suitable controls for maintaining a temperature of $105 \pm 2^\circ\text{C}$.

3.2 *Air Oven*, with suitable controls for maintaining a temperature of $105 \pm 2^\circ\text{C}$.

4. Procedure

4.1 If not a liquid, melt the sample using a water bath. Mix the sample thoroughly and accurately weigh 0.7 to 1.0 g to 0.1

mg into a 50-mL narrow-mouth Erlenmeyer flask. Place the flask in the air oven for 1 h at $105 \pm 2^\circ\text{C}$. After about 15 min of oven time, rotate the flask gently to coat the specimen over the entire bottom of the flask. Place the flask in a vacuum oven for 8 h at $105 \pm 2^\circ\text{C}$ and a vacuum (negative gage pressure) of 27 to 29 in. Hg (absolute pressure of 25 to 35 mm Hg). Cool in a desiccator for $\frac{1}{2}$ h and reweigh.

5. Calculation

5.1 Calculate the percent of nonvolatile matter (solids) as follows:

$$\text{Nonvolatile matter (solids), \%} = (R \times 100)/S \quad (1)$$

where:

R = grams of residue, and

S = specimen weight used, g.

6. Precision and Bias

6.1 Precision and bias were not established at the time this test method was written. An effort is being made to obtain the precision and, if obtainable, it will be published in future revisions. This test method has been in use for many years, and its usefulness has been well established.

7. Keywords

7.1 nonvolatile matter; quaternary ammonium chlorides; solids content

¹ This test method is under the jurisdiction of ASTM Committee D-1 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.32 on Drying Oils.

Current edition approved March 15, 1992. Published May 1992. Originally published as D 2079 – 62 T. Last previous edition D 2079 – 82 (1987).

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).