

SLOVENSKI STANDARD oSIST ISO 4308-1:2012

01-januar-2012

Žerjavi in dvigalna oprema - Izbira dvigalnih vrvi - 1. del: Splošno

Cranes and lifting appliances - Selection of wire ropes - Part 1: General

Grues et appareils de levage - Choix des câbles - Partie 1: Généralités

Ta slovenski standard je istoveten z: ISO 4308-1:2003

ICS:

53.020.30 Pribor za dvigalno opremo Accessories for lifting

equipment

oSIST ISO 4308-1:2012 en,fr

oSIST ISO 4308-1:2012

oSIST ISO 4308-1:2012

INTERNATIONAL STANDARD

ISO 4308-1

Third edition 2003-05-01

Cranes and lifting appliances — Selection of wire ropes —

Part 1: **General**

Grues et appareils de levage — Choix des câbles — Partie 1: Généralités



ISO 4308-1:2003(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents Page

Forew	ord	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Type of rope	2
5	Duty conditions	2
6 6.1 6.2 6.3 6.4	Selection procedure Calculation of C values $Z_{\rm p}$ values Calculation of minimum rope diameter Calculation of minimum breaking force	3 3 4
7	Diameter of rope drums and sheaves	5
8	Stationary ropes	6
9	Dangerous conditions	6
10	Care, maintenance, examination and discard	6
Annex	A (normative) Lifting appliances to which this part of ISO 4308 is applicable	7
Annex	B (informative) Examples of wire rope selection	8
Annex	C (informative) Other selection aspects	9
Annex	CD (normative) Hoists — Diameter of compensating sheaves	21
Biblio	graphy	22

ISO 4308-1:2003(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4308-1 was prepared by Technical Committee ISO/TC 96, *Cranes*, Subcommittee SC 3, *Selection of wire ropes*.

This third edition cancels and replaces the second edition (ISO 4308-1:1986), which has been technically revised.

ISO 4308 consists of the following parts, under the general title *Cranes and lifting appliances* — *Selection of wire ropes*:

- Part 1: General
- Part 2: Mobile cranes Coefficient of utilization

Cranes and lifting appliances — Selection of wire ropes —

Part 1:

General

1 Scope

This part of ISO 4308 specifies two methods for the selection of wire rope to be used on lifting appliances as designated in ISO 4306-1, one based on the value of the rope selection factor C and the other based on the value of the coefficient of utilization $Z_{\rm D}$

This part of ISO 4308 establishes the minimum requirements for acceptable strength and performance levels of wire ropes with respect to the design, application and maintenance of the lifting appliance.

This part of ISO 4308-1 establishes the minimum requirements for the diameters of drums and sheaves that are to be associated with the selected wire rope.

A non-exhaustive list of types of lifting appliance to which this part of ISO 4308 is applicable is given in Annex A.

Annex B provides some examples of rope selection.

Annex C gives factors, additional to those mentioned above, which may need consideration when selecting the wire rope.

Annex D specifies the selection method for the diameter of the compensating sheave when used in relation to hoists.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2408:1985, Steel wire ropes for general purposes — Characteristics

ISO 4301-1:1986, Cranes and lifting appliances — Classification — Part 1: General

ISO 4306-1:1990, Cranes — Vocabulary — Part 1: General

ISO 4309, Cranes — Wire ropes — Care, maintenance (including installation), inspection

ISO 4308-1:2003(E)

3 Terms and definitions

For the purposes of this part of ISO 4308, the following terms and definitions apply.

3.1

parallel-closed rope

stranded rope consisting of at least two layers of strand laid helically in one closing operation around a strand or fibre centre

3.2

rotation-resistant rope multi-strand rope non-rotating rope

stranded rope designed to generate reduced levels of torque and rotation when loaded

NOTE 1 Rotation-resistant ropes generally comprise an assembly of two or more layers of strands laid helically around a centre, the direction of lay of the outer strands being opposite to that of the underlying layer.

NOTE 2 Ropes having three or four strands can also be designed to exhibit rotation-resistant properties.

3.3

single-layer rope

stranded rope consisting of one layer of strands laid helically around a core

3.4

stranded rope

assembly of several strands, laid helically in one or more layers around a core (single-layer rope) or centre (rotation-resistant or parallel-closed rope)

NOTE Single-layer ropes consisting of three and four strands may or may not have a core.

4 Type of rope

Where possible, the wire rope selected shall be in accordance with ISO 2408.

Selection of wire rope not specified by ISO 2408 is permitted, but in such cases the supplier of the wire rope shall show, to the user, documentation which is supported by the rope-maker's technical file for the product, that clearly demonstrates that the product has acceptable strength and performance levels with respect to the design of mechanisms, application and maintenance of the appliance.

5 Duty conditions

The mechanisms of lifting appliances shall be classified according to the duty conditions laid down in ISO 4301-1.