



**Speech and multimedia Transmission Quality (STQ);
QoS aspects for popular services in mobile networks;
Part 3: Typical procedures for Quality of Service
measurement equipment**

ITEN Standard PREVIEW
<https://standards.iteh.ai/standard/etsi-ts-102-250-3-v2.3.1-8538-49b4-99b0-0c56635d425/etsi-ts-102-250-3-v2.3.1-8538-49b4-99b0-0c56635d425/>

ReferenceRTS/STQ-00187m

Keywords

3G, GSM, network, QoS, service, speech

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	9
4 Aim of measurement	10
5 Classification of services.....	10
5.1 Classification guidelines.....	10
5.2 General structure of service descriptions.....	11
6 General aspects for all types of services.....	11
6.1 Set-up and control	11
6.2 Phase and result classification	11
7 Telephony measurements	12
7.1 General aspects.....	12
7.1.1 Transaction definition and transaction types.....	12
7.1.2 Parameter overview	12
7.1.3 Additional transaction result definitions	13
7.1.4 Content quality.....	13
7.1.5 Verification of usable two-way connection.....	14
7.2 Speech telephony.....	14
7.2.1 Transaction definition and transaction types for speech telephony	14
7.2.2 Parameter overview for speech telephony	14
7.2.3 Additional transaction results for speech telephony	14
7.2.4 Content quality for speech telephony.....	14
7.2.5 Verification of usable two-way connection for speech telephony	14
7.3 Video telephony	14
7.3.1 Transaction definition and transaction types for video telephony	14
7.3.2 Parameter overview for video telephony	15
7.3.3 Additional transaction result definitions for video telephony	15
7.3.4 Content quality for video telephony	15
7.3.5 Verification of usable two-way connection for video telephony	15
7.3.6 Call setup considerations for MTSI calls.....	15
7.4 Group Call	16
7.4.1 Transaction definition and transaction types for group calls	16
7.4.2 Parameter overview for group calls	16
7.4.3 Additional transaction result definitions for group calls.....	16
7.4.4 Content quality for group calls	16
7.4.5 Verification of usable connection for group calls	17
8 Store-and-forward services measurement	17
8.1 General aspects.....	17
8.1.1 Transaction phase and parameter overview	18
8.1.2 Additional transaction result definitions	18
8.1.3 Content quality for Store-and-Forward Services	19
8.2 SMS measurements	19
8.2.1 General aspects of SMS measurements	19
8.2.2 Transaction definitions and transaction types for SMS	19

8.2.3	Testing mode for SMS-MT	20
8.2.4	Testing mode for SMS-MO	20
8.2.5	Transaction phase and parameter overview for SMS	20
8.2.6	Possible transaction results for SMS	20
8.2.7	Content quality for SMS	21
8.3	MMS	21
8.3.1	General aspects of MMS measurements	21
8.3.2	Transaction definitions and transaction types for MMS	21
8.3.3	Transaction phase and parameter overview for MMS	22
8.3.4	Additional transaction result definitions for MMS	22
8.3.5	Content quality for MMS	23
8.4	E-Mail	23
8.4.1	Transaction definitions for E-Mail	23
8.4.1.1	Protocols	23
8.4.1.2	Reference content	23
8.4.1.3	Content integrity	24
8.4.1.4	Push functionality	24
8.4.1.5	Header only download	24
8.4.1.6	Timeouts	24
8.4.1.7	General requirements and limitations	24
8.4.2	Transaction scenarios for e-mail	25
8.4.2.1	Upload scenario	25
8.4.2.2	Download scenario	26
8.4.2.3	End-to-end scenario with IMAP4	26
8.5	SDS	27
8.5.1	General aspects of SDS measurements	27
8.5.2	Transaction phase and parameter overview for SDS	28
8.5.3	Possible transaction results for SDS	28
8.5.4	Content quality for SDS	28
9	Data measurements	28
9.1	Common aspects	28
9.1.1	Transaction definition and transaction types for data measurements	28
9.1.2	Server types	29
9.1.3	Test data content	29
9.1.4	Transaction phase and parameter overview	29
9.1.4.1	General	29
9.1.4.2	Packet-switched access	30
9.1.4.3	Circuit-switched access	30
9.1.4.4	Direct Services	31
9.1.5	Possible transaction results	31
9.1.6	Content quality	32
9.1.7	Content integrity	32
9.2	FTP	32
9.2.1	Transaction definition and transaction types for FTP	32
9.2.2	Transaction phase and parameter overview for FTP	32
9.2.3	Possible transaction results for FTP	32
9.2.4	Content quality for FTP	32
9.2.5	Content integrity for FTP	32
9.3	HTTP	33
9.3.1	Transaction definition and transaction types for HTTP	33
9.3.2	Transaction phase and parameter overview for HTTP	33
9.3.3	Possible transaction results for HTTP	33
9.3.4	Content quality for HTTP	33
9.3.5	Content integrity for HTTP	33
9.4	E-mail	33
9.5	WAP	33
9.5.1	Transaction definition and transaction types for WAP	33
9.5.2	Transaction phase and parameter overview for WAP	34
9.5.3	Possible transaction results for WAP	35
9.5.4	Content quality for WAP	35
9.5.5	Content integrity for WAP	36

9.6	Streaming Video.....	36
9.6.1	Transaction definition and transaction types for streaming video	36
9.6.2	Transaction phase and parameter overview for streaming video.....	36
9.6.3	Possible transaction results for Streaming Video.....	36
9.6.4	Content quality for Streaming Video	36
9.6.5	Content integrity for Streaming video	36
9.7	Media Download	37
9.7.1	Transaction definition and types for Media Download.....	37
9.7.1.1	OMA network elements	37
9.7.1.2	OMA download use cases	38
9.7.1.2.1	Combined OMA download use case	38
9.7.1.2.2	Separate OMA download use case	39
9.7.1.3	DRM use cases.....	40
9.7.1.3.1	Combined delivery DRM use case	40
9.7.1.3.2	Separate delivery DRM use case	40
9.7.2	Transaction phase and parameter overview for Media Download.....	41
9.7.2.1	Overview of basic parameters for Media Download.....	41
9.7.2.2	Media Download subphases.....	42
9.7.2.3	Combined OMA download and combined delivery DRM use case.....	43
9.7.2.4	Separate OMA download and combined delivery DRM use case	43
9.7.2.5	Combined OMA download and separate delivery DRM use case	43
9.7.2.6	Separate OMA download and separate delivery DRM use case	44
9.7.2.7	Additional information about parameters for Media Download	44
9.7.2.8	Recommended Testing Method for Media Download	44
9.7.3	Possible transaction results for Media Download	44
9.7.4	Content quality for Media Download	44
9.7.5	Content integrity for Media Download.....	44
Annex A (informative):	Bibliography.....	45
History	46

ITEH STANDARD
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/etsi-ts-102-250-3-v2.3.1>
8538-49b4-99b0-0c56635d5325
2013-06

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Speech and multimedia Transmission Quality (STQ).

The present document is part 3 of a multi-part deliverable covering the QoS aspects for popular services in mobile networks, as identified below:

- Part 1: "Assessment of Quality of Service";
- Part 2: "Definition of Quality of Service parameters and their computation";
- Part 3: "Typical procedures for Quality of Service measurement equipment";**
- Part 4: "Requirements for Quality of Service measurement equipment";
- Part 5: "Definition of typical measurement profiles";
- Part 6: "Post processing and statistical methods";
- Part 7: "Network based Quality of Service measurements".

Part 1 builds an umbrella document for this multi-part deliverable. It summarizes the basics of Quality of Service, always seen from the user's perspective. Differences to Quality of Experience (QoE) are also discussed. In extension to generic definitions, specific definitions for this multi-part deliverable are stated here. Furthermore, it gives guidance to assure that QoS assessments can be conducted in a meaningful way and proposes an according process.

Part 2 defines QoS parameters and their computation for popular services in mobile networks. The parameter definition is split into several parts. It contains an abstract definition which gives a generic description of the parameter, an abstract equation and the corresponding user and technical trigger points.

The harmonized definitions given in part 2 are considered as prerequisites for the comparison of QoS measurements and measurement results.

The present document describes the measurement procedures needed to perform the measurements of QoS parameters in line with the definitions given in part 2, applying the test profiles defined in part 5.

Part 4 defines the minimum requirements of QoS measurement equipment for mobile networks in the way that the values and trigger points needed to compute the QoS parameter as defined in part 2 can be measured following the procedures defined in part 3. Test equipment fulfilling the specified minimum requirements will allow performing the proposed measurements in a reliable and reproducible way.

Part 5 specifies typical measurement profiles which are required to enable benchmarking of different mobile networks both within and outside national boundaries.

Part 6 describes procedures to be used for statistical calculations in the field of QoS measurement of mobile networks using probing systems.

Part 7 describes how Quality of Service measurements should be done inside the network without direct access to the end point terminal.

Introduction

The present document describes the measurement procedures needed to perform the measurements of QoS parameters in line with the definitions given in part 2 [i.5], applying the test profiles defined in part 5 [3].

The aim of standardization of QoS measurements is to ensure that measurements done at different times and with different equipment produce comparable results. To reach this goal, not only computation rules have to be standardized. Since the result of measurements will depend on the way these measurements are performed, well-defined procedure definitions are also required to ensure comparable data.

iteh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c68b54b3-8538-49b4-99b0-0c56635d5325/etsi-ts-102-250-3-v2.3.1-2013-06>

1 Scope

The present document describes typical procedures used for QoS measurements on mobile communication networks, along with settings and parameters for such measurements.

Where possible, existing ITU-T or ETSI definitions are referenced. In some cases ITU-T or ETSI definitions do not exist or are considered too generic, then a more service and mobile network specific definition is chosen.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T P.56: "Objective measurement of active speech level".
- [2] Void
- [3] ETSI TS 102 250-5: "Speech and multimedia Transmission Quality (STQ); QoS aspects for popular services in mobile networks; Part 5: Definition of typical measurement profiles".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] IETF RFC 3501: "Internet message access protocol - version 4rev1".
- [i.2] IETF RFC 2177: "IMAP4 IDLE command".
- [i.3] IETF RFC 2821: "Simple Mail Transfer Protocol".
- [i.4] IETF RFC 1939: "Post Office Protocol - Version 3".
- [i.5] ETSI TS 102 250-2: "Speech and multimedia Transmission Quality (STQ); QoS aspects for popular services in mobile networks; Part 2: Definition of Quality of Service parameters and their computation".
- [i.6] ETSI TS 100 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

A-party: in direct transactions, the party initiating the transaction (calling party)

NOTE: In store-and-forward transactions, the party sending content.

B-party: in direct transactions, the termination or counterpart of a transaction

NOTE: In store-and-forward transactions, the party receiving content.

content: entirety of information transferred within a transaction, seen from the user's perspective

NOTE: In case of services requiring entrance procedures (e.g. server login with FTP), information flow to achieve the state of being able to transfer actual user data is not counted as content.

EXAMPLE: Single text message in SMS service; single multimedia message consisting of video, audio, and text components in MMS service.

direct transaction: real-time transaction between two entities

maximum expected delivery time: for store-and-forward services, this defines the time span within which a message has to be received by the B-party to rate the transaction successful from the user's perspective

service family: group of services having main characteristics in common

EXAMPLE: Speech and Video Telephony, as well as SMS and MMS, are assumed to form a service family.

store-and forward transaction: transaction where information is sent from one party A to another party B using an entity C to store information sent from A and attempting to deliver it to B

transaction: single, complete, typical usage of a particular service

NOTE 1: At the beginning of each clause describing a particular service or family of services, the typical transaction for this particular service is described.

NOTE 2: Each type of transaction has parameters. The sum of all parameters describes the transaction completely. A parameter set is assumed to be complete if, under constant outer conditions, all transactions using this parameter set provide the same result.

transaction result: set (list) of possible outcomes for a particular transaction

NOTE: Services belonging to the same service family share the same set of transaction results.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AOV	Angles Of View
APN	Access Point Name
CMTI	is not an abbreviation, it's an AT command, please remove it
CS	Circuit Switched
CSD	Circuit Switched Data
DNS	Domain Name Server
DRM	Digital Rights Management
FR	Failure Rate
FTP	File Transfer Protocol
GC	Group Call
GGSN	Gateway GPRS Support Node

GSM	Global Mobile System
HTML	Hyper Text Markup Language
HTTP	Hyper Text Transfer Protocol
ICMP	Internet Control Management Protocol
IP	Internet Protocol
MEDT	Maximum Expected Delivery Time
MMS	Multimedia Messaging Service
MOF	Mobile Originated to Fixed
MOM	Mobile Originated to Mobile
MTM	Mobile Terminated, originator is also a Mobile unit
MTSI	Multimedia Telephony over IMS
MTU	Maximum Transmission Unit
NAT	Network Address Translation
OMA	Open Media Access
OS	Operating System
PC	Personal Computer
PDP	Packet Data Protocol
PDU	Packet Data Unit
POP3	Post Office Protocol Version 3
PS	Packet Switched
PSD	Packet Switched Data
QoS	Quality of Service
RTP	Realtime Transport Protocol
S&F	Store and Forward
SDP	Service Delivery Platform
SDS	Short Data Service
SDS-TL	Short Data Service Transport Layer
SMS	Short Message Service
SMSC	Short Message Service Centre
SMS-MO	SMS Mobile Originated
SMS-MT	SMS Mobile Terminated
SMTP	Simple Mail Transfer Protocol
TCP/IP	Transmission Control Protocol/Internet Protocol
TETRA	Terrestrial Trunked Radio
UDP	User Datagram Protocol
UE	User Equipment
URL	Uniform Resource Locator
URL/IP	Uniform Resource Location
WAP	Wireless Access Protocol
WAP	Wireless Application Protocol

*Full standard:
https://standards.etsi.org/catalog/standards/sist/c68b54b3-
92d4-99b0-0e5635d5325/etsi-ts-102-250-3-v2.3.1-
06*

4 Aim of measurement

The aim of measurements described in the present document is to assess the network under test for its Quality of Service (QoS) parameters as defined in TS 102 250-2 [i.5]. This is to determine the network quality for the respective transactions from the user's view.

5 Classification of services

5.1 Classification guidelines

For the purpose of the present document, services are classified using what is considered to be their dominating property. The first distinction is made between direct and store-and-forward services:

- Direct-transaction services are services where there is - in the user's perception - a direct end-to-end connection.

- Store-and-forward services are services where content is stored in the network and delivered to the recipient at a later point in time.

As a technically usable differentiation, a service is considered to be direct if it is possible to decide on end-to-end content transfer success from the initiating party (A-party) of the connection within the scope of the transaction itself.

NOTE: e-Mail is a special case since it has both aspects of direct and of store and forward services. In the present document, it is, as in part 2 [i.5] of this multi-part deliverable, treated in the clause on store and forward services.

5.2 General structure of service descriptions

In the following, each service family description will contain the following structural elements:

- A general part defining:
 - the basic transaction definition and if applicable, transaction types;
 - a description of the transaction phase combined with a table of parameters governing transaction behaviour in this phase;
 - a description of all possible outcomes of a single transaction;
 - a description of content quality measurement definitions (if applicable)
- In case there are service-dependent differences, a service-dependent part having the same structure as above.

6 General aspects for all types of services

6.1 Set-up and control

Measurements should be conducted in a way that user behaviour is realistically modelled. Parameters and settings which have substantial influence on results need to be under control of the measurement equipment.

The testcase design (configuration and user profile) - to the degree necessary to fully reproduce the test - shall be part of the measurement documentation.

It is assumed that for all types of services under test, a testcase consists of a number of single identical transactions. The measurement equipment and control shall ensure that the starting conditions are the same for each transaction. This includes, among other things, that pause times are sufficiently long that the equipment is in a stable (idle) state again. The parameter "guard time" sets a minimum value for the pause between transactions.

It is assumed that all QoS-relevant transaction parameters are recorded for proper post-processing and are kept constant during measurements. If a measurement contains more than one parameter set, evaluation shall be made for each parameter set separately.

6.2 Phase and result classification

In order to ensure common wording, the following clause defines terms and definitions for service measurements.

It is assumed that each transaction can be described at least by one seamless sequence of phases. There may exist several Angles Of View (AOV), each leading to a different phase description.

EXAMPLE: Internet services (as described by its QoS parameters defined in TS 102 250-2 [i.5] model A and B). AOV differ here by different assumptions on start of service usage. Each AOV, however, is a consistent description by seamlessly connected phases.

Phases may be further described having sub-phases.

Pauses between transactions are not explicitly mentioned in this picture, but are relevant with respect to parameter reporting. Typically, there is a minimum pause (guard time) ensuring that the system under test is in a stable starting condition for the next test.

Depending on the used radio access technology the duration of required pauses may differ significantly.

However, this duration may be adjusted to local conditions or special testing goals, but this shall be reported.

If the pause duration is too short, side effects may occur, resulting in all kinds of transient effects and distortions in measurement data. It should be made certain that all the QoS parameters to be measured are not affected by the pause time.

Tables 1 to 4 void

7 Telephony measurements

This clause deals with telephony services. In general, the term "content" will be used throughout this clause for the information flow exchanged between participating users during a call. Depending on the type of service, content can be audio or audio and video.

7.1 General aspects

7.1.1 Transaction definition and transaction types

The basic transaction for telephony testing is equivalent to a single call to a counterpart extension.

7.1.2 Parameter overview

Table 5: Parameter overview for telephony measurements

Phase	Parameters
Service Access	Call counterpart: This includes the type of equipment (dedicated unit, unique identifier (e.g. called party number), automatic answer with taped message, etc.).
	Call type.
	Time-out value.
Service Usage	Call duration.
	Content flow direction: This is an inner parameter for a transaction. Basically, all combinations of uplink/downlink dynamics are possible: <ul style="list-style-type: none"> - Uplink only; - Downlink only; - Conversational (alternating uplink and downlink). This is the recommended standard testing mode. Other testing modes are considered to be used only for special purposes; - "Duplex" (uplink and downlink flow simultaneously).
	Codec settings.
	Algorithm and scale used for speech quality evaluation.
Call clear-down	Guard time.
Pause	Pause duration. For current UEs, a pause time of at least 15 seconds (guard time) is recommended. However, this duration may be adjusted to local conditions or special testing goals, but this shall be reported. If the pause duration is too short, side effects may occur, resulting in all kinds of transient effects and distortions in measurement data. It should be made certain that all the QoS parameters to be measured are not affected by the pause time.

The last transaction within a measurement sequence does not require a pause.