



SLOVENSKI STANDARD
SIST EN 301 502 V10.2.1:2013
01-februar-2013

Globalni sistem mobilnih komunikacij (GSM) - Harmonizirani EN za opremo za bazne postaje, ki zajema bistvene zahteve člena 3.2 direktive R&TTE

Global System for Mobile communications (GSM) - Harmonized EN for Base Station Equipment covering the essential requirements of article 3.2 of the R&TTE Directive

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 301 502 Version 10.2.1**
<https://standards.iteh.ai/catalog/standards/sist/652a2f56-2894-4783-912d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013>

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 301 502 V10.2.1:2013 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 502 V10.2.1:2013](https://standards.iteh.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013)

<https://standards.iteh.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013>

ETSI EN 301 502 V10.2.1 (2012-11)



**Global System for Mobile communications (GSM);
Harmonized EN for Base Station Equipment covering the
essential requirements of article 3.2 of the R&TTE Directive**

[SIST EN 301 502 V10.2.1:2013](https://standards.iteh.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013)

<https://standards.iteh.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013>

Reference

REN/MSG-0006

Keywords

base station, cellular, GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 502 V10.2.1:2013

<https://standards.iteh.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b695d/sist-en-301-502-v10-2-1-2013>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2012.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references	10
3 Definitions and abbreviations.....	10
3.1 Definitions	10
3.2 Abbreviations	13
4 Technical requirements specifications	14
4.1 Environmental profile.....	14
4.2 Conformance requirements	14
4.2.1 Modulation accuracy.....	15
4.2.1.1 Definition	15
4.2.1.2 Limit.....	16
4.2.1.3 Conformance.....	17
4.2.2 Mean transmitted RF carrier power	17
4.2.2.1 Definition	17
4.2.2.2 Limit.....	17
4.2.2.3 Conformance.....	18
4.2.3 Transmitted RF carrier power versus time.....	18
4.2.3.1 Definition	18
4.2.3.2 Limit.....	18
4.2.3.3 Conformance.....	22
4.2.4 Adjacent channel power.....	22
4.2.4.1 Spectrum due to modulation and wideband noise.....	22
4.2.4.1.1 Definition.....	22
4.2.4.1.2 Limit	22
4.2.4.1.3 Conformance	24
4.2.4.2 Switching transients spectrum.....	24
4.2.4.2.1 Definition.....	24
4.2.4.2.2 Limit	24
4.2.4.2.3 Conformance	25
4.2.5 Spurious emissions from the transmitter antenna connector.....	25
4.2.5.1 Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	25
4.2.5.1.1 Definition.....	25
4.2.5.1.2 Limit	25
4.2.5.1.3 Conformance	25
4.2.5.2 Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	25
4.2.5.2.1 Definition.....	25
4.2.5.2.2 Limit	25
4.2.5.2.3 Conformance	26
4.2.5.3 Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	26
4.2.5.3.1 Definition.....	26
4.2.5.3.2 Limit	27
4.2.5.3.3 Conformance	27
4.2.6 Intermodulation attenuation	27
4.2.6.1 Definition	27
4.2.6.2 Limit.....	27

4.2.6.2.1	For BTS not belonging to the multicarrier BTS class.....	27
4.2.6.2.2	For BTS belonging to the multicarrier BTS class.....	27
4.2.6.3	Conformance.....	28
4.2.7	Intra Base Station System intermodulation attenuation	28
4.2.7.1	Definition	28
4.2.7.2	Limit.....	28
4.2.7.2.1	For BTS not belonging to the multicarrier BTS class.....	28
4.2.7.2.2	For BTS belonging to the multicarrier BTS class.....	28
4.2.7.3	Conformance.....	28
4.2.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	29
4.2.8.1	Definition	29
4.2.8.2	Limit.....	29
4.2.9	Static Reference Sensitivity Level	30
4.2.9.1	Definition	30
4.2.9.2	Limit.....	30
4.2.9.3	Conformance.....	33
4.2.10	Multipath Reference Sensitivity Level	33
4.2.10.1	Definition	33
4.2.10.2	Limit.....	33
4.2.10.3	Conformance.....	42
4.2.11	Reference Interference Level.....	42
4.2.11.1	Definition	42
4.2.11.2	Limit.....	42
4.2.11.3	Conformance.....	57
4.2.12	Blocking Characteristics	58
4.2.12.1	Definition	58
4.2.12.2	Limit.....	58
4.2.12.2.1	Blocking	58
4.2.12.2.2	Spurious response	59
4.2.12.3	Conformance.....	59
4.2.13	Intermodulation characteristics.....	59
4.2.13.1	Definition	59
4.2.13.2	Limit.....	59
4.2.13.3	Conformance.....	59
4.2.14	AM suppression.....	59
4.2.14.1	Definition	59
4.2.14.2	Limit.....	60
4.2.14.3	Conformance.....	60
4.2.15	Spurious emissions from the receiver antenna connector	60
4.2.15.1	Definition	60
4.2.15.2	Limit.....	60
4.2.15.3	Conformance.....	60
4.2.16	Radiated spurious emissions	60
4.2.16.1	Definition	60
4.2.16.2	Limit.....	61
4.2.16.3	Conformance.....	61
5	Testing for compliance with technical requirements.....	61
5.1	Environmental conditions for testing	61
5.2	Interpretation of the measurement results	61
5.3	Essential radio test suites.....	62
5.3.1	Modulation accuracy.....	63
5.3.1.1	Test case.....	63
5.3.1.2	Test Environment.....	64
5.3.2	Mean transmitted RF carrier power	64
5.3.2.1	Test case.....	64
5.3.2.2	Test Environment.....	65
5.3.3	Transmitted RF carrier power versus time.....	65
5.3.3.1	Test case.....	65
5.3.3.2	Test Environment.....	66
5.3.4	Adjacent channel power.....	66
5.3.4.1	Spectrum due to modulation and wideband noise.....	66

5.3.4.1.1	Test case	66
5.3.4.1.2	Test Environment	67
5.3.4.2	Switching transients spectrum.....	67
5.3.4.2.1	Test case	67
5.3.4.2.2	Test Environment	68
5.3.5	Spurious emissions from the transmitter antenna connector.....	68
5.3.5.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	68
5.3.5.1.1	Test case	68
5.3.5.1.2	Test Environment	69
5.3.5.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	69
5.3.5.2.1	For BTS not belonging to the multicarrier BTS class.....	69
5.3.5.2.2	For BTS belonging to the multicarrier BTS class.....	70
5.3.5.3	Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	72
5.3.5.3.1	Test case	72
5.3.5.3.2	Test Environment	72
5.3.6	Intermodulation attenuation	72
5.3.6.1	Test case.....	72
5.3.6.2	Test Environment.....	74
5.3.7	Intra Base Station System intermodulation attenuation	74
5.3.7.1	Test case.....	74
5.3.7.2	Test Environment.....	75
5.3.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	75
5.3.8.1	Test case.....	75
5.3.8.2	Test Environment.....	77
5.3.9	Static reference sensitivity level.....	78
5.3.9.1	Test case.....	78
5.3.9.2	Test Environment.....	80
5.3.10	Multipath Reference Sensitivity Level	80
5.3.10.1	Test case.....	80
5.3.10.2	Test Environment.....	85
5.3.11	Reference Interference Level.....	85
5.3.11.1	Test case.....	85
5.3.11.2	Test Environment.....	94
5.3.12	Blocking Characteristics	95
5.3.12.1	Test case.....	95
5.3.12.2	Test Environment.....	99
5.3.13	Intermodulation characteristics	99
5.3.13.1	Test case.....	99
5.3.13.2	Test Environment.....	101
5.3.14	AM suppression	101
5.3.14.1	Test case.....	101
5.3.14.2	Test Environment.....	103
5.3.15	Spurious emissions from the receiver antenna connector	103
5.3.15.1	Test case.....	103
5.3.15.2	Test Environment.....	104
5.3.16	Radiated spurious emissions	104
5.3.16.1	Test case.....	105
5.3.16.2	Test Environment.....	107

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	108
-----------------------------	--	------------

Annex B (normative):	General test conditions and declarations.....	110
-----------------------------	--	------------

B.1	Declaration by manufacturer	110
B.1.1	Output power and determination of power class	110
B.1.2	Specified frequency range	110
B.1.3	Frequency hopping	111
B.1.4	RF power control.....	111

B.1.5	Downlink discontinuous transmission (DTX)	111
B.2	BTS Configurations.....	111
B.2.1	Receiver diversity.....	112
B.2.2	Duplexers	112
B.2.3	Power supply options	113
B.2.4	Ancillary RF amplifiers.....	113
B.2.5	BSS using antenna arrays	113
B.2.6	BTS supporting 8-PSK modulation.....	115
B.2.7	BTS supporting additional modulations in EGPRS2.....	115
B.2.8	Supported Symbol Rate.....	115
B.2.9	Support of RTTI and/or FANR	115
B.2.10	Multicarrier BTS	115
B.2.11	BTS supporting VAMOS	117
Annex C (normative): Test environments.....		118
C.1	Normal test environment.....	118
C.2	Extreme test environment.....	118
C.2.1	Extreme temperature	119
C.3	Vibration.....	119
C.4	Power supply	119
Annex D: Void		120
Annex E (informative): Bibliography.....		121
History		122

iTech STANDARD PREVIEW
(standards.itech.ai)

[SIST EN 301 502 V10.2.1:2013](https://standards.itech.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013)

<https://standards.itech.ai/catalog/standards/sist/652a2f56-2894-4783-9f2d-a1b8d93b6986/sist-en-301-502-v10-2-1-2013>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.7].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonised Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarised in annex A.

National transposition dates	
Date of adoption of this EN:	2 November 2012
Date of latest announcement of this EN (doa):	28 February 2013
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2013
Date of withdrawal of any conflicting National Standard (dow):	31 August 2014

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment type:

- 1) GSM base stations.

Table 1-1: GSM Base Station System frequency bands

GSM band	Direction of transmission	GSM Base Station System relevant frequency bands
P-GSM 900	Transmit	935 MHz to 960 MHz
	Receive	890 MHz to 915 MHz
E-GSM 900	Transmit	925 MHz to 960 MHz
	Receive	880 MHz to 915 MHz
R-GSM 900	Transmit	921 MHz to 960 MHz
	Receive	876 MHz to 915 MHz
DCS 1 800	Transmit	1 805 MHz to 1 880 MHz
	Receive	1 710 MHz to 1 785 MHz
GSM 450	Transmit	460,4 MHz to 467,6 MHz
	Receive	450,4 MHz to 457,6 MHz
GSM 480	Transmit	488,8 MHz to 496 MHz
	Receive	478,8 MHz to 486 MHz

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive), Article 3.2, which states that "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In regards to interference to systems operating in adjacent bands guidance for single carrier BTS and multicarrier BTS is provided in ECC Report 146 [i.4].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 121 905 (V10.3.0) (03/2011): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Vocabulary for 3GPP Specifications (3GPP TR 21.905 version 10.3.0 Release 10)".

- [2] ETSI TS 151 021 (V10.4.0) (03/2012): "Digital cellular telecommunications system (Phase 2+); Base Station System (BSS) equipment specification; Radio aspects (3GPP TS 51.021 version 10.4.0 Release 10)".
- [3] ETSI TS 145 002 (V10.3.0) (03/2012): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path (3GPP TS 45.002 version 10.3.0 Release 10)".
- [4] ETSI TS 145 004 (V10.0.0) (04/2011): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 10.0.0 Release 10)".
- [5] ETSI TS 145 005 (V10.4.0) (03/2012): "Digital cellular telecommunications system (Phase 2+); Radio Transmission and reception (3GPP TS 45.005 version 10.4.0 Release 10)".
- [6] Void.
- [7] ETSI TS 145 010 (V10.1.0) (04/2011): "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization (3GPP TS 45.010 version 10.1.0 Release 10)".
- [8] ETSI TS 144 060 (V10.8.0) (03/2012): "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control / Medium Access Control (RLC/MAC) protocol (3GPP TS 44.060 version 10.8.0 Release 10)".
- [9] ETSI TR 100 028 (all parts) (V1.4.1) (12/2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [10] ETSI EN 300 019-1-0 (V2.1.2) (09/2003): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [11] ETSI EN 300 019-1-3 (V2.3.2) (11/2009): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations".
- [12] ETSI EN 300 019-1-4 (V2.1.2) (04/2003): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weatherprotected locations".
- [13] IEC 60068-2: "Environmental testing procedures:
Part 2-1 (ed.6, 3/2007): Tests - Test A: Cold;
Part 2-2 (ed. 5, 7/2007): Tests - Test B: Dry heat;
Part 2-6 (ed.7, 12/2007): Tests - Test Fc: Vibration (sinusoidal);
Part 2-64 (ed. 2, 4/2008): Tests - Test Fh: Vibration, broadband random and guidance".
- [14] IEC 60721: "Classification of environmental conditions:
Part 1 (ed.2.2, 10/2002): Environmental parameters and their severities;
Part 2-1 (ed.1.1, 10/2002): Environmental conditions appearing in nature - Temperature and humidity;
Part 2-4 (ed.1.1, 10/2002): Environmental conditions appearing in nature - Solar radiation and temperature;
Part 3-0 (ed.1.1, 10/2002): Classification of groups of environmental parameters and their severities – Introduction".
- [15] ETSI TS 124 022 (V10.0.1) (04/2011): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Radio Link Protocol (RLP) for circuit switched bearer and teleservices (3GPP TS 24.022 version 10.0.1 Release 10)".
- [16] ETSI TS 148 020 (V10.0.1) (05/2011): "Digital cellular telecommunications system (Phase 2+); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS-MSC) interface (3GPP TS 48.020 version 10.0.1 Release 10)".
- [17] ITU-T Recommendation O.153 (10/1992): "Basic Parameters for the measurement of error performance at bit rates below the primary rate".

- [18] ITU-R Recommendation SM.329-11 (01/2011): "Unwanted emissions in the spurious domain".
- [19] ETSI TS 145 001 (V10.1.0) (01/2012): "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path; General description (3GPP TS 45.001 version 10.1.0 Release 10)".
- [20] ITU-T Recommendation O.151 (10/1992): "Error performance measuring equipment operating at the primary rate and above".
- [21] CEPT/ERC/Recommendation 74-01E (01/2011): "Unwanted emissions in the spurious domain".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.4] ECC Report 146: "Compatibility between GSM MCBTS and other services (TRR, RSBN/PRMG, HC-SDMA, GSM-R, DME, MIDS, DECT) operating in the 900 and 1800 MHz frequency bands", 6th July 2010.
- [i.5] ETSI EN 301 908-1: "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 1: Introduction and common requirements".
- [i.6] ETSI EN 301 908-18: "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS)".
- [i.7] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 121 905 [1] and the following apply:

8-PSK: modulation type as defined in TS 145 004 [4], clause 3

16-QAM: modulation type as defined in TS 145 004 [4], clause 4 for EGPRS2-A and clause 5 for EGRPS2-B

32-QAM: modulation type as defined in TS 145 004 [4], clause 4 for EGPRS2-A and clause 5 for EGRPS2-B

ancillary RF amplifier: piece of equipment, which when connected by RF coaxial cables to the BTS, has the primary function to provide amplification between the transmit and/or receive antenna connector of a BTS and an antenna without requiring any control signal to fulfil its amplifying function

AQPSK: modulation type as defined in TS 145 004 [4], clause 6

base station RF bandwidth: instantaneous bandwidth in which a BTS belonging to the multicarrier BTS class transmits or transmits and receives multiple carriers simultaneously

BSS: in the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS

NOTE: If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

Base Station System Test Equipment (BSSTE): See annex B in TS 151 021 [2].

carrier frequency: centre of the ARFCN under test

circuit switched logical channels: all the standard GSM logical channels, including traffic channels (TCH), common control channels (RACH) and dedicated control channels (SDCCH, SACCH)

E-GSM: extended GSM 900 band (includes P-GSM band)

ECSD: any subset of the E-TCH traffic channels and related control channels

EGPRS: any subset of the packet traffic channels PDTCH/MCS-1 to MCS-9 and related control channels

EGPRS2: any of EGPRS2-A and EGPRS2-B

EGPRS2-A: packet traffic channels utilizing any subset of the packet traffic channels MCS-1 to 6 and PDTCH/UAS-7 to UAS-11 in uplink, together with MCS-1 to 4 and PDTCH/DAS-5 to DAS-12 in downlink, and related control channels

NOTE: In addition, MCS-7 and MCS-8 may be used in downlink when either the USF or the PAN or both are addressed to one or more EGPRS mobile stations.

EGPRS2-B: packet traffic channels utilizing any subset of the packet traffic channels MCS-1 to 4 and PDTCH/UBS-5 to UBS-12 in uplink, together with MCS-1 to 4 and PDTCH/DBS-5 to DBS-12 in downlink, and related control channels

NOTE: In addition, MCS-6 to MCS-9, DAS-5, DAS-6, DAS-8, DAS-9, DAS-10 pad, DAS-11, and DAS-12 pad may be used in downlink under the conditions specified in TS 144 060 [8].

enclosure port: physical boundary of the apparatus through which electromagnetic fields may radiate or impinge

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

GMSK: modulation type as defined by TS 145 004 [4], clause 2

GPRS: any subset of the packet traffic channels PDTCH/CS-1 to CS-4 and related control channels

GSM: unless otherwise specified, references to GSM include GSM 400, GSM 900 and DCS 1 800

GSM 400: unless otherwise specified, references to GSM 400 include GSM 450 and GSM 480 band

GSM 900: unless otherwise specified, references to GSM 900 include P-GSM, E-GSM and R-GSM band

manufacturer: in the present document, a reference to a manufacturer also applies to an agent of the manufacturer

maximum base station RF bandwidth: maximum bandwidth in which a BTS belonging to the multicarrier BTS class transmits or transmits and receives multiple carriers simultaneously

maximum transmit filter bandwidth: maximum bandwidth of the duplexer or the transmit filter used in a BTS belonging to the multicarrier BTS class transmitting carriers simultaneously

micro-BTS: low-power BTS with performance requirements defined in TS 145 005 [5]

NOTE: In the present document, this also includes a BSS which incorporates a micro-BTS.

minimum carrier frequency spacing: minimum spacing between the centre frequencies of simultaneously transmitted or received GSM carriers of a BTS belonging to the multicarrier BTS class

NOTE: The minimum carrier frequency spacing is 600 kHz.

multicarrier BTS: class of BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously, either in multicarrier transmitter only, or, in both multicarrier transmitter and multicarrier receiver

multicarrier BTS equipped with multicarrier receiver: subgroup of multicarrier BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously, in both multicarrier transmitter and multicarrier receiver

normal BTS: any BTS or BSS as defined by TS 145 005 [5] which is not a micro-BTS or pico-BTS

operating band: transmit and receive operating bands together comprise the frequency band supported by the BSS

NOTE: As defined in clause B.1.2.

P-GSM: primary GSM 900 band

packet switched logical channels: all the General Packet Radio Services (GPRS) packet data logical channels, including packet traffic channels (PDTCH and PACCH) and packet common control channels (PRACH)

pico-BTS: low-power BTs with performance requirements defined in TS 145 005 [5]

NOTE: In the present document, this also includes a BSS which incorporates a pico-BTS.

port: particular interface, of the specified equipment (apparatus), with the electromagnetic environment

QPSK: modulation type as defined TS 145 004 clause 5 [4], used in EGPRS2-B

R-GSM: Railways GSM 900 band (includes P-GSM band and E-GSM band)

radio digital unit: equipment which contains base band and functionality for controlling radio unit

radio equipment: equipment which contains radio digital unit and radio unit

radio unit: equipment which contains transmitter and receiver

relevant RX band (or relevant receive band): receive band for the frequency band of BTS declared by the manufacturer

NOTE: As defined in clause 1.

relevant TX band (or relevant transmit band): transmit band for the frequency band of BTS declared by the manufacturer

NOTE: As defined in clause 1.

SCPIR_DL: As defined in TS 145 004 [4], clause 6.

SCPIR_UL: As defined in TS 145 005 [5], clause 1.3.

sub-block: contiguous allocated block of spectrum for use by the same Base Station

NOTE: There may be multiple instances of sub-blocks within an RF bandwidth.

sub-block bandwidth: bandwidth of one sub-block

sub-block gap: frequency gap between two consecutive sub-blocks within an RF bandwidth, where the RF requirements in the gap are based on co-existence for un-coordinated operation

VAMOS mode: As defined in TS 145 001 [19], clause 13.1.

VAMOS sub-channel: As defined in TS 145 001 [19], clause 13.1.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 121 905 [1] and the following apply:

AGC	Automatic Gain Control
AM	Amplitude Modulation
AMR	Adaptive Multi-Rate
AMR-WB	Adaptive - Wideband
AQPSK	Adaptive Quadrature Phase Shift Keying
ARFCN	Absolute Radio Frequency Channel Number
B	Bottom
BCCH	Broadcast Control Channel
BER	Bit Error Ratio
BFI	Bad Frame Indication
BLER	Block Error Ratio
BS	Base Station
BSC	Base Station Controller
BSS	Base Station System
BSSTE	Base Station System Test Equipment
BTS	Base Transceiver Station
BTTI	Basic Transmission Time Interval
BW	Bandwidth
DAS	EGPRS2 Downlink Level A modulation and coding Scheme
DBS	EGPRS2 Downlink Level B modulation and coding Scheme
DC	Direct Current
DCS	Digital Cellular System
DTX	Discontinuous Transmission
ECSD	Enhanced Circuit Switched Data
EGPRS	Enhanced GPRS
EGPRS2	Enhanced GPRS phase 2
ESIDR	Erased SID frame Rate
E-TCH	Enhanced Traffic Channel
EVM	Error Vector Magnitude
EVRFR	Erased Valid RATSCCH Frame Rate
EVSIDR	Erased Valid SID frame Rate
EVSIDUR	Erased Valid SID_UPDATE frame Rate associated to an adaptive speech traffic channel
FACCH	Fast Associated Control Channel
FANR	Fast Ack/Nack Reporting
FER	Frame Erasure Ratio
FH	Frequency Hopping
FS	Full rate Speech
GMSK	Gaussian Minimum Shift Keying
GPRS	General Packet Radio Service
GSM-R	GSM Railway
HB	Higher symbol rate Burst
IM	InterModulation
M	Middle
MCBTS	multicarrier BTS
MCS	Modulation Coding Scheme
MFS	Multipath Fading Simulator
MS	Mobile Station
MSC	Mobile service Switching Centre
MSE	Mean Square Error
MXM	Mixed Mode
NB	Normal Burst
NT	Non Transparent
O-FACCH	Octal Fast Associated Control Channel
PACCH	Packet Associated Control CHannel
PAN	Piggy-backed Ack/Nack message
PCS	Personal Communication System
PDTCH	Packet Data Traffic Channel