

SLOVENSKI STANDARD SIST EN 13523-2:2014

01-september-2014

Nadomešča: SIST EN 13523-2:2002

Prevlečene kovine, ki se navijajo - Preskusne metode - 2. del: Sijaj

Coil coated metals - Test methods - Part 2: Gloss

Bandbeschichtete Metalle - Prüfverfahren - Teil 2: Glanz

Tôles prélaquées - Méthodes d'essai - Partie 2: Brillant (standards.iteh.ai)

Ta slovenski standard je istoveten z: TEN EN:13523-2:2014 https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-

<u>ICS:</u>

17.180.20	Barve in merjenje svetlobe	Colours and measurement of light
25.220.60	Organske prevleke	Organic coatings

SIST EN 13523-2:2014

en,fr,de



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 13523-2:2014 https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-7936d38c7dc9/sist-en-13523-2-2014

SIST EN 13523-2:2014

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 13523-2

June 2014

ICS 25.220.60

Supersedes EN 13523-2:2001

English Version

Coil coated metals - Test methods - Part 2: Gloss

Tôles prélaquées - Méthodes d'essai - Partie 2: Brillant

Bandbeschichtete Metalle - Prüfverfahren - Teil 2: Glanz

This European Standard was approved by CEN on 7 May 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

<u>SIST EN 13523-22014</u>

https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-7936d38c7dc9/sist-en-13523-2-2014



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Ref. No. EN 13523-2:2014 E

SIST EN 13523-2:2014

EN 13523-2:2014 (E)

Contents

Forewo	ord	.3
Introdu	uction	.5
1	Scope	.6
2	Normative references	.6
3	Terms and definitions	.6
4	Principle	.6
5	Apparatus	.6
6	Sampling	.6
7	Test panels	.7
8	Procedure	.7
8.1	Selection of the measuring geometry	
8.2	Calibration	
8.3	Measurement	
9	Expression of results	.7
10	Expression of results ITEM STANDARD PREVIEW Precision Test report (standards.iteh.ai)	.7
	(standards.iteh.ai)	_
11		
Bibliog	Jraphy	.9
	https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-	

7936d38c7dc9/sist-en-13523-2-2014

Foreword

This document (EN 13523-2:2014) has been prepared by Technical Committee CEN/TC 139 "Paints and varnishes", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2014, and conflicting national standards shall be withdrawn at the latest by December 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13523-2:2001.

The main technical changes are:

- a) the text was aligned with the revision of EN ISO 2813, i.e. the result of the measurement is expressed in gloss units (GU);
- b) the definition for specular gloss was deleted;
- c) for calibration of the glossmeter, a reference to EN ISO 2813 was added;
- d) a remark on preconditioning was added;
- e) the procedure was amended so that measurements can be taken in the rolling direction or perpendicular to the rolling direction, which has to be stated in the test report;
- f) the selection of the measuring geometry was aligned with the revision of EN ISO 2813.
- g) for precision data, a reference to EN ISO 2813 was added.
- EN 13523, Coil coated metals Test methods, consists of the following parts:
- Part 0: General introduction
- Part 1: Film thickness
- Part 2: Gloss
- Part 3: Colour difference Instrumental comparison
- Part 4: Pencil hardness
- Part 5: Resistance to rapid deformation (impact test)
- Part 6: Adhesion after indentation (cupping test)
- Part 7: Resistance to cracking on bending (T-bend test)
- Part 8: Resistance to salt spray (fog)
- Part 9: Resistance to water immersion
- Part 10: Resistance to fluorescent UV radiation and water condensation

EN 13523-2:2014 (E)

- Part 11: Resistance to solvents (rubbing test)
- Part 12: Resistance to scratching
- Part 13: Resistance to accelerated ageing by the use of heat
- Part 14: Chalking (Helmen method)
- Part 15: Metamerism
- Part 16: Resistance to abrasion
- Part 17: Adhesion of strippable films
- Part 18: Resistance to staining
- Part 19: Panel design and method of atmospheric exposure testing
- Part 20: Foam adhesion
- Part 21: Evaluation of outdoor exposed panels
- Part 22: Colour difference Visual comparison
- Part 23: Resistance to humid atmospheres containing sulfur dioxide
- Part 24: Resistance to blocking and pressure marking iteh.ai)
- Part 25: Resistance to humidity
- SIST EN 13523-2:2014
- Part 26: Resistance to condensation of water 7936d38c7dc9/sist-en-13523-2-2014
- Part 27: Resistance to humid poultice (Cataplasm test)
- Part 29: Resistance to environmental soiling (Dirt pick-up and striping)

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

In EN 1396 and EN 10169, tolerances against nominal gloss are given for different gloss ranges of the coil coated product.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 13523-2:2014 https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-7936d38c7dc9/sist-en-13523-2-2014

1 Scope

This part of EN 13523 specifies the procedure for determining the gloss of an organic coating on a metallic substrate. Gloss is a characteristic of fundamental importance to the appearance of the coil coated product.

The apparatus requires a flat specimen of size greater than the aperture, thus, uneven surfaces cannot be measured.

This method is applicable to all pigmented and unpigmented coatings including metallic/pearlescent coatings. However, for textured coatings it is only indicative.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13523-0:2014, Coil coated metals — Test methods — Part 0: General introduction

EN 23270, Paints and varnishes and their raw materials — Temperatures and humidities for conditioning and testing (ISO 3270)

EN ISO 2813, Paints and varnishes — Determination of specular gloss of non-metallic paint films at 20°, 60° and 85° (ISO 2813)

iTeh STANDARD PREVIEW

3 Terms and definitions

(standards.iteh.ai) For the purposes of this document, the terms and definitions given in EN 13523-0:2014 and the following SIST EN 13523-2:2014 apply.

https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-7936d38c7dc9/sist-en-13523-2-2014

3.1 gloss

optical property of a surface, characterized by its ability to reflect light specularly

[SOURCE: FprEN ISO 4618:2014, 2.132, modified, Note 1 to entry deleted]

Principle 4

The gloss of the organic coating is determined by measuring the specular reflectance. The angle of incident light is usually 60°, but angles of 20° or 85° may be used for more accurate measurement of high or low gloss values.

5 Apparatus

Ordinary laboratory apparatus, together with the following:

5.1 60° glossmeter or multi-angle glossmeter, in accordance with EN ISO 2813.

Calibration standards, as recommended by the manufacturer of the glossmeter, in accordance with 5.2 EN ISO 2813.

Sampling 6

See EN 13523-0.

7 Test panels

See EN 13523-0.

8 Procedure

8.1 Selection of the measuring geometry

Specify the optimum reflector geometry based on a measurement of the sample with the 60° geometry:

- The 60° geometry is applicable to all paint films, but for very high gloss and near-matt films 20° or 85° might be more suitable.
- The 20° geometry is intended to give improved differentiation between high-gloss paint films, i.e. films with a 60° gloss higher than about 70 GU (gloss units).
- The 85° geometry is intended to give improved differentiation between low-gloss paint films, i.e. films with a 60° gloss lower than about 10 GU (gloss units).

8.2 Calibration

Adjust the instrument with a high-gloss reference standard to the assigned gloss value, as specified in EN ISO 2813.

8.3 Measurement iTeh STANDARD PREVIEW

Measure the gloss at ambient temperature. For more accurate measurements, as required for instance in case of dispute, the temperature shall be (23 ± 2) °C and the relative humidity (50 ± 5) %, in accordance with EN 23270. Conditioning is carried out in accordance with EN 13523-0:2014, Clause 6.

https://standards.iteh.ai/catalog/standards/sist/fc0de59a-4cf2-4dd1-a744-

The gloss may be measured in the rolling direction or perpendicular to the rolling direction. The direction of measurement shall be stated in the test report.

Place the instrument's aperture over the coated specimen and note the gloss reading. Take readings at not less than three different parts of the coated specimen at the specified geometry (60°, 20° or 85°). Report the gloss as the average of these readings and report the geometry used if it is not 60°.

9 Expression of results

Express the result of the measurements in gloss units (GU), as the average of the readings taken.

10 Precision

For precision data see EN ISO 2813.

11 Test report

The test report shall contain at least the following information:

- a) all details necessary to identify the product tested;
- b) a reference to this part of EN 13523 (EN 13523-2);
- c) the geometry used if it is not 60°;
- d) whether the measurement has been taken in the rolling direction or perpendicular to the rolling direction;