

SLOVENSKI STANDARD
SIST EN 301 473 V1.4.1:2013
01-maj-2013

Satelitske zemeljske postaje in sistemi (SES) - Letalske zemeljske postaje (AES), ki obratujejo v letalski mobilni satelitski storitvi (AMSS) in mobilni satelitski storitvi (MSS) oziroma v letalski mobilni satelitski storitvi na poti (AMS(R)S) in mobilni satelitski storitvi (MSS), v območju pod 3 GHz

Satellite Earth Stations and Systems (SES) - Aircraft Earth Stations (AES) operating below 3 GHz under the Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS) and/or the Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS)

iTEH STANDARD PREVIEW

(standards.iteh.ai)

[SIST EN 301 473 V1.4.1:2013](#)
<https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7f3a-4bc7-a4e4-7debbb5f8cdd/sist-en-301-473-v1-4-1-2013>

Ta slovenski standard je istoveten z: EN 301 473 Version1.4.0

ICS:

33.060.30 Radiorelejni in fiksni satelitski Radio relay and fixed satellite komunikacijski sistemi communications systems

SIST EN 301 473 V1.4.1:2013

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 473 V1.4.1:2013

<https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7f3a-4bc7-a4e4-7debbb5f8cdd/sist-en-301-473-v1-4-1-2013>

ETSI EN 301 473 V1.4.1 (2013-03)



**Satellite Earth Stations and Systems (SES);
Aircraft Earth Stations (AES) operating below 3 GHz under the
Aeronautical Mobile Satellite Service (AMSS)/
Mobile Satellite Service (MSS) and/or the
Aeronautical Mobile Satellite on Route Service (AMS(R)S)/
Mobile Satellite Service (MSS)**

Reference

REN/SES-00325

Keywords

aeronautical, AMSS, earth station, mobile, MSS,
satellite***ETSI***650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)

[SIST EN 301 473 V1.4.1:2013](#)
<https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7f3a-4bc7-a4e4-7debb5fb4000?version=1.4.1&date=2013-03-01>

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|--|----|
| Intellectual Property Rights | 8 |
| Foreword..... | 8 |
| Introduction | 8 |
| 1 Scope | 9 |
| 2 References | 9 |
| 2.1 Normative references | 9 |
| 2.2 Informative references..... | 10 |
| 3 Definitions and abbreviations..... | 10 |
| 3.1 Definitions | 10 |
| 3.2 Abbreviations | 11 |
| 4 General | 12 |
| 4.1 Presentation of equipment for testing purposes..... | 12 |
| 4.2 Aircraft earth stations | 12 |
| 4.3 Description of equipment | 13 |
| 5 Requirements for AES transmitting in the band 1 610 MHz to 1 626,5 MHz | 14 |
| 5.1 Unwanted emissions limits outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on) | 14 |
| 5.1.1 Purpose | 14 |
| 5.1.2 Conformance requirements..... | 14 |
| 5.1.3 Method of test | 14 |
| 5.1.4 Peak measurement | 15 |
| 5.1.5 Average measurement..... | 15 |
| 5.1.6 Test requirements..... | 16 |
| 5.2 Unwanted emissions limits within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on) | 16 |
| 5.2.1 Purpose | 16 |
| 5.2.2 Conformance requirements..... | 16 |
| 5.2.3 Method of test | 17 |
| 5.2.4 Measurement method..... | 18 |
| 5.2.5 Test requirements..... | 18 |
| 5.3 EIRP density limits within the operational band | 18 |
| 5.3.1 Purpose | 18 |
| 5.3.2 Conformance requirements..... | 18 |
| 5.3.3 Method of test | 19 |
| 5.3.4 Peak Limit Test..... | 19 |
| 5.3.5 Mean Limit Test | 19 |
| 5.3.6 Test requirements..... | 20 |
| 5.4 Unwanted emissions limits (carrier-off)..... | 20 |
| 5.4.1 Purpose | 20 |
| 5.4.2 Conformance requirements..... | 20 |
| 5.4.3 Method of test | 20 |
| 5.4.4 Peak measurement | 21 |
| 5.4.5 Average measurement..... | 21 |
| 5.4.6 Test requirements..... | 21 |
| 5.5 AES Control and Monitoring Functions (CMF)..... | 21 |
| 5.5.1 Special test equipment | 21 |
| 5.5.2 Self-monitoring functions | 22 |
| 5.5.2.1 Processor monitoring | 22 |
| 5.5.2.1.1 Purpose | 22 |
| 5.5.2.1.2 Conformance requirements..... | 22 |
| 5.5.2.1.3 Method of test..... | 22 |
| 5.5.2.2 Transmit frequency generation sub-system monitoring | 22 |
| 5.5.2.2.1 Purpose | 22 |

| | | |
|-----------|---|----|
| 5.5.2.2.2 | Conformance requirements..... | 22 |
| 5.5.2.2.3 | Method of test..... | 22 |
| 5.5.3 | Network control authorization and reception..... | 22 |
| 5.5.3.1 | Network control authorization | 22 |
| 5.5.3.1.1 | Purpose | 22 |
| 5.5.3.1.2 | Conformance requirements..... | 23 |
| 5.5.3.1.3 | Method of test..... | 23 |
| 5.5.3.1.4 | Test procedure | 23 |
| 5.5.3.1.5 | Test requirement..... | 23 |
| 5.5.3.2 | Network control reception transmit frequency control..... | 23 |
| 5.5.3.2.1 | Purpose | 23 |
| 5.5.3.2.2 | Conformance requirements..... | 24 |
| 5.5.3.2.3 | Method of test..... | 24 |
| 5.5.3.2.4 | Test procedure | 24 |
| 5.5.3.2.5 | Test requirement..... | 24 |
| 5.6 | Equipment identity | 24 |
| 5.6.1 | Purpose | 24 |
| 5.6.2 | Conformance requirements..... | 24 |
| 5.6.3 | Method of test | 25 |
| 5.6.4 | Test procedure | 25 |
| 5.6.5 | Test requirements..... | 25 |
| 6 | Requirements for AES transmitting in the band 1 626,5 MHz to 1 660,5 MHz and the band 1 668,0 MHz to 1 675,0 MHz | 25 |
| 6.1 | Unwanted emissions limits outside the band 1 626,5 MHz to 1 660,5 MHz and the band 1 660,5 MHz to 1 662,5 MHz and also outside the band 1 666,0 MHz to 1 668,0 MHz, the band 1 668,0 MHz to 1 675,0 MHz and the band 1 675,0 MHz to 1 677,0 MHz | 25 |
| 6.1.1 | Purpose | 25 |
| 6.1.2 | Conformance requirements..... | 26 |
| 6.1.3 | Testing for carrier on state (standards.iteh.ai) | 32 |
| 6.1.3.1 | Method of test | 32 |
| 6.1.3.2 | Measurement method | 33 |
| 6.1.3.3 | Test requirements | 33 |
| 6.1.4 | Testing for carrier off state (standards.iteh.ai) | 33 |
| 6.1.4.1 | Method of test | 33 |
| 6.1.4.2 | Peak measurement method..... | 34 |
| 6.1.4.3 | Average measurement..... | 34 |
| 6.1.4.4 | Test requirements | 34 |
| 6.2 | Unwanted emissions limits within the band 1 626,5 MHz to 1 660,5 MHz and the band 1 660,5 MHz to 1 662,5 MHz and also within the band 1 666,0 MHz to 1 668,0 MHz, the band 1 668,0 MHz to 1 675,0 MHz and the band 1 675,0 MHz to 1 677,0 MHz | 35 |
| 6.2.1 | Purpose | 35 |
| 6.2.2 | Conformance requirements | 35 |
| 6.2.2.1 | General | 35 |
| 6.2.2.2 | Specification 1: Carrier-on state | 35 |
| 6.2.2.3 | Specification 2: Carrier-off state | 38 |
| 6.2.3 | Testing for carrier on state | 38 |
| 6.2.3.1 | Method of test | 38 |
| 6.2.3.2 | Measurement method | 39 |
| 6.2.3.3 | Test requirements | 39 |
| 6.2.4 | Testing for carrier off state | 39 |
| 6.2.4.1 | Method of test | 39 |
| 6.2.4.2 | Peak measurement method..... | 40 |
| 6.2.4.3 | Average measurement | 40 |
| 6.2.4.4 | Test requirements | 40 |
| 6.3 | AES Control and Monitoring Functions (CMF)..... | 40 |
| 6.3.1 | Special test equipment | 40 |
| 6.3.2 | Self-monitoring functions | 41 |
| 6.3.2.1 | Processor monitoring | 41 |
| 6.3.2.1.1 | Purpose | 41 |
| 6.3.2.1.2 | Conformance requirements..... | 41 |
| 6.3.2.1.3 | Method of test..... | 41 |

| | | |
|-----------|--|----|
| 6.3.2.2 | Transmit frequency generation sub-system monitoring | 41 |
| 6.3.2.2.1 | Purpose | 41 |
| 6.3.2.2.2 | Conformance requirements..... | 41 |
| 6.3.2.2.3 | Method of test..... | 41 |
| 6.3.3 | Network control authorization and reception..... | 41 |
| 6.3.3.1 | Network control authorization | 41 |
| 6.3.3.1.1 | Purpose | 41 |
| 6.3.3.1.2 | Conformance requirements..... | 42 |
| 6.3.3.1.3 | Method of test..... | 42 |
| 6.3.3.1.4 | Test procedure | 42 |
| 6.3.3.1.5 | Test requirement..... | 42 |
| 6.3.3.2 | Network control reception transmit frequency control..... | 42 |
| 6.3.3.2.1 | Purpose | 42 |
| 6.3.3.2.2 | Conformance requirements..... | 43 |
| 6.3.3.2.3 | Method of test..... | 43 |
| 6.3.3.2.4 | Test procedure | 43 |
| 6.3.3.2.5 | Test requirement..... | 43 |
| 6.4 | Equipment identity | 43 |
| 6.4.1 | Purpose | 43 |
| 6.4.2 | Conformance requirements..... | 43 |
| 6.4.3 | Method of test | 44 |
| 6.4.4 | Test procedure | 44 |
| 6.4.5 | Test requirements..... | 44 |
| 7 | Requirements for NGSO AES transmitting in the band 1 980 MHz to 2 010 MHz | 44 |
| 7.1 | Unwanted emissions limits outside the band 1 980,1 MHz to 2 009,9 MHz (carrier-on) | 44 |
| 7.1.1 | Purpose | 44 |
| 7.1.2 | Conformance requirements..... | 44 |
| 7.1.3 | Method of test | 45 |
| 7.1.4 | Peak measurement | 46 |
| 7.1.5 | Average measurement..... | 46 |
| 7.1.6 | Test requirements..... | 46 |
| 7.2 | Unwanted emissions limits within the bands 1 980,1 MHz to 2 009,9 MHz, 1 978,1 MHz to 1 980,1 MHz and 2 009,9 MHz to 2 011,9 MHz (carrier-on) https://standards.iteh.ai/catalog/standards/sist/153a0312-15a-4bc7-a4c7-7debb516ccdd/sist-en-301-473-v1-4-1-2013 | 46 |
| 7.2.1 | Purpose | 46 |
| 7.2.2 | Conformance requirements..... | 47 |
| 7.2.3 | Method of test | 47 |
| 7.2.4 | Measurement method..... | 48 |
| 7.2.5 | Test requirements..... | 48 |
| 7.3 | Unwanted emissions limits (carrier-off)..... | 48 |
| 7.3.1 | Purpose | 48 |
| 7.3.2 | Conformance requirements..... | 48 |
| 7.3.3 | Method of test | 49 |
| 7.3.4 | Peak measurement | 49 |
| 7.3.5 | Average measurement..... | 49 |
| 7.3.6 | Test requirements..... | 50 |
| 7.4 | AES Control and Monitoring Functions (CMF)..... | 50 |
| 7.4.1 | Special test equipment | 50 |
| 7.4.2 | Self-monitoring functions | 50 |
| 7.4.2.1 | Processor monitoring | 50 |
| 7.4.2.1.1 | Purpose | 50 |
| 7.4.2.1.2 | Conformance requirements..... | 50 |
| 7.4.2.1.3 | Method of test..... | 50 |
| 7.4.2.2 | Transmit frequency generation sub-system monitoring | 50 |
| 7.4.2.2.1 | Purpose | 50 |
| 7.4.2.2.2 | Conformance requirements..... | 51 |
| 7.4.2.2.3 | Method of test..... | 51 |
| 7.4.3 | Network control authorization and reception..... | 51 |
| 7.4.3.1 | Network control authorization | 51 |
| 7.4.3.1.1 | Purpose | 51 |
| 7.4.3.1.2 | Conformance requirements..... | 51 |
| 7.4.3.1.3 | Method of test..... | 51 |

| | | |
|-----------------------------|--|-----------|
| 7.4.3.1.4 | Test procedure | 51 |
| 7.4.3.1.5 | Test requirement | 52 |
| 7.4.3.2 | Network control reception | 52 |
| 7.4.3.2.1 | Transmit frequency control | 52 |
| 7.5 | Equipment identity | 53 |
| 7.5.1 | Purpose | 53 |
| 7.5.2 | Conformance requirements | 53 |
| 7.5.3 | Method of test | 53 |
| 7.5.4 | Test procedure | 53 |
| 7.5.5 | Test requirements | 53 |
| 8 | Protection of the global navigation satellite service operating in the band 1 559 MHz to 1 610 MHz | 54 |
| 8.1 | 1 559 MHz to 1 605 MHz | 54 |
| 8.1.1 | Purpose | 54 |
| 8.1.2 | Conformance requirements | 54 |
| 8.2 | 1 605 MHz to 1 610 MHz | 54 |
| 8.2.1 | Purpose | 54 |
| 8.2.2 | Conformance requirements | 54 |
| 8.3 | Method of test | 55 |
| 8.4 | Average measurement | 55 |
| 8.5 | Test requirements | 55 |
| 9 | Protection of the radio astronomy services operating in the band 1 610,6 MHz to 1 613,8 MHz and in the band 1 660 MHz to 1 670 MHz | 56 |
| 9.1 | Purpose | 56 |
| 9.2 | Conformance requirements | 56 |
| 9.2.1 | Alternative 1 iTeh STANDARD PREVIEW (https://standards.iteh.ai/catalog/standards/sist/155ab3b-7b3a-4bc7-a4e4/debb518cd/sist-en-301-473-v1-4-1-2013) | 56 |
| 9.2.2 | Alternative 2 | 57 |
| 9.2.3 | Protection of the radio astronomy service in the 1 660,0 MHz to 1 670,0 MHz band | 57 |
| 9.3 | Method of test - unwanted emissions (alternative 1) | 57 |
| 9.4 | Test procedure - unwanted emissions (alternative 1) | 57 |
| 9.5 | Test requirement - unwanted emissions (alternative 1) | 58 |
| 9.6 | Method of test - CMF function (alternative 2) | 58 |
| 9.7 | Test procedure - CMF function (alternative 2) | 58 |
| 9.8 | Test requirement - CMF function (alternative 2) | 59 |
| Annex A (normative): | General test requirements | 60 |
| A.1 | AES test modes | 60 |
| A.2 | Special Test Equipment | 60 |
| A.2.1 | STE description | 60 |
| A.2.2 | Use of STE for control and monitoring functions tests | 61 |
| A.2.3 | Test modulating signal | 61 |
| A.3 | Laboratory Test Equipment | 62 |
| A.4 | Interpretation of the measurement results | 62 |
| A.5 | Test report | 62 |
| Annex B (normative): | Environmental conditions | 63 |
| B.1 | General | 63 |
| B.2 | Environmental conformance requirements | 63 |
| B.3 | Environmental test conditions | 63 |
| Annex C (normative): | Arrangements for measurement of emissions from AES | 64 |
| C.1 | General | 64 |
| C.2 | Carrier-on emissions | 64 |
| C.2.1 | Equipment required | 64 |

| | | |
|-------------------------------|--|-----------|
| C.2.2 | Equipment arrangement | 65 |
| C.2.3 | Emissions from 4 GHz to 18 GHz..... | 65 |
| C.2.4 | Emissions from 10 kHz to 4 GHz..... | 65 |
| C.3 | Carrier-off emissions..... | 66 |
| C.3.1 | Equipment required | 66 |
| C.3.2 | Equipment arrangement | 66 |
| C.3.3 | Carrier-off emissions from 4 GHz to 18 GHz | 66 |
| C.3.4 | Carrier-off emissions from 10 kHz to 4 GHz | 67 |
| Annex D (informative): | Explanation of nominated bandwidth..... | 68 |
| D.1 | Introduction | 68 |
| D.2 | Interpretation of Parameters [B _n , f _c , a, b]..... | 68 |
| D.3 | Choice of nominated bandwidth..... | 68 |
| D.4 | Maximum value for nominated bandwidth | 70 |
| Annex E (informative): | Bibliography..... | 72 |
| History | 73 | |

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 473 V1.4.1:2013](#)

<https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7f3a-4bc7-a4e4-7debbb5f8cdd/sist-en-301-473-v1-4-1-2013>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

| National transposition dates | |
|--|------------------|
| Date of adoption of this EN: | 22 February 2013 |
| Date of latest announcement of this EN (doa): | 31 May 2013 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 30 November 2013 |
| Date of withdrawal of any conflicting National Standard (dow): | 30 November 2013 |

SIST EN 301 473 V1.4.1:2013
<https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7f3a-4bc7-a4e4-7debbb5f8cdd/sist-en-301-473-v1-4-1-2013>

Introduction

An AES to be effectively used on board an aircraft will also be subject to airworthiness approval. This approval will refer to additional requirements (e.g. ISO 7137 equivalent to EUROCAE ED-14D and RTCA DO-160D [1]). Foreseeable evolution of the GNSS (i.e. Galileo or GPS L5) would result in the coming years in specific requirements to protect the use of the GNSS signals on board aircraft. Therefore these new GNSS frequency bands may require different protection than currently stated in the present document.

1 Scope

The present document specifies certain minimum technical performance requirements of Aircraft Earth Station (AES) equipment with both transmit and receive capabilities for operation in the Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS), and/or in the Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS), in the frequency bands given in table 1.

Table 1: Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS), and/or Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS) frequency bands

| | AMSS/MSS and/or AMS(R)S/MSS frequency bands |
|--------------|--|
| AES transmit | 1 610 MHz to 1 626,5 MHz |
| AES receive | 1 613,8 MHz to 1 626,5 MHz |
| AES receive | 2 483,5 MHz to 2 500 MHz |
| AES transmit | 1 626,5 MHz to 1 660,5 MHz |
| AES receive | 1 525 MHz to 1 559 MHz |
| AES transmit | 1 668 MHz to 1 675 MHz |
| AES receive | 1 518 MHz to 1 525 MHz |
| AES transmit | 1 980 MHz to 2 010 MHz |
| AES receive | 2 170 MHz to 2 200 MHz |

The technical requirements in the present document are in two major categories:

- **emission limits:** to protect other radio services and systems from harmful interference generated by the AES in normal use;
- **AES Control and Monitoring Functions (CMF):** to protect other radio services and systems from unwanted transmissions from the AES. The CMF in each AES is capable of answering to commands from the Network Control Facilities (NCF) for its supporting satellite network.

NOTE: The requirements for Network Control Facilities (NCF) for S-PCN MES transmitting in the 1 610 MHz to 1 626,5 MHz band or the 1 980 MHz to 2 010 MHz band are contained in ETS 300 735 [4]; these requirements are also applicable to AES transmitting in those bands.

An AES may be subject to additional or alternative requirements in other standards depending on its functionality, in particular if it supports a service which is considered a justified case for regulation of terminal equipment interworking via the public telecommunications network. An AES will also be subject to additional airworthiness certification requirements.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ISO 7137 equivalent to EUROCAE ED-14D and RTCA DO-160D: "Aircraft - Environmental conditions and test procedures for airborne equipment".

- [2] ITU-T Recommendation O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [3] RTCA DO-210D: "Minimum Operational Performance Standards (MOPS) for Geosynchronous Orbit Aeronautical Mobile Satellite Services (AMSS) Avionics".
- [4] ETSI ETS 300 735: "Satellite Personal Communications Networks (S-PCN); Network Control Facilities (NCF) for Mobile Earth Stations (MES), including handheld earth stations, for S-PCN in the 1,6/2,4 GHz and the 2,0 GHz bands, providing voice and/or data communications under the Mobile Satellite Service (MSS)".
- [5] ITU Radio Regulations 2008.

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ECC/DEC (04)09: "ECC Decision of 12 November 2004 on the designation of the band 1518 to 1525 MHz and 1670 to 1675 MHz for the Mobile-Satellite Service".
- [i.2] Annex 10 Volume III - AMSS and AMS(R)S specific sections (Aeronautical Telecommunications) to the convention on International Civil Aviation (ICAO annex 10).

3 Definitions and abbreviations

iTeh STANDARD PREVIEW

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

<https://standards.iteh.ai/catalog/standards/sist/155ab3b-7Ba-4bc7-a4e4-7e00d58cd0d3>

antenna subsystem: includes all those RF components from the physical aperture of the antenna(s) to a single antenna port where the interconnecting cable to the transceiver is to be attached; and related ancillary components; e.g. beam-steering units and RF relays, if present

applicant: party seeking an approval, or to place an AES on the European market, i.e. the manufacturer of the equipment, or his authorized representative, or an equipment supplier to the European market

carrier-on state (allocated a channel): state when AES is transmitting a signal in a continuous or non-continuous mode

carrier-off state (idle mode): state when AES is powered on but not transmitting a signal, i.e. not in the carrier-on state

conducted measurement: measurement of emissions from an antenna port of the AES made by direct wired connection to the port

Effective Isotropically Radiated Power (EIRP): product of transmitter power and maximum antenna gain, equivalent to an isotropic source radiating uniformly in all directions

Externally Mounted Equipment (EME): IE module which is intended to be externally mounted, as declared by the manufacturer

Installable Equipment (IE): equipment which is intended to be fitted to an aircraft

Internally Mounted Equipment (IME): IE module which is not defined as Externally Mounted Equipment (EME)

Laboratory Test Equipment (LTE): logical grouping that contains the standard test equipment provided by a test laboratory

MSS band: continuous range of frequencies allocated by the ITU to the MSS

narrow-band system: system in which the nominal carrier frequency spacing for AESs in the Earth-to-Space direction is less than 300 kHz

network control channel: channel by which an AES receives general control information from the NCF of its network

NCF control message: message, normally originating from a network, to a specified terminal or set of terminals of the network which indicates to the terminal or set of terminals that it/they should carry out some specific action or should enter or maintain some specific state

NOTE: For test purposes NCF control messages may originate from Special Test Equipment.

named Bandwidth (Bn): bandwidth of the Aircraft Earth Station (AES) radio frequency transmission

NOTE 1: Bn is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified levels of unwanted emissions. See annex D.

NOTE 2: The Bn is defined relative to the AES actual carrier frequency f_c .

Bn is the width of the frequency interval $[f_c - a, f_c + b]$, where a and b, which is specified by the terminal manufacturer and may vary with f_c .

The frequency interval $[f_c - a, f_c + b]$ does not encompass more than either:

- i) when $a = b$, 4 nominal carrier frequencies for narrow-band systems;
- ii) when $a \neq b$, 1 nominal carrier frequency for narrow-band systems; or
- iii) 1 nominal carrier frequency for wideband systems.

The frequency interval $[f_c - a, f_c + b]$ is within the operational band of the AES.

operational band: sub-portion of an MSS band which has been assigned in the earth-to-space direction to the MSS network within which the AES is operating

radiated measurement: measurement of an actual radiated field

Special Test Equipment (STE): equipment provided by the applicant which allows a test laboratory to control the AES so that the tests required by EN 301 473 can be performed

test laboratory: laboratory which performs conformance testing

test load: substantially non-reactive, non-radiating power attenuator which is capable of safely dissipating the power from the transmitter(s)

transceiver subsystem: subsystem which includes transmitter, receiver and diplexer/LNA (if used) that interfaces at RF at the antenna port where it connects to the interconnecting cable, and with other on-board avionics equipment

unwanted emissions: unwanted emissions are those falling outside the nominated bandwidth in the carrier-on state, and those generated in the carrier-off state

wideband system: system in which the nominal carrier frequency spacing for AESs in the Earth-to-Space direction is equal to or greater than 300 kHz

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|---------|--|
| AES | Aircraft Earth Station |
| AMS(R)S | Aeronautical Mobile Satellite on Route Service |
| AMSS | Aeronautical Mobile Satellite Service |
| ARINC | Aeronautical Radio Inc. |
| Bn | nominated Bandwidth |
| CDMA | Code Division Multiple Access |
| CMF | Control and Monitoring Functions |
| dBW | deciBel relative to 1 Watt |
| EIRP | Effective Isotropically Radiated Power |

| | |
|---------|---|
| EME | Externally Mounted Equipment |
| EN | European Standard |
| ETS | European Telecommunications Standard |
| EUROCAE | EUROpean Organization for Civil Aviation Equipment |
| GES | Ground Earth Station |
| GNSS | Global Navigation Satellite System |
| HLD | HPA and LNA/D |
| HPA | High Power Amplifier |
| IE | Installable Equipment |
| IME | Internally Mounted Equipment |
| ITU | International Telecommunications Union |
| LNA/D | Low Noise Amplifier/Diplexer |
| LRU | Line Replaceable Unit |
| LTE | Laboratory Test Equipment |
| MES | Mobile Earth Station |
| MIC | MES (or AES) unique Identification Code (within its satellite network) |
| MSS | Mobile Satellite Service |
| NCF | Network Control Facility |
| NGSO | Non-Geostationary Satellite Orbit // Non-geostationary Orbit // Non Geo-Synchronous Orbit |
| RA | Radio Astronomy |
| RF | Radio Frequency |
| RTCA | Radio Technical Commission for Aeronautics, a company incorporated in the USA |
| SARP | Standard And Recommended Practice |
| SES | Satellite Earth Stations and systems |
| S-PCN | Satellite-Personal Communications Network |
| STE | Special Test Equipment |
| STU | Satellite Terminal Unit |
| TDMA | Time Division Multiple Access |
| TTE | Telecommunications Terminal Equipment |

Test STANDARD PREVIEW
(standards.iteh.ai)

4 General SIST EN 301 473 V1.4.1:2013 <https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7f3a-4bc7-a4e4-7debbb5f8cdd/sist-en-301-473-v1-4-1-2013>

4.1 Presentation of equipment for testing purposes

The applicant may provide to a test laboratory one or more preliminary or production models of the AES equipment, as appropriate, for testing for conformance against the technical requirements of the present document.

If the AES is intended for use with an active antenna, this shall be provided as part of the AES.

If a statement of conformance with the EN is given by the test laboratory on the basis of tests on a preliminary model, then the statement of conformance shall apply to corresponding production models only if they are identical in all technical respects with the preliminary model tested.

4.2 Aircraft earth stations

Aircraft Earth Stations are Installable Equipments (IE).

AES for public transport aircraft typically consist of up to four major modules known in the avionics world as Line Replaceable Units (LRU), interconnected by ARINC standard interwiring. These four major modules are:

- 1) the Satellite Terminal Unit (STU);
- 2) the High Power Amplifier (HPA);
- 3) the Low Noise Amplifier/Diplexer (LNA/D);
- 4) the antenna subsystem.

NOTE: The HPA and LNA/D are sometimes referred to together as the HLD.

Items 1, 2 and 3 above, are Internally Mounted Equipments (IME); item 4 above, is an externally mounted equipment (EME).

AES for non-public transport aircraft may have other arrangements.

The control panel for the AES may be part of a unit common with other communications systems on board, or it may be a dedicated, separate unit, or it may be integrated into a self contained AES.

If the control panel is part of a shared communications panel, the control panel and its interwiring are not regarded as part of the AES. However they, or a simulation of them, may be required to activate the AES for test purposes.

In the other cases, the control panel and any interconnecting cables are regarded as part of the AES and are subject to the requirements of the present document.

4.3 Description of equipment

The applicant shall provide to the test laboratory a statement which contains all of the information related to the AES and its testing environment which will enable the test laboratory to run an appropriate test suite against the AES.

This shall include:

- AES configuration (description of IME, EME, interconnecting cables);
- for each AES component equipment, the applicable Equipment Categories as defined in ISO 7137 equivalent to EUROCAE ED-14D and RTCA DO-160D [1];
- the method by which the equipment can be switched into its test modes (see note);
**iTeh STANDARD PREVIEW
(standards.iteh.ai)**
- the fault conditions which cause transmission shut-down;
- the maximum antenna gain;

and, if appropriate, at the choice of the applicant:

<https://standards.iteh.ai/catalog/standards/sist/155ab3f3-7fa4-4bc7-a4e4-7de081fcd3c7/deleted/sist/en301-473-v1.4.1-2013>

- the maximum antenna gain at the frequency of particular measured unwanted emissions;
- the multicarrier capability;
- in an information leaflet:
 - 1) the name of the network with which the AES is designed to operate;
 - 2) if applicable, the maximum value of nominated bandwidth for that network, as defined by the network operator;
 - 3) if applicable, the a and b values of the nominated bandwidth for each nominal carrier frequency of the AES;
 - 4) the operating frequency range(s) of the AES;
 - 5) if applicable, the frequency sub-bands and operating conditions for which different EIRP density limits apply;
 - 6) the maximum gross data rate at which the AES is designed to operate;
 - 7) the agreement of the network operator to the above information.

NOTE: If Special Test Equipment (STE) is required see clause A.2.