



SLOVENSKI STANDARD
SIST EN 301 908-19 V6.2.1:2013

01-oktober-2013

**Celična omrežja IMT - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2
direktive R&TTE - 19. del: Uporabniška oprema TDD OFDMA TDD WMAN (mobilni
WiMAX)**

IMT cellular networks - Harmonized EN covering the essential requirements of article 3.2
of the R&TTE Directive - Part 19: OFDMA TDD WMAN (Mobile WiMAX) TDD User
Equipment (UE)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-19 V6.2.1:2013](https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5feecb40d/sist-en-301-908-19-v6-2-1-2013)

[https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-](https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5feecb40d/sist-en-301-908-19-v6-2-1-2013)

[ba5feecb40d/sist-en-301-908-19-v6-2-1-2013](https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5feecb40d/sist-en-301-908-19-v6-2-1-2013)

Ta slovenski standard je istoveten z: EN 301 908-19 Version 6.2.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

SIST EN 301 908-19 V6.2.1:2013 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-19 V6.2.1:2013

<https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5f6eeeb40d/sist-en-301-908-19-v6-2-1-2013>

ETSI EN 301 908-19 V6.2.1 (2013-06)



**IMT cellular networks;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 19: OFDMA TDD WMAN (Mobile WiMAX)**

TDD User Equipment (UE)

SIST EN 301 908-19 V6.2.1:2013
<https://standards.etsi.org/standards/sist/301908-19/301908-19-v6-2-1-2013-8279-ba5f6eeceb40d/sist-en-301-908-19-v6-2-1-2013>

Reference

REN/MSG-TFES-010-19

Keywords

IMT, IMT-2000, mobile, OFDMA, radio,
regulation, TDD, WiMAX, WMAN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-19 V6.2.1:2013

<https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5f6eeeb404/ETSI-MSG-TFES-010-19-v6-2-1-2013>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references	8
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols	9
3.3 Abbreviations	9
4 Essential requirements specification	10
4.1 Environmental profile.....	10
4.2 Conformance requirements	10
4.2.1 Introduction.....	10
4.2.2 Transmitter Maximum Output Power	10
4.2.2.1 Definition	10
4.2.2.2 Limits	10
4.2.2.3 Conformance	10
4.2.3 Transmitter Spectrum Emission Mask	11
4.2.3.1 Definition	11
4.2.3.2 Limits	11
4.2.3.2.1 Requirements for 5 MHz channel bandwidth	11
4.2.3.2.2 Requirements for 10 MHz channel bandwidth	11
4.2.3.3 Conformance	12
4.2.4 Transmitter Spurious Emissions	12
4.2.4.1 Definition	12
4.2.4.2 Limits	12
4.2.4.2.1 Requirements for 5 MHz channel bandwidth	12
4.2.4.2.2 Requirements for 10 MHz channel bandwidth	13
4.2.4.2.3 Requirements for UE Coexistence.....	13
4.2.4.3 Conformance	13
4.2.5 Transmitter Minimum Output Power.....	13
4.2.5.1 Definition	13
4.2.5.2 Limits	13
4.2.5.3 Conformance	13
4.2.6 Receiver Adjacent Channel Selectivity (ACS)	14
4.2.6.1 Definition	14
4.2.6.2 Limits	14
4.2.6.3 Conformance	14
4.2.7 Receiver Blocking Characteristics	14
4.2.7.1 Definition	14
4.2.7.2 Limits	14
4.2.7.3 Conformance	16
4.2.8 Receiver Spurious Response	16
4.2.8.1 Definition	16
4.2.8.2 Limits	16
4.2.8.3 Conformance	17
4.2.9 Receiver Intermodulation Characteristics	17
4.2.9.1 Definition	17
4.2.9.2 Limits	17
4.2.9.3 Conformance	18
4.2.10 Receiver Spurious Emissions.....	18

4.2.10.1	Definition	18
4.2.10.2	Limits	18
4.2.10.3	Conformance.....	18
4.2.11	Transmitter Adjacent Channel Leakage Power Ratio	19
4.2.11.1	Definition	19
4.2.11.2	Limits	19
4.2.11.2.1	Requirements for 5 MHz channel bandwidth	19
4.2.11.2.2	Requirements for 10 MHz channel bandwidth	19
4.2.11.3	Conformance.....	20
5	Testing for compliance with technical requirements.....	20
5.1	Environmental conditions for testing	20
5.2	Product information.....	20
5.3	Interpretation of the measurement results	20
5.4	Essential radio test suites.....	21
5.4.1	Transmitter Maximum and Minimum Output Power	21
5.4.1.1	Method of measurement.....	21
5.4.1.1.1	Initial conditions	22
5.4.1.1.2	Procedure.....	22
5.4.1.2	Test requirements.....	22
5.4.2	Transmitter Spectrum Emission Mask.....	22
5.4.2.1	Method of measurement.....	23
5.4.2.1.1	Initial conditions	23
5.4.2.1.2	Procedure.....	23
5.4.2.2	Test requirements.....	24
5.4.3	Transmitter spurious emissions.....	24
5.4.3.1	Method of measurement.....	24
5.4.3.1.1	Initial conditions	24
5.4.3.1.2	Procedure.....	25
5.4.3.2	Test requirements.....	25
5.4.4	Receiver Adjacent Channel Selectivity (ACS)	25
5.4.4.1	Method of measurement.....	25
5.4.4.1.1	Initial conditions	26
5.4.4.1.2	Procedure.....	26
5.4.4.2	Test requirements.....	26
5.4.5	Receiver Blocking Characteristics	26
5.4.5.1	Method of measurement.....	26
5.4.5.1.1	Initial conditions	27
5.4.5.1.2	Procedure.....	27
5.4.5.2	Test requirements.....	28
5.4.6	Receiver Spurious Response.....	28
5.4.6.1	Method of measurement.....	28
5.4.6.1.1	Initial conditions	28
5.4.6.1.2	Procedure.....	28
5.4.6.2	Test requirements.....	29
5.4.7	Receiver Intermodulation characteristics	29
5.4.7.1	Method of measurement.....	29
5.4.7.1.1	Initial conditions	29
5.4.7.1.2	Procedure.....	30
5.4.7.2	Test requirements.....	30
5.4.8	Receiver Spurious Emissions.....	30
5.4.8.1	Method of measurement.....	30
5.4.8.1.1	Initial conditions	31
5.4.8.1.2	Procedure.....	31
5.4.8.2	Test requirements.....	31
5.4.9	Transmitter Adjacent Channel Leakage Power Ratio	31
5.4.9.1	Method of measurement.....	31
5.4.9.1.1	Initial conditions	32
5.4.9.1.2	Procedure.....	32
5.4.9.2	Test requirements.....	33

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	34
Annex B (normative):	Environmental profile	36
Annex C (informative):	Void	37
Annex D (informative):	Bibliography.....	38
History		39

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 908-19 V6.2.1:2013](https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5f6eeecb40d/sist-en-301-908-19-v6-2-1-2013)

<https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5f6eeecb40d/sist-en-301-908-19-v6-2-1-2013>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.8].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 19 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

[https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-](https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5f6eeeb40d/sist-en-301-908-19-v6-2-1-2013)

[ba5f6eeeb40d/sist-en-301-908-19-v6-2-1-2013](https://standards.iteh.ai/catalog/standards/sist/5950aaa0-9c17-4e33-8279-ba5f6eeeb40d/sist-en-301-908-19-v6-2-1-2013)

National transposition dates

Date of adoption of this EN:	10 June 2013
Date of latest announcement of this EN (doa):	30 September 2013
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2014
Date of withdrawal of any conflicting National Standard (dow):	31 March 2015

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment type:

- User Equipment for IMT-2000 OFDMA TDD WMAN (Mobile WiMAX) operating in TDD mode.

This radio equipment type is capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: OFDMA TDD WMAN User Equipment frequency bands

Mobile WiMAX Band Class Index	IMT-2000 OFDMA TDD WMAN service operating bands	Channel Bandwidth
1.B	2 300 MHz to 2 400 MHz	5 MHz and 10 MHz
3.A	2 500 MHz to 2 690 MHz	5 MHz and 10 MHz
5L.A	3 400 MHz to 3 600 MHz	5 MHz
5L.C	3 400 MHz to 3 600 MHz	10 MHz
5H.A	3 600 MHz to 3 800 MHz	5 MHz
5H.C	3 600 MHz to 3 800 MHz	10 MHz

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive 1999/5/EC [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 908-1 (V6.2.1) (04-2013): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 1: Introduction and common requirements".
- [2] CEPT/ERC/Recommendation 74-01E (Edition of January, 2011) (Siófok 98, Nice 99, Sesimbra 02, Hradec Kralove 05): "Unwanted emissions in the spurious domain".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.4] ETSI TR 102 215 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.5] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Recommendation ITU-R SM.329-12 (2012): "Unwanted emissions in the spurious domain".
- [i.8] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

SIST EN 301 908-19 V6.2.1:2013

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive 1999/5/EC [i.2] and the following apply:

burst: period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

environmental profile: declared range of environmental conditions under which equipment within the scope of the present document is required to be compliant

integral antenna: antenna which is declared to be part of the radio equipment by the manufacturer

NOTE: Even when equipment with an integral antenna is concerned, it might still be possible to separate the antenna from the equipment using a special tool. In such cases the assessment of the radio equipment and of the antenna against requirements of the present document may be done separately.

maximum output power: mean power level per carrier of the base station measured at the antenna connector in a specified reference condition

mean power: when applied to a modulated signal, this is the power (transmitted or received) in a bandwidth

nominal maximum output power: maximum nominal mean power level per carrier of the user equipment available at the antenna connector declared by the manufacturer; for equipment implementing dynamic change of modulation format, it is intended as the maximum nominal mean power associated to the modulation format delivering the highest power

receiver thermal noise power: equal to $k \times T \times BW \times F$

WiMAX: trademarked name for the OFDMA TDD WMAN IMT technology

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{BS}	Base Station Interface A
A_{MS}	Mobile Station Interface A
A_{UUT}	Unit Under Test Interface A
BW	Assigned channel bandwidth
dB	Decibel
dBc	Decibel relative to carrier
dBm	Decibel relative to 1 milliwatt
f	Frequency of measurement
f_c	Centre frequency of the assigned channel
F	Receiver noise figure
GHz	GigaHertz
k	Boltzmann's constant
M_{BS}	Base Station Interface M
MHz	MegaHertz
M_{MS}	Mobile Station Interface M
N	Maximum number of antennas in a multiple antenna configuration
N_{th}	Receiver thermal noise power expressed in dBm
P_{SENS}	Receiver sensitivity level at BER $\leq 10^{-6}$ (or equivalent PER) performance, corresponding to the most robust modulation and coding rate supported by the technology
P_{SENS5}	Receiver sensitivity level at BER 10^{-6} for a 5 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology
P_{SENS10}	Receiver sensitivity level at BER 10^{-6} for a 10 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology
P_{nom}	Declared nominal maximum output Power
T	Ambient temperature in Kelvin

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BCI	Band Class Index
BER	Bit Error Ratio
BS	Base Station
CW	Continuous Wave
ERM	Electromagnetic compatibility and Radio spectrum Matters
EUT	Equipment Under Test
IMT	International Mobile Telecommunications
MSG	Mobile Standards Group
OFDMA	Orthogonal Frequency Division Multiple Access
PER	Packet Error Ratio
R&TTE	Radio equipment and Telecommunications Terminal Equipment
RF	Radio Frequency
RMS	Root Mean Square
RRC	Root Raised Cosine
TDD	Time Division Duplexing
TFES	Task Force for European Standards for IMT
UE	User Equipment
UUT	Unit Under Test
WMAN	Wireless Metropolitan Area Network

4 Essential requirements specification

With reference to article 3.2 of 1999/5/EC Directive [i.2] the phenomena in this clause have been identified as relevant to the essential requirements.

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

4.2 Conformance requirements

This clause describes the conformance requirements for OFDMA TDD WMAN User Equipment.

4.2.1 Introduction

To meet the essential requirement under article 3.2 of Directive 1999/5/EC [i.2] (R&TTE Directive) for IMT-2000 User Equipment (UE) seven essential parameters in addition to those in EN 301 908-1 [1] have been identified. Table 4.2.1-1 provides a cross reference between these seven essential parameters and the corresponding nine technical requirements for equipment within the scope of the present document.

Table 4.2.1-1: Cross references

Essential parameter	Corresponding technical requirements
Spectrum emissions mask	4.2.3 Transmitter Spectrum emissions mask
	4.2.11 Transmitter adjacent channel leakage power ratio
Conducted spurious emissions in active mode	4.2.4 Transmitter spurious emissions
Accuracy of maximum output power	4.2.2 Transmitter maximum output power
Prevention of harmful interference through control of power	4.2.5 Transmitter minimum output power
Conducted spurious emission in idle mode	4.2.10 Receiver spurious emissions
Impact of interference on receiver performance	4.2.7 Receiver Blocking characteristics
	4.2.8 Receiver spurious response
	4.2.9 Receiver Intermodulation characteristics
Receiver adjacent channel selectivity	4.2.6 Receiver Adjacent Channel Selectivity (ACS)
Control and Monitoring functions	EN 301 908-1 [1], clause 4.2.4 Control and Monitoring functions

4.2.2 Transmitter Maximum Output Power

4.2.2.1 Definition

The UE maximum output power is measured over total allocated channel bandwidth available at the antenna connector.

4.2.2.2 Limits

The UE maximum output power shall not exceed 26 dBm.

4.2.2.3 Conformance

Conformance tests described in clause 5.4.1 shall be carried out.

4.2.3 Transmitter Spectrum Emission Mask

4.2.3.1 Definition

Spectrum emission mask defines an out of band emission requirement for the transmitter. These out of band emissions are unwanted emissions outside the channel bandwidth resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions.

4.2.3.2 Limits

A UE transmitting on a single RF carrier configured in accordance with the manufacturer's specification shall not exceed the allowed level specified in tables 4.2.3.2.1-1 to 4.2.3.2.2-4 for the relevant nominal channel bandwidth of 5 MHz or 10 MHz and the relevant BCI.

Integration bandwidth refers to the frequency range over which the emission power is integrated.

Δf is defined as the frequency offset in MHz from the channel centre frequency.

4.2.3.2.1 Requirements for 5 MHz channel bandwidth

Table 4.2.3.2.1-1: Spectrum Emission Mask for 5 MHz channel bandwidth – BCI 1.B and 3.A

Segment number	Offset from channel centre frequency (Δf) (MHz)	Integration bandwidth (kHz)	Allowed emission level within the integration bandwidth (dBm)
1	2,5 to < 3,5	50	-13,00
2	3,5 to < 7,5	1 000	-13,00
3	7,5 to < 8	500	-16,00
4	8 to < 10,4	1 000	-25,00
5	10,4 to < 12,5	1 000	-25,00

Table 4.2.3.2.1-2: Spectrum Emission Mask for 5 MHz channel bandwidth – BCI 5L.A and 5H.A

Segment number	Offset from channel centre frequency (Δf) (MHz)	Integration bandwidth (kHz)	Allowed emission level within the integration bandwidth (dBm)
1	2,5 to < 3,5	30	-33,5 - 15(Δf - 2,5)
2	3,5 to < 7,5	1 000	-33,5 - 1(Δf - 3,5)
3	7,5 to < 8,5	1 000	-37,5 - 10(Δf - 7,5)
4	8,5 to < 12,5	1 000	-47,5

4.2.3.2.2 Requirements for 10 MHz channel bandwidth

Table 4.2.3.2.2-1: Spectrum emission mask for 10 MHz channel bandwidth – BCI 1.B and 3.A

Segment number	Offset from channel centre frequency (Δf) (MHz)	Integration bandwidth (kHz)	Allowed emission level within the integration bandwidth (dBm)
1	5 to < 6	100	-13,00
2	6 to < 10	1 000	-13,00
3	10 to < 11	1 000	-13 - 12(Δf - 10)
4	11 to < 15	1 000	-25,00
5	15 to < 20	1 000	-25,00
6	20 to < 25	1 000	-25,00