



# SLOVENSKI STANDARD

## SIST EN 301 908-2 V6.2.1:2014

01-februar-2014

---

**Celična omrežja IMT - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2  
direktive R&TTE - 2. del: CDMA z neposrednim razprševanjem ("Direct Spread")  
(UTRA FDD) (UE)**

IMT cellular networks - Harmonized EN covering the essential requirements of article 3.2  
of the R&TTE Directive - Part 2: CDMA Direct Spread (UTRA FDD) User Equipment  
(UE)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 908-2 V6.2.1:2014](https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7caf6/sist-en-301-908-2-v6-2-1-2014)

[https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-  
895297c7caf6/sist-en-301-908-2-v6-2-1-2014](https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7caf6/sist-en-301-908-2-v6-2-1-2014)

**Ta slovenski standard je istoveten z: EN 301 908-2 Version 6.2.1**

---

**ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

**SIST EN 301 908-2 V6.2.1:2014**                      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 908-2 V6.2.1:2014](https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7caf6/sist-en-301-908-2-v6-2-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7caf6/sist-en-301-908-2-v6-2-1-2014>

# ETSI EN 301 908-2 V6.2.1 (2013-10)



Harmonized European Standard

**IMT cellular networks;  
Harmonized EN covering the essential requirements  
of article 3.2 of the R&TTE Directive;  
Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)**

SIST EN 301 908-2 V6.2.1:2014  
<https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7eaf6/sist-en-301-908-2-v6-2-1-2014>

## Reference

---

REN/MSG-TFES-010-02

## Keywords

---

3G, 3GPP, cellular, digital, IMT, mobile, radio,  
regulation, UMTS, UTRA, WCDMA

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 908-2 V6.2.1:2014

<https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7e1d1/ren-msg-tfes-010-02-v6-2-1-2014>  
**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Introduction .....	6
1 Scope .....	7
2 References .....	8
2.1 Normative references .....	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations .....	9
3.1 Definitions.....	9
3.2 Symbols.....	10
3.3 Abbreviations .....	10
4 Technical requirements specifications .....	12
4.1 Environmental profile.....	12
4.2 Conformance requirements .....	12
4.2.1 Introduction.....	12
4.2.2 Transmitter maximum output power.....	12
4.2.2.1 Transmitter maximum output power.....	12
4.2.2.1.1 Definition.....	12
4.2.2.1.2 Limits .....	13
4.2.2.1.3 Conformance .....	13
4.2.2.2 Transmitter maximum output power for DC-HSUPA.....	13
4.2.2.2.1 Definition for DC-HSUPA.....	13
4.2.2.2.2 Limits for DC-HSUPA.....	13
4.2.2.2.3 Conformance .....	14
4.2.3 Transmitter spectrum emission mask.....	14
4.2.3.1 Transmitter spectrum emission mask.....	14
4.2.3.1.1 Definition.....	14
4.2.3.1.2 Limits .....	14
4.2.3.1.3 Conformance .....	14
4.2.3.2 Transmitter spectrum emission mask for DC-HSUPA .....	15
4.2.3.2.1 Definition for DC-HSUPA .....	15
4.2.3.2.2 Limits for DC-HSUPA .....	15
4.2.3.2.3 Conformance .....	15
4.2.4 Transmitter spurious emissions.....	15
4.2.4.1 Transmitter spurious emissions.....	15
4.2.4.1.1 Definition.....	15
4.2.4.1.2 Limits .....	15
4.2.4.1.3 Conformance .....	17
4.2.4.2 Transmitter spurious emissions for DC-HSUPA .....	17
4.2.4.2.1 Definition for DC-HSUPA .....	17
4.2.4.2.2 Limits for DC-HSUPA .....	17
4.2.4.2.3 Conformance .....	19
4.2.5 Transmitter minimum output power .....	20
4.2.5.1 Transmitter minimum output power.....	20
4.2.5.1.1 Definition.....	20
4.2.5.1.2 Limits .....	20
4.2.5.1.3 Conformance .....	20
4.2.5.2 Transmitter minimum output power for DC-HSUPA .....	20
4.2.5.2.1 Definition for DC-HSUPA .....	20
4.2.5.2.2 Limits for DC-HSUPA .....	20
4.2.5.2.3 Conformance .....	20
4.2.6 Receiver Adjacent Channel Selectivity (ACS) .....	20
4.2.6.1 Definition .....	20

4.2.6.2	Limits .....	21
4.2.6.3	Conformance .....	21
4.2.7	Receiver blocking characteristics .....	21
4.2.7.1	Definition .....	21
4.2.7.2	Limits .....	21
4.2.7.3	Conformance .....	23
4.2.8	Receiver spurious response .....	23
4.2.8.1	Definition .....	23
4.2.8.2	Limits .....	23
4.2.8.3	Conformance .....	24
4.2.9	Receiver intermodulation characteristics .....	24
4.2.9.1	Definition .....	24
4.2.9.2	Limits .....	24
4.2.9.3	Conformance .....	25
4.2.10	Receiver spurious emissions .....	25
4.2.10.1	Definition .....	25
4.2.10.2	Limits .....	25
4.2.10.3	Conformance .....	27
4.2.11	Out-of-synchronization handling of output power .....	27
4.2.11.1	Definition .....	27
4.2.11.2	Limits .....	27
4.2.11.3	Conformance .....	28
4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR) .....	28
4.2.12.1	Transmitter adjacent channel leakage power ratio (ACLR) .....	28
4.2.12.1.1	Definition .....	28
4.2.12.1.2	Limits .....	28
4.2.12.1.3	Conformance .....	29
4.2.12.2	Adjacent channel leakage power ratio for DC-HSUPA .....	29
4.2.12.2.1	Definition for DC-HSUPA .....	29
4.2.12.2.2	Limits for DC-HSUPA .....	29
4.2.12.2.3	Conformance .....	29
5	Testing for compliance with technical requirements .....	29
5.1	Environmental conditions for testing .....	29
5.2	Interpretation of the measurement results .....	30
5.3	Essential radio test suites .....	31
5.3.1	Transmitter maximum output power .....	31
5.3.1.1	Method of test .....	31
5.3.1.1.1	Initial conditions .....	31
5.3.1.1.1A	Initial conditions for DC-HSUPA .....	31
5.3.1.1.2	Procedure .....	32
5.3.1.1.2A	Procedure for DC-HSUPA .....	32
5.3.1.2	Test requirements .....	32
5.3.2	Transmitter spectrum emission mask .....	32
5.3.2.1	Method of test .....	32
5.3.2.1.1	Initial conditions for UEs not supporting HSDPA and/or E-DCH .....	32
5.3.2.1.1A	Initial conditions for UEs supporting HSDPA and/or E-DCH .....	32
5.3.2.1.1B	Initial conditions for DC-HSUPA .....	33
5.3.2.1.2	Procedure for UEs not supporting HSDPA and/or E-DCH .....	33
5.3.2.1.2A	Procedure for UEs supporting HSDPA and/or E-DCH .....	33
5.3.2.1.2B	Procedure for DC-HSUPA .....	33
5.3.2.2	Test requirements .....	33
5.3.3	Transmitter spurious emissions .....	34
5.3.3.1	Method of test .....	34
5.3.3.1.1	Initial conditions .....	34
5.3.3.1.1A	Initial conditions for DC-HSUPA .....	34
5.3.3.1.2	Procedure .....	34
5.3.3.1.2A	Procedure for DC-HSUPA .....	34
5.3.3.2	Test requirements .....	34
5.3.4	Transmitter minimum output power .....	35
5.3.4.1	Method of test .....	35
5.3.4.1.1	Initial conditions .....	35

5.3.4.1.1A	Initial conditions for DC-HSUPA .....	35
5.3.4.1.2	Procedure.....	35
5.3.4.1.2A	Procedure for DC-HSUPA .....	35
5.3.4.2	Test requirements.....	35
5.3.5	Receiver Adjacent Channel Selectivity (ACS) .....	36
5.3.5.1	Method of test .....	36
5.3.5.1.1	Initial conditions.....	36
5.3.5.1.2	Procedure.....	36
5.3.5.2	Test requirements.....	36
5.3.6	Receiver blocking characteristics .....	36
5.3.6.1	Method of test .....	36
5.3.6.1.1	Initial requirements.....	36
5.3.6.1.2	Procedure.....	37
5.3.6.2	Test requirements.....	37
5.3.7	Receiver spurious response.....	37
5.3.7.1	Method of test .....	37
5.3.7.1.1	Initial conditions.....	37
5.3.7.1.2	Procedure.....	37
5.3.7.2	Test requirements.....	37
5.3.8	Receiver Intermodulation characteristics.....	37
5.3.8.1	Method of test .....	37
5.3.8.1.1	Initial conditions.....	37
5.3.8.1.2	Procedure.....	38
5.3.8.2	Test requirements.....	38
5.3.9	Receiver spurious emissions .....	38
5.3.9.1	Method of test .....	38
5.3.9.1.1	Initial conditions.....	38
5.3.9.1.2	Procedure.....	38
5.3.9.2	Test requirements.....	38
5.3.10	Out-of-synchronization handling of output power.....	38
5.3.10.1	Method of test .....	38
5.3.10.1.1	Initial conditions.....	38
5.3.10.1.2	Procedure.....	39
5.3.10.2	Test requirements.....	39
5.3.11	Transmitter adjacent channel leakage power ratio.....	39
5.3.11.1	Method of test .....	39
5.3.11.1.1	Initial conditions for UEs not supporting HSDPA and/or E-DCH .....	39
5.3.11.1.1A	Initial conditions for UEs supporting HSDPA and/or E-DCH .....	40
5.3.11.1.1B	Initial conditions for DC-HSUPA .....	40
5.3.11.1.2	Procedure for UEs not supporting HSDPA and/or E-DCH.....	40
5.3.11.1.2A	Procedure for UEs supporting HSDPA and/or E-DCH .....	40
5.3.11.1.2B	Procedure for DC-HSUPA .....	40
5.3.11.2	Test requirements.....	40
<b>Annex A (normative):</b>	<b>HS Requirements and conformance Test specifications Table (HS-RTT).....</b>	<b>41</b>
<b>Annex B (normative):</b>	<b>Environmental profile .....</b>	<b>43</b>
B.1	General .....	43
B.1.1	Introduction .....	43
B.1.2	Temperature .....	43
B.1.3	Voltage .....	43
B.1.4	Test environment.....	43
<b>Annex C:</b>	<b>Void .....</b>	<b>45</b>
<b>Annex D (informative):</b>	<b>Bibliography.....</b>	<b>46</b>
History .....		47

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to mandates M/284 and M/406 issued from the European Commission under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.10].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [10].

[https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-](https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7ea16/sist-en-301-908-2-v6-2-1-2014)

[895297c7ea16/sist-en-301-908-2-v6-2-1-2014](https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7ea16/sist-en-301-908-2-v6-2-1-2014)

### National transposition dates

Date of adoption of this EN:	7 October 2013
Date of latest announcement of this EN (doa):	31 January 2014
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2014
Date of withdrawal of any conflicting National Standard (dow):	31 July 2015

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].



# 1 Scope

The present document applies to the following radio equipment type:

- User Equipment for IMT-2000 CDMA Direct Spread (UTRA FDD).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1-1.

**Table 1-1: UTRA FDD operating bands**

UTRA FDD Band	Direction of transmission	UTRA FDD operating bands
I	Transmit	1 920 MHz to 1 980 MHz
	Receive	2 110 MHz to 2 170 MHz
III	Transmit	1 710 MHz to 1 785 MHz
	Receive	1 805 MHz to 1 880 MHz
VII	Transmit	2 500 MHz to 2 570 MHz
	Receive	2 620 MHz to 2 690 MHz
VIII	Transmit	880 MHz to 915 MHz
	Receive	925 MHz to 960 MHz
XV	Transmit	1 900 MHz to 1 920 MHz
	Receive	2 600 MHz to 2 620 MHz
XVI	Transmit	2 010 MHz to 2 025 MHz
	Receive	2 585 MHz to 2 600 MHz
XX	Transmit	832 MHz to 862 MHz
	Receive	791 MHz to 821 MHz
XXII	Transmit	3 410 MHz to 3 490 MHz
	Receive	3 510 MHz to 3 590 MHz

iTech STANDARD PREVIEW  
(standards.itech.ai)

The present document covers requirements for UTRA FDD User Equipment from 3GPP Releases 99, 4, 5, 6, 7, 8, 9, and 10. In addition, the present document covers requirements for UTRA FDD User Equipment in the operating bands specified in TS 102 735 [i.4].

NOTE 1: For Band XX:

- for user equipment designed to be mobile or nomadic, the requirements in the present document measured at the antenna port also show conformity to the corresponding requirement defined as TRP (total radiated power), as described in Commission Decision 2010/267/EU [i.7], ECC Decision (09)03 [i.8] and CEPT Report 30 [i.9];
- for user equipment designed to be fixed or installed, the present document does not address the requirements described in Commission Decision 2010/267/EU [i.7], ECC Decision (09)03 [i.8] and CEPT Report 30 [i.9].

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE 2: A list of such ENs is included on the web site <http://www.newapproach.org/>.

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] ETSI TS 134 121-1 (V10.7.0) (07-2013): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) conformance specification; Radio transmission and reception (FDD); Part 1: Conformance specification (3GPP TS 34.121-1 version 10.7.0 Release 10)".
- [3] ETSI TS 134 108 (V11.6.0) (07-2013): "Universal Mobile Telecommunications System (UMTS); LTE; Common test environments for User Equipment (UE); Conformance testing (3GPP TS 34.108 version 11.6.0 Release 11)".
- [4] ETSI TS 134 109 (V10.1.0) (01-2012): "Universal Mobile Telecommunications System (UMTS); Terminal logical test interface; Special conformance testing functions (3GPP TS 34.109 version 10.1.0 Release 10)".
- [5] ETSI TS 125 101 (V10.9.0) (07-2013): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) radio transmission and reception (FDD) (3GPP TS 25.101 version 10.9.0 Release 10)".
- [6] IEC 60068-2-1 (03-2007): "Environmental testing - Part 2-1: Tests. Test A: Cold".
- [7] IEC 60068-2-2 (07-2007): "Environmental testing - Part 2-2: Tests. Test B: Dry heat".
- [8] ETSI TS 125 214 (V10.6.0) (03-2012): "Universal Mobile Telecommunications System (UMTS); Physical layer procedures (FDD) (3GPP TS 25.214 version 10.6.0 Release 10)".
- [9] ETSI TS 145 004 (V10.0.0) (04-2011): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 10.0.0 Release 10)".
- [10] ETSI EN 301 908-1 (V6.2.1) (04-2013): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 1: Introduction and common requirements".

### 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".

- [i.4] ETSI TS 102 735 (V7.1.0): "Universal Mobile Telecommunications System (UMTS); Band-specific requirements for UMTS Frequency Division Duplex (FDD) operation in the bands 1 900 MHz to 1 920 MHz paired with 2 600 MHz to 2 620 MHz and 2 010 MHz to 2 025 MHz paired with 2 585 MHz to 2 600 MHz".
- [i.5] Void.
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Commission Decision 2010/267/EU of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.8] ECC Decision (09)03 of 30 October 2009 on harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz.
- [i.9] CEPT Report 30 of 30 October 2009 to the European Commission in response to the Mandate on "The identification of common and minimal (least restrictive) technical conditions for 790 - 862 MHz for the digital dividend in the European Union".
- [i.10] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions (standards.iteh.ai)

For the purposes of the present document, the following terms and definitions apply:

**chip rate:** rate of "chips" (modulated symbols after spreading) per second  
<https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7/etn/sist-en-301-908-2-v6-2-1-2014>

NOTE: The UTRA FDD chip rate is 3,84 Mchip/s.

**data rate:** rate of the user information, which is transmitted over the Air Interface

EXAMPLE: Output rate of the voice codec.

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**maximum output power:** measure of the maximum power the UE can transmit (i.e. the actual power as would be measured assuming no measurement error) in a bandwidth of at least  $(1 + \alpha)$  times the chip rate of the radio access mode

NOTE: The period of measurement is assumed to be at least one timeslot.

**mean power:** power (transmitted or received) in a bandwidth of at least  $(1 + \alpha)$  times the chip rate of the radio access mode, when applied to a WCDMA modulated signal

NOTE: The period of measurement is assumed to be at least one timeslot unless otherwise stated.

**node B:** logical node responsible for radio transmission/reception in one or more cells to/from the User Equipment

**nominal maximum output power:** nominal power defined by the UE power class

**operating band:** frequency range that is defined with a specific set of technical requirements, in which UTRA FDD operates

NOTE: Operating bands for UTRA are designated with Roman numerals, while the corresponding operating bands for E-UTRA are designated with Arabic numerals.

**power spectral density:** function of power versus frequency and when integrated across a given bandwidth, the function represents the mean power in such a bandwidth

NOTE 1: When the mean power is normalized to (divided by) the chip-rate it represents the mean energy per chip. Some signals are directly defined in terms of energy per chip, (DPCH\_Ec, Ec, OCNS\_Ec and S-CCPCH\_Ec) and others defined in terms of PSD ( $I_o$ ,  $I_{oc}$ ,  $I_{or}$  and  $\hat{I}_{or}$ ). There also exist quantities that are a ratio of energy per chip to PSD (DPCH\_Ec/ $I_{or}$ , Ec/ $I_{or}$ , etc.). This is the common practice of relating energy magnitudes in communication systems.

NOTE 2: It can be seen that if both energy magnitudes in the ratio are divided by time, the ratio is converted from an energy ratio to a power ratio, which is more useful from a measurement point of view. It follows that an energy per chip of X dBm/3,84 MHz can be expressed as a mean power per chip of X dBm. Similarly, a signal PSD of Y dBm/3,84 MHz can be expressed as a signal power of Y dBm.

NOTE 3: The units of Power Spectral Density (PSD) are extensively used in the present document.

**RRC filtered mean power:** mean power as measured through a root raised cosine filter with roll-off factor  $\alpha$  and a bandwidth equal to the chip rate of the radio access mode

NOTE: The RRC filtered mean power of a perfectly modulated WCDMA signal is 0,246 dB lower than the mean power of the same signal.

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$\alpha$	Roll-off factor of the root raised cosine filter, $\alpha = 0,22$
DPCH_Ec	Average energy per PN chip for DPCH
$E_c$	Average energy per PN chip
$F_{uw}$	Frequency of unwanted signal

NOTE: This is specified in bracket in terms of an absolute frequency(s) or a frequency offset from the assigned channel frequency.

$I_o$	The total received power spectral density, including signal and interference, as measured at the UE antenna connector
$I_{oc}$	Power spectral density (integrated in a noise bandwidth equal to the chip rate and normalized to the chip rate) of a band limited white noise source (simulating interference from cells, which are not defined in a test procedure) as measured at the UE antenna connector
$I_{or}$	Total transmit power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal at the Node B antenna connector
$\hat{I}_{or}$	Received power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal as measured at the UE antenna connector
$\beta_c$	Gain factor for DPCCH
$\beta_d$	Gain factor for DPDCH
$\beta_{hs}$	Gain factor for HS-DPCCH
$\beta_{ec}$	Gain factor for E-DPCCH
$\beta_{ed}$	Gain factor for E-DPDCH

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Access Channel
ACL	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio

CDMA Code Division Multiple Access  
 CW Continuous Wave

NOTE: Unmodulated signal.

DC-HSUPA Dual Cell HSUPA  
 DCH Dedicated Channel

NOTE: Which is mapped into Dedicated Physical Channel.

DL Downlink  
 DPCCH Dedicated Physical Control CHannel  
 DPCH Dedicated Physical Channel  
 DPDCH Dedicated Physical Data CHannel  
 E-DCH Enhanced Dedicated Channel  
 E-DPCCH Enhanced DPCCH  
 E-DPDCH Enhanced DPDCH  
 EMC ElectroMagnetic Compatibility  
 ERM Electromagnetic compatibility and Radio spectrum Matters  
 EUT Equipment Under Test  
 FDD Frequency Division Duplex  
 GMSK Gaussian Minimum Shift Keying  
 GSM Global System for Mobile  
 HS-DPCCH High Speed DPCCH  
 HSDPA High Speed Downlink Packet Access  
 HSUPA High Speed Uplink Packet Access  
 IMT International Mobile Telecommunications  
 LTE Long Term Evolution  
 MPR Maximum Power Reduction  
 MSG Mobile Standards Group  
 OCNS Orthogonal Channel Noise Simulator

NOTE: A mechanism used to simulate the users or control signals on the other orthogonal channels of a downlink. <https://standards.iteh.ai/catalog/standards/sist/da6d5405-3473-4744-adab-895297c7eaf6/sist-en-301-908-2-v6-2-1-2014>

PCH Paging Channel  
 PN PseudoNoise  
 PSD Power Spectral Density  
 <REFSENS> Reference sensitivity  
 RF Radio Frequency  
 RRC Root Raised Cosine  
 R&TTE Radio and Telecommunications Terminal Equipment  
 SS System Simulator

NOTE: See TS 134 121-1 [2].

TFES Task Force for European Standards for IMT  
 TH Temperature High  
 TH/VH High extreme Temperature/High extreme Voltage  
 TH/VL High extreme Temperature/Low extreme Voltage  
 TL Temperature Low  
 TL/VH Low extreme Temperature/High extreme Voltage  
 TL/VL Low extreme Temperature/Low extreme Voltage  
 TPC Transmit Power Control  
 TRP Total Radiated Power  
 UARFCN UTRA Absolute Radio Frequency Channel Number  
 UE User Equipment  
 UL Uplink  
 UMTS Universal Mobile Telecommunications System  
 UTRA Universal Terrestrial Radio Access  
 VH Higher extreme Voltage  
 VL Lower extreme Voltage  
 WCDMA Wideband Code Division Multiple Access