

Sixth edition
2004-11-15

Corrected version
2005-06-01

Motorcycle tyres and rims (metric series) —

**Part 1:
Design guides**

*Pneumatiques et jantes pour motocycles (séries millimétriques) —
Partie 1: Guide de conception*

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

ISO 5751-1:2004

<https://standards.iteh.ai/catalog/standards/sist/71f42ff0-647e-46fe-8350-75cb0d97628/iso-5751-1-2004>



Reference number
ISO 5751-1:2004(E)

© ISO 2004

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 5751-1:2004

<https://standards.iteh.ai/catalog/standards/sist/71f42ff0-647e-46fe-8350-75cb0d97628/iso-5751-1-2004>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Tyre designation	1
4.1 General	1
4.2 Size and construction	2
4.3 Service description	2
4.4 Other service characteristics	3
4.5 Designation examples	4
5 Tyre dimensions	5
5.1 Calculation of design tyre dimensions	5
5.2 Calculation of max. overall tyre dimensions in service	6
5.3 Calculation of min. dimensions — Section width, S_{\min}	7
5.4 Measuring tyre dimensions — Procedure	7
6 Tread configurations	7
7 Tyre load-carrying capacity	9
8 Speed symbols	9
9 Centrifugal radius	9
Annex A (informative) Guideline values for metric series	11
Bibliography	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5751-1 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 10, *Cycle, moped, motorcycle tyres and rims*.

This sixth edition cancels and replaces the fifth edition (ISO 5751-1:2001), which has been technically revised.

ISO 5751 consists of the following parts, under the general title *Motorcycle tyres and rims (metric series)*:

- *Part 1: Design guides* <https://standards.iteh.ai/catalog/standards/sist/71f42ff0-647e-46fe-8350-75cb0d97628/iso-5751-1-2004>
- *Part 2: Tyre dimensions and load-carrying capacities*
- *Part 3: Range of approved rim contours*

This corrected version of ISO 5751-1:2004 incorporates the following correction:

- the addition of an introductory sentence, table numbering and table titles in Annex A.

Motorcycle tyres and rims (metric series) —

Part 1: Design guides

1 Scope

This part of ISO 5751 gives guidelines for the design of, and specifies the designation and calculation of the dimensions for, metric-series motorcycle tyres. It is applicable to motorcycle tyres with a reduced height/width ratio (100 and lower) that can be fitted on cylindrical bead-seat or 5° tapered bead-seat rims. It is also applicable to other concepts of tyre and rim, provided the appropriate rim/section ratios and coefficients are established for them.

NOTE See ISO 4249 for motorcycle tyres and rims (code-designated series) of rim diameter codes 13 and above, and ISO 6054 for those of codes 12 and below.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4223-1:2002, *Definitions of some terms used in the tyre industry — Part 1: Pneumatic tyres*

ISO 4249-3, *Motorcycle tyres and rims (code-designated series) — Part 3: Rims*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4223-1 apply.

4 Tyre designation

4.1 General

The designation of the tyre shall be shown on its sidewall and shall include the following markings, placed close to each other:

- size and construction (see 4.2);
- service description (see 4.3).

4.2 Size and construction

4.2.1 Characteristics

The size and construction characteristics shall be indicated as follows:

Nominal section width	/	Nominal aspect ratio	Tyre construction code	Nominal rim diameter code
-----------------------------	---	----------------------------	------------------------------	---------------------------------

4.2.2 Nominal section width

The nominal section width shall be expressed in millimetres.

4.2.3 Nominal aspect ratio

The nominal aspect ratio shall be expressed as a percentage. It shall be a multiple of 10 for aspect ratios 70 and higher, and a multiple of 5 for aspect ratios lower than 70.

4.2.4 Tyre construction code

The tyre construction code shall be

- “B” for bias belted-type constructions
- “-” for diagonal ply tyres, and
- “R” for radial ply tyres.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

ISO 5751-1:2004

NOTE 1 See also 4.4.3 for codes adopted for tyres suitable for speeds in excess of 240 km/h. Other codes will be established for new concepts (constructions) of tyres.

NOTE 2 The term *bias belted construction* describes a pneumatic tyre structure of diagonal (bias ply) type in which the carcass is restricted by a substantially inextensible circumferential belt.

NOTE 3 With reference to the definition of radial ply tyre given in ISO 4223-1, for the purposes of this part of ISO 5751, “substantially at 90°” means angles between 65° and 90° as measured from the centreline of the tread.

4.2.5 Nominal rim diameter

The nominal rim diameter shall normally be expressed by a code (see Table 1). However, it shall be expressed in millimetres for new and future concepts where the application either of existing tyres on new-concept rims or of new-concept tyres on existing rims would be incompatible.

4.3 Service description

The characteristics shall be indicated as follows:

Load index	Speed symbol
-------------------	---------------------

For load indices and speed symbols and their corresponding loads and speeds, see ISO 4223-1:2002, Tables A.1 and A.2.

Table 1 — Nominal rim diameter codes

Dimensions in millimetres

Nominal rim diameter code	
Code	Nominal rim diameter D_r
8	203
10	254
12	305
13 M/C	330
14 M/C	356
15 M/C	381
16 M/C	406
17 M/C	432
18 M/C	457
19 M/C	483
20 M/C	508
21 M/C	533
23 M/C	584

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.4 Other service characteristics

ISO 5751-1:2004

4.4.1 In the case of tubeless tyres, the marking "TUBELESS" shall be shown on the tyre.

75cb0d97628/iso-5751-1-2004

4.4.2 In the case of a preferred direction of rotation of the tyre, an arrow shall be used to indicate that direction.

4.4.3 Tyres designed for vehicles having a maximum speed capacity in excess of 240 km/h shall be identified by means of the following speed categories, and not by the tyre construction code:

- "VB" or "ZB" for bias belted construction;
- "VR" or "ZR" for radial construction.

"ZB" and "ZR" should be used for the equipment of newly designed motorcycles with a maximum speed over 240 km/h.

This identification shall be placed inside the tyre designation (see 4.2.1), instead of in the tyre construction code, as follows.

- a) For speed category "V", "VB" or "VR" tyres suitable for speeds of over 240 km/h, a service description shall be marked with the speed symbol "V" between parentheses, e.g. "120/60 VR 17 (55 V)".
- b) For speed category "ZB" or "ZR" tyres suitable for speeds up to 270 km/h, a service description shall be marked with the speed symbol "W", e.g. "120/60 ZR 17 55 W".
- c) For speed category "ZB" or "ZR" tyres suitable for speeds of over 270 km/h, the service description shall be marked with the speed symbol "W" between parentheses, e.g. "120/60 ZR 17 (55 W)".

The maximum speed approved by the tyre manufacturer may also be marked on the tyre, e.g. "V250" to identify a maximum speed of 250 km/h.

4.4.4 The symbol “MST” may be used to identify special service tyres.

4.4.5 The symbol “DP” may be used to identify tread type C tyres.

4.5 Designation examples

4.5.1 A motorcycle tyre having

- a) a size and construction of
 - nominal section width, 120 mm,
 - nominal aspect ratio, 80,
 - diagonal construction, and
 - nominal rim diameter code 18, with
- b) a service description consisting of
 - a load-carrying capacity of 290 kg, corresponding to load index “65”, and
 - a maximum speed of 180 km/h, corresponding to speed symbol “S”,

shall be marked:

120/80 - 18 M/C

65 S

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.5.2 A motorcycle tyre having

<https://standards.iteh.ai/catalog/standards/sist/71f42ff0-647e-46fe-8350-75cb0d97628/iso-5751-1-2004>
ISO 5751-1:2004

- a) a size and construction of
 - nominal section width, 140 mm,
 - nominal aspect ratio, 70,
 - radial construction, and
 - nominal rim diameter code 17, with
- b) a service description consisting of
 - a reference speed in excess of 240 km/h
 - a reference load-carrying capacity of 300 kg, corresponding to load index “66”, and
 - a maximum speed of 270 km/h, corresponding to speed symbol “W”,

shall be marked:

140/70 ZR 17 M/C

66 W

The same tyre approved for speeds in excess of 270 km/h shall be marked:

140/70 ZR 17 M/C

(66 W)

5 Tyre dimensions

5.1 Calculation of design tyre dimensions

5.1.1 Theoretical rim width, R_{th}

The theoretical rim width, R_{th} , shall be calculated as follows:

$$R_{th} = K_1 \times S_N$$

where

K_1 is the rim/section ratio;

S_N is the nominal section width.

For tyres of existing concepts, K_1 shall be equal to

- 0,6 for aspect ratios 100, 90, 80,
- 0,7 for aspect ratios 70, 65, 60,
- 0,8 for aspect ratios 55, 50 and
- 0,9 for aspect ratios 45, 40.

NOTE K_1 will be defined later for aspect ratios below 40.

5.1.2 Measuring rim width, R_m

The measuring rim width, R_m , is width A of the existing rim width nearest to R_{th} . See ISO 4249-3 for widths of existing rims.

5.1.3 Design tyre section width, S

The design tyre section width, S , shall be the nominal section width, S_N , transferred from R_{th} to R_m , calculated as follows:

$$S = S_N + K_2 (R_m - R_{th})$$

rounded to the nearest whole number.

For tyres of existing concepts, $K_2 = 0,4$.

5.1.4 Design tyre section height, H

The design tyre section height, H , shall be calculated as follows:

$$H = S_N \frac{H/S}{100}$$

rounded to the nearest whole number,

where

S_N is the nominal section width;

H/S is the nominal aspect ratio.

5.1.5 Design tyre overall diameter, D_o

The design tyre overall diameter, D_o , shall be calculated as follows:

$$D_o = D_r + 2H$$

where

D_r is the nominal rim diameter;

H is the design tyre section height.

NOTE For those tyres using a nominal rim diameter code, see Table 1 for the value of D_r to be used.

5.1.6 Values

Guideline values for the design tyre dimensions for metric-series motorcycles tyres are given in Annex A.

5.2 Calculation of maximum overall tyre dimensions in service

5.2.1 General

The calculations of 5.2.2 and 5.2.3, as well as Clause 9, are for use by vehicle manufacturers in designing for tyre clearances.

5.2.2 Maximum overall width in service, W_{max}

The maximum overall width in service, W_{max} , shall be calculated as follows:

$$W_{max} = S \times a$$

where

S is the design tyre section width;

a is the appropriate coefficient (see Table 2).

It includes protective ribs, lettering, embellishments, tread overhang, manufacturing tolerances and growth due to service.

5.2.3 Maximum overall diameter in service, $D_{o,max}$

The maximum overall diameter in service, $D_{o,max}$, shall be calculated as follows:

$$D_{o,max} = D_r + 2Hb$$

where

D_r is the nominal rim diameter;

H is the design tyre section height;

b is the appropriate coefficient (see Table 2).

It includes manufacturing tolerances and growth due to service (for deformation due to centrifugal force, see Clause 9).

5.3 Calculation of minimum dimensions — Section width, S_{\min}

The minimum section width, S_{\min} , shall be equal to the product of the design tyre section width, S , and the appropriate coefficient:

$$S_{\min} = 0,96S$$

$S - S_{\min}$ shall be at least 4 mm.

NOTE In the case of type B tread tyres, minimum section width refers to overall tread width.

5.4 Measuring tyre dimensions — Procedure

Before measuring, mount the tyre on the measuring rim ready for tyre fitment, inflate to the recommended pressure, and allow to stand for a minimum of 24 h at normal room temperature, after which readjust the inflation pressure to the original value.

6 Tread configurations

These attributions of tread type configurations to the type of service are to be considered as examples only. The choice of a given tread type configuration for a given tyre is at the discretion of the tyre manufacturer alone.

Figure 1 shows various tread configurations:

- tread type A corresponds to highway service tyres manufactured for speed symbols up to “S”;
- tread type B corresponds to highway service tyres (for high performance vehicles) manufactured for speed symbols “S” and higher;
- tread type C corresponds to tyres for on-and-off-road service manufactured for speed symbols up to and including “H”;
- tread type D corresponds to tyres for exclusive off-road service manufactured for speed symbol “M”.