

SLOVENSKI STANDARD SIST-TS ISO/TS 19103:2009

01-maj-2009

Geographic information - Conceptual schema language

Information géographique Schéma de langage conceptuel

(standards.iteh.ai) Ta slovenski standard je istoveten z: ISO/TS 19103:2005

100	https://standards.iteh.ai/catalog/sta	<u>60/TS 19103:2009</u> ndards/sist/c39eb9d7-a351-4889-ba66- st-ts-iso-ts-19103-2009
<u>ICS:</u> 35.240.70	Uporabniške rešitve IT v znanosti	IT applications in science

SIST-TS ISO/TS 19103:2009

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS ISO/TS 19103:2009 https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009

TECHNICAL SPECIFICATION

ISO/TS 19103

First edition 2005-07-15

Geographic information — Conceptual schema language

Information géographique — Schéma de language conceptuel

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST-TS ISO/TS 19103:2009</u> https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009



Reference number ISO/TS 19103:2005(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS ISO/TS 19103:2009 https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forewo	ord	iv
Introdu	ction	. v
1	Scope	. 1
2	Conformance	. 1
3	Normative references	. 1
4 4.1 4.2 4.3	Terms, definitions and abbreviations ISO/TS 19103 terms UML terms Abbreviations	. 1 . 3
5	Organization	. 7
6 6.1 6.2 6.3 6.4 6.5 6.6 6.7 6.8 6.9 6.10 6.11 6.12 6.13 6.14	The ISO/TS 19103 UML Profile. Introduction General usage of UML Classes Attributes iTeh STANDARD PREVIEW Data types. Operations	. 8 . 9 . 9 28 29 29 30 31 32 32
Annex	A (normative) Abstract test suite	34
Annex	B (informative) On conceptual schema languages	35
Annex	C (informative) Modeling guidelines	45
Annex	D (informative) Introduction to UML	54
Bibliog	raphy	67

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote; TANDARD PREVIEW
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

SIST-TS ISO/TS 19103:2009

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

IISO/TS 19103 was prepared by Technical Committee ISO/TC 211, Geographic information/Geomatics.

Introduction

This Technical Specification of the ISO geographic information standards is concerned with the adoption and use of a conceptual schema language (CSL) for developing computer-interpretable models, or schemas, of geographic information. Standardization of geographic information requires the use of a formal CSL to specify unambiguous schemas that can serve as a basis for data interchange and the definition of interoperable services. An important goal of the ISO geographic information standards is to create a framework in which data interchange and service interoperability can be realized across multiple implementation environments. The adoption and consistent use of a CSL to specify geographic information is of fundamental importance in achieving this goal.

There are two aspects to this Technical Specification. First, a CSL must be selected that meets the requirements for rigorous representation of geographic information. This Technical Specification identifies the combination of the Unified Modeling Language (UML) static structure diagram with its associated Object Constraint Language (OCL) and a set of basic type definitions as the conceptual schema language for specification of geographic information. Secondly, this Technical Specification provides guidelines on how UML should be used to create geographic information and service models that are a basis for achieving the goal of interoperability.

One goal of the ISO geographic information standards using UML models is that they will provide a basis for mapping to encoding schemas as defined in ISO 19118, as well as a basis for creating implementation specifications for implementation profiles for various environments.

(standards.iteh.ai)

<u>SIST-TS ISO/TS 19103:2009</u> https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS ISO/TS 19103:2009 https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009

Geographic information — Conceptual schema language

1 Scope

This Technical Specification provides rules and guidelines for the use of a conceptual schema language within the ISO geographic information standards. The chosen conceptual schema language is the Unified Modeling Language (UML).

This Technical Specification provides a profile of the Unified Modeling Language (UML) for use with geographic information. In addition, it provides guidelines on how UML should be used to create standardized geographic information and service models.

2 Conformance

Any conceptual schema written for a specification, including a profile or functional standard, that claims conformance with this Technical Specification shall pass all of the requirements described in the abstract test suite in Annex A. Non-UML schemas shall be considered conformant if there is a well-defined mapping from a model in the source language into an equivalent model in UML and that this model in UML is conformant.

Normative references DIST-15160/16 17002000 https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-SIST-TS ISO/TS 19103:2009 3

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19101:2002, Geographic Information — Reference model

ISO/IEC 19501:2005, Information technology — Open Distributed Processing — Unified Modeling Language (UML) Version 1.4.2

4 Terms, definitions and abbreviations

4.1 ISO/TS 19103 terms

For the purposes of this document, the following terms and definitions apply.

4.1.1 application manipulation and processing of data in support of user requirements

[ISO 19101]

4.1.2 application schema conceptual schema for data required by one or more applications

[ISO 19101]

SIST-TS ISO/TS 19103:2009

ISO/TS 19103:2005(E)

4.1.3

conceptual model

model that defines concepts of a universe of discourse

[ISO 19101]

4.1.4

conceptual schema formal description of a conceptual model

[ISO 19101]

4.1.5

data type

specification of a value domain with operations allowed on values in this domain

EXAMPLE Integer, Real, Boolean, String, Date and SG Point (conversion of data into a series of codes).

NOTE Data types include primitive predefined types and user-definable types.

4.1.6

domain

well-defined set

NOTE Domains are used to define the domain set and range set of attributes, operators and functions.

4.1.7

feature

abstraction of real world phenomena

[ISO 19101]

SIST-TS ISO/TS 19103:2009

https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-

iTeh STANDARD PREVIEW

(standards.iteh.ai)

NOTE 1 A feature may occur as a type or an instance. Feature type or feature instance should be used when only one is meant.

NOTE 2 In UML^[8] a feature is a property, such as operation or attribute, which is encapsulated as part of a list within a classifier, such as interface, class or data type.

4.1.8

feature association

relationship that links instances of one **feature** type with instances of the same or a different **feature** type

[ISO 19109]

NOTE 1 A feature association may occur as a type or an instance. Feature association type or feature association instance is used when only one is meant.

NOTE 2 Feature associations include aggregation of features.

4.1.9 feature attribute characteristic of a feature

[ISO 19101]

NOTE 1 A feature attribute has a name, a data type, and a value domain associated to it. A feature attribute for a feature instance also has an attribute value taken from the value domain.

NOTE 2 A feature attribute may occur as a type or an instance. Feature attribute type or feature attribute instance should be used when only one is meant.

4.1.10 feature operation operation that every **instance** of a **feature** type may perform

[ISO 19110]

EXAMPLE 1 An operation upon a "dam" is to raise the dam. The result of this operation is to raise the level of water in a reservoir.

EXAMPLE 2 An operation by a "dam" might be to block vessels from navigating along a "watercourse".

NOTE Feature operations provide a basis for feature type definition.

4.1.11 metadata data about data

[ISO 19115]

4.1.12 metadata element discrete unit of metadata

[ISO 19115]

NOTE 1 Metadata elements are unique within a metadata entity. REVIEW

NOTE 2 Equivalent to an attribute in UML terminology s.iteh.ai)

4.1.13

schema <u>SIST-TS ISO/TS 19103:2009</u> formal description of a model dards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009

[ISO 19101]

4.1.14

service distinct part of the functionality that is provided by an entity through interfaces

[ISO/IEC TR 14252]

4.1.15 value domain set of accepted values

EXAMPLE The range 3-28, all integers, any ASCII character, enumeration of all accepted values (green, blue, white).

4.2 UML terms

The following are UML terms that are adapted from ISO/IEC 19501.

4.2.1

actor

coherent set of roles that users of use cases play when interacting with these use cases

NOTE An actor may be considered to play a separate role with regard to each use case with which it communicates.

4.2.2

aggregation

special form of association that specifies a whole-part relationship between the aggregate (whole) and a component part

NOTE See composition.

4.2.3

association

semantic relationship between two or more classifiers that specifies connections among their instances

A binary association is an association among exactly two classifiers (including the possibility of an association NOTE from a classifier to itself).

4.2.4

attribute

feature within a classifier that describes a range of values that instances of the classifier may hold

NOTE 1 An attribute is semantically equivalent to a composition association; however, the intent and usage is normally different.

NOTE 2 "Feature" used in this definition is the UML meaning of the term and is not meant as defined in 4.1 of this Technical Specification.

4.2.5

behaviour

observable effects of an operation or event, including its results PREVIEW (standards.iteh.ai)

4.2.6

cardinality number of elements in a set SIST-TS ISO/TS 19103:2009 https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-1ef2cad55192/sist-ts-iso-ts-19103-2009

NOTE Contrast: multiplicity.

4.2.7

class

description of a set of objects that share the same attributes, operations, methods, relationships and semantics

NOTE A class may use a set of interfaces to specify collections of operations it provides to its environment. See: interface

4.2.8

classifier

mechanism that describes behavioural and structural features

NOTE Classifiers include interfaces, classes, datatypes, and components.

4.2.9

component

modular, deployable, and replaceable part of a system that encapsulates implementation and exposes a set of interfaces

A component represents a physical piece of implementation of a system, including software code (source, NOTE binary or executable) or equivalents such as scripts or command files.

4.2.10

composition

form of aggregation which requires that a part instance be included in at most one composite at a time, and that the composite **object** is responsible for the creation and destruction of the parts

NOTE Parts with non-fixed multiplicity may be created after the composite itself, but once created they live and die with it (i.e. they share lifetimes). Such parts can also be explicitly removed before the death of the composite. Composition may be recursive. Synonym: composite aggregation.

4.2.11

constraint

semantic condition or restriction

NOTE Certain constraints are predefined in the UML, others may be user defined. Constraints are one of three extensibility mechanisms in UML. See: tagged value, stereotype.

4.2.12

dependency

relationship between two modeling elements, in which a change to one modeling element (the independent element) will affect the other modeling element (the dependent element)

4.2.13

generalization

taxonomic **relationship** between a more general element and a more specific element that is fully consistent with the more general element and contains additional information

NOTE An instance of the more specific element may be used where the more general element is allowed. See: inheritance.

4.2.14

inheritance mechanism by which more specific elements incorporate structure and behaviour of more general elements related by behaviour (standards.iteh.ai)

NOTE See generalization.

SIST-TS ISO/TS 19103:20094.2.15https://standards.iteh.ai/catalog/standards/sist/c39eb9d7-a351-4889-ba66-
1ef2cad55192/sist-ts-iso-ts-19103-2009

entity that has unique identity, a set of **operations** can be applied to it, and state that stores the effects of the **operations**

NOTE See: object.

4.2.16

interface

named set of operations that characterize the behaviour of an element

4.2.17

metamodel

model that defines the language for expressing a model

4.2.18

method implementation of an operation

NOTE It specifies the algorithm or procedure associated with an operation.

4.2.19

multiplicity

specification of the range of allowable cardinalities that a set may assume

NOTE Multiplicity specifications may be given for roles within associations, parts within composites, repetitions and other purposes. Essentially a multiplicity is a (possibly infinite) subset of the non-negative integers. Contrast: cardinality.

4.2.20

object

entity with a well-defined boundary and identity that encapsulates state and behaviour

NOTE State is represented by attributes and relationships, behaviour is represented by operations, methods and state machines. An object is an instance of a class. See: class, instance.

4.2.21

operation

service that can be requested from an object to affect behaviour

NOTE 1 An operation has a signature, which may restrict the actual parameters that are possible.

NOTE 2 Definition from UML Reference Manual: A specification of a transformation or query that an object may be called to execute.

NOTE 3 An operation has a name and a list of parameters. A method is a procedure that implements an operation. It has an algorithm or procedure description.

4.2.22

package

general purpose mechanism for organizing elements into groups

NOTE Packages may be nested within other packages. Both model elements and diagrams may appear in a package.

iTeh STANDARD PREVIEW

4.2.23 refinement

relationship that represents a fuller specification of something that has already been specified at a certain level of detail

NOTE For example, a design class is a refinement of an analysis class of a state of a st

1ef2cad55192/sist-ts-iso-ts-19103-2009

4.2.24

relationship

semantic connection among model elements

NOTE Kinds of relationships include association, generalization, metarelationship, flow and several kinds grouped under dependency.

4.2.25

specification

declarative description of what something is or does

NOTE Contrast: implementation.

4.2.26

stereotype

new type of modeling element that extends the semantics of the metamodel

NOTE Stereotypes must be based on certain existing types or classes in the metamodel. Stereotypes may extend the semantics, but not the structure of pre-existing types and classes. Certain stereotypes are predefined in the UML, others may be user defined. Stereotypes are one of three extensibility mechanisms in UML. The others are constraint and tagged value.

4.2.27

tagged value

explicit definition of a property as a name-value pair

NOTE In a tagged value, the name is referred as the tag. Certain tags are predefined in the UML; others may be user defined. Tagged values are one of three extensibility mechanisms in UML. The others are constraint and stereotype.

4.2.28

type

stereotyped class that specifies a domain of objects together with the operations applicable to the objects, without defining the physical implementation of those objects

NOTE A type may have attributes and associations.

4.2.29

value

element of a type domain

NOTE 1 A value may consider a possible state of an object within a class or type (domain).

NOTE 2 A data value is an instance of a data type, a value without identity.

4.3 Abbreviations

API	Application Programming Interface
CASE	Computer Aided Software Engineering
CORBA	Common Object Request Broker Architecture
CSL	Conceptual schema language
CSMF	Conceptual Schema Modeling Facility
DCOM/OLE	Distributed Compound Object Model/Object Linking and Embedding
GFM	General Feature Modelandards.iteh.ai)
OCL	Object Constraint Language
ODMG	Object Database Management Group/sist/c39cb9d7-a351-4889-ba66-
OMG	1ef2cad55192/sist-ts-iso-ts-19103-2009 Object Management Group
ODP	Open Distributed Processing
ODBC	Open Database Connection
SRS	Spatial Reference System
UML	Unified Modeling Language
url	Uniform Resource Locator
XML	Extended Markup Language
XMI	XML Metamodel Interchange

5 Organization

This Technical Specification contains a UML Profile which provides modeling guidelines for how to use UML for modeling compliant with the ISO geographic information standards.

The main technical content of this Technical Specification is found in Clause 6. An introduction to the general usage of UML is given in 6.1 and 6.2. The description of classes and attributes in 6.3 and 6.4 is based on general rules for UML. Data types described in 6.5 are developed for this Technical Specification, as standard UML does not prescribe the use of specific data types. More information on the necessary precision level of UML models required by this Technical Specification is provided in 6.6, 6.7 and 6.8. The conventions for defining optional attributes and associations are described in 6.9. Naming rules are described in 6.10.