

SLOVENSKI STANDARD SIST EN ISO 21178:2013

01-junij-2013

Nadomešča:

SIST EN ISO 21178:2007

Naprave za kontinuirni transport - Lahki trakovi tračnih transporterjev - Ugotavljanje električnih upornosti (ISO 21178:2013)

Light conveyor belts - Determination of electrical resistances (ISO 21178:2013)

iTeh STANDARD PREVIEW

Courroies transporteuses légères Détermination des résistances électriques (ISO 21178:2013)

SIST EN ISO 21178:2013

https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-

Ta slovenski standard je istoveten 2:620/sisEN ISO 21178:2013

ICS:

53.040.10 Transporterji Conveyors

53.040.20 Deli za transporterje Components for conveyors

SIST EN ISO 21178:2013 en

SIST EN ISO 21178:2013

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN ISO 21178:2013</u> https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013

EUROPEAN STANDARD

EN ISO 21178

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2013

ICS 53.040.10

Supersedes EN ISO 21178:2006

English Version

Light conveyor belts - Determination of electrical resistances (ISO 21178:2013)

Courroies transporteuses légères - Détermination des résistances électriques (ISO 21178:2013)

This European Standard was approved by CEN on 4 March 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions. The STANDARD PREVIEW

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

SIST EN ISO 21178:2013

https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

EN ISO 21178:2013 (E)

Contents	Page
Foreword	3

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 21178:2013 https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013

EN ISO 21178:2013 (E)

Foreword

This document (EN ISO 21178:2013) has been prepared by Technical Committee ISO/TC 41 "Pulleys and belts (including veebelts)" in collaboration with Technical Committee CEN/TC 188 "Conveyor belts" the secretariat of which is held by SNV.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2013, and conflicting national standards shall be withdrawn at the latest by October 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 21178:2006.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW

(stan Endorsement riotice)

The text of ISO 21178:2013 has been approved by CEN as EN ISO 21178:2013 without any modification.

SIST EN ISO 21178:2013

https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013

SIST EN ISO 21178:2013

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN ISO 21178:2013</u> https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013

SIST EN ISO 21178:2013

INTERNATIONAL STANDARD

ISO 21178

Second edition 2013-03-15

Light conveyor belts — Determination of electrical resistances

Courroies transporteuses légères — Détermination des résistances électriques

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 21178:2013 https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013



Reference number ISO 21178:2013(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 21178:2013 https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Co	ontents	Page
Fore	reword	iv
1	Scope	1
2	Normative references	1
3	Symbols	
4	 Electrical surface resistances 4.1 Method A: measurement of surface resistance R_{OA} omni-directionally 4.2 Method B: measurement of surface resistance R_{OB} in longitudinal and transverse direction 	2
5	Electrical surface resistivity ρ_s 5.1General5.2Principle5.3Apparatus5.4Preparation and preservation of test pieces prior to testing5.5Procedure5.6Expression of results5.7Test report	
6	Electrical volume resistances 6.1 Volume resistance R_D perpendicular to plane of belt 6.2 Volume resistance, R_{Di} , in longitudinal and transverse direction paralle	10
7	Electrical volume resistivity $\rho_{\rm D}$ 7.1 Procedure (Standards.iteh.ai) 7.2 Expression of results 7.3 Test report SIST EN ISO 211782013	18 18
Ann	nex A (informative) Comparative values for electrical resistances 9104	19
Rihl	5616f260b620/sist-en-iso-21178-2013	2.0

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21178 was prepared by Technical Committee ISO/TC 41, *Pulleys and belts (including veebelts)*, Subcommittee SC 3, *Conveyor belts*.

This second edition cancels and replaces the first edition (ISO 21178:2005), of which it constitutes a minor revision.

iTeh STANDARD PREVIEW

(standards.iteh.ai)

SIST EN ISO 21178:2013 https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-5616f260b620/sist-en-iso-21178-2013

Light conveyor belts — Determination of electrical resistances

1 Scope

This International Standard specifies test methods for determining the electrical resistances of light conveyor belts according to ISO 21183-1. The resistances are surface resistance, volume resistance perpendicular to the belt plane, and longitudinal and transverse volume resistance parallel to the belt plane. This International Standard also specifies two test methods for determining the surface resistivity and the volume resistivity.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable to its application. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 18573, Conveyor belts — Test atmospheres and conditioning periods

3 Symbols

iTeh STANDARD PREVIEW

Symbol	(standards.iteh.ai)	Unit	
R_{OA}	Electrical surface resistance, method A 1178:2013 https://standards.iteh.ai/catalog/standards/sist/7a21d710-9a89-4600-9104-	Ω	
R_{OB}	Electrical surface resistance, method-Bi-iso-21178-2013	Ω	
R_{OG}	Electrical surface resistance for the determination of $ ho_{\mathrm{S}}$	Ω	
R_{D}	Electrical volume resistance perpendicular to the plane of the belt	Ω	
R_{Di}	Electrical volume resistance in longitudinal and transverse direction parallel to the plane of the belt	Ω	
$ ho_{ extsf{S}}$	Electrical surface resistivity	Ω	
$ ho_{ m D}$	Electrical volume resistivity	Ω·cm	
$d_{1/2/3}$	Diameter of electrode	cm	
$d_{\rm m}$	Middle of the gap diameter	cm	
g	Width of the gap	cm	
Α	Surface of the electrode	cm^2	
h	Thickness of test piece	cm	

NOTE The SI unit of surface resistivity, ρ_s , is the ohm (Ω) . In practice, this is sometimes referred to as "ohm/square" or " Ω /sq" or " Ω / \square ". The size of the square is immaterial.

4 Electrical surface resistances

4.1 Method A: measurement of surface resistance R_{OA} omni-directionally

4.1.1 Applicability

This method is applicable to belts which are electrically two-dimensionally isotropic in the plane of the belt.

4.1.2 Principle

An electric current of specified voltage is passed via electrodes through a suitably prepared test piece taken from the belt.

4.1.3 Apparatus

- **4.1.3.1 Sheet of insulating material**, a little larger than the test piece
- **4.1.3.2 Two cylindrical and coaxial brass electrodes**, the base of one being circular and that of the other annular. The dimensions and masses are given in <u>Figure 2</u>. The bases of these electrodes shall be machined flat and polished.
- **4.1.3.3 Flexible insulated wire**, connected to each electrode.

iTeh STANDARD PREVIEW

- **4.1.3.4 Ohmmeter**, having a measuring range up to $10^{10} \Omega$ and accurate to within $\pm 5 \%$. **(Standards.iteh.ai)**
- **4.1.3.5 Source of direct current**, adjustable up to 500 V, and not permitting a current greater than 10 mA. <u>SIST EN ISO 21178:2013</u>

NOTE The source of current can be either an accumulator or a rectified, stabilized a c4 power supply.

5616f260b620/sist-en-iso-21178-2013

4.1.4 Test piece

4.1.4.1 Material

Test piece material shall be new, unused ("virgin"), but shall not be tested sooner than five days after manufacture. It shall be free from contamination and superficial damage.

4.1.4.2 Dimensions

The test pieces shall be square, $300 \text{ mm} \times 300 \text{ mm}$ minimum, and shall be cut from the full thickness of the belt.

4.1.4.3 Number

Three test pieces shall be taken. One test piece shall be taken from the middle of the belt, the other two test pieces shall be taken 100 mm from each of the belt edges.

4.1.4.4 Cleaning

If necessary, clean both surfaces of the test pieces by rubbing with fuller's earth (hydrated magnesium-aluminium silicate), for example, using a clean cloth. After cleaning away all traces of the powder, wipe the surface with a clean cloth moistened with distilled water and then dry with a clean cloth.