



# SLOVENSKI STANDARD

## SIST ISO 14560:2010

01-julij-2010

---

**Postopki prevzemnega vzorčenja po opisnih spremenljivkah - Nivoji kakovosti, specificirani s številom neskladnih primerkov na milijon**

Acceptance sampling procedures by attributes - Specified quality levels in nonconforming items per million

### iTeh STANDARD PREVIEW

Règles d'échantillonnage par attributs en vue d'acceptation - Niveaux spécifiés de qualité en termes d'individus non conformes pour un million d'individus

[SIST ISO 14560:2010](https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a4b17c93b1/sist-iso-14560-2010)

Ta slovenski standard je istoveten z: **ISO 14560:2004**

---

**ICS:**

03.120.30	Uporaba statističnih metod	Application of statistical methods
-----------	----------------------------	------------------------------------

**SIST ISO 14560:2010**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 14560:2010

<https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a4f3f7e93b1/sist-iso-14560-2010>

# INTERNATIONAL STANDARD

# ISO 14560

First edition  
2004-08-15

Corrected version  
2004-11-01

---

---

## Acceptance sampling procedures by attributes — Specified quality levels in nonconforming items per million

*Règles d'échantillonnage par attributs en vue d'acceptation — Niveaux  
spécifiés de qualité en termes d'individus non conformes pour un million  
d'individus*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 14560:2010](https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a43f7e93b1/sist-iso-14560-2010)

[https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-  
0a43f7e93b1/sist-iso-14560-2010](https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a43f7e93b1/sist-iso-14560-2010)



Reference number  
ISO 14560:2004(E)

© ISO 2004

**ISO 14560:2004(E)****PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 14560:2010](https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a43f7e93b1/sist-iso-14560-2010)

<https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a43f7e93b1/sist-iso-14560-2010>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

<b>Contents</b>	<b>Page</b>
Foreword .....	iv
Introduction.....	v
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms, definitions, symbols and abbreviated terms</b> .....	<b>1</b>
<b>4 General principles</b> .....	<b>2</b>
4.1 Objective .....	2
4.2 Quality assessment of product.....	2
4.3 Acceptance sampling of a lot.....	2
<b>5 Estimation of quality levels in nonconforming items per million items</b> .....	<b>3</b>
5.1 Prerequisites.....	3
5.2 Data sources .....	3
5.3 Estimation of $p_M$ , the process quality level .....	3
5.4 Sampling requirements and guidelines .....	4
5.5 Examples of estimation of the quality level.....	4
5.6 Reporting results.....	5
<b>6 Lot acceptance sampling requirements and procedures</b> .....	<b>6</b>
6.1 Overview.....	6
6.2 Requirements and guidelines .....	6
6.3 Lot acceptance procedure.....	7
6.4 Illustrated use of Table 1 .....	7
<b>7 Single sampling plans indexed by LQL in nonconforming items per million items</b> .....	<b>8</b>
<b>Annex A (normative) Data exclusion</b> .....	<b>12</b>
<b>Annex B (informative) Underlying theory for generating point estimates of quality level in fraction nonconforming</b> .....	<b>15</b>
<b>Annex C (informative) Statistical theory and calculation of Table 1</b> .....	<b>17</b>
<b>Bibliography</b> .....	<b>19</b>

## ISO 14560:2004(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14560 was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 5, *Acceptance sampling*.

This corrected version of ISO 14560:2004 incorporates the following correction: in Annex C the maximum consumer's risk has been corrected to 21 %.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
<https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a43f7e93b1/sist-iso-14560-2010>

## Introduction

For processes that produce nonconforming items relatively rarely, it is advantageous to replace traditional methods of estimating and reporting quality levels by more suitable methods. For example, an estimated outgoing quality level reported as 10 nonconforming items per million items carries a more immediately comprehensible message than either 0,00001 nonconforming items per item or 0,001 nonconforming items per 100 items. This International Standard provides alternative methods that use nonconforming items per million items terminology in estimating and reporting quality levels.

This International Standard provides a means by which quality requirements, stated to be no worse than a given number of nonconforming items per million items, can be verified on a lot-by-lot basis. Procedures are also provided for estimation of the process quality level based on evidence from previous audit and/or lot acceptance samples. Additionally, guidance is given for presuming a process quality level so that the verification procedure can be used when prior sample data is inadequate or not available.

A key feature of this International Standard is that it provides incentives for suppliers to improve their quality. The lot acceptance portion of this specification requires larger sample sizes when quality declines, smaller sample sizes when quality improves. If a customer specifies the same quality requirements to multiple suppliers of a product, those suppliers with superior quality will require, on average, smaller samples for acceptance sampling.

This document is based upon the US Electronic Industries Alliance standards EIA-554 and EIA-555, which it consolidates and reorients to indicate that the procedures are generic and can therefore also be used in industrial or service applications not generally serviced by EIA.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

SIST ISO 14560:2010  
<https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a43f7e93b1/sist-iso-14560-2010>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 14560:2010

<https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a4f3f7e93b1/sist-iso-14560-2010>



# Acceptance sampling procedures by attributes — Specified quality levels in nonconforming items per million

## 1 Scope

This International Standard specifies, for quality levels expressed as nonconforming items per million items, procedures for estimating the quality level of a single entity (e.g. a lot) and, when the production process is in statistical control, for estimating the process quality level based on evidence from several samples. Procedures are also specified for using this information when selecting a suitable sampling plan so as to verify that the quality level of a given lot does not exceed a stated limiting quality level (LQL). For the case where no prior sample data is available, guidance is given for presuming a process quality level in selecting a plan.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2859-1, *Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

ISO 3534-1, *Statistics — Vocabulary and symbols — Part 1: Probability and general statistical terms*

ISO 3534-2, *Statistics — Vocabulary and symbols — Part 2: Statistical quality control*

## 3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in ISO 2859-1, ISO 3534-1 and ISO 3534-2, and the following symbols and abbreviated terms apply.

- Ac acceptance number, representing the largest number of nonconforming items found in the sample that permits the acceptance of the lot, as given in the sampling plan
- $d$  number of nonconforming items observed
- $d_i$  number of nonconforming items found in the sample from the  $i$ th lot
- LQL limiting quality level, in nonconforming items per million items (i.e. the actual quality level of a lot that corresponds to a probability of 21 % or less of lot acceptance for the sampling plan used)
- $L_P$  lower limit to the assessed process quality level for a given LQL and Ac, used for selecting a plan from Table 1

NOTE 1  $L_P$  is the lowest actual quality level of a lot for which the probability of lot acceptance is 90 % or more for a sampling plan with the given acceptance number, but which is less than 90% for a sampling plan with the next smaller acceptance number for the same LQL.

**ISO 14560:2004(E)**

$m$	total number of lots that are subjected to inspection
$n$	number of items sampled from a lot
$n_i$	number of items sampled from the $i$ th lot
$p$	quality level in fraction nonconforming items
$\hat{p}$	estimator of $p$
$p_M$	quality level in nonconforming items per million items, $p_M = p \times 10^6$
$\hat{p}_M$	estimator of $p_M$
$P_{1,M}$	producer's risk quality level in nonconforming items per million items (i.e. the quality level that corresponds to a probability of lot rejection of 5 %)
$P_{2,M}$	consumer's risk quality level in nonconforming items per million items (i.e. the quality level that corresponds to a probability of lot acceptance of 10 %)
$U_P$	upper limit to the assessed process quality level for a given LQL and $A_c$ , used for selecting a plan from Table 1

NOTE 2  $U_P$  is the highest actual quality level of a lot for which the probability of lot acceptance is 90 % or more for the sampling plan used.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

### 4 General principles

#### 4.1 Objective

[SIST ISO 14560:2010](https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a4937e92b1/sist-iso-14560-2010)

[https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-](https://standards.iteh.ai/catalog/standards/sist/013d06d5-10a9-4c41-957c-0a4937e92b1/sist-iso-14560-2010)

The objective of this International Standard is twofold: the quality assessment of product and the acceptance sampling of a lot when quality is high, as indicated by the fact that it is typically expressed in terms of numbers of nonconforming items per million items.

#### 4.2 Quality assessment of product

It is assumed that the product has been through its manufacture, inspection, test and final acceptance procedures, including procedures for eliminating unrepresentative lots.

When sampling from a consecutive series of lots, the assessment procedures in this International Standard are applicable when

- a) the production process is in statistical control, and
- b) the cumulative number of inspected items (audit and/or lot acceptance items) is 400 or more.

#### 4.3 Acceptance sampling of a lot

Sampling procedures are provided to verify that the quality is no worse than the limiting quality level (LQL). An estimate of the process quality level in nonconforming items per million items, based on previous data, is used to select the appropriate sampling plan. Presumption (rather than estimation) of the process quality level is permitted when determining sampling plans for the first few lots in a series or for isolated lots, unless and until enough data is available to form a valid estimate. It is recommended that estimation of the process quality level commence when the total number of inspected items (audit and/or lot acceptance items) from one or more consecutive lots is 400 or more; otherwise, continue to presume the process quality level (see 6.1). The sampling plans in this International Standard are indexed by the LQL and the estimated (or presumed) process quality level.

Suppliers are encouraged to not only drive their processes to a state of statistical control, but also to employ continuous improvement techniques to raise the quality of their products. As quality levels improve, suppliers can then benefit from this International Standard's provision for reduction in acceptance sample size.

Acceptance sampling procedures given in this International Standard can be used when processes have actual nonconforming quality levels of up to 37 606 nonconforming items per million items. However, selecting a small LQL may result in a prohibitively large sample size (see Table 1). For large LQLs, existing sampling plans in other international standards (e.g. ISO 2859-1) may be more appropriate depending upon user requirements.

## 5 Estimation of quality levels in nonconforming items per million items

### 5.1 Prerequisites

Users of this document should confirm that all of the following are met for the products whose quality level is being reported:

- a) processes meet the assumptions of 4.2;
- b) attribute sampling inspection for the characteristics being reported is conducted for product that has completed production;
- c) when products are manufactured at more than one location, product from each line or system of production is considered separately.

### 5.2 Data sources

The estimation of process quality levels is based on

- a) past results from audit samples that are drawn at random from the population, and/or
- b) past lot acceptance data.

Data from lots that fail the lot acceptance procedure, whether audit sample data or lot acceptance data, may be excluded from the calculations only if the conditions of Annex A are met. Inspection lots of products which fail acceptance criteria are either assumed to be 100 % inspected with all nonconforming items being removed from the lot, or are removed from consideration for shipment and discarded.

### 5.3 Estimation of $p_M$ , the process quality level

This is as follows.

- a) When sample results from only a single lot are available, from which  $d$  nonconforming items have been found in a sample of size  $n$ ,  $p_M$  is estimated using the formula

$$\hat{p}_M = \left( \frac{d + 0,7}{n + 0,4} \right) \times 10^6 \quad (1)$$

A mathematical justification for Equation (1) is presented in Annex B.