



SLOVENSKI STANDARD SIST ISO 12647-2:2005

01-januar-2005

; fUz bUHM bc`c[]U!`JcXYb`Y`dfcWgU]nXYUj YfUgf]fUb] `VUfj b] `nj `Y _cj ž
dfYg_i gb] `]b`dfc]nj cXb] `cXhgcj `!`&"XY.`DfcWg]j `cZgYfbYa `h]g_i

Graphic technology -- Process control for the production of half-tone colour separations, proof and production prints -- Part 2: Offset lithographic processes

iTeh STANDARD PREVIEW

Technologie graphique -- Maîtrise des procédés pour la fabrication des séparations de couleur en ton tramé, des épreuves et des tirages en production -- Partie 2: Procédés lithographiques offset

[SIST ISO 12647-2:2005](https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005)

[https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-](https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005)

[7a13c1e289d4/sist-iso-12647-2-2005](https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005)

Ta slovenski standard je istoveten z: ISO 12647-2:2004

ICS:

37.100.01 01.060.01 Graphic technology in general

SIST ISO 12647-2:2005

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 12647-2:2005

<https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005>

**Graphic technology — Process control
for the production of half-tone colour
separations, proof and production
prints —**

Part 2:

Offset lithographic processes

iTeh STANDARD PREVIEW

(standards.iteh.ai)

*Technologie graphique — Maîtrise des procédés pour la fabrication des
séparations de couleur en ton tramé, des épreuves et des tirages en
production —*

SIST ISO 12647-2:2005
Partie 2: Procédés lithographiques offset

<https://standards.iteh.ai/catalog/standards/sist/85304561-3a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 12647-2:2005](https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005)

<https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Requirements	2
5 Test methods — Tone value and tone-value increase of a print	12
6 Reporting of printing conditions	12
Annex A (informative) Methods for establishing the colour of a standard ink on the paper types	14
Annex B (informative) Dependence of the tone value increase of press prints on screen frequency	16
Annex C (informative) Grey balance	18
Bibliography	19

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 12647-2:2005](https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005)

<https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 12647 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12647-2 was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

This second edition cancels and replaces the first edition (ISO 12647-2:1996), which has been extensively revised. The revisions include the following:

- a) introduction of digital data as input;
- b) reduction of the tone value increase by roughly 3 %;
- c) changes in the colouration of the primary and secondary solids (Table 2);
- d) introduction of an additional measurement condition with a specified white backing;
- e) general clean-up.

In view of the misconceptions about the use of density and grey balance values, it was decided to move this information to an informative annex.

ISO 12647 consists of the following parts, under the general title *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints*:

- *Part 1: Parameters and measurement methods*
- *Part 2: Offset lithographic processes*
- *Part 3: Coldset offset lithography and letterpress on newsprint*
- *Part 4: Publication gravure process*
- *Part 5: Screen printing*
- *Part 6: Flexographic printing*

Introduction

Part 1 of ISO 12647 serves to provide definitions, the general principles, the general order of the material to be covered in the subsequent parts 2 to 6, the definition of the data, the measurement conditions and the reporting style.

This part of ISO 12647 lists values or sets of values of the primary parameters specified in ISO 12647-1 and related technical properties of a half-tone offset lithographic print. Primary parameters include the screening parameters, the tone value increase, the colours of the solids and the print substrate. Conformance to the specified values in proof and production printing assure, in principle, a good visual match between specimens produced. Exceptions from this general observation are discussed in the following paragraph.

The purpose of a proof print is to simulate the visual characteristics of the finished print product as closely as possible. In order to visually match a particular print, off-press proofing processes often require values for solid-tone coloration and tone-value increase that are different from those of the printing process they are meant to simulate. This is caused by differences in phenomena such as gloss, light scatter (within the print substrate or the colorant), metamerism and transparency. Such differences are likely for those off-press proofing processes in which the print substrate, the colorants and the technology for applying them are significantly different from offset press printing. In such cases the user or the supplier needs to ensure that appropriate corrections are specified.

Another problem area is the matching of a digital off-press proof on an opaque substrate to a double-sided print on a less-than-opaque, lightweight printing paper as used in heat-set web printing. If the proof is made with colour management profiles based on measurements with white backing, there will be an unavoidable difference between proof and production prints, placed on a black backing in accordance with the specifications of this part of ISO 12647. The possible occurrence of such differences needs to be well communicated, in advance, to the parties concerned.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 12647-2:2005

<https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a13c1e289d4/sist-iso-12647-2-2005>

Graphic technology — Process control for the production of half-tone colour separations, proof and production prints —

Part 2: Offset lithographic processes

1 Scope

This part of ISO 12647 specifies a number of process parameters and their values to be applied when preparing colour separations for four-colour offset printing or when producing four-colour prints by one of the following methods: heat-set web, sheet-fed or continuous forms process printing, or proofing for one of these processes; or offset proofing for half-tone gravure.

The parameters and values are chosen in view of the complete process covering the process stages “colour separation”, “film setting”, “making of the printing forme”, “proof production”, “production printing” and “surface finishing”.

This part of ISO 12647 is

- directly applicable to proofing and printing processes that use colour separation films as input;
<https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373->
- directly applicable to proofing and printing from printing formes produced by filmless methods as long as direct analogies to film production systems are maintained;
- applicable to proofing and printing with more than four process colours as long as direct analogies to four-colour printing are maintained, such as for data and screening, for print substrates and printing parameters;
- applicable by analogy to line screens and non-periodic screens.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the reference document (including any amendments) applies.

ISO 5-3:1995, *Photography — Density measurements — Part 3: Spectral conditions*

ISO 8254-1:1999, *Paper and board — Measurement of specular gloss — Part 1: 75° gloss with a converging beam, TAPPI method*

ISO 12642:1996, *Graphic technology — Prepress digital data exchange — Input data for characterization of 4-colour process printing*

ISO 12647-1:2004, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 1: Parameters and measurement methods*

3 Terms and definitions

For the purposes of this document, the definitions given in ISO 12647-1 and the following apply.

3.1

positive-acting plate

⟨offset printing⟩ offset printing plate for use with positive-polarity film

3.2

negative-acting plate

⟨offset printing⟩ offset printing plate for use with negative-polarity film

3.3

four-colour continuous forms printing

offset process performed on small width web-fed presses for use with personalized mailings

3.4

commercial/speciality printing

general-purpose sheet-fed and non-magazine heat-set web offset printing

3.5

heat-set web printing

lithographic offset printing on web-type print substrates with printing ink that requires heat for drying

3.6

tone value

⟨printing forme⟩ percentage of surface area that appears to be receptive to printing ink

NOTE 1 With some plate types, the tone value thus defined is smaller than the percentage of surface area that is visibly distinct from the background.

[SIST ISO 12647-2:2005](https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a15c1c289d4/sist-iso-12647-2-2005)

NOTE 2 Formerly known as the film printing dot area. "Dot area" is now a deprecated term.

<https://standards.iteh.ai/catalog/standards/sist/853045b1-5a16-4cd9-a373-7a15c1c289d4/sist-iso-12647-2-2005>

4 Requirements

4.1 General

The following subclauses are arranged in accordance with the order set out in ISO 12647-1; they also depend on this part for the general principles, the definition of the data, the measurement conditions and the reporting style.

4.2 Data files, colour-separation films and printing formes

4.2.1 General

Data delivered for printing shall be in the colour formats CMYK or three-component. In all cases, digital data files or colour separation film sets delivered for printing should be accompanied by a proof print that simulates the intended printing condition and that conforms to 4.3. This fact shall be verifiable by measuring a well-specified control strip or a similar control device that is printed on the proof print along with the subject.

In the case of digital data, the intended printing condition shall be indicated. Where the latter is included in the registry of characterizations maintained by the ICC and the digital data is CMYK, the name used in the ICC registry is usually used for identification in lieu of including an ICC output profile. If the intended printing condition is not included in said registry, an ICC output profile shall be included. If the data are other than CMYK, the data shall be defined colorimetrically using an ICC input profile or another mechanism and an ICC CMYK output profile shall be included. The rendering intent to be used with the output profile shall be communicated.

4.2.2 Film or printing forme quality

In order to permit the reproduction of at least 100 tone-value steps, the resolution of the image setter or plate setter should be set accordingly.

EXAMPLE 1 If, for a screen employing single half-tone cell modulation, the intended nominal screen ruling is 70 cm^{-1} , the resolution of the image setter or the plate setter should not be smaller than 700 cm^{-1} (1 800 dpi). For a screen with super-cell technology, it is possible to set the resolution to a smaller value.

Unless otherwise specified, the core density of colour-separation films shall be at least 2,5 above the transmission density of the clear film (film base plus fog). The transmission density in the centre of a clear half-tone dot shall not be more than 0,1 above the corresponding value of a large clear area. The transmission density of the clear film shall not be higher than 0,15. Both measurements shall be made with a (UV) transmission densitometer whose spectral products conform to ISO type 1 printing density as defined in ISO 5-3.

NOTE 1 The clear-film density requirement is based on the understanding that the density range of the clear areas of all films that are to be exposed onto the same plate are not expected to exceed 0,10. Note further that 0,05 represents the lowest commonly found value for ISO type 1 printing density. For half-tone films with clear film densities outside this range, agreements between the supplier of colour separations and the recipient are required. Contacting or duplicating can also be used to bring half-tone films with dissimilar clear film densities into agreement.

NOTE 2 As a practical guide, a core density of 2,5 above the clear-film density will normally be achieved if the density of large solid areas is more than 3,5 above the clear-film density.

NOTE 3 If a user wishes to use a blue filter for transmission density measurements on colour-separation films, it is necessary to determine, for the particular film type and processing conditions, the correlation between densities obtained with the blue filter and those obtained with an ISO type 1 printing density instrument; for the measurement of core density, an ISO type 2 printing instrument is applicable.

The fringe width of a colour-separation film shall not be greater than one-fortieth of the screen width.

A half-tone dot that is produced by several exposures of a focal spot shall be fully rendered and not be split up into distinct parts. This requirement also applies to direct platemaking.

Other than for the clear-film density requirement, the colour-separation film quality shall be evaluated according to the informative Annex B of ISO 12647-1:2004.

4.2.3 Screen frequency (film or printing forme)

For four-colour work, the screen ruling (screen frequency) should be within the range 45 cm^{-1} to 80 cm^{-1} . Preferred nominal screen rulings are

- a) 45 cm^{-1} to 70 cm^{-1} for web-offset periodical printing;
- b) 52 cm^{-1} to 70 cm^{-1} for continuous-forms process printing on coated paper, 52 cm^{-1} for uncoated paper;
- c) 60 cm^{-1} and higher for commercial/speciality printing.

NOTE 1 Outside of the range 45 cm^{-1} to 80 cm^{-1} , the general principles specified in ISO 12647-1 remain valid but specific values might differ.

NOTE 2 With computer-generated screening, the "screen frequency" is often varied slightly from one process colour to another in order to minimize moiré patterns. For example, there might be a difference of 3 cm^{-1} or 4 cm^{-1} between the colours C, M, Y.

NOTE 3 For the black or yellow colour half-tone, a screen ruling is sometimes used which is substantially finer than the nominal screen ruling of the remaining colours, for example, 84 cm^{-1} versus 60 cm^{-1} .