



SLOVENSKI STANDARD
kSIST FprEN 14318-1:2012
01-november-2012

Toplotnoizolacijski proizvodi za stavbe - Proizvodi iz trde poliuretanske pene (PUR) in poliizocianuratne pene (PIR), oblikovani na mestu vgradnje - 1. del: Specifikacija penastega sistema pred vgradnjo

Thermal insulating products for buildings - In-situ formed dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 1: Specification for the rigid foam dispensed system before installation

Wärmedämmstoffe für das Bauwesen - An der Verwendungsstelle hergestellte Wärmedämmung aus dispensiertem Polyurethan (PUR)- und Polyisocyanurat (PIR)-Hartschaum - Teil 1: Spezifikation für das Schaumsystem vor dem Einbau

Produits isolant thermiques destinés aux applications du bâtiment - Produits en mousse rigide de polyuréthane (PUR) ou de polyisocyanurate (PIR) injectée, formés en place - Partie 1: Spécifications relatives aux systèmes d'injection du polyuréthane ou du polyisocyanurate avant mise en oeuvre

Ta slovenski standard je istoveten z: FprEN 14318-1

ICS:

91.100.60	Materiali za toplotno in zvočno izolacijo	Thermal and sound insulating materials
-----------	---	--

kSIST FprEN 14318-1:2012	en,fr,de
---------------------------------	-----------------

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

FINAL DRAFT
FprEN 14318-1

August 2012

ICS 91.100.60

English Version

**Thermal insulating products for buildings - In-situ formed
dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR)
foam products - Part 1: Specification for the rigid foam
dispensed system before installation**

Produits isolant thermiques destinés aux applications du bâtiment - Produits en mousse rigide de polyuréthane (PUR) ou de polyisocyanurate (PIR) injectée, formés en place - Partie 1: Spécifications relatives aux systèmes d'injection du polyuréthane ou du polyisocyanurate avant mise en oeuvre

Wärmedämmstoffe für das Bauwesen - An der Verwendungsstelle hergestellte Wärmedämmung aus dispensiertem Polyurethan (PUR)- und Polyisocyanurat (PIR)-Hartschaum - Teil 1: Spezifikation für das Schaumsystem vor dem Einbau

This draft European Standard is submitted to CEN members for third formal vote. It has been drawn up by the Technical Committee CEN/TC 88.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
Foreword.....	5
1 Scope	6
2 Normative references	6
3 Terms, definitions, symbols and abbreviations	7
3.1 Terms and definitions	7
3.2 Symbols and abbreviations	9
3.2.1 Symbols used in this standard.....	9
3.2.2 Designation code in this standard	10
3.2.3 Abbreviations used in this standard.....	10
4 Requirements	10
4.1 General.....	10
4.2 For all applications	11
4.2.1 Thickness measurements	11
4.2.2 Thermal resistance and thermal conductivity	11
4.2.3 Reaction profile and free-rise density	11
4.2.4 Short term water absorption by partial immersion	11
4.2.5 Water vapour transmission	12
4.2.6 Durability characteristics.....	12
4.2.7 Reaction to fire of the products	12
4.2.8 Closed cell content.....	13
4.3 Specific applications	13
4.3.1 General.....	13
4.3.2 Sound absorption	13
4.3.3 Dangerous substances	13
4.3.4 Substrate adhesion strength perpendicular to faces	14
4.3.5 Reaction to fire of products in standardised assemblies simulating end-use applications	14
4.3.6 Continuous glowing combustion.....	14
4.3.7 Dimensional stability under specified temperature and humidity conditions	14
5 Test methods.....	15
5.1 Sampling and test specimen preparation	15
5.1.1 Thermal conductivity.....	15
5.1.2 Other characteristics	15
5.2 Conditioning.....	15
5.3 Testing	15
5.3.1 General.....	15
5.3.2 Thermal resistance and thermal conductivity	15
6 Designation code	17
7 Evaluation of conformity.....	17
7.1 General.....	17
7.2 Initial type testing	18
7.3 Factory production control.....	18
8 Marking, labelling and technical information	18
8.1 Marking and labelling	18
8.2 Technical information	18
Annex A (normative) Determination of declared aged thermal conductivity and aged thermal resistance	20
A.1 Introduction	20
A.2 Input data.....	20
A.3 Declared values.....	20

A.3.1	General	20
A.3.2	Case where thermal resistance and thermal conductivity are declared	20
A.3.3	Case where thermal resistance alone is declared	20
Annex B	(normative) Determination of substrate adhesion strength perpendicular to faces	22
B.1	Principle	22
B.2	Apparatus	22
B.3	Test specimen	22
B.4	Procedure	22
B.5	Report	23
Annex C	(normative) Determination of the aged values of thermal resistance and thermal conductivity	24
C.1	General	24
C.2	Sampling and test specimen preparation	24
C.3	Determination of the initial value of thermal conductivity	25
C.4	Determination of the accelerated aged value of thermal conductivity	26
C.4.1	Procedure	26
C.4.2	Measurement of the accelerated aged value of thermal conductivity	27
C.4.3	Addition of the safety increments (to be used with the accelerated ageing procedure only)	27
C.4.4	Acceleration test (optional and for diffusion open products only, in combination with the accelerated ageing procedure)	28
C.4.5	Determination of the accelerated aged value of thermal conductivity considering the acceleration factor (optional method and for diffusion open products only, in combination with the accelerated ageing procedure)	28
C.5	Fixed increment procedure	28
C.5.1	Conditions	28
C.5.2	Normality test	29
C.5.3	Calculation of the aged value of thermal conductivity	29
C.6	Declaration of the aged values of thermal resistance and aged thermal conductivity	30
C.6.1	General	30
C.6.2	Product grouping	30
C.6.3	Initial values of thermal conductivity used to calculate the $\lambda_{90/90}$ value	30
C.6.4	Aged values of thermal conductivity used to calculate the $\lambda_{90/90}$ value	31
Annex D	(normative) Initial type testing (ITT) and Factory production control (FPC)	32
Annex E	(normative) Determination of the reaction profile and free-rise density	34
E.1	Introduction	34
E.2	Principle	34
E.3	Apparatus	34
E.4	Procedure	34
E.4.1	Pre-treatment of polyol component	34
E.4.2	Making the foam	34
E.4.3	Presentation of reaction profile data	34
E.5	Free-rise density	35
E.5.1	General	35
E.5.2	Core free-rise density	35
E.5.3	Beaker free-rise density	35
E.5.4	Presentation of free-rise density result	35
Annex F	(normative) Sample preparation method for the test specimens for the thermal conductivity test	36
F.1	Procedure	36
Annex G	(normative) Sample preparation method for the test specimens other than thermal conductivity	37
G.1	Principle	37
G.2	Procedure	37
Annex H	(normative) Testing for reaction to fire of products	38
H.1	Scope	38
H.2	Product and installation parameters	38

FprEN 14318-1:2012 (E)

H.3	Mounting and fixing.....	39
H.3.1	Ignitability (EN ISO 11925-2).....	39
H.3.2	Single Burning Item [SBI] (EN 13823).....	39
H.4	Field of application	41
Annex I (normative) Testing for reaction to fire of products in standardised assemblies		
	simulating end-use application(s).....	43
I.1	Scope	43
I.2	Product and installation parameters	43
I.3	Mounting and fixing.....	44
I.3.1	Ignitability (EN ISO 11925-2).....	44
I.3.2	Single Burning Item [SBI] (EN 13823).....	44
I.4	Field of application	47
Annex J (informative) Example for the determination of the declared aged values of thermal		
	conductivity and thermal resistance for a product.....	50
J.1	Case where both thermal conductivity and thermal resistance are declared.....	50
Annex K (normative) Instructions for compiling thermal resistance performance charts.....		
K.1	Introduction	52
K.2	General.....	52
K.3	Procedure for the manufacturer to create the performance charts	54
K.3.1	Performance charts for diffusion open faces	54
K.3.2	Performance chart for one diffusion open face and one diffusion tight face	55
K.3.3	Performance chart for diffusion tight faces	56
K.3.4	For products classified CCC4	57
K.3.5	For products classified CCC1	57
K.3.6	For products classified CCC2 and CCC3	58
Annex ZA (informative) Clause of this European Standard addressing the provisions of the		
	provisions of the EU Construction Products Directive	59
ZA.1	Scope and relevant characteristics	59
ZA.2	Procedure for attestation of conformity of in-situ formed dispensed rigid polyurethane (PUR) and rigid polyisocyanurate foam (PIR) products	61
ZA.2.1	Systems of attestation of conformity	61
ZA.2.2	EC Certificate and Declaration of conformity.....	63
ZA.3	CE marking and labelling.....	64
	Bibliography	66

Foreword

This document (FprEN 14318-1:2012) has been prepared by Technical Committee CEN/TC 88 “Thermal insulating materials and products”, the secretariat of which is held by DIN.

This document is currently submitted to the third Formal Vote.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 89/106/EEC.

For relationship with EU Directive 89/106/EEC, see informative Annex ZA, which is an integral part of this document.

This European Standard consists of two parts which form a package. The first part is the harmonised part satisfying the mandate and the CPD and is the basis for the CE marking covering the products, which are placed on the market. The second part, which is the non-harmonised part, covers the specification for the installed products. Both parts need to be used for the application of the insulation product in the end-use applications covered by EN 14318.

This European Standard is one of a series for mineral wool, expanded clay, expanded perlite, exfoliated vermiculite, polyurethane/polyisocyanurate, cellulose, bound expanded polystyrene and expanded polystyrene in-situ formed insulation products used in buildings, but this standard may be used in other areas where appropriate.

The reduction in energy used and emissions produced during the installed life of insulation products exceeds by far the energy used and emissions made during the production and disposal processes.

This document is one of a series of standards as listed below:

EN 14318-1, *Thermal insulating products for buildings — In-situ formed dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products — Part 1: Specification for the rigid foam dispensed system before installation*

EN 14318-2, *Thermal insulating products for buildings — In-situ formed dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products — Part 2: Specification for the installed insulation products*

FprEN 14318-1:2012 (E)**1 Scope**

This European Standard specifies requirements for in-situ formed dispensed rigid polyurethane (PUR) and rigid polyisocyanurate (PIR) foam products when installed into cavity walls.

This Part 1 of this European Standard is a specification for the rigid foam dispensing system before installation.

Part 1 of this European Standard describes the product characteristics and includes procedures for testing, marking and labelling and the rules for evaluation of conformity.

This European Standard does not specify the required levels of all properties that should be achieved by a product to demonstrate fitness for purpose in a particular end-use application. The required levels are to be found in regulations or non-conflicting standards.

This European Standard does not cover factory made rigid polyurethane (PUR) or polyisocyanurate (PIR) foam insulation products or in-situ products intended to be used for the insulation of building equipment and industrial installations.

NOTE Foam products are either called flexible or rigid. The flexible products are used in upholstery and mattresses and are characterised by their ability to deflect, support and recover to their original thickness continually during their in-use phase. Those that are not flexible are termed rigid and do not possess these flexible characteristics. They are mostly used for thermal insulation purposes and vary widely in their compression strength values. Once the cell structure is crushed in a rigid foam, it does not recover its thickness fully. Some of these rigid foams are very low in density with very low compression strengths and are sometimes described “commercially” as “soft foams” or “semi-rigid” foams. This note has been included to clarify that all foams with such descriptions are covered by this standard’s use of the term rigid foam.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 312, *Particleboards — Specifications*

EN 508-1, *Roofing products from metal sheet — Specification for self-supporting products of steel, aluminium or stainless steel sheet — Part 1: Steel*

EN 520, *Gypsum plasterboards — Definitions, requirements and test methods*

EN 823, *Thermal insulating products for building applications — Determination of thickness*

EN 1602, *Thermal insulating products for building applications — Determination of the apparent density*

EN 1604, *Thermal insulating products for building applications — Determination of dimensional stability under specified temperature and humidity conditions*

EN 1609, *Thermal insulating products for building applications — Determination of short term water absorption by partial immersion*

EN 12086:1997, *Thermal insulating products for building applications — Determination of water vapour transmission properties*

EN 12667:2001, *Thermal performance of building materials and products — Determination of thermal resistance by means of guarded hot plate and heat flow meter methods — Products of high and medium thermal resistance*