

SLOVENSKI STANDARD
kSIST FprEN 14315-2:2012
10-oktober-2012

Toplotnoizolacijski proizvodi za stavbe - Proizvodi iz brizgane poliuretanske pene (PUR) in poliizocianuratne pene (PIR), oblikovani na mestu vgradnje - 2. del: Specifikacija za vgrajene izolacijske proizvode

Thermal insulating products for buildings - In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 2: Specification for the installed insulation products

Wärmedämmstoffe für das Bauwesen - An der Verwendungsstelle hergestellte Wärmedämmung aus Polyurethan (PUR)- und Polyisocyanurat (PIR)-Spritzschaum - Teil 2: Spezifikation für die eingebauten Produkte

Produits isolants thermiques destinés aux applications du bâtiment - Produits en mousse rigide de polyuréthane (PUR) ou de polyisocyanurate (PIR) projetée, formés en place - Partie 2 : Spécifications relatives aux produits isolants après mise en oeuvre

Ta slovenski standard je istoveten z: FprEN 14315-2

ICS:

91.100.60	Materiali za toplotno in zvočno izolacijo	Thermal and sound insulating materials
-----------	---	--

kSIST FprEN 14315-2:2012

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

FINAL DRAFT
FprEN 14315-2

August 2012

ICS 91.100.60

English Version

**Thermal insulating products for buildings - In-situ formed
sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR)
foam products - Part 2: Specification for the installed insulation
products**

Produits isolants thermiques destinés aux applications du bâtiment - Produits en mousse rigide de polyuréthane (PUR) ou de polyisocyanurate (PIR) projetée, formés en place - Partie 2 : Spécifications relatives aux produits isolants après mise en oeuvre

Wärmedämmstoffe für das Bauwesen - An der Verwendungsstelle hergestellte Wärmedämmung aus Polyurethan (PUR)- und Polyisocyanurat (PIR)-Spritzschäum - Teil 2: Spezifikation für die eingebauten Produkte

This draft European Standard is submitted to CEN members for third formal vote. It has been drawn up by the Technical Committee CEN/TC 88.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms, definitions, symbols and abbreviations	4
3.1 Terms and definitions	4
3.2 Symbols and abbreviations	6
4 Requirements	6
4.1 General.....	6
4.2 Suitability of the building for the installation of the product	6
5 In-situ measurements and calculations	6
5.1 Declared installed insulation thickness	6
5.2 Declared installed aged thermal resistance, R_D	6
5.3 Declared installed insulation density	6
5.4 Foam quality checks carried out by the installer	7
6 Guidelines for installation.....	7
7 Installer's declaration	7
Annex A (normative) Method of the determination of the declared installed insulation thickness	8
A.1 Procedure	8
Annex B (normative) Methods for the determination of the declared installed insulation density.....	9
B.1 Principle.....	9
B.2 Procedure	9
B.2.1 General.....	9
B.2.2 Destructive testing.....	9
B.2.3 Non-destructive testing.....	9
B.3 Test report	9
Annex C (normative) Immersion method for the determination of the declared installed insulation density	10
C.1 Scope	10
C.2 Principles.....	10
C.3 Equipment necessary.....	10
C.4 Products and reagents.....	10
C.5 Procedure	10
C.6 Results	11
Annex D (normative) Suitability of the building to receive the insulation product.....	12
D.1 Building.....	12
D.2 Site survey.....	12
Annex E (normative) Installation Guidelines.....	13
E.1 General.....	13
E.2 Substrate preparation	13
E.3 Substrate conditions	13
E.4 Spraying machine preparation	13
E.4.1 Preparation	13
E.4.2 Mixing ratio.....	13
E.5 Spraying procedure	14
E.6 Protection against UV radiation	14
E.7 An example of a suitable declaration form which can be used by the installer	15

Foreword

This document (FprEN 14315-2:2012) has been prepared by Technical Committee CEN/TC 88 “Thermal insulating materials and products”, the secretariat of which is held by DIN.

This document is currently submitted to the third Formal Vote.

This European Standard consists of two parts which form a package. The first part is the harmonised part satisfying the mandate and the CPD and which is the basis for the CE marking covering the products, which are placed on the market. The second part, which is the non-harmonised part, covers the specification for the installed products. Both Parts need to be used for the application of the insulation products in the end-use applications covered by EN 14315.

Attention is drawn to the need to take into account any complementary member state rules (e.g. installation rules) which together with this Part 2 of this European Standard ensures the fitness for purpose of the installed product.

This European Standard is one of a series for mineral wool, expanded clay, expanded perlite, exfoliated vermiculite, polyurethane/polyisocyanurate, cellulose, bound expanded polystyrene and expanded polystyrene in-situ formed insulation products used in buildings, but this standard may be used in other areas where appropriate.

The reduction in energy used and emissions produced during the installed life of insulation products exceeds by far the energy used and emissions made during the production and disposal processes.

FprEN 14315-2:2012 (E)**1 Scope**

This European Standard specifies requirements for in-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products when applied to walls, ceilings, roofs, suspended ceilings and floors.

This Part 2 of this European Standard is a specification for the installed insulation product.

This Part 2 of this European Standard describes, when taken together with Part 1 of EN 14315, the product characteristics that are linked to the essential requirements of the EU Construction Products Directive. It also specifies the checks and tests to be used for the declarations made by the installer of the product.

This European Standard does not specify the required levels of all properties to be achieved by a product to demonstrate fitness for purpose in a particular application. The required levels are to be found in regulations or non-conflicting standards.

This European Standard does not cover factory made rigid polyurethane (PUR) or polyisocyanurate (PIR) foam products or in-situ products intended to be used for the insulation of building equipment and industrial installations.

NOTE Foam products are either called flexible or rigid. The flexible products are used in upholstery and mattresses and are characterised by their ability to deflect, support and recover to their original thickness continually during their in-use phase. Those that are not flexible are termed rigid and do not possess these flexible characteristics. They are mostly used for thermal insulation purposes and vary widely in their compression strength values. Once the cell structure is crushed in a rigid foam, it does not recover its thickness fully. Some of these rigid foams are very low in density with very low compression strengths and are sometimes described “commercially” as “soft foams” or “semi-rigid” foams. This note has been included to clarify that all foams with such descriptions are covered by this standard’s use of the term rigid foam.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1602, *Thermal insulating products for building applications — Determination of the apparent density*

EN ISO 9229:2007, *Thermal insulation — Vocabulary (ISO 9229:2007)*

FprEN 14315-1:2012, *Thermal insulating products for buildings — In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products — Part 1: Specification for the foam system before installation*

3 Terms, definitions, symbols and abbreviations**3.1 Terms and definitions**

For the purposes of this document, the terms and definitions given in EN ISO 9229:2007 and the following apply.

3.1.1**polyurethane foam PUR
(in-situ formed products)**

rigid cellular plastics insulation material or product with a structure based on polymers mainly of the polyurethane type