

SLOVENSKI STANDARD
kSIST FprEN 14320-1:2012

01-november-2012

**Toplotnoizolacijski proizvodi za opremo stavb in industrijske inštalacije -
Proizvodi iz trde poliuretanske pene (PUR) in poliizocianuratne pene (PIR),
oblikovani na mestu vgradnje - 1. del: Specifikacije penastega sistema pred
vgradnjo**

Thermal insulating products for building equipment and industrial installations - In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate foam (PIR) products - Part 1: Specification for the rigid foam spray system before installation

Wärmedämmstoffe für die technische Gebäudeausrüstung und für betriebstechnische Anlagen in der Industrie - An der Verwendungsstelle hergestellte Wärmedämmung aus Polyurethan (PUR)- und Polyisocyanurat (PIR)-Spritzschaum - Teil 1: Spezifikation für das Schaumsystem vor dem Einbau

Produits d'isolation thermiques destinés aux applications du bâtiment et aux installations industrielles - Produits en mousse rigide de polyuréthane (PUR) et de polyisocyanurate (PIR) projetée, formés en place - Partie 1: Spécifications relatives aux systèmes de projection du polyuréthane et du polyisocyanurate avant mise en oeuvre

Ta slovenski standard je istoveten z: FprEN 14320-1

ICS:

91.100.60	Materiali za topotno in zvočno izolacijo	Thermal and sound insulating materials
-----------	--	--

kSIST FprEN 14320-1:2012

en,fr,de

**EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM**

**FINAL DRAFT
FprEN 14320-1**

August 2012

ICS 91.100.60

English Version

Thermal insulating products for building equipment and industrial installations - In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate foam (PIR) products - Part 1: Specification for the rigid foam spray system before installation

Produits d'isolation thermiques destinés aux applications du bâtiment et aux installations industrielles - Produits en mousse rigide de polyuréthane (PUR) et de polyisocyanurate (PIR) projetée, formés en place - Partie 1: Spécifications relatives aux systèmes de projection du polyuréthane et du polyisocyanurate avant mise en oeuvre

Wärmedämmstoffe für die technische Gebäudeausrüstung und für betriebstechnische Anlagen in der Industrie - An der Verwendungsstelle hergestellte Wärmedämmung aus Polyurethan (PUR)- und Polyisocyanurat (PIR)-Spritzschaum - Teil 1: Spezifikation für das Schaumsystem vor dem Einbau

This draft European Standard is submitted to CEN members for third formal vote. It has been drawn up by the Technical Committee CEN/TC 88.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
Foreword	5
1 Scope	6
2 Normative references	6
3 Terms, definitions, symbols and abbreviations	7
3.1 Terms and definitions	7
3.2 Symbols and abbreviations	9
3.2.1 Symbols used in this standard	9
3.2.2 Designation codes used in this standard	10
3.2.3 Abbreviations used in this standard	10
4 Requirements	10
4.1 General	10
4.2 For all applications	11
4.2.1 Thickness measurements	11
4.2.2 Thermal conductivity	11
4.2.3 Reaction to fire of the products	11
4.2.4 Reaction profile and free-rise density	12
4.2.5 Durability characteristics	12
4.2.6 Closed cell content	13
4.3 For specific applications	13
4.3.1 General	13
4.3.2 Water vapour transmission	13
4.3.3 Short-term water absorption by partial immersion	13
4.3.4 Compressive stress or compressive strength	13
4.3.5 Dangerous substances	14
4.3.6 Maximum service temperature	14
4.3.7 Minimum service temperature	14
4.3.8 Rate of release of corrosive substances	14
4.3.9 Substrate adhesion strength perpendicular to faces	14
4.3.10 Testing for reaction to fire of the products in standardised assemblies simulating end-use application(s)	15
4.3.11 Continuous glowing combustion	15
4.3.12 Dimensional stability under specified temperature and humidity conditions	15
5 Test methods	16
5.1 Sampling	16
5.2 Conditioning	16
5.3 Testing	16
5.3.1 General	16
5.3.2 Thermal conductivity	16
6 Designation code	19
7 Evaluation of conformity	19
7.1 General	19
7.2 Initial type testing	20
7.3 Factory production control	20
8 Marking, labelling and technical information	20
8.1 Marking and labelling	20
8.2 Technical information	20
Annex A (normative) Initial Type Testing (ITT) and Factory Production Control (FPC)	22
Annex B (normative) Preparation of the test sample	24

B.1	Principle.....	24
B.2	Procedure for thermal conductivity samples	24
B.3	Procedure for samples to be used for other test specimens	24
Annex C (normative) Determination of the aged values of thermal resistance and thermal conductivity		25
C.1	General	25
C.2	Sampling and test specimen preparation	26
C.3	Determination of the initial value of thermal conductivity	26
C.4	Determination of the accelerated aged value of thermal conductivity	27
C.4.1	Procedure	27
C.4.2	Measurement of the accelerated aged value of thermal conductivity	28
C.4.3	Addition of the safety increments (to be used with the accelerated ageing procedure only)	28
C.4.4	Acceleration test (optional and for diffusion open products only, in combination with the accelerated ageing procedure)	29
C.4.5	Determination of the accelerated aged value of thermal conductivity considering the acceleration factor (optional method and for diffusion open products only, in combination with the accelerated ageing procedure)	29
C.5	Fixed increment procedure	29
C.5.1	Conditions	29
C.5.2	Normality test.....	30
C.5.3	Calculation of the aged value of thermal conductivity.....	30
C.6	"Safe values" curve of aged thermal conductivity values versus temperature	32
C.6.1	Principle.....	32
C.6.2	Procedure	32
Annex D (normative) Determination of the reaction profile and free-rise density		33
D.1	Introduction.....	33
D.2	Principle.....	33
D.3	Apparatus	33
D.4	Procedure	33
D.4.1	Pre-treatment of polyol component.....	33
D.4.2	Making the foam	33
D.4.3	Presentation of reaction profile data.....	34
D.5	Free-rise density	34
D.5.1	General	34
D.5.2	Core free-rise density	34
D.5.3	Beaker free-rise density	34
D.5.4	Presentation of free-rise density result.....	34
Annex E (normative) Determination of substrate adhesion strength perpendicular to faces		35
E.1	Principle.....	35
E.2	Apparatus	35
E.3	Sample preparation and conditioning.....	35
E.4	Preparation of test specimens	35
E.5	Testing procedure	35
E.6	Presentation of results.....	35
Annex F (normative) Testing for reaction to fire of the products		36
F.1	Scope	36
F.2	Product and installation parameters	36
F.3	Mounting and fixing	37
F.3.1	Ignitability (EN ISO 11925-2).....	37
F.3.2	Single Burning Item [SBI] (EN 13823).....	37
F.4	Field of application.....	39
Annex G (normative) Testing for reaction to fire of products in standardised assemblies simulating end-use application(s)		41
G.1	Scope	41
G.2	Product and installation parameters	41
G.3	Mounting and fixing	42
G.3.1	Ignitability (EN ISO 11925-2).....	42

FprEN 14320-1:2012 (E)

G.3.2 Single Burning Item [SBI] (EN 13823).....	42
G.4 Field of application	47
Annex ZA (informative) Clause of this European Standard addressing the provisions of the EU Construction Products Directive.....	51
Z.A.1 Scope and relevant characteristics	51
Z.A.2 Procedure for attestation of conformity of in-situ formed sprayed rigid polyurethane (PUR) and rigid polyisocyanurate foam (PIR) products	52
Bibliography	59

Foreword

This document (FprEN 14320-1:2012) has been prepared by Technical Committee CEN/TC 88 "Thermal insulating materials and products", the secretariat of which is held by DIN.

This document is currently submitted to the third Formal Vote.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 89/106/EEC.

For relationship with EU Directive 89/106/EEC, see informative Annex ZA, which is an integral part of this document.

This European Standard consists of two parts which form a package. The first part is the harmonised part satisfying the mandate and the CPD and is the basis for the CE marking covering the products, which are placed on the market. The second part, which is the non-harmonised part, covers the specification for the installed products. Both parts need to be used for the application of the insulation products in the end-use applications covered by the EN 14320.

This European Standard is one of a series for expanded perlite, exfoliated vermiculite and polyurethane/polyisocyanurate in-situ formed insulation products used in building equipment and industrial installations, but this standard may be used in other areas where appropriate.

The reduction in energy used and emissions produced during the installed life of insulation products exceeds by far the energy used and emissions made during the production and disposal processes.

This document is one of a series of standards as listed below:

EN 14320-1, *Thermal insulating products for building equipment and industrial installations — In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products — Part 1: Specification for the rigid foam dispensed system before installation*

EN 14320-2, *Thermal insulating products for building equipment and industrial installations — In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products — Part 2: Specification for the installed insulation products*

FprEN 14320-1:2012 (E)

1 Scope

This European Standard specifies requirements for in-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products for the insulation of building equipment and industrial installations, for example storage vessels, pipes and ducts used for the supply of fuels, oil, other liquids, hot and cold water, air and other gases.

Depending on the type of foam products complying with this standard, they may have service temperature ranges which lie within the limits of ± 200 °C.

This Part 1 of this European Standard is a specification for the rigid foam system before installation.

Part 1 of this European Standard describes the product characteristics and it includes procedures for testing, marking and labelling and the rules for evaluation of conformity.

This European Standard does not specify the required levels of all properties that should be achieved by a product to demonstrate fitness for purpose in a particular end-use application. The required levels are to be found in regulations or non-conflicting standards.

This European Standard does not cover factory made rigid polyurethane or polyisocyanurate foam insulation products or in-situ products intended to be used for the insulation of buildings.

This standard does not specify performance requirements for direct airborne sound insulation and acoustic absorption applications.

NOTE Foam products are either called flexible or rigid. The flexible products are used in upholstery and mattresses and are characterised by their ability to deflect, support and recover to their original thickness continually during their in-use phase. Those that are not flexible are termed rigid and do not possess these flexible characteristics. They are mostly used for thermal insulation purposes and vary widely in their compression strength values. Once the cell structure is crushed in a rigid foam, it does not recover its thickness fully. Some of these rigid foams are very low in density with very low compression strengths and are sometimes described "commercially" as "soft foams" or "semi-rigid" foams. This note has been included to clarify that all foams with such descriptions are covered by this standard's use of the term rigid foam.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 312, *Particleboards — Specifications*

EN 508-1, *Roofing products from metal sheet — Specification for self-supporting products of steel, aluminium or stainless steel sheet — Part 1: Steel*

EN 520, *Gypsum plasterboards — Definitions, requirements and test methods*

EN 823, *Thermal insulating products for building applications — Determination of thickness*

EN 826, *Thermal insulating products for building applications — Determination of compression behaviour*

EN 1602, *Thermal insulating products for building applications — Determination of the apparent density*

EN 1604, *Thermal insulating products for building applications — Determination of dimensional stability under specified temperature and humidity conditions*