

**INTERNATIONAL  
STANDARD**

**ISO/IEC  
14165-116**

First edition  
2005-08

---

---

**Information technology –  
Fibre channel –**

**Part 116:  
10 Gigabit Fibre Channel (10GFC)**

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

---

---



Reference number  
ISO/IEC 14165-116:2005(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

**INTERNATIONAL  
STANDARD**

**ISO/IEC  
14165-116**

First edition  
2005-08

---

---

**Information technology –  
Fibre channel –**

**Part 116:  
10 Gigabit Fibre Channel (10GFC)**

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

---

---



PRICE CODE

W

*For price, see current catalogue*

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

## Contents

FOREWORD	9
INTRODUCTION	10
<b>1 Scope</b>	<b>11</b>
<b>2 Normative references</b>	<b>11</b>
<b>3 Definitions and conventions</b>	<b>12</b>
3.1 Definitions	12
3.2 Editorial Conventions	12
3.2.1 General	12
3.2.2 Hexadecimal notation	12
3.2.3 Transmission rate abbreviations	13
3.2.4 Acronyms and other abbreviations	14
3.2.5 Special symbols	15
3.3 Keywords	15
3.4 Notation	16
3.4.1 State diagram conventions	16
<b>4 Structure and concepts</b>	<b>19</b>
4.1 Overview	19
4.2 10GFC structure	20
4.2.1 FC-3 general description	20
4.2.2 FC-2 general description	20
4.2.3 FC-1 general description	21
4.2.4 FC-0 general description	22
<b>5 Functional characteristics</b>	<b>23</b>
5.1 General characteristics	23
5.2 10GFC physical variant nomenclature	23
716fd430ec71/iso-iec-14165-116-2005	
<b>6 Optical interface specification</b>	<b>24</b>
6.1 General	24
6.2 850 nm Parallel (4 lane) PMD, type 1200-MX-SN4P-I	24
6.2.1 Overview	24
6.2.2 PMD MDIO function mapping	24
6.2.3 PMD functional specifications	25
6.2.4 Operating ranges	27
6.2.5 PMD to MDI optical specifications for 1200-MX-SN4P-I	27
6.2.6 Optical measurement requirements	30
6.2.7 Environmental specifications	31
6.2.8 Environment	31
6.2.9 PMD labeling requirements	32
6.3 850 nm Serial PMD, type 1200-MX-SN-I	32
6.3.1 General	32
6.3.2 Optical specifications	32
6.3.3 Jitter, measurement and safety specifications	33
6.4 850 nm CWDM (four wavelength) PMD, type 1200-MX-SN4-I	34
6.4.1 Overview	34
6.4.2 Wavelength-division multiplexed-lane assignments	34
6.4.3 Operating ranges	34
6.4.4 Transmitter optical specifications	34
6.4.5 Receive optical specifications	34
6.4.6 Eye Safety	35

iteh STANDARD PREVIEW  
(standards.iteh.ai)

6.5 1 310 nm Serial PMD, type 1200-SM-LL-L . . . . .	36
6.5.1 General . . . . .	36
6.5.2 Optical specifications . . . . .	36
6.5.3 Jitter, measurement and safety specifications . . . . .	36
6.6 1 310 nm CWDM (four wavelength) PMD, type 1200-X-LC4-L . . . . .	37
6.6.1 General . . . . .	37
6.6.2 Optical specifications . . . . .	37
6.6.3 Jitter, measurement and safety specifications . . . . .	37
<b>7 Optical interface receptacle specification . . . . .</b>	<b>38</b>
7.1 General . . . . .	38
7.2 Optical interface connector . . . . .	38
7.3 Optical receptacle . . . . .	38
7.4 Optical plug . . . . .	38
<b>8 Optical interface cable plant specifications . . . . .</b>	<b>40</b>
8.1 Overview . . . . .	40
8.2 Fibre optic cable plant model . . . . .	40
8.2.1 Optical fibre connection . . . . .	40
8.2.2 Medium dependent interface (MDI) . . . . .	40
8.3 Characteristics of the fiber optic cabling . . . . .	41
8.3.1 General . . . . .	41
8.3.2 Optical fiber and cable . . . . .	41
8.3.3 Cable plant optical return loss . . . . .	41
8.3.4 Connectors and splices . . . . .	41
<b>9 newFC-1 and 10GFC Levels . . . . .</b>	<b>44</b>
9.1 Definitions and nomenclature . . . . .	44
9.2 Overview . . . . .	44
9.3 Byte lane ordering . . . . .	44
9.4 XGMII control characters and ordered set translation . . . . .	46
9.4.1 General . . . . .	46
9.4.2 FC-1 to XGMII translation tables . . . . .	46
9.4.3 Unsupported FC-1 ordered sets . . . . .	47
9.4.4 Reserved codes . . . . .	48
9.4.5 10GFC error character . . . . .	48
9.5 XAUI idle characters . . . . .	48
9.6 Ordered set mapping from XGMII to XAUI interface . . . . .	49
9.7 10GFC Level functions . . . . .	49
9.7.1 General . . . . .	49
9.7.2 Ordered set translation . . . . .	50
9.7.3 Link fault signalling . . . . .	50
9.7.4 10GFC primitive sequence qualification state diagram . . . . .	50
9.7.5 XGMII and FC-1 primitive sequence interaction . . . . .	52
9.8 FC-1 level rules, requirements and functions . . . . .	52
9.8.1 General . . . . .	52
9.8.2 FC-1 link fault and error indications . . . . .	52
9.8.3 FC_Port state machine . . . . .	53
9.8.4 Arbitrated loop functions . . . . .	53
9.8.5 Inter-frame gap (IFG) rules . . . . .	53
9.8.6 XGMII primitive sequence   Q   rules . . . . .	54
9.8.7 XGMII primitive signal   P   rules . . . . .	55
9.8.8 EOF handling . . . . .	55
9.8.9 10GFC Errors (/E/) . . . . .	56
<b>10 10 gigabit media independent interface (XGMII) . . . . .</b>	<b>57</b>
10.1 General . . . . .	57

10.2 Overview . . . . .	57
10.2.1 General . . . . .	57
10.2.2 XGMII characteristics . . . . .	57
10.2.3 Rate of operation . . . . .	57
10.2.4 Byte lane connections . . . . .	57
10.3 XGMII data stream . . . . .	58
10.3.1 General . . . . .	58
10.3.2 Inter-frame gap (IFG) . . . . .	58
10.3.3 Preamble and start of frame (SOF) . . . . .	59
10.3.4 Data frame size . . . . .	59
10.3.5 Data   CRC   . . . . .	59
10.3.6 End of frame   EOF   . . . . .	59
10.4 XGMII fault Indications . . . . .	59
<b>11 XGMII extender sublayer (XGXS) and 10 gigabit attachment unit interface (XAUI) . . . . .</b>	<b>60</b>
11.1 General . . . . .	60
11.2 XGXS and XAUI rate of operation . . . . .	60
<b>12 8B/10B physical coding sublayer (PCS) and physical medium attachment (PMA) sublayers . . . . .</b>	<b>61</b>
12.1 General . . . . .	61
12.2 Overview . . . . .	61
12.3 Rate of operation . . . . .	61
12.4 Ordered set mapping between XGMII and 8B/10B PCS . . . . .	61
12.4.1 General . . . . .	61
12.4.2 8B/10B encoding . . . . .	61
12.4.3 Data skew and multiple clock domain operation . . . . .	61
12.5 8B/10B PCS to XGMII mapping . . . . .	62
12.5.1 Reserved codes . . . . .	62
12.5.2 Invalid characters . . . . .	62
12.5.3 Terminate   T   . . . . .	62
12.5.4 Error /E/ . . . . .	63
12.6 Transmit and Receive state diagrams . . . . .	63
716fd430ec71/iso-iec-14165-116-2005	
<b>13 Physical coding sublayer (PCS) for 64B/66B . . . . .</b>	<b>65</b>
13.1 General . . . . .	65
13.2 Single lane 64B/66B bit encoding . . . . .	65
<b>14 10 gigabit sixteen bit interface (XSBI) . . . . .</b>	<b>66</b>
<b>15 Port management . . . . .</b>	<b>67</b>
<b>Annex A (informative) Cable plant employing cross-connects . . . . .</b>	<b>68</b>
A.1 Characteristics of fiber optic cabling . . . . .	68
<b>Annex B (normative) 10GFC to SONET mapping . . . . .</b>	<b>70</b>
<b>Annex C (informative) FC-AL-2 to 10GFC mapping . . . . .</b>	<b>71</b>
C.1 General . . . . .	71
C.2 Overview . . . . .	71
C.3 FC-AL-2 mapping . . . . .	71
C.3.1 General . . . . .	71
C.3.2 Unsupported FC-1 ordered sets . . . . .	71
C.4 Concerns about FC-AL-2 operation . . . . .	71
C.5 Forcing LPSM to Point-to-Point Mode . . . . .	72
<b>Annex D (informative) 8B/10B PCS State Diagrams . . . . .</b>	<b>74</b>

D.1 General . . . . .	74
D.2 Overview . . . . .	74
D.3 Transmit source state diagram . . . . .	74
D.3.1 General . . . . .	74
D.3.2 Send data state . . . . .	74
D.3.3 Transmission errors . . . . .	75
D.3.4 Primitive signal $  P  $ transmission . . . . .	75
D.3.5 Primitive sequence $  Q  $ transmission . . . . .	75
D.3.6 Idle pattern $  I  $ generation . . . . .	75
D.4 PCS receive state diagram . . . . .	76
D.4.1 General . . . . .	76
D.4.2 Reception Error . . . . .	76
D.4.3 Primitive sequence $  Q  $ and primitive signal $  P  $ reception . . . . .	77
D.4.4 Idle pattern reception . . . . .	80
<b>Annex E (normative) XAUI and 8B/10B PCS test patterns . . . . .</b>	<b>81</b>
E.1 general . . . . .	81
E.2 High frequency test pattern . . . . .	81
E.3 Low frequency test pattern . . . . .	81
E.4 Mixed frequency test pattern . . . . .	81
E.5 Continuous jitter test pattern (CJPAT) . . . . .	81
<b>BIBLIOGRAPHY . . . . .</b>	<b>84</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

Table 1	ISO and American Conventions . . . . .	12
Table 2	Data rate abbreviations . . . . .	13
Table 3	Acronyms and other abbreviations (Continued) . . . . .	14
Table 4	Symbols . . . . .	15
Table 5	State diagram operators . . . . .	18
Table 6	1200-MX-SN4P-I PMD type and associated sublayer and clause . . . . .	24
Table 7	SIGNAL_DETECT value definition . . . . .	26
Table 8	Operating range for 1200-MX-SN4P-I over each optical fiber type . . . . .	28
Table 9	Transmit characteristics for the 1200-MX-SN4P-I PMD . . . . .	28
Table 10	Receive characteristics for the 1200-MX-SN4P-I PMD . . . . .	29
Table 11	BERT mask specifications . . . . .	29
Table 12	Applied Sinusoidal Jitter . . . . .	30
Table 13	1200-MX-SN4-I PMD type and associated sublayer and clause . . . . .	34
Table 14	Wavelength-division-multiplexed lane assignments . . . . .	34
Table 15	Transmit characteristics . . . . .	35
Table 16	1200-MX-SN4-I receive characteristics . . . . .	35
Table 17	10GFC Cable Plant Variants . . . . .	40
Table 18	Optical interface, cable plant and link budget (serial and parallel variants) . . . . .	42
Table 19	Optical interface, cable plant and link budget (CWDM variants) . . . . .	43
Table 20	XGMII control characters . . . . .	46
Table 21	Frame delimiters . . . . .	46
Table 22	Primitive signals (standard) . . . . .	48
Table 23	XAUI idle characters . . . . .	48
Table 24	XAUI frame layout . . . . .	49
Table 25	Primitive sequence start . . . . .	53
Table 26	Changing primitive sequence . . . . .	54
Table 27	Ending primitive sequence . . . . .	55
Table 28	Byte lane connections . . . . .	58
Table 29	10GFC and 10GbE XAUI frame layout . . . . .	58
Table 30	XGMII to 8B/10B PCS mapping . . . . .	62
Table 31	8B/10B PCS to XGMII mapping . . . . .	63
Table 32	Ordered sets and special characters . . . . .	64
Table A.1	Optical interface, cable plant and link budget (serial and parallel variants) . . . . .	68
Table A.2	Optical interface, cable plant and link budget (CWDM variants) . . . . .	69
Table C.1	Primitive signals (arbitrated loop) . . . . .	72
Table C.2	Primitive sequences (arbitrated loop) . . . . .	73
Table D.1	Idle pattern generation . . . . .	76
Table D.2	Primitive signal transmission . . . . .	77
Table D.3	Short inter-frame gap . . . . .	78
Table D.4	8B/10B primitive sequence start . . . . .	78
Table D.5	8B/10B continuing primitive sequence . . . . .	79
Table D.6	8B/10B changing primitive sequence . . . . .	79
Table D.7	8B/10B ending primitive sequence . . . . .	80
Table D.8	Minimal frame idle pattern generation . . . . .	80
Table E.1	Continuous jitter test pattern (CJPAT) frame format . . . . .	83

Figure 1 State diagram notation example	16
Figure 2 Fibre channel structure	19
Figure 3 Node functional configuration	20
Figure 4 10GFC physical variant nomenclature	23
Figure 5 Block diagram for one direction of the 1200-MX-SN4P-I PMD signal paths	25
Figure 6 Mask of the sinusoidal component of jitter tolerance (informative)	30
Figure 7 MPO plug and receptacle	39
Figure 8 MPO fiber lane numbering	39
Figure 9 Fiber optic cable plant model	40
Figure 10 XGMII relationship to OSI, 10GbE and 10GFC	45
Figure 11 Byte lane ordering	45
Figure 12 FC-1/10GFC/XGMII Interaction	50
Figure 13 10GFC primitive sequence qualification state diagram	52

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

**INFORMATION TECHNOLOGY –  
FIBRE CHANNEL –  
Part 116: 10 Gigabit Fibre Channel (10GFC)**

**FOREWORD**

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) All users should ensure that they have the latest edition of this publication.
- 4) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 5) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14165-116 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.  
<http://stds.itec.intake.standards.iec.org/716fd430ec71/iso-iec-14165-116-2005>

## INTRODUCTION

The Fibre Channel signalling and physical requirements described in this document cover

- link architecture including retiming (see clause 5)
- physical layer specifications(see clause 6)
- connector performance specifications (see clause 7)
- link and cable plant management specifications (see clause 8)
- FC-1 data path interface (see clause 9)
- optional interconnect interfaces (see clauses 10, 11 and 14)
- transmission coding (see clauses 12 and 13)
- management interface and register set (see clause 15).

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 14165-116:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>

**INFORMATION TECHNOLOGY –  
FIBRE CHANNEL –  
Part 116: 10 Gigabit Fibre Channel (10GFC)**

## 1 Scope

This part of ISO/IEC 14165 describes the signalling and physical requirements that may be utilized by Fibre Channel-2 (FC-2) level transport data at a rate in excess of 10 Gbit/s.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-1-41, *Optical fibres – Part 1-41: Measurement methods and test procedures – Bandwidth*

IEC 60793-1-49, *Optical fibres – Part 1-49: Measurement methods and test procedures – Differential mode delay*

IEC 60793-2, *Optical fibres – Part 2: Product specifications – General*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*

IEC 60825-1:1993, *Safety of laser products – Part 1: Equipment classification, requirements and user's guide, including Amendment 1 (1997) and Amendment 2 (2001)*

IEC 60950-1, *Information technology equipment – Safety – Part 1: General requirements*

IEC 61280-4-1, *Fibre-optic communication subsystem test procedures – Part 4-1: Cable plant and links – Multimode fibre-optic cable plant attenuation measurement*  
<https://standards.iec.ch/catalog/standards/sisu9ac3615a-80a3-4028-bbf3-716f1430e71/iso-iec-14165-116-2005>

IEC 61280-4-2, *Fibre-optic communication subsystem basic test procedures – Part 4-2: Fibre optic cable plant – Single-mode fibre optic cable plant attenuation*

IEC 61300-3-3, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-3: Examinations and measurements – Active monitoring of changes in attenuation and return loss*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61753-1-1, *Fibre optic interconnecting devices and passive components performance standard – Part 1-1: General and guidance – Interconnecting devices (connectors)*

IEC 61753-021-2, *Fibre optic interconnecting devices and passive component performance standard – Part 021-2: Fibre optic connectors terminated on single-mode fibre for category C – Controlled environment*

IEC 61753-022-2, *Fibre optic interconnecting devices and passive components performance standard – Part 022-2: Fibre optic connectors terminated on multimode fibre for category C – Controlled environment*

IEC 61754-7, *Fibre optic connector interfaces – Part 7: Type MPO connector family*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications (also referred to as 10GbE)<sup>1</sup>*

---

<sup>1</sup> Including forthcoming ISO/IEC 8802-3, Amendment 1, *Media Access Control (MAC) Parameters, Physical Layers and Management Parameters for 10 Gbit/s Operation*.

**ITU-T Recommendation G.707, Network node interface for the synchronous digital hierarchy (SDH).**

**ITU-T Recommendation G.709, Interfaces to the Optical Transport Network (OTN).**

### 3 Definitions and conventions

#### 3.1 Definitions

For the purpose of this International Standard the following definition applies:

##### 3.1.1 compliance point

external connector for transmitters and receivers

#### 3.2 Editorial conventions

##### 3.2.1 General

In FC-PI, a number of conditions, mechanisms, sequences, parameters, events, states, or similar terms are printed with the first letter of each word in uppercase and the rest lowercase (e.g., Exchange, Class). Any lowercase uses of these words have the normal technical English meanings.

Numbered items do not represent any priority. Any priority is explicitly indicated.

The ISO convention of numbering is used (i.e., the thousands and higher multiples are separated by a space and a comma is used as the decimal point). A comparison of the American and ISO conventions is shown in table 1.

**Table 1 – ISO and American conventions**

ISO	American
0,6	0.6
1.000	1,000
1 323 462,9	1,323,462.9

In case of any conflict between figure, table and text, the text, then tables, and finally figures take precedence. Exceptions to this convention are indicated in the appropriate subclauses.

In all of the figures, tables, and text of this document, the most significant bit of a binary quantity is shown on the left side. Exceptions to this convention are indicated in the appropriate subclauses.

The term “shall” is used to indicate a mandatory rule. If such a rule is not followed, the results are unpredictable unless indicated otherwise.

If a field or a control bit in a frame is specified as not meaningful, the entity which receives the frame shall not check that field or control bit.

##### 3.2.2 Hexadecimal notation

Hexadecimal notation is used to represent fields. For example, a four-byte Process\_Associator field containing a binary value of 00000000 11111111 10011000 11111010 is shown in hexadecimal format as hex ‘00 FF 98 FA’.

##### 3.2.3 Transmission rate abbreviations

The exact transmission rates are used in the tables and the abbreviated forms are used in text. Note that 3,187 5 gigabaud (GBd) is the preferred ISO method and is used instead of 3 187,5 megabaud (MBd) where it makes sense to do so.

**Table 2 – Data rate abbreviations**

Notation	Notation (FC-FS style)	True signalling rate
3,187 5 GBd	3 187,5 MBd	3 187,5 MBd

**Table 2**

Notation	Notation (FC-FS style)	True signalling rate
10,2 Gb/s	10 200 Mb/s	10 200 Mb/s
10,518 75 GBd	10 518,75 MBd	10 518,75 MBd
12,75 GBd	12 750 MBd	12 750 MBd

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14165-116:2005](https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005)  
<https://standards.iteh.ai/catalog/standards/sist/9ae3615a-80a3-4b28-bbf3-716fd430ec71/iso-iec-14165-116-2005>