

# INTERNATIONAL STANDARD

# ISO/IEC 14776-115

First edition  
2004-11

---

---

**Information technology –  
Small computer system interface (SCSI) –**

**Part 115:  
Parallel Interface-5 (SPI-5)**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14776-115:2004](https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004)

<https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004>



Reference number  
ISO/IEC 14776-115:2004(E)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14776-115:2004](https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004)

<https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004>

# INTERNATIONAL STANDARD

# ISO/IEC 14776-115

First edition  
2004-11

---

---

**Information technology –  
Small computer system interface (SCSI) –  
Part 115:  
Parallel Interface-5 (SPI-5)**  
**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14776-115:2004](https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004)  
<https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004>

© ISO/IEC 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

---

---



PRICE CODE **XG**

*For price, see current catalogue*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14776-115:2004](https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004)

<https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004>

## Contents

	Page
Foreword .....	19
Introduction .....	20
1 Scope .....	21
2 Normative references .....	22
2.1 Normative references .....	22
2.2 Approved references .....	22
2.3 References under development .....	23
2.4 Other references .....	23
3 Definitions, symbols, abbreviations, and conventions .....	23
3.1 Definitions .....	23
3.2 Symbols and abbreviations .....	32
3.3 Keywords .....	33
3.4 Conventions .....	34
3.5 Notation for Procedures and Functions .....	35
4 SCSI parallel interface model .....	36
4.1 SCSI parallel interface model overview .....	36
4.2 Cables, connectors, signals, transceivers .....	36
4.3 Physical architecture of bus segment .....	36
4.4 Driver-receiver connections .....	37
4.5 Physical topology details and definitions .....	37
4.6 Bus segment loading .....	39
4.7 Termination requirements .....	39
4.8 SCSI device Addressing .....	39
4.9 Clocking methods for data transfers .....	40
4.10 Paced transfer on a SCSI bus .....	42
4.11 Data transfers .....	44
4.11.1 Data transfer modes .....	44
4.11.1.1 Asynchronous transfers .....	44
4.11.1.2 Synchronous transfers .....	44
4.11.1.3 Paced transfers .....	44
4.11.2 ST DATA phase parallel transfers .....	44
4.11.3 DT DATA phase parallel transfers .....	45
4.11.3.1 DT DATA phase parallel transfers format .....	45
4.11.3.2 Data group transfers .....	45
4.11.3.3 Information unit transfers .....	45
4.12 Negotiation .....	46
4.12.1 Negotiation introduction .....	46
4.12.2 Negotiation algorithm .....	46
4.12.3 When to negotiate .....	47
4.12.4 Negotiable fields .....	48
4.12.4.1 Negotiable fields introduction .....	48
4.12.4.2 Transfer agreements .....	49
4.12.4.3 Transfer period factor .....	49
4.12.4.4 REQ/ACK offset .....	51
4.12.4.5 Transfer width exponent .....	52
4.12.4.6 Protocol options .....	52
4.12.4.6.1 Protocol options introduction .....	52
4.12.4.6.2 IU_REQ .....	53
4.12.4.6.3 DT_REQ .....	54

4.12.4.6.4 QAS_REQ .....	54
4.12.4.6.5 HOLD_MCS .....	54
4.12.4.6.6 WR_FLOW .....	55
4.12.4.6.7 RD_STRM .....	55
4.12.4.6.8 RTI .....	55
4.12.4.6.9 PCOMP_EN .....	55
4.12.5 Negotiable field combinations .....	56
4.12.6 Message restrictions .....	57
4.12.7 Negotiation message sequences .....	58
4.12.7.1 Negotiation message sequences overview .....	58
4.12.7.2 SCSI initiator port originated PPR negotiation .....	59
4.12.7.3 SCSI initiator port originated WDTR negotiation .....	60
4.12.7.4 SCSI initiator port originated SDTR negotiation .....	62
4.12.7.5 SCSI target port originated WDTR negotiation .....	64
4.12.7.6 SCSI target port originated SDTR negotiation .....	67
4.13 Protocol .....	68
5 SCSI parallel interface connectors .....	71
5.1 SCSI parallel interface connectors overview .....	71
5.2 Non-shielded connector .....	71
5.2.1 Non-shielded connector alternative 1 - A cable .....	71
5.2.2 Non-shielded connector alternative 2 - A cable .....	71
5.2.3 Non-shielded connector alternative 3 - P cable .....	72
5.2.4 Non-shielded connector alternative 4 .....	72
5.3 Shielded connector .....	78
5.3.1 Shielded connector overview .....	78
5.3.2 Shielded connector alternative 1 - A cable .....	78
5.3.3 Shielded connector alternative 2 - A cable .....	78
5.3.4 Shielded connector alternative 3 - P cable .....	78
5.3.5 Shielded connector alternative 4 - P cable .....	78
5.4 Connector contact assignments .....	86
5.4.1 Connector contact assignments overview .....	86
5.4.2 Differential connector contact assignments .....	87
6 SCSI bus segment interconnect .....	90
6.1 SCSI bus segment interconnect overview .....	90
6.2 SCSI bus segment cables .....	90
6.3 Interconnect characteristics for signals .....	91
6.3.1 SCSI bulk cable .....	91
6.3.2 Minimum conductor size for signals .....	92
6.3.3 Local transmission line impedance .....	92
6.3.4 Extended distance transmission line impedance .....	92
6.3.5 Capacitance .....	92
6.3.6 Differential propagation time and propagation time skew .....	92
6.3.7 Differential attenuation .....	92
6.3.8 Crosstalk .....	93
6.4 Decoupling characteristics for TERMPWR lines .....	93
6.5 Connection requirements for RESERVED lines .....	94
6.6 Cables used with LVD transceivers .....	94
6.7 LVD stub length and spacing .....	95
7 SCSI parallel interface electrical characteristics .....	96
7.1 SCSI parallel interface electrical characteristics overview .....	96
7.2 LVD termination .....	96
7.2.1 LVD termination overview .....	96
7.2.2 LVD driver characteristics .....	101
7.2.3 LVD receiver characteristics .....	104

7.2.4 LVD capacitive loads .....	105
7.2.4.1 Management of LVD release glitches .....	107
7.2.5 SE/HVD transmission mode detection .....	109
7.2.5.1 SE/HVD transmission mode detection overview .....	109
7.2.5.2 LVD DIFFSENS driver .....	109
7.2.5.3 LVD DIFFSENS receiver .....	110
7.3 Terminator power .....	112
8 SCSI bus signals .....	114
8.1 SCSI bus signals overview .....	114
8.2 Signal descriptions .....	114
8.3 LVD Signal states .....	117
8.4 OR-tied signals .....	118
8.5 Signal sources .....	118
9 SCSI parallel bus timing .....	120
9.1 SCSI parallel bus timing values .....	120
9.2 Timing description .....	126
9.2.1 Arbitration delay .....	126
9.2.2 ATN transmit setup time .....	127
9.2.3 ATN receive setup time .....	127
9.2.4 Bus clear delay .....	127
9.2.5 Bus free delay .....	127
9.2.6 Bus set delay .....	127
9.2.7 Bus settle delay .....	128
9.2.8 Cable skew .....	128
9.2.9 Chip noise in receiver .....	128
9.2.10 Clock jitter .....	128
9.2.11 Crosstalk time shift .....	128
9.2.12 Flow control receive hold time .....	128
9.2.13 Flow control receive setup time .....	128
9.2.14 Flow control transmit hold time .....	128
9.2.15 Flow control transmit setup time .....	128
9.2.16 Offset induced time asymmetry .....	129
9.2.17 pCRC receive hold time .....	129
9.2.18 pCRC receive setup time .....	129
9.2.19 pCRC transmit hold time .....	129
9.2.20 pCRC transmit setup time .....	129
9.2.21 Data release delay .....	129
9.2.22 DIFFSENS voltage filter time .....	129
9.2.23 Physical disconnection delay .....	129
9.2.24 Power on to selection .....	129
9.2.25 QAS arbitration delay .....	130
9.2.26 QAS assertion delay .....	130
9.2.27 QAS release delay .....	130
9.2.28 QAS non-DATA phase REQ(ACK) period .....	130
9.2.29 Receive assertion period .....	130
9.2.30 Receive hold time .....	130
9.2.31 Receive internal hold time .....	130
9.2.32 Receive internal setup time .....	130
9.2.33 Receive negation period .....	131
9.2.34 Receive setup time .....	131
9.2.35 Receive REQ(ACK) period tolerance .....	131
9.2.36 Receive REQ assertion period with P_CRCA transitioning .....	131
9.2.37 Receive REQ negation period with P_CRCA transitioning .....	131
9.2.38 Receive Skew Compensation .....	131
9.2.39 Receiver amplitude time skew .....	131

9.2.40 Receiver de-skewed data valid window .....	131
9.2.41 REQ(ACK) period .....	132
9.2.42 Reset delay .....	132
9.2.43 Reset hold time .....	132
9.2.44 Reset to selection .....	132
9.2.45 Residual skew error .....	133
9.2.46 Selection abort time .....	133
9.2.47 Selection time-out delay .....	133
9.2.48 Signal timing skew .....	133
9.2.49 Skew correction range .....	133
9.2.50 Strobe offset tolerance .....	134
9.2.51 System deskew delay .....	134
9.2.52 System noise at launch .....	134
9.2.53 System noise at receiver .....	134
9.2.54 Time asymmetry .....	134
9.2.55 Transmit assertion period .....	134
9.2.56 Transmit hold time .....	135
9.2.57 Transmit ISI Compensation .....	135
9.2.58 Transmit negation period .....	135
9.2.59 Transmit setup time .....	135
9.2.60 Transmit REQ(ACK) period tolerance .....	135
9.2.61 Transmit REQ assertion period with P_CRCA transitioning .....	135
9.2.62 Transmit REQ negation period with P_CRCA transitioning .....	135
9.2.63 Transmitter skew .....	135
9.2.64 Transmitter time asymmetry .....	136
9.3 Measurement points .....	136
9.3.1 Measurement points overview .....	136
9.3.2 LVD measurement points .....	137
9.4 Receiver Masks .....	139
9.4.1 Synchronous transfers and for fast-160 paced transfer clocking signals .....	139
9.4.2 Paced transfers with precompensation enabled on fast-160 .....	140
9.4.3 Paced transfers with precompensation disabled on fast-160 and fast-320 .....	142
9.5 Timing parameters .....	148
9.6 Setup and hold timings .....	148
9.6.1 ST data transfer calculations .....	148
9.6.2 DT data transfer calculations .....	149
10 SCSI bus phases .....	151
10.1 SCSI bus phases overview .....	151
10.2 BUS FREE phase .....	151
10.3 Expected and unexpected bus free phases .....	151
10.4 Arbitration .....	152
10.4.1 Arbitration and QAS overview .....	152
10.4.2 NORMAL ARBITRATION phase .....	152
10.4.3 QAS protocol .....	153
10.4.4 QAS phase .....	154
10.5 SELECTION phase .....	155
10.5.1 Selection Overview .....	155
10.5.2 Selection using attention condition .....	156
10.5.2.1 Starting the SELECTION phase when using attention condition .....	156
10.5.2.2 Information unit transfers disabled .....	156
10.5.2.3 Information unit transfers enabled .....	156
10.5.2.4 Selection using attention condition time-out procedure .....	156
10.5.3 Selection without using attention condition .....	157
10.5.3.1 Information unit transfers disabled or enabled .....	157
10.5.3.2 Selection without using attention condition time-out procedure .....	157
10.6 RESELECTION phase .....	158



10.6.1 RESELECTION phase overview .....	158
10.6.2 Physical reconnection .....	158
10.6.3 Physical reconnection time-out procedure .....	159
10.7 Information transfer phases .....	159
10.7.1 Information transfer phases overview .....	159
10.7.2 Asynchronous transfer .....	160
10.7.3 Synchronous transfer .....	161
10.7.3.1 Synchronous transfer overview .....	161
10.7.3.2 ST synchronous transfer .....	161
10.7.3.3 DT synchronous transfer .....	162
10.7.3.3.1 DT synchronous transfer overview .....	162
10.7.3.3.2 Information unit transfer .....	162
10.7.3.3.3 DT DATA IN phase information unit transfer exception condition handling .....	163
10.7.3.3.4 DT DATA OUT phase information unit transfer exception condition handling .....	164
10.7.3.3.5 Data group data field transfer .....	165
10.7.3.3.6 Data Group Pad field and pCRC field transfer to SCSI initiator port .....	165
10.7.3.3.7 Data Group Pad field and pCRC field transfer to SCSI target port .....	167
10.7.4 Paced transfer .....	168
10.7.4.1 Paced transfer overview .....	168
10.7.4.2 Paced transfer training pattern .....	169
10.7.4.2.1 Training pattern overview .....	169
10.7.4.2.2 DT DATA IN phase training pattern .....	170
10.7.4.2.3 DT DATA OUT phase training pattern .....	171
10.7.4.3 P1 data valid/invalid state transitions .....	172
10.7.4.3.1 P1 data valid/invalid state transitions overview .....	172
10.7.4.3.2 Starting pacing transfers at end of training pattern .....	173
10.7.4.3.3 Starting pacing transfers with no training pattern .....	173
10.7.4.3.4 Ending pacing transfers .....	174
10.7.4.4 Paced information unit transfer .....	174
10.7.4.5 Deskewing .....	175
10.7.5 Wide transfer .....	175
10.8 COMMAND phase .....	176
10.8.1 COMMAND phase description .....	176
10.8.2 COMMAND phase exception condition handling .....	176
10.9 DATA phase .....	177
10.9.1 DATA phase overview .....	177
10.9.2 DT DATA IN phase .....	177
10.9.3 DT DATA OUT phase .....	177
10.9.4 ST DATA IN phase .....	177
10.9.5 ST DATA OUT phase .....	177
10.10 STATUS phase .....	177
10.10.1 STATUS phase description .....	177
10.10.2 STATUS phase exception condition handling .....	178
10.11 MESSAGE phase .....	178
10.11.1 MESSAGE phase overview .....	178
10.11.2 MESSAGE IN phase .....	178
10.11.3 MESSAGE IN phase exception condition handling .....	178
10.11.4 MESSAGE OUT phase .....	178
10.11.5 MESSAGE OUT phase exception condition handling .....	179
10.12 Signal restrictions between phases .....	179
11 DATA BUS protection .....	181
11.1 DATA BUS protection overview .....	181
11.2 ST DATA BUS protection using parity .....	181
11.3 DT DATA BUS protection using CRC .....	181
11.3.1 DT DATA BUS protection using CRC overview .....	181
11.3.2 Error detection capabilities .....	181

11.3.3 Order of bytes in the CRC field .....	182
11.3.4 CRC generation and checking .....	184
11.3.5 Test cases .....	184
12 SCSI bus conditions .....	185
12.1 SCSI bus conditions overview .....	185
12.2 Attention condition .....	185
12.3 Bus reset condition .....	186
12.4 Hard reset .....	186
12.5 Reset events .....	187
12.5.1 Reset events overview .....	187
12.5.2 Bus reset event .....	187
12.5.3 Power on reset event .....	187
12.5.4 Target reset event .....	187
13 SCSI bus phase sequences .....	188
13.1 SCSI bus phase sequences overview .....	188
13.2 Phase sequences with information units disabled .....	189
13.2.1 Phase sequences for physical reconnection or selection using attention condition .....	189
13.2.2 Phase sequences for selection without using attention condition .....	190
13.3 Phase sequences with information unit enabled .....	191
13.3.1 Phase sequences for physical reconnection or selection without using attention condition ..	191
13.3.2 Phase sequences for selection using attention condition .....	192
14 SPI information units .....	193
14.1 SPI information unit overview .....	193
14.2 Information unit transfer logical operations .....	193
14.3 SPI information units .....	199
14.3.1 SPI command information unit .....	199
14.3.2 SPI L_Q information unit .....	203
14.3.3 SPI data information unit .....	206
14.3.4 SPI data stream information unit .....	207
14.3.5 SPI status information unit .....	208
15 SCSI pointers .....	212
16 SCSI messages .....	213
16.1 SCSI messages overview .....	213
16.2 Message protocols and formats .....	213
16.2.1 Message protocol rules .....	213
16.2.2 Message formats .....	213
16.2.3 One-byte messages .....	214
16.2.4 Two-byte messages .....	214
16.2.5 Extended messages .....	214
16.3 Link control messages .....	216
16.3.1 Link control message codes .....	216
16.3.2 DISCONNECT .....	217
16.3.3 IDENTIFY .....	217
16.3.4 IGNORE WIDE RESIDUE .....	218
16.3.5 INITIATOR DETECTED ERROR .....	219
16.3.6 LINKED COMMAND COMPLETE .....	219
16.3.7 MESSAGE PARITY ERROR .....	219
16.3.8 MESSAGE REJECT .....	219
16.3.9 MODIFY DATA POINTER .....	220
16.3.10 MODIFY BIDIRECTIONAL DATA POINTER .....	221
16.3.11 NO OPERATION .....	222
16.3.12 PARALLEL PROTOCOL REQUEST .....	222

16.3.13 QAS REQUEST .....	222
16.3.14 RESTORE POINTERS .....	223
16.3.15 SAVE DATA POINTERS .....	223
16.3.16 SYNCHRONOUS DATA TRANSFER REQUEST .....	223
16.3.17 TASK COMPLETE .....	223
16.3.18 WIDE DATA TRANSFER REQUEST .....	224
16.4 Task attribute messages .....	224
16.4.1 Task attribute message overview and codes .....	224
16.4.2 ACA .....	225
16.4.3 HEAD OF QUEUE .....	226
16.4.4 ORDERED .....	226
16.4.5 SIMPLE .....	227
16.5 Task management messages .....	228
16.5.1 Task management message codes .....	228
16.5.2 ABORT TASK .....	228
16.5.3 ABORT TASK SET .....	229
16.5.4 CLEAR ACA .....	229
16.5.5 CLEAR TASK SET .....	229
16.5.6 LOGICAL UNIT RESET .....	229
16.5.7 TARGET RESET .....	230
17 Command processing considerations and exception conditions .....	231
17.1 Command processing considerations and exception conditions overview .....	231
17.2 Asynchronous event notification .....	231
17.3 Incorrect initiator connection .....	231
17.4 Unexpected RESELECTION phase .....	232
18 SCSI management features for the SCSI parallel interface .....	233
18.1 SCSI mode parameters .....	233
18.1.1 SCSI mode parameter overview and codes .....	233
18.1.2 Disconnect-Reconnect mode page .....	234
18.1.3 Logical Unit Control mode page .....	237
18.1.4 Port Control mode page .....	238
18.1.4.1 Port Control mode page overview .....	238
18.1.4.2 Margin Control mode subpage .....	240
18.1.4.3 Saved Training Configuration Values mode subpage .....	242
18.1.4.4 Negotiated Settings mode subpage .....	244
18.1.4.5 Report Transfer Capabilities mode subpage .....	245
19 SCSI parallel interface services .....	246
19.1 SCSI parallel interface services overview .....	246
19.2 Procedure objects .....	246
19.3 Application client SCSI command services .....	247
19.3.1 Application client SCSI command services overview .....	247
19.3.2 Send SCSI command service .....	248
19.4 Device server SCSI command services .....	248
19.4.1 Device server SCSI command services overview .....	248
19.4.2 Data-in delivery service .....	248
19.4.3 Data-out delivery service .....	249
19.5 Task management services .....	249
19.5.1 Task management functions overview .....	249
19.5.2 Task management functions .....	249
19.5.3 ABORT TASK .....	250
19.5.4 ABORT TASK SET .....	250
19.5.5 CLEAR ACA .....	250
19.5.6 CLEAR TASK SET .....	250
19.5.7 LOGICAL UNIT RESET .....	250

19.5.8 RESET SERVICE DELIVERY SUBSYSTEM .....	250
19.5.9 TARGET RESET .....	250
19.5.10 WAKEUP .....	250
Annex A (normative) Additional requirements for LVD SCSI drivers and receivers .....	251
A.1 System level requirements .....	251
A.2 Driver requirements .....	253
A.2.1 Driver requirements overview .....	253
A.2.2 Differential output voltage, VS .....	253
A.2.3 Offset (common-mode output) voltage (VCM) .....	257
A.2.4 Short-circuit currents (IO-S and IO+S) .....	258
A.2.5 Open-circuit output voltages ( $V_{O-(OC)}$ and $V_{O+(OC)}$ ) .....	259
A.2.6 Output signal waveform .....	260
A.2.7 Dynamic output signal balance (VCM(PP) ) .....	261
A.3 Receiver characteristics .....	263
A.3.1 Receiver characteristics overview .....	263
A.3.2 Receiver steady state input voltage requirements .....	263
A.3.2.1 Steady state input voltage requirements for fast-160 and slower receivers .....	263
A.3.2.2 Steady state input voltage requirements for fast-320 receivers .....	263
A.3.3 Compliance test .....	264
A.3.4 Receiver setup and hold times .....	265
A.3.5 Fast-160 receiver bandwidth specifications .....	265
A.4 Transceiver characteristics .....	267
A.4.1 Transceiver output/input currents, II-L and II+L .....	267
A.4.2 Transceiver maximum input voltages .....	267
Annex B (normative) SCSI bus fairness .....	268
B.1 Model .....	268
B.2 Determining fairness by monitoring prior bus activity .....	268
B.2.1 Fairness for normal arbitration method .....	268
B.2.2 Fairness for QAS .....	269
B.3 Fairness algorithm .....	269
B.3.1 Fairness states overview .....	269
B.3.2 Fairness idle state .....	269
B.3.3 Fairness wait state .....	269
B.3.4 Fairness participate state .....	269
B.3.5 Lockout delay .....	269
B.3.6 Mixed arbitration .....	270
B.4 SCSI initiator port fairness recommendations .....	270
Annex C (normative) Non-shielded connector alternative 4 .....	271
C.1 Non-shielded connector alternative 4 signal definitions .....	271
C.2 VOLTAGE and GROUND signals .....	271
C.3 CHARGE signals .....	272
C.4 SPINDLE SYNC .....	272
C.5 ACTIVE LED OUT .....	273
C.6 Motor start controls .....	273
C.7 SCSI ID selection .....	274
C.8 MATED signals .....	275
C.8.1 MATED signals overview .....	275
C.8.2 MATED 2/drive side .....	276
C.8.3 MATED 2/backplane side .....	276
C.8.4 MATED 1/drive side .....	276
C.8.5 MATED 1/backplane side .....	276

Annex D (normative) Removal and insertion of SCSI devices .....	278
D.1 Removal and insertion of SCSI devices overview .....	278
D.2 Case 1 - Power off during removal or insertion .....	278
D.3 Case 2 - RST signal asserted continuously during removal or insertion .....	278
D.4 Case 3 - Current I/O processes not allowed during insertion or removal .....	278
D.5 Case 4 - Current I/O process allowed during insertion or removal .....	279
Annex E (normative) Simple expander requirements .....	280
E.1 Introduction .....	280
E.2 Glossary .....	280
E.3 Bus segments in a SCSI domain .....	280
E.4 Simple bus expanders .....	281
E.5 Homogeneous type .....	282
E.6 Heterogeneous types .....	282
E.7 SCSI domain examples using simple expanders .....	282
E.8 Rules for SCSI domains using simple expanders .....	283
E.8.1 Rule summary .....	283
E.8.2 Rule 1 .....	284
E.8.3 Rule 2 .....	284
E.8.4 Rule 3 .....	285
E.8.5 Rule 4 .....	286
E.8.5.1 Effects of wired-or glitches .....	286
E.8.5.2 Simple expander propagation delay effects .....	286
E.8.5.3 Sample calculations .....	287
E.8.6 Rule 5 .....	288
E.8.7 Rule 6 .....	288
E.9 Special performance considerations for SCSI domains with simple expanders .....	289
Annex F (normative) Expander Communication Protocol .....	292
F.1 Introduction .....	292
F.2 Glossary and Definitions .....	292
F.3 Symbols and abbreviations .....	293
F.4 Enabling ECP .....	293
F.5 Communicative expander function structures .....	293
F.6 Expander functions .....	296
F.6.1 Outbound multiple functions .....	296
F.6.1.1 Outbound multiple function data transfer rules .....	296
F.6.1.2 ASSIGN ADDRESS .....	296
F.6.1.3 MARGIN CONTROL .....	297
F.6.2 Outbound single functions .....	298
F.6.2.1 Outbound single function data transfer rules .....	298
F.6.2.2 CONTROL .....	299
F.6.3 Inbound multiple functions .....	300
F.6.3.1 Inbound multiple function data transfer rules .....	300
F.6.3.2 MARGIN REPORT .....	300
F.6.3.3 REPORT CAPABILITES .....	301
F.6.3.4 REPORT CURRENT STATUS .....	302
F.6.4 Inbound single functions .....	303
F.6.4.1 Inbound single function data transfer rules .....	303
F.6.4.2 EXPANDER INQUIRY .....	304
F.6.4.3 REPORT SAVED TRAINING CONFIGURATION VALUES .....	305
F.7 Data Transfer Requirements .....	307
Annex G (informative) Interconnecting bus segments of different widths .....	308

iTech STANDARD PREVIEW  
(standards.itech.ai)

[ISO/IEC 14776-115:2004](https://standards.itech.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5e-2b6de532437f/iso-iec-14776-115-2004)

<https://standards.itech.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5e-2b6de532437f/iso-iec-14776-115-2004>

[2b6de532437f/iso-iec-14776-115-2004](https://standards.itech.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5e-2b6de532437f/iso-iec-14776-115-2004)

Annex H (informative) SCSI ICONS .....	310
Annex I (informative) Backplane construction guidelines .....	311
I.1 Universal backplane construction .....	311
I.1.1 Universal backplane construction overview .....	311
I.1.2 Microstrip .....	311
I.1.3 Embedded Microstrip .....	311
I.1.4 Stripline .....	312
I.1.5 Dual Stripline .....	313
I.1.6 Differential Impedance .....	314
I.1.7 Single ended impedance .....	315
I.1.8 Differential stripline .....	315
I.1.9 Dielectric material selection .....	318
I.1.10 Vias .....	318
I.1.11 Transmission Lines .....	320
Annex J (informative) SPI-5 to SCSI-2 terminology mapping .....	325
Annex K (informative) Bibliography .....	326

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[ISO/IEC 14776-115:2004](https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004)

<https://standards.iteh.ai/catalog/standards/sist/ded6ed47-ab29-4072-ba5c-2b6dc532437f/iso-iec-14776-115-2004>

## Tables

	Page
1 LVD transceiver/speed support map .....	36
2 Negotiable fields and effects of successful negotiation .....	48
3 Responding message requirements .....	49
4 Transfer agreements .....	49
5 Transfer Period Factor .....	50
6 Transfer Period Factor relationships .....	51
7 REQ/ACK offset .....	52
8 Transfer Width Exponent .....	52
9 Protocol option bits .....	53
10 Bus phases resulting from iu_req changes .....	54
11 Valid negotiable field combinations .....	57
12 Cross-reference to A cable contact assignments .....	86
13 LVD contact assignments - A cable .....	87
14 LVD contact assignments - P cable .....	88
15 LVD contact assignments - non-shielded alternative 4 connector .....	89
16 LVD local transmission line impedance .....	92
17 Bulk cable capacitance limits .....	92
18 Attenuation requirements for SCSI bulk cable .....	93
19 LVD maximum bus segment path length between terminators .....	95
20 Minimum stub connection spacing for LVD SCSI devices .....	95
21 Absolute electrical limits at the device connector .....	96
22 Input current requirements at the device connector for lines not being driven by the device .....	96
23 I-V requirements for differential impedance, common mode impedance, and $V_{BIAS}$ tests .....	99
24 Values for LVD termination balance test .....	101
25 Fast-160 precompensation .....	102
26 Values for LVD capacitive loads .....	107
27 Glitch management requirements for SCSI devices using LVD drivers .....	108
28 LVD DIFFSENS driver specifications .....	109
29 DIFFSENS receiver operating requirements .....	111
30 Terminator power characteristics at the terminator .....	113
31 Arbitration priorities by SCSI ID .....	114
32 P_CRC signal usage requirements .....	116
33 Signal sources .....	119
34 SCSI bus control timing values .....	120
35 SCSI bus data & information phase ST timing values .....	121
36 Miscellaneous SCSI bus data & information phase DT timing values .....	122
37 Transmit SCSI bus data & information phase DT timing values .....	123
38 Receive SCSI bus data & information phase DT timing values .....	124
39 SCSI fast-160 and fast-320 non-compensatable timing budget .....	125
40 SCSI fast-160 and fast-320 interconnect timing budget .....	126
41 Receiver Eye Mask Values .....	143
42 Information transfer phases .....	160
43 Wide SCSI byte order .....	176
44 Parity checking rules for SELECTION and RESELECTION phases .....	181
45 SPI information units .....	193
46 SPI command information unit .....	200
47 TASK ATTRIBUTE .....	201
48 TASK MANAGEMENT FUNCTIONS .....	202
49 SPI L_Q information unit .....	204
50 TYPE .....	205
51 BIDI DIRECTION .....	206
52 SPI data information unit .....	207
53 SPI data stream information unit .....	208
54 SPI status information unit .....	209
55 PACKETIZED FAILURES field .....	210