INTERNATIONAL STANDARD

ISO 17194

First edition 2007-03-15

Structural adhesives — A standard database of properties

Adhésifs structuraux — Base de données des caractéristiques

iTeh STANDARD PREVIEW (standards.iteh.ai)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 17194:2007 https://standards.iteh.ai/catalog/standards/sist/02df5f11-b18e-412b-b7a3-c9278b3ccbf9/iso-17194-2007

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

| Contents | | | |
|------------------------|--|--------|--|
| | eword | | |
| Intro | oduction | v | |
| 1 | Scope | 1 | |
| 2 | Normative references | 1 | |
| 3 | Principle | 2 | |
| 4 | Test specimens | 2 | |
| 5 | Test conditions | 2 | |
| 6 6.1 6.2 6.3 | Test procedures Basic properties Durability in different environments A simple stress analysis | 2 4 | |
| 7 | Precision | 5 | |
| | iographyiTeh STANDARD PREVIEW | 6 | |

ISO 17194:2007 https://standards.iteh.ai/catalog/standards/sist/02df5f11-b18e-412b-b7a3-c9278b3ccbf9/iso-17194-2007

(standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17194 was prepared by Technical Committee ISO/TC 61, Plastics, Subcommittee SC 11, Products.

iTeh STANDARD PREVIEW (standards.iteh.ai)

Introduction

Over recent years, there has been an increase in the use of computer methods for the selection and evaluation of structural adhesives and for assistance with the manufacture and design of joints with these materials. The data sheets from materials suppliers generally do not supply all the property data that are needed to support the application of these methods.

This International Standard specifies a set of basic properties for adhesives commonly required for the use of these materials in a wide range of applications. Test methods and test conditions are recommended for the measurement of the data to enable traceability of presented values. For each property, a single (preferred) test method and specific test conditions are identified in order to improve the comparability of data on different materials generated by different data suppliers.

In selecting the contents for this database, attempts have been made to find a balance in the quantity of data specified. Too much and data suppliers will be reluctant to produce the data, too little and the database has limited value. The aim is therefore not to present a comprehensive list of properties for adhesives but to be selective in identifying the most important properties that are needed for the use of adhesives for different applications. It should be noted that many adhesives have been developed with special properties for a particular application. It is possible that these properties will not be specified in the list associated with this International Standard. However, scope has been included within this standard for the presentation of additional data under test conditions identified by the data supplier. In this way, the special properties of the adhesive can be presented with the basic data.

(standards.iteh.ai)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Structural adhesives — A standard database of properties

1 Scope

This International Standard specifies a set of basic properties commonly required for the selection and use of structural adhesives in different applications. ISO standard test methods and test conditions are also recommended for the measurement of these data to facilitate traceability of recorded values (see Introduction).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 62, Plastics — Determination of water absorption

ISO 527-1:1993, Plastics — Determination of tensile properties — Part 1: General principles

ISO 527-2, Plastics — Determination of tensile properties — Part 2: Test conditions for moulding and extrusion plastics

ISO 171942007

ISO 868, Plastics and ebonite in Determination of indentation hardness by means of a durometer (Shore hardness) c9278b3ccbf9/iso-17194-2007

ISO 1183 (all parts), Plastics — Methods for determining the density of non-cellular plastics

ISO 1817, Rubber, vulcanized — Determination of the effect of liquids

ISO 2555, Plastics — Resins in the liquid state or as emulsions or dispersions — Determination of apparent viscosity by the Brookfield Test method

ISO 2577, Plastics — Thermosetting moulding materials — Determination of shrinkage

ISO 3219, Plastics — Polymers/resins in the liquid state or as emulsions or dispersions — Determination of viscosity using a rotational viscometer with defined shear rate

ISO 4578, Adhesives — Determination of peel resistance of high-strength adhesive bonds — Floating-roller method

ISO 4587, Adhesives — Determination of tensile lap-shear strength of rigid-to-rigid bonded assemblies

ISO 6721-4, Plastics — Determination of dynamic mechanical properties — Part 4: Tensile vibration — Non-resonance method

ISO 6721-5, Plastics — Determination of dynamic mechanical properties — Part 5: Flexural vibration — Non-resonance method

ISO 9142, Adhesives — Guide to the selection of standard laboratory ageing conditions for testing bonded joints

© ISO 2007 – All rights reserved

ISO 10364, Adhesives — Determination of working life (pot life) of multi-component adhesives

ISO 11343, Adhesives — Determination of dynamic resistance to cleavage of high-strength adhesive bonds under impact conditions — Wedge impact method

ISO 11357-2, Plastics — Differential scanning calorimetry (DSC) — Part 2: Determination of glass transition temperature

ISO 11359-2, Plastics — Thermomechanical analysis (TMA) — Part 2: Determination of coefficient of linear thermal expansion and glass transition temperature

ISO 15166-1, Adhesives — Methods of preparing bulk specimens — Part 1: Two-part systems

ISO 15166-2, Adhesives — Methods of preparing bulk specimens — Part 2: Elevated-temperature-curing one-part systems

ISO 17212, Structural adhesives — Guidelines for the surface preparation of metals and plastics prior to adhesive bonding

IEC 60093, Methods of test for volume resistivity and surface resistivity of solid electrical insulating materials

IEC 60243-1, Electrical strength of insulating materials — Test methods — Part 1: Tests at power frequencies

3 Principle

iTeh STANDARD PREVIEW

A list is presented of properties that are generally useful for the selection and application of structural adhesives. Recommended test methods and test conditions are given for each property to help in the determination of values and to promote the presentation of traceable and comparable data.

ISO 17194:2007

https://standards.iteh.ai/catalog/standards/sist/02df5f11-b18e-412b-b7a3-c9278b3ccbf9/iso-17194-2007

4 Test specimens

Where possible, use the test specimens recommended in the test method standards employed to measure the properties given in Tables 1, 2 and 3. If alternative test methods are used, the test method reference shall be recorded with the results. The preparation of test specimens shall be as specified in ISO 17212 for joint specimens and ISO 15166-1 or ISO 15166-2 for bulk specimens. Since the properties of adhesives generally depend on the concentration of absorbed water, specimens shall be stored dry or in an atmosphere of $(50 \pm 10) \%$ RH at $(23 \pm 2) ^{\circ}$ C prior to testing, for a sufficient time to reach zero or equilibrium water content as indicated by no significant further changes in the mass of the specimen with storage time.

5 Test conditions

Where possible, use the test conditions specified for each property in Tables 1, 2 and 3. If alternative test conditions are used, these shall be recorded with the results.

6 Test procedures

6.1 Basic properties

Test methods and test conditions recommended for the acquisition of data for basic properties are given in Table 1. The measurement temperature is (23 ± 2) °C. For measurements obtained at other temperatures, record the temperature with the result.

Table 1 — Basic properties at 23 °C

Record cure temperature, cure time, post-cure temperature and post-cure time used for specimen preparation. Record also whether specimens have been stored dry or at 50 % RH prior to testing.

| Property | Units | Test method | Additional conditions | |
|--|-------------------|---|---|--|
| Tensile modulus | GPa | ISO 527-2 | | |
| Stress at failure | MPa | | See Note 1. | |
| Strain at failure | % | | | |
| Yield stress | MPa | | See Note 2. | |
| Yield strain | % | | OCC NOIC 2. | |
| Lap shear strength | MPa | ISO 4587 | Record thickness of adhesive layer. Record adherend material and surface treatment (see ISO 17212). | |
| T-peel strength | MPa | ISO 4578 | Record adherend material and surface treatment (see ISO 17212). | |
| Impact resistance | kN/m | ISO 11343 See Note 3 | Use symmetrical wedge. | |
| Hardness | Shore A or D | ISO 868 | 3 s duration. | |
| Glass transition temperature | °C | ISO 11357-2 | | |
| Dynamic mechanical modulus vs temperature (DMTA) curve | h STANI | ISO 6721-4 or AISO 6721-5 | From – 40 °C to above T_g . | |
| Thermal expansion coefficient | (stand | arks:113597a.a | Record values at 23 $^{\circ}$ C and at a temperature above $T_{\rm g}$. | |
| Service temperature range | °C IS | 0 17 See Note 4 | | |
| Viscosity https://stand | | standS0:25552rl5fl1 cbf9/idS0732492007 | Record shear strain rate and time under load if the adhesive is thixotropic. | |
| Working life | min | ISO 10364 | | |
| Volume change during cure | % | ISO 2577 | | |
| Density | kg/m ³ | ISO 1183 | | |
| Water absorption | % | ISO 62 | Saturation value at (23 ± 2) °C. | |
| Volume resistivity | ohm⋅m | IEC 60093 | | |
| Electric strength | kV/mm | IEC 60243-1 | Use a specimen with a thickness of the adhesive layer of 0,5 mm. See Note 5. | |

- NOTE 1 Strain at failure for ductile materials is measured after yield and therefore requires the measurement of a nominal strain. The nominal strain is derived from measurements of grip separation instead of extensometer values. See ISO 527-1:1993, Subclauses 4.5 and 9.5, for the definition and measurement of nominal strain.
- NOTE 2 See ISO 527-1:1993, Subclauses 4.3.1 and 4.4.1, for definitions of stress and strain at yield.
- NOTE 3 A wider interest in the toughness of an adhesive relates to a knowledge of the temperature of the transition from ductile to brittle behaviour. This temperature can be derived from measurements of toughness, using the cleavage test ISO 11343, as a function of temperature. Related information can be obtained from measurements of ductility at different temperatures using tests for fracture energy under impact (ISO 179-1 and ISO 179-2) or strain at failure in tensile tests on bulk specimens (ISO 527).
- NOTE 4 The service temperature range will be determined by the criteria used to decide maximum and minimum operating temperatures. Generally, the upper temperature is decided by the glass transition temperature $T_{\rm g}$ and the lower temperature by the transition from ductile to brittle behaviour. This lower temperature limit can be determined from measurements of toughness or ductility with temperature (see Note 3).
- NOTE 5 The measured value of electric strength is very dependent on the thickness of the adhesive layer.