

SLOVENSKI STANDARD
SIST EN 300 175-3 V2.5.1:2013

01-oktober-2013

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 3.
del: Plast krmiljenja dostopa do prenosnega medija (MAC)**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part
3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [SIST EN 300 175-3 V2.5.1:2013](https://standards.iteh.ai/catalog/standards/sist/35cd5a2-8262-4b98-a7e1-efcf42e93094/sist-en-300-175-3-v2-5-1-2013)
<https://standards.iteh.ai/catalog/standards/sist/35cd5a2-8262-4b98-a7e1-efcf42e93094/sist-en-300-175-3-v2-5-1-2013>

ICS:

33.070.30 Digitalne izboljšane Digital Enhanced Cordless
 brezvrvične telekomunikacije Telecommunications (DECT)
 (DECT)

SIST EN 300 175-3 V2.5.1:2013 en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 300 175-3 V2.5.1:2013

<https://standards.iteh.ai/catalog/standards/sist/35cf55a2-8262-4b98-a2e1-efcf42e93094/sist-en-300-175-3-v2-5-1-2013>

ETSI EN 300 175-3 v2.5.1 (2013-08)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer

[SIST EN 300 175-3 V2.5.1:2013](#)
<https://standards.iteh.ai/catalog/standards/sist/35cf55a2-8262-4b98-a2e1-efcf42e93094/sist-en-300-175-3-v2-5-1-2013>

Reference

REN/DECT-000268-3

Keywords

DECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA***ETSI***650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)[SIST EN 300 175-3 V2.5.1:2013](#)<https://standards.iteh.ai/catalog/standards/sist/35cf55a2-8262-4b98-a2e1-efc42e930470?version=v2-5-1-2013>Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	14
Foreword	14
1 Scope	15
2 References	15
2.1 Normative references	15
2.2 Informative references	16
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols and abbreviations	17
4 Description of the MAC layer	20
4.1 MAC layer reference model	20
4.1.1 General	21
4.1.2 Cluster Control Function (CCF)	21
4.1.3 Cell Site Functions (CSF)	21
4.1.4 Relationship to physical layer elements	21
4.2 Frame and multiframe structures	22
4.2.1 General	22
4.2.2 Frame structure	22
4.2.3 Multiframe structure	24
4.3 State definitions	24
4.3.1 PP states	24
4.3.2 RFP states	25
5 Overview of MAC layer services	26
5.1 General	26
5.1.1 Broadcast Message Control (BMC)	26
5.1.2 Connectionless Message Control (CMC)	26
5.1.3 Multi-Bearer Control	26
5.2 Service descriptions	26
5.2.1 Common functions	26
5.2.2 BMC service	27
5.2.3 CMC service	27
5.2.4 MBC services	27
5.3 Logical channels	28
5.3.1 MBC connection endpoints (MC-SAP logical channels)	28
5.3.1.1 The higher layer C-plane channels, C	28
5.3.1.2 The higher layer U-Plane channels, I	29
5.3.1.3 The higher layer U-Plane control channels, G _F and G _{FA}	29
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF}	29
5.3.2 CMC endpoints (MB-SAP logical channels)	30
5.3.2.1 The connectionless C-Plane channels, CL	30
5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P	30
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF}	30
5.3.3 BMC endpoint (MA-SAP logical channel)	30
5.3.3.1 The slow broadcast channel, B _S	30
5.3.3.2 The ULE broadcast channel, B _U	31
5.3.4 Internal MAC control channels	31
5.3.4.1 The system information channel, Q	31
5.3.4.2 Identities channel, N	31
5.3.4.3 The MAC control channel, M	31
5.3.4.4 MAC paging channel, P	32
5.3.4.5 The Compound System Information Channel, Q _C	32
5.3.4.6 The Split Identities Channel, N _S	32
5.3.4.7 The ULE MAC Control Channel, M _U	32

5.3.4.8	The ULE Paging Channel, P _U	32
5.4	SAP definitions	32
5.4.1	MA SAP	33
5.4.2	MB SAP	33
5.4.3	MC SAP	33
5.4.4	ME SAP	34
5.4.5	Order of transmission.....	34
5.5	Bearers.....	34
5.5.1	Bearer types	34
5.5.2	Bearer operation.....	35
5.6	Connection oriented services.....	35
5.6.1	Connection types	35
5.6.1.1	Basic connections.....	36
5.6.1.2	Advanced connections	36
5.6.1.2.1	Rules for ECN selection in advanced connections	36
5.6.1.2.2	Expedited operations in advanced connections	37
5.6.1.3	Connection identifiers	37
5.6.1.4	Complementary connections.....	37
5.6.2	Symmetric and asymmetric connections.....	37
5.6.2.1	Symmetric connections	38
5.6.2.2	Asymmetric connections	43
5.7	Broadcast and connectionless services.....	54
5.7.1	The broadcast services	54
5.7.1.1	The continuous broadcast service	54
5.7.1.2	The non-continuous broadcast service	55
5.7.2	The connectionless services	55
5.7.2.1	Connectionless downlink services	55
5.7.2.2	Connectionless uplink services	55
5.8	ULE Broadcast services	56
5.8.1	The continuous ULE broadcast service.....	56
6	Multiplexing	56
6.1	CCF multiplexing functions ds.itech.ai/catalog/standards/sist/25cf55a2-8262-4b98-a2e1-ef-f12e93094/sist.en.300-175.3.v2.5.1-2013	56
6.2	CSF multiplexing functions ds.itech.ai/catalog/standards/sist/25cf55a2-8262-4b98-a2e1-ef-f12e93094/sist.en.300-175.3.v2.5.1-2013	57
6.2.1	Bit Mappings (MAP)	62
6.2.1.1	D-field mapping (D-MAP).....	62
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	63
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	64
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	64
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	65
6.2.1.2	A-field Mapping (A-MAP)	66
6.2.1.3	B-field Mapping (B-MAP).....	67
6.2.1.3.1	Unprotected format.....	67
6.2.1.3.2	Encoded protected format.....	69
6.2.1.3.3	Multisubfield protected format.....	69
6.2.1.3.4	Singlesubfield protected format switches	72
6.2.1.3.5	Constant-size subfield protected format	73
6.2.2	Time multiplexers	76
6.2.2.1	Tail MULTipleXer (T-MUX)	76
6.2.2.1.1	T-MUX algorithm for RFP transmissions	76
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	78
6.2.2.2	B-field control multiplexer (E/U-MUX)	78
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes	80
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield	80
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation	94
6.2.2.4	Priority scheme in E or E+U mode	95
6.2.3	MAC Encryption	96
6.2.4	Scrambling.....	96
6.2.5	Error control.....	98
6.2.5.1	R-CRC overview	98
6.2.5.2	R-CRC generation and checking.....	99
6.2.5.3	X-CRC overview.....	99

6.2.5.4	X-CRC generation and checking.....	99
6.2.5.5	B-CRC generation and checking.....	102
6.2.6	Broadcast controller.....	102
7	Medium access layer messages	102
7.1	Header field.....	103
7.1.1	Overview/formatting.....	103
7.1.2	Tail identification, TA, bits a_0 to a_2	103
7.1.3	The "Q1/BCK" bit, bit a_3	103
7.1.4	B-field identification, BA, bits a_4 to a_6	104
7.1.5	The "Q2" bit, bit a_7	105
7.2	Messages in the tail field	105
7.2.1	Overview	105
7.2.2	Identities information (N_T).....	106
7.2.3	System information and multiframe marker (Q_T).....	106
7.2.3.1	General.....	106
7.2.3.2	Static system information.....	107
7.2.3.2.1	General, $Q_H = 0, 1$ (hex)	107
7.2.3.2.2	Q_H and Normal-Reverse (NR)	107
7.2.3.2.3	Slot Number (SN).....	107
7.2.3.2.4	Start Position (SP)	108
7.2.3.2.5	ESCAPE bit (ESC)	108
7.2.3.2.6	Number of transceivers.....	108
7.2.3.2.7	Extended RF carrier information available (Mc).....	109
7.2.3.2.8	RF carriers available (RF-cars).....	109
7.2.3.2.9	Spare bits (SPR)	109
7.2.3.2.10	Carrier number.....	109
7.2.3.2.11	Extended static system information available (Ext-System-Info) and spare bit	110
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	110
7.2.3.3	Extended RF carrier information part.....	110
7.2.3.3.1	General, $Q_H = 2$ (hex)	110
7.2.3.3.2	Further RF carrier extensions.....	111
7.2.3.3.3	Number of RF carriers.....	111
7.2.3.4	Fixed part capabilities.....	111
7.2.3.4.1	General, $Q_H = 3$ (hex)	111
7.2.3.4.2	Standard capabilities.....	111
7.2.3.5	Extended fixed part capabilities	113
7.2.3.5.1	General, $Q_H = 4$ (hex)	113
7.2.3.5.2	Extended Physical and MAC layer capabilities.....	113
7.2.3.5.3	Extended higher layer capabilities.....	114
7.2.3.6	Secondary access rights identities	114
7.2.3.6.1	General, $Q_H = 5$ (hex)	114
7.2.3.6.2	SARI message	114
7.2.3.7	Multiframe number	115
7.2.3.7.1	General, $Q_H = 6$ (hex)	115
7.2.3.7.2	Multiframe number	115
7.2.3.8	Escape	115
7.2.3.8.1	General, $Q_H = 7$ (hex)	115
7.2.3.8.2	Escape information	115
7.2.3.9	Extended RF carrier information part 2	115
7.2.3.9.1	General, $Q_H = 9$ (hex)	115
7.2.3.10	Transmit information	116
7.2.3.10.1	General, $Q_H = B$ (hex)	116
7.2.3.11	Extended fixed part capabilities (part 2)	117
7.2.3.11.1	General, $Q_H = C$ (hex)	117
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2).....	117
7.2.3.11.3	Extended higher layer capabilities (part 2)	118
7.2.3.12	Extended static system information	118
7.2.3.12.1	General, $Q_H = D$ (hex)	118
7.2.3.12.2	Spare bits (Spare)	118
7.2.3.12.3	RFP slot scheme info	118
7.2.4	Paging Tail (P_T)	119

7.2.4.1	General format	119
7.2.4.1.1	P _T format for full and long page messages	119
7.2.4.1.2	P _T format for short page messages	119
7.2.4.1.3	P _T format for zero length page messages	119
7.2.4.1.4	P _T format for MAC_Resume_and_Control_page message	119
7.2.4.2	P _T header format.....	120
7.2.4.2.1	General format.....	120
7.2.4.2.2	Bit a ₈ is the extend flag.....	120
7.2.4.2.3	B _S SDU length indication	120
7.2.4.3	MAC layer information for PT.....	121
7.2.4.3.1	Information type	121
7.2.4.3.2	Fill bits / Blind long slot (j=640 / j=672) information	121
7.2.4.3.3	Blind full slot information	122
7.2.4.3.4	Bearer description.....	122
7.2.4.3.5	Escape.....	123
7.2.4.3.6	Dummy or connectionless downlink bearer marker	123
7.2.4.3.7	Bearer handover/replacement and no-emission mode information	123
7.2.4.3.8	RFP status and modulation types.....	124
7.2.4.3.9	Active carriers	125
7.2.4.3.10	RFP power level	125
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	126
7.2.4.3.12	Extended modulation types	126
7.2.5	MAC control (M _T)	127
7.2.5.1	General format and contents	127
7.2.5.2	Basic connection control	127
7.2.5.2.1	General	127
7.2.5.2.2	Format for most messages.....	128
7.2.5.2.3	WAIT	128
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}.....	128
7.2.5.3	Advanced connection control.....	129
7.2.5.3.1	General	129
7.2.5.3.2	ACCESS_REQUEST	129
7.2.5.3.3	BEARER_HANDOVER REQUEST.....	129
7.2.5.3.4	CONNECTION_HANDOVER REQUEST	129
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST	130
7.2.5.3.6	BEARER_CONFIRM	130
7.2.5.3.7	WAIT	130
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}	130
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}	133
7.2.5.3.10	Channel_list.....	133
7.2.5.3.11	Unconfirmed_dummy.....	134
7.2.5.3.12	Unconfirmed_handover	134
7.2.5.3.13	RELEASE	134
7.2.5.4	MAC layer test messages	135
7.2.5.4.1	Basic format	135
7.2.5.4.2	FORCE_TRANSMIT	136
7.2.5.4.3	LOOPBACK_DATA	136
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY	137
7.2.5.4.5	ESCAPE	138
7.2.5.4.6	NETWORK_TEST.....	138
7.2.5.4.7	CLEAR_TEST_MODES.....	138
7.2.5.4.8	CHANGE_MODULATION_SCHEME	138
7.2.5.5	Quality control	139
7.2.5.5.1	Prolonged preamble diversity	140
7.2.5.6	Broadcast and connectionless services	141
7.2.5.7	Encryption control.....	141
7.2.5.8	B-field setup, first PT transmission.....	142
7.2.5.9	Escape	143
7.2.5.10	TARI message	143
7.2.5.11	REP connection control.....	143
7.2.5.11.1	General	143
7.2.5.11.2	Format for most messages	143

7.2.5.11.3	REP CHANNEL MAP REQUEST	144
7.2.5.11.4	REP CHANNEL MAP CONFIRM	144
7.2.5.12	Advanced connection control part 2	144
7.2.5.12.1	General	144
7.2.5.12.2	Short description of the advanced connection control part 2 messages	144
7.2.5.12.3	Format for most advanced connection control part 2 messages	145
7.2.5.12.4	Format for "ready for release with G _{FA} " and "expedited release with G _{FA} " messages	145
7.2.5.12.5	Reason codes in "ready for release with G _{FA} " and "expedited release with G _{FA} " messages	146
7.2.5.12.6	Format for "Null or GFchannel transmission" message	148
7.3	Messages in the B-field	148
7.3.1	Overview	148
7.3.2	Advanced connection control	150
7.3.2.1	General format	150
7.3.2.2	BEARER_REQUEST	150
7.3.2.3	BEARER_CONFIRM	151
7.3.2.4	WAIT	151
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}	151
7.3.2.6	BANDWIDTH_B_{Req;Cfm}	152
7.3.2.7	CHANNEL_LIST	153
7.3.2.8	UNCONFIRMED_DUMMY	153
7.3.2.9	UNCONFIRMED_HANDOVER	153
7.3.2.10	RELEASE	153
7.3.3	Null or I _{PF} segmentation info	155
7.3.3.1	Spare or I _{PF} segmentation info	156
7.3.3.2	Extended NCF bits	156
7.3.4	Quality control	157
7.3.4.1	General format	157
7.3.4.2	Bearer and connection control	157
7.3.4.3	RESET	159
7.3.4.4	Bearer quality in an asymmetric connection	159
7.3.5	Extended system information	160
7.3.5.1	General format	160
7.3.5.2	TARI messages	160
7.3.5.3	"no-emission" mode sync information or ULE Dummy Bearer subfield 2	160
7.3.5.3.1	"no-emission" mode sync information for dummy bearer	160
7.3.5.3.2	ULE Dummy Bearer subfield 2	161
7.3.5.4	ULE Dummy Bearer subfield 3	161
7.3.5.5	ULE Dummy Bearer subfield 0	161
7.3.5.6	ULE Dummy Bearer subfield 1	162
7.3.6	G _F channel data packet	162
7.3.7	Escape	163
8	Medium access layer primitives	163
8.1	Connection oriented service primitives	163
8.1.1	Connection setup: MAC_CON {req;ind;cfm}	163
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}	165
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}	166
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}	166
8.1.5	Restart DLC: MAC_RES_DLC {ind}	166
8.1.6	Connection release: MAC_DIS {req;ind}	167
8.1.7	MAC bandwidth: MAC_BW {ind;res}	167
8.1.8	Encryption	167
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}	167
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}	168
8.1.9	C-plane switching procedure	168
8.1.9.1	C-plane switching procedure: MAC_C _S _C _F {req, cfm, ind, res}	168
8.1.9.2	C-plane switching procedure: MAC_C _S C _F _END {ind}	168
8.2	Connectionless and broadcast service primitives	169
8.2.1	Paging: MAC_PAGE {req;ind}	169
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}	169
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}	170

8.2.4	"no-emission" mode.....	170
8.3	Management primitives	170
8.3.1	Connection control.....	170
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	170
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}	170
8.3.1.3	Bearer release: MAC_ME_REL {req}	170
8.3.1.4	MBC release report: MAC_ME_REL_REPORT {ind}	171
8.3.2	System information and identities	171
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}	171
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}	171
8.3.2.3	System information output: MAC_ME_INFO {ind;res}	171
8.3.2.4	Extended system info: MAC_ME_EXT. {req;ind;res;cfm}	171
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}	171
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}	172
8.3.5	Error reports: MAC_ME_ERROR {ind;res}	172
8.4	Flow control	172
8.4.1	MA SAP flow control	172
8.4.2	MB SAP flow control	172
8.4.3	MC SAP flow control	172
9	Broadcast and connectionless procedures	175
9.1	Downlink broadcast and connectionless procedures	175
9.1.1	Downlink broadcast procedure	175
9.1.1.1	Broadcast information.....	175
9.1.1.2	Channel selection for downlink broadcast services.....	175
9.1.1.3	Downlink broadcast procedure description.....	177
9.1.2	Downlink connectionless procedure	177
9.1.2.1	Channel selection at the RFP.....	177
9.1.2.2	Downlink connectionless procedure description.....	177
9.1.3	Paging broadcast procedure.....	177
9.1.3.1	RFP paging broadcasts.....	178
9.1.3.2	PP paging procedures.....	180
9.1.3.2.1	PP paging detection https://standards.iteh.ai/catalog/standards/sist/35cf55a2-8262-4b98-a2c1-052e93094/sist-en-300-175-3-v2.5.1-2013	180
9.1.3.2.2	PP paging processing https://standards.iteh.ai/catalog/standards/sist/35cf55a2-8262-4b98-a2c1-052e93094/sist-en-300-175-3-v2.5.1-2013	180
9.2	Uplink connectionless procedures	180
9.2.1	General.....	180
9.2.2	Bearer selection for the connectionless uplink.....	181
9.2.3	Procedure for the connectionless uplink	181
9.2.3.1	Predicates	181
9.2.3.2	PT D-field construction.....	181
9.2.3.3	PT transmission sequence	182
9.2.3.4	FT procedure	182
9.3	Non-continuous broadcast procedure	183
9.3.1	Request for specific Q channel information.....	183
9.3.1.1	A-field procedure	183
9.3.1.2	B-field procedure	183
9.3.2	Request for a new dummy bearer	184
9.4	"No-emission" mode procedures	184
9.4.1	Initiation of the "no-emission" mode	184
9.4.1.1	Successful activation (countdown to zero).....	184
9.4.1.2	Multiframe countdown stopped by FT	185
9.4.1.3	Multiframe countdown stopped by PT	185
9.4.1.4	PT does not receive multiframe countdown "zero"	186
9.4.2	Behaviour during power-down-mode	186
9.4.3	Waking up, FT initiated	186
9.4.4	Waking up, PT initiated	190
9.5	Ultra Low Energy (ULE) Mode Procedures.....	191
9.5.1	Initiation of the ULE Mode	191
9.5.1.1	ULE Dummy Bearer Subfield 0	192
9.5.1.2	ULE Dummy Bearer Subfield 1	192
9.5.1.3	ULE Dummy Bearer Subfield 2	193
9.5.1.3.1	M _U Channel Info 1 coding	194

9.5.1.3.2	M _U Channel Info 2 coding.....	194
9.5.1.4	ULE Dummy Bearer Subfield 3.....	194
9.5.1.5	Broadcast/Paging Channels.....	195
10	Connection oriented service procedures.....	196
10.1	Overview	196
10.2	C/O connection setup	196
10.2.1	General.....	196
10.2.2	Initiation of a basic and a normal connection setup	197
10.2.3	Initiation of a fast connection setup	197
10.2.4	Connection setup procedure description	197
10.2.4.1	Creation of MBCs	197
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	199
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation.....	200
10.2.4.3.1	Symmetric connection	202
10.2.4.3.2	Asymmetric uplink connection.....	202
10.2.4.3.3	Asymmetric downlink connection.....	202
10.2.4.3.4	Connection established	203
10.2.5	Expedited connections	203
10.3	C/O connection modification	203
10.3.1	Advanced connection: bandwidth modification.....	203
10.3.1.1	Suspend and resume.....	205
10.3.1.1.1	Expedited suspend and resume.....	205
10.3.1.2	MAC resume paging	205
10.3.1.3	ULE resume paging	206
10.3.2	Advanced connection: service type or slot type modification	206
10.3.2.1	Procedure for service type modification	206
10.3.2.2	Procedures for slot type modification	207
10.3.2.2.1	Procedure for slot type modification full to double	207
10.3.2.2.2	Procedure for slot type modification double to full	208
10.3.2.2.3	Procedures for slot type modification to/from long	208
10.3.2.2.4	Procedure for slot type modification in multibearer connections	208
10.3.2.3	Procedure for ECN number modification in an advanced connection	209
10.3.3	Connection type modification	209
10.3.3.1	Procedure for connection type modification basic to advanced	210
10.3.3.1.1	General procedure	210
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double	210
10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long	211
10.3.3.2	Procedure for connection type modification advanced to basic	211
10.3.4	Modulation type modification	211
10.3.4.1	Adaptive code rate	213
10.4	C/O connection release	213
10.4.1	General.....	213
10.4.1.1	C/O connection release in packet mode connections	214
10.4.2	Procedure description	214
10.5	C/O bearer setup.....	214
10.5.1	Single bearer setup procedures	214
10.5.1.1	Basic bearer setup procedure	215
10.5.1.2	A-field advanced single bearer setup procedure	217
10.5.1.2.1	PT initiated	217
10.5.1.2.2	FT initiated	220
10.5.1.3	B-field single bearer setup procedure	221
10.5.1.3.1	PT initiated	221
10.5.1.3.2	FT initiated	223
10.5.1.4	Double simplex setup procedure	223
10.5.1.4.1	Terminology and Predicates	223
10.5.1.4.2	General description.....	224
10.5.1.4.3	Channel selection procedure for circuit mode connections	225
10.5.1.4.4	Channel selection procedure for packet mode connections	225
10.5.1.4.5	Indirect setup procedure	226

10.5.1.4.6	Direct setup procedure	227
10.5.1.4.7	Handling of encrypted connections	230
10.5.1.5	Complementary connection bearer setup	231
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure	232
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	233
10.5.1.7.1	Default rules for TA code "111"	233
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission"	234
10.5.1.8	Expedited bearer setup procedures	234
10.5.1.8.1	General	234
10.5.1.8.2	Procedure for Single-burst setup and release	235
10.5.1.8.3	Procedure for Multi burst setup	236
10.5.1.8.4	Announcement "Ready for Release"	238
10.5.1.8.5	Indirect FT initiated expedited bearer setup procedure	239
10.5.1.8.6	Insertion of U-plane in "Expedited access request" messages	239
10.5.1.8.7	Connected state (TBC) in expedited bearer setup	239
10.5.1.8.8	Encryption synchronization in expedited bearer setup	240
10.5.1.8.9	Use of short slots in expedited connections	240
10.5.2	Channel list procedures	241
10.5.2.1	General	241
10.5.2.2	Description of the channel list messages	241
10.5.2.3	Usage of the channel list messages	242
10.6	C/O bearer handover	243
10.6.1	General	243
10.6.2	Duplex bearer handover procedure	244
10.6.3	Double simplex bearer handover	244
10.6.4	Bearer replacement	245
10.6.4.1	General bearer replacement	245
10.6.4.2	Frequency replacement	245
10.7	C/O bearer release	247
10.7.1	General	247
10.7.2	Bearer release procedure description	247
10.7.2.1	Unacknowledged release procedure	247
10.7.2.1.1	Crossed bearer release procedure	248
10.7.2.2	Acknowledged release procedure	248
10.7.2.3	Fast release procedure	248
10.7.2.4	REP relayed bearer release	249
10.7.3	Expedited bearer release procedures	249
10.7.3.1	General Expedited Release procedure	249
10.7.3.1.1	Procedure description	249
10.7.3.1.2	Exceptional cases and error handling	250
10.7.3.2	Special cases of expedited release procedures	251
10.7.3.2.1	Single-message expedited release procedure	251
10.7.3.2.2	Abnormal expedited release procedure	251
10.8	C/O data transfer	251
10.8.1	Higher layer associated signalling (C)	251
10.8.1.1	C _S channel data	251
10.8.1.1.1	Transmission principle	252
10.8.1.1.2	Numbering principle	252
10.8.1.2	C _F channel data	252
10.8.1.2.1	Transmission principle	253
10.8.1.2.2	Numbering principle	253
10.8.1.3	Q1 and Q2 bit settings for all services except I _{P_error_correct}	253
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I _N	253
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I _{P_error_detect}	254
10.8.1.3.3	Q2 bit settings	254
10.8.1.3.4	Q1 bit settings	255
10.8.1.3.5	Q1 and Q2 settings when B-field is in E-mux modes	256
10.8.1.3.6	Q1 and Q2 settings when B-field is in "no-B-field" mode	257
10.8.1.3.7	Q1, Q2 and BCK settings when there are transitions in the coding rules or when the rules applicable to both directions are not the same	258
10.8.1.3.8	Q1 and Q2 settings when B-field mode is unknown	258

10.8.2	MOD-2 protected I channel operation (I_p).....	258
10.8.2.1	General	258
10.8.2.1.1	Use of selective reception	259
10.8.2.2	Limiting the lifetime of packets	259
10.8.2.2.1	Lifetime setting and management	259
10.8.2.3	A-field shall always be correct	261
10.8.2.4	Use of the acknowledge bits	261
10.8.2.4.1	Q2 and BCK bit setting for I_p _error_correction services	261
10.8.2.4.2	BCK bit setting	262
10.8.2.5	Data jump procedures	262
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement	262
10.8.2.5.2	Unilateral jump	262
10.8.2.5.3	MAC I_p bearer reset	264
10.8.2.6	Bearer handover and bearer replacement procedures	264
10.8.2.6.1	General	264
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel	264
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel	265
10.8.2.7	Exchange of data from/to higher layers	265
10.8.2.7.1	Operation if I_{PF} channel is supported	266
10.8.3	Higher layer unprotected information (I_N) and MAC_error_detection services (I_p).....	266
10.8.3.1	I_N _minimum_delay service (I_{NA})	266
10.8.3.2	I_N _normal_delay service (I_{NB})	266
10.8.3.3	I_p _error_detection service	267
10.8.3.3.1	Operation if I_{PF} channel is supported	267
10.8.3.4	I_p _encoded_protected service (I_{PX})	267
10.8.4	Higher layer U-plane channel (I_{PF}) in E+U type mux	267
10.8.4.1	Purpose of the I_{PF} channel	267
10.8.4.2	Activation of the E+U type mux mode	268
10.8.4.3	I_{PF} procedures	268
10.8.4.3.1	I_{PF} basic procedures	268
10.8.4.3.2	I_{PF} advanced procedures	269
10.8.4.3.3	Special case: slots not multiple of 64 bits	269
10.8.4.4	I_{PF} Mod-2 protected operation	270
10.8.4.5	I_{PF} _error_detect operation	270
10.8.4.6	I_{PF} _operation with I_N service	270
10.8.4.7	Backcompatibility rule	271
10.9	C/O procedures for FT connections with CRFP	271
10.9.1	Dual C/O bearer setup	271
10.9.2	C/O connection release of connection with CRFP	271
10.9.3	C/O connection suspend and resume	271
11	Medium access layer management procedures	272
11.1	Broadcasting	272
11.1.1	RFP transmission	272
11.1.2	PP reception	272
11.2	Extended system information	272
11.2.1	PP requests	272
11.2.2	RFP response	272
11.3	PP states and state transitions	272
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states	272
11.3.2	Entry into the Idle_Locked state	273
11.3.3	Actions in the Idle_Locked state	273
11.3.3.1	Page detection in Idle_Locked state	273
11.3.3.2	Setup detection in Idle_Locked state	274
11.3.4	Idle_Locked and Active_Locked state transitions	275
11.4	Physical channel selection	275
11.4.1	The channel selection lists	275
11.4.2	Physical channel and RFP selection at the PP	277
11.4.3	Physical channel selection at the RFP	278
11.4.4	Hand over criteria due to in-connection base identification	280
11.4.5	Handover criteria due to interference	280

11.4.6	Exception in channel selection rules for Ultra Low Energy devices	281
11.5	In-connection quality control	281
11.5.1	RFPI handshake	281
11.5.2	Frequency control	281
11.5.2.1	RFP measurement of frequency error	281
11.5.2.2	PT frequency correction	281
11.6	Maximum allowed system load at RFPs	281
11.7	PMID and FMID definitions	281
11.7.1	FMID definition.....	281
11.7.2	PMID definition.....	282
11.7.2.1	'X'PMID definition.....	282
11.8	RFP idle receiver scan sequence	282
11.9	PT receiver scan sequence	283
11.10	Management of connections associated with Broadband data links.....	283
11.11	Management procedures for "no-emission" mode.....	283
11.11.1	Behaviour during "no-emission" mode.....	284
11.12	Physical channel selection procedures for DECT Ultra Low Energy (ULE)	284
11.12.1	General.....	284
11.12.2	Overall architecture of ULE channel selection processes	284
11.12.3	Process M0 (RFP side pre-selection process).....	285
11.12.4	Broadcast mechanism	285
11.12.5	Process M1 (PP side channel selection process).....	286
11.12.6	Setup attempt and evaluation of responses	287
11.12.7	Process M2 (collision handling/collision avoidance process).....	288
11.12.7.1	Equations.....	289
11.12.7.2	Algorithm.....	289
12	Medium access layer test message procedure..... iTeh STANDARD PREVIEW (standards.iteh.ai)	289
12.1	Introduction	289
12.2	General	290
12.2.1	Portable part testing	291
12.2.2	Fixed part testing	291
12.2.3	Applicability of test messages https://standards.iteh.ai/catalog/standards/sist/35cf55a2-8262-4b98-a2c1-ef142e93094/sist-en-300-175-3-v2.5.1-2013	291
12.3	FORCE_TRANSMIT	292
12.3.1	Portable part.....	292
12.3.2	Fixed part.....	292
12.4	LOOPBACK_DATA	293
12.4.1	Portable part.....	293
12.4.2	Fixed Part.....	293
12.4.2.1	IUTs implementing the DECT scrambler	293
12.4.2.2	IUTs implementing a proprietary scrambler	293
12.5	DEFEAT_ANTENNA_DIVERSITY	293
12.6	NETWORK_TEST	294
12.7	ESCAPE	294
12.8	CLEAR_TEST_MODES	294
12.9	CHANGE_MODULATION_SCHEME	294
Annex A (normative):	MAC layer timers and constants	295
A.1	Timers and Time Windows	295
A.2	Constants	295
A.2.1	Constants for the ULE channel selection algorithms	296
Annex B (informative):	Construction of the CRC polynomial and error detecting performance	297
Annex C (informative):	MAC relationship to other layers.....	298
Annex D (informative):	Synchronization	299
Annex E (normative):	Scrambling patterns	300
Annex F (informative):	Seamless handover operation	301

F.1	I channel data flow for I _N _minimum_delay service	301
Annex G (normative):	Requirements for PPs with direct PP to PP communication mode.....	302
G.1	Description of operation in direct PP to PP communication mode	302
G.2	Requirements.....	303
G.2.1	Setting the PP in direct communications mode	303
G.2.2	Specific Alternative 1 requirements	303
G.2.2.1	When the PP has not initiated a call.....	303
G.2.2.2	When the PP initiates a call	303
G.2.3	Specific Alternative 2 Requirements.....	304
Annex H (normative):	Requirements for FPs with Wireless FT to FT (W-FT2FT) communication mode.....	305
H.1	Introduction	305
H.2	Description of operation in W-FT2FT communication mode	306
Annex I (normative):	Channel coding and Modulation	307
I.1	Channel coding.....	308
I.1.1	The parallel Turbo Code Principle	308
I.1.2	The FOCTC implementation.....	308
I.1.2.1	The FOCTC concept.....	308
I.1.2.2	The FOCTC structure and the component code.....	309
I.1.2.3	The FOCTC Inner interleaving algorithm	311
I.1.2.4	FOCTC Inner interleaving size adaptation to all Physical Packet Formats	312
I.2	Adaptive coding and Modulation Embodiment.....	314
I.2.1	Adaptive code rates	314
I.2.1.1	Adaptive code rates for the double slot structure (physical packet P80)	315
I.2.1.2	Adaptive code rates for the full slot structure (physical packet P32).....	316
I.2.1.3	Adaptive code rates for the half slot structure (physical packet P00j with j=80).....	316
I.2.2	Puncturing patterns.....	317
I.2.3	Channel Capacity for the B-field map configurations.....	318
I.2.3.1	Double Slot Structure.....	318
I.2.3.2	Full Slot Structure	319
I.2.3.3	Half Slot Structure	320
I.3	Change Modulation Scheme	320
I.4	B-Field Binary Interleaving.....	320
I.4.1	General description.....	320
I.4.2	Mathematical Description	322
I.4.2.1	L(k) Expression	322
I.4.2.2	Interleaving Spreading ΔL(s) Expression	323
I.4.3	B-field binary interleaving parameters	324
I.4.3.1	Physical packet Format P80 (double slot structure).....	324
I.4.3.2	Physical packet Format P32 (full slot structure).....	325
I.4.3.3	Physical packet Format P00j with j=80 (Half-Slot structure)	325
Annex J (informative):	Channel decoding.....	326
Annex K (informative):	Additional information on MAC messages.....	327
K.1	Historic use of some MAC service codes.....	327
Annex L (informative):	Bibliography.....	328
Annex M (informative):	Change history	329
History	330	