



**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 8: Speech and audio coding and transmission**

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard: https://standards.iteh.ai/catalog/standards/etsi/en-300-175-8-130408
https://standards.iteh.ai/catalog/standards/etsi/en-300-175-8-130408

ReferenceREN/DECT-000268-8

Keywords

7 kHz, audio, broadband, codec, DECT, handsfree, IMT-2000, loudspeaking, mobility, narrowband, quality, radio, speech, TDD, TDMA, telephony, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	11
Foreword.....	11
1 Scope	12
2 References	12
2.1 Normative references	12
2.2 Informative references.....	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions.....	15
3.2 Symbols and abbreviations.....	16
4 Configurations.....	18
4.1 Reference configuration	18
4.1.1 Basic configuration	18
4.1.2 Portable Part (PP)	19
4.1.2.1 Functional organization.....	19
4.1.2.2 Volume control	20
4.1.3 Fixed Part (FP).....	20
4.1.3.1 Digital interface.....	20
4.1.3.2 Analog interface	21
4.1.3.3 FP adaptive volume control	22
4.2 Test configurations	22
5 Encoding.....	22
5.1 32 kbit/s full term (ADPCM) G.726.....	22
5.1.1 Algorithm.....	22
5.1.2 Bit sequence.....	22
5.1.3 Characteristics of G.726 ADPCM codec	22
5.2 64 kbit/s PCM G.711.....	23
5.2.1 Algorithm.....	23
5.2.2 Bit sequence.....	23
5.2.3 Characteristics of G.711 PCM codec	23
5.2.4 Automatic detection of FAX/modem tone and switch to G.711	23
5.3 Wideband speech codec G.722 at 64 kbit/s.....	24
5.3.1 Algorithm.....	24
5.3.2 Bit sequence.....	24
5.3.3 Characteristics of G.722 wideband codec.....	24
5.3.4 Optional Packet Loss Concealment algorithm (PLC).....	24
5.4 Wideband speech codec G.729.1 up to 32 kbit/s.....	25
5.4.1 Algorithm.....	25
5.4.2 Bit sequence.....	25
5.4.3 Characteristics of G.729.1 codec	25
5.4.4 Packet Loss Concealment algorithm (PLC).....	25
5.4.5 Supported bit rate in DECT	26
5.5 Super-wideband MPEG-4 speech and audio coding	26
5.5.1 Algorithm.....	26
5.5.2 64 kbit/s, MPEG-4 ER AAC-LD codec.....	26
5.5.3 32 kbit/s, MPEG-4 ER AAC-LD codec.....	27
5.6 Other codings	27
6 Transmission aspects.....	27
6.1 Relative level.....	27
6.2 Acoustic reference level	27
6.3 Volume control.....	27
7 Audio specifications	28
7.1 Overall description	28
7.1.1 Introduction to DECT audio specifications	28
7.1.2 Introduction to the audio types	28

7.1.3	List of Audio types	29
7.1.4	Audio types for Portable Parts	29
7.1.5	Audio types for Fixed Parts	30
7.1.6	Complete DECT system	30
7.1.7	Structure of the specification of the audio types	31
7.1.8	Audio Types and codecs	37
7.1.9	Audio Types and physical interfaces	37
7.2	Audio types applicable to Portable Parts	37
7.2.1	Performance levels of DECT Portable Parts (handsets).....	37
7.2.2	Type 0: Reference PP (RePP).....	38
7.2.3	PP Type 1a: "Classic" GAP narrowband handset	38
7.2.3.1	Introduction.....	38
7.2.3.2	Compatible services and codecs.....	39
7.2.3.3	Specification.....	39
7.2.4	PP Type 1b: "Improved" GAP narrowband handset.....	39
7.2.4.1	Introduction.....	39
7.2.4.2	Compatible services and codecs.....	39
7.2.4.3	Specification.....	39
7.2.5	PP Type 1c: HATS-tested "standard" narrowband handset	39
7.2.5.1	Introduction.....	39
7.2.5.2	Compatible services and codecs.....	40
7.2.5.3	Specification.....	40
7.2.6	PP Type 1d: HATS-tested "improved" narrowband handset	40
7.2.6.1	Introduction.....	40
7.2.6.2	Compatible services and codecs.....	40
7.2.6.3	Specification.....	40
7.2.7	PP Type 3a: HATS tested narrowband "standard" loudspeaking handsfree	40
7.2.7.1	Introduction.....	40
7.2.7.2	Compatible services and codecs.....	41
7.2.7.3	Specification.....	41
7.2.8	PP Type 3b: HATS tested narrowband "improved" loudspeaking handsfree	41
7.2.8.1	Introduction.....	41
7.2.8.2	Compatible services and codecs.....	41
7.2.8.3	Specification.....	41
7.2.9	PP Type 2a: P.311-tested wideband handset.....	41
7.2.9.1	Introduction.....	41
7.2.9.2	Compatible services and codecs.....	41
7.2.9.3	Specification.....	42
7.2.10	PP Type 2b: HATS-tested "standard" wideband handset or headset	42
7.2.10.1	Introduction.....	42
7.2.10.2	Compatible services and codecs.....	42
7.2.10.3	Specification.....	42
7.2.11	PP Type 2c: HATS tested "improved" wideband handset or headset	42
7.2.11.1	Introduction.....	42
7.2.11.2	Compatible services and codecs.....	42
7.2.11.3	Specification.....	43
7.2.12	PP Type 4a: HATS tested wideband "standard" loudspeaking handsfree	43
7.2.12.1	Introduction.....	43
7.2.12.2	Compatible services and codecs.....	43
7.2.12.3	Specification.....	43
7.2.13	PP Type 4b: HATS tested wideband "improved" loudspeaking and handsfree	43
7.2.13.1	Introduction.....	43
7.2.13.2	Compatible services and codecs.....	44
7.2.13.3	Specification.....	44
7.2.14	PP Type 5a: super-wideband 14 kHz handset.....	44
7.2.14.1	Introduction.....	44
7.2.14.2	Compatible services and codecs.....	44
7.2.14.3	Specification.....	44
7.2.15	PP Type 5b: super-wideband 14 kHz loudspeaking handsfree	44
7.2.15.1	Introduction.....	44
7.2.15.2	Compatible services and codecs.....	44
7.2.15.3	Specification.....	44

7.2.16	PP Type 6: PPs with external 2 wire, 3,1 kHz telephony interface.....	44
7.2.16.1	Introduction.....	44
7.2.16.2	Compatible services and codecs.....	44
7.2.16.3	Specification.....	45
7.3	Audio transmission types applicable to Fixed Parts.....	45
7.3.1	FP Type 0: Reference FP (ReFP).....	45
7.3.2	FP Type 1a: "classical" Fixed Part for ISDN Network.....	46
7.3.2.1	Introduction.....	46
7.3.2.2	Compatible services and codecs.....	46
7.3.2.3	Specifications.....	46
7.3.2.3.1	Transcoding and equalization.....	46
7.3.2.3.2	PP type detection.....	47
7.3.2.3.3	Activation of audio processing functions.....	47
7.3.2.3.4	Transmission specification.....	47
7.3.3	FP Type 1b: "new" Fixed Part for ISDN Network.....	47
7.3.3.1	Introduction.....	47
7.3.3.2	Compatible services and codecs.....	47
7.3.3.3	Specification.....	48
7.3.3.3.1	Transcoding and equalization.....	48
7.3.3.3.2	PP type detection.....	48
7.3.3.3.3	Activation of audio processing functions.....	48
7.3.3.3.4	Transmission specification.....	49
7.3.4	FP Type 2: FP with analog 2-wire interface, 3,1 kHz service.....	49
7.3.4.1	Introduction.....	49
7.3.4.2	Compatible services, physical interfaces and codecs.....	49
7.3.4.3	Specification.....	49
7.3.4.3.1	Transcoding, equalization and conversion.....	49
7.3.4.3.2	PP type detection and activation of audio processing functions.....	49
7.3.4.3.3	Transmission specification.....	50
7.3.5	FP Type 3: VoIP narrowband Fixed Part.....	50
7.3.5.1	Introduction.....	50
7.3.5.2	Compatible services, physical interfaces and codecs.....	50
7.3.5.3	Specification.....	51
7.3.5.3.1	Transcoding and equalization.....	51
7.3.5.3.2	PP type detection.....	51
7.3.5.3.3	Activation of audio processing functions.....	51
7.3.5.3.4	Transmission specification.....	52
7.3.6	FP Type 4: ISDN wideband Fixed Part.....	52
7.3.6.1	Introduction.....	52
7.3.6.2	Compatible services and codecs.....	52
7.3.6.3	Specification.....	52
7.3.6.3.1	Transcoding and equalization.....	52
7.3.6.3.2	PP type detection.....	52
7.3.6.3.3	Activation of audio processing functions.....	53
7.3.6.3.4	Transmission specification.....	53
7.3.7	FP Type 5: VoIP wideband Fixed Part.....	53
7.3.7.1	Introduction.....	53
7.3.7.2	Compatible services, physical interfaces and codecs.....	53
7.3.7.3	Specification.....	54
7.3.7.3.1	Transcoding and equalization.....	54
7.3.7.3.2	PP type detection.....	54
7.3.7.3.3	Activation of audio processing functions.....	54
7.3.7.3.4	Transmission specification.....	55
7.3.8	FP Type 6a: FP handling an Internal call inside a DECT FP (any service).....	55
7.3.8.1	Introduction.....	55
7.3.8.2	Compatible services, physical interfaces and codecs.....	55
7.3.8.3	Specification.....	55
7.3.9	FP Type 6b: FP handling an n-party conference inside a DECT FP (any service).....	55
7.3.9.1	Introduction.....	55
7.3.9.2	Compatible services, physical interfaces and codecs.....	56
7.3.9.3	Specification for the conference bridge.....	56
7.3.10	FP Type 7: DECT Repeater part (REP).....	56

7.3.10.1	Introduction.....	56
7.3.10.2	Compatible services, physical interfaces and codecs.....	56
7.3.10.3	Specification.....	56
7.4	Additional features.....	56
7.4.1	Introduction.....	56
7.4.2	Echo canceller in Fixed Part.....	57
7.4.3	Echo suppressor in Fixed Part.....	57
7.5	Transmission characteristics for Portable Parts.....	58
7.5.1	Transmission characteristics for Portable Part type 1a ("Classic GAP" handset).....	58
7.5.1.1	PP frequency responses.....	58
7.5.1.1.1	Sending.....	58
7.5.1.1.2	Receiving.....	59
7.5.1.2	PP sending and receiving loudness ratings.....	59
7.5.1.2.1	Nominal values.....	59
7.5.1.2.2	User-controlled volume control in PP.....	59
7.5.1.2.3	PP adaptive volume control.....	60
7.5.1.3	Sidetone.....	60
7.5.1.3.1	Talker sidetone.....	60
7.5.1.3.2	Listener sidetone.....	60
7.5.1.4	Terminal coupling loss.....	61
7.5.1.4.1	Weighted Terminal Coupling Loss (TCLw).....	61
7.5.1.4.2	Stability loss.....	61
7.5.1.5	Distortion.....	61
7.5.1.5.1	Sending.....	61
7.5.1.5.2	Receiving.....	61
7.5.1.5.3	Sidetone.....	62
7.5.1.6	Out of band signals.....	62
7.5.1.6.1	Sending (discrimination against out of band input signals).....	62
7.5.1.6.2	Receiving (spurious out of band signals).....	62
7.5.1.7	Noise.....	62
7.5.1.7.1	Sending.....	62
7.5.1.7.2	Band-limited noise.....	62
7.5.1.7.3	Receiving.....	62
7.5.1.7.4	Level of sampling frequency (receiving).....	62
7.5.1.8	Acoustic shock.....	63
7.5.1.8.1	Continuous signal.....	63
7.5.1.8.2	Peak signal.....	63
7.5.1.9	PP Delay.....	63
7.5.1.10	PP ambient noise rejection.....	63
7.5.2	Additional requirements for PP type 1b ("improved GAP" handset).....	63
7.5.2.1	Terminal coupling loss.....	63
7.5.2.1.1	Weighted Terminal Coupling Loss (TCLw).....	63
7.5.2.2	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	63
7.5.2.3	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	64
7.5.2.4	Activation in Sending Direction.....	64
7.5.2.5	Activation in Receiving Direction.....	65
7.5.3	Transmission characteristics for PP types 1c and 1d (HATS tested, narrowband telephony handsets).....	65
7.5.3.1	PP frequency responses.....	65
7.5.3.1.1	Sending.....	65
7.5.3.1.2	Receiving.....	66
7.5.3.2	PP sending and receiving loudness ratings.....	68
7.5.3.2.1	Nominal values.....	68
7.5.3.2.2	User-controlled volume control in PP.....	69
7.5.3.2.3	PP adaptive volume control.....	69
7.5.3.3	Sidetone.....	70
7.5.3.3.1	Talker sidetone.....	70
7.5.3.3.2	D Factor.....	70
7.5.3.3.3	Sidetone delay.....	70
7.5.3.4	Terminal coupling loss.....	70
7.5.3.4.1	TCLw of Portable Part.....	70
7.5.3.4.2	Stability loss.....	71
7.5.3.5	Distortion.....	71

7.5.3.5.1	Sending Distortion.....	71
7.5.3.5.2	Receiving Distortion.....	71
7.5.3.6	Out of band signals.....	72
7.5.3.6.1	Out-of-Band Signals in Send direction.....	72
7.5.3.6.2	Out-of-band signals in receiving direction	72
7.5.3.7	Noise	72
7.5.3.7.1	Sending.....	72
7.5.3.7.2	Receiving.....	72
7.5.3.8	Acoustic shock.....	73
7.5.3.8.1	Continuous signal.....	73
7.5.3.8.2	Peak signal.....	73
7.5.3.9	Delay.....	73
7.5.3.10	Variation of gain with input level-sending.....	73
7.5.3.11	Double Talk Performance	74
7.5.3.11.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	74
7.5.3.11.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	74
7.5.3.11.3	Detection of Echo Components during Double Talk.....	75
7.5.3.11.4	Minimum activation level and sensitivity of double talk detection.....	75
7.5.3.12	Switching characteristics.....	75
7.5.3.12.1	Activation in Sending Direction.....	75
7.5.3.12.2	Activation in Receiving Direction.....	76
7.5.3.12.3	Silence Suppression and Comfort Noise Generation.....	76
7.5.3.12.4	Performance in sending direction in the presence of background noise.....	76
7.5.3.12.5	Speech Quality in the Presence of Background Noise.....	76
7.5.3.12.6	Quality of Background Noise Transmission (with Far End Speech).....	77
7.5.3.12.7	Quality of background noise transmission (with Near End Speech).....	77
7.5.3.13	Quality of echo cancellation.....	77
7.5.3.13.1	Temporal echo effects	77
7.5.3.13.2	Spectral Echo Attenuation.....	77
7.5.4	Transmission characteristics for PP types 3a and 3b (narrowband loudspeaking and handsfree devices).....	78
7.5.4.1	Sending sensitivity/frequency response.....	78
7.5.4.2	Receive sensitivity/frequency response.....	78
7.5.4.3	Sending loudness rating.....	81
7.5.4.4	Receive loudness rating.....	81
7.5.4.5	Sending distortion.....	82
7.5.4.6	Receiving distortion.....	82
7.5.4.7	Out-of-band signals in sending direction.....	82
7.5.4.8	Out-of-band signals in receiving direction.....	83
7.5.4.9	Sending noise.....	83
7.5.4.10	Receiving noise.....	83
7.5.4.11	Terminal Coupling Loss of PP.....	84
7.5.4.12	Stability Loss of PP.....	84
7.5.4.13	Double Talk Performance	84
7.5.4.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	84
7.5.4.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	85
7.5.4.13.3	Detection of Echo Components during Double Talk.....	85
7.5.4.13.4	Minimum activation level and sensitivity of double talk detection.....	86
7.5.4.14	Switching characteristics.....	86
7.5.4.14.1	Activation in Sending Direction.....	86
7.5.4.14.2	Activation in Receiving Direction.....	86
7.5.4.14.3	Silence Suppression and Comfort Noise Generation.....	86
7.5.4.14.4	Performance in sending direction in the presence of background noise.....	87
7.5.4.14.5	Speech Quality in the Presence of Background Noise.....	87
7.5.4.14.6	Quality of Background Noise Transmission (with Far End Speech).....	87
7.5.4.14.7	Quality of background noise transmission (with Near End Speech).....	87
7.5.4.15	Quality of echo cancellation.....	87
7.5.4.15.1	Temporal echo effects	88
7.5.4.15.2	Spectral Echo Attenuation.....	88
7.5.5	Transmission characteristics for PP type 2a (P.311 tested, wideband handset).....	88
7.5.5.1	Sending characteristics.....	88
7.5.5.1.1	Loudness rating.....	88

7.5.5.1.2	Sensitivity/frequency characteristics	88
7.5.5.1.3	Noise.....	89
7.5.5.1.4	Distortion.....	89
7.5.5.1.5	Discrimination against out-of-band input signals	89
7.5.5.2	Receiving characteristics.....	89
7.5.5.2.1	Loudness rating	89
7.5.5.2.2	Sensitivity/frequency characteristics	89
7.5.5.2.3	Noise.....	89
7.5.5.2.4	Distortion.....	90
7.5.5.2.5	Spurious out-of-band receiving signals	90
7.5.5.3	Sidetone characteristics.....	90
7.5.5.3.1	Talker sidetone	90
7.5.5.3.2	Sidetone distortion.....	90
7.5.5.4	Echo path loss characteristics.....	90
7.5.5.4.1	Weighted terminal coupling loss	90
7.5.5.4.2	Stability loss	91
7.5.6	Transmission characteristics for PP type 2b and 2c (HATS tested wideband handsets)	91
7.5.6.1	PP frequency responses.....	91
7.5.6.1.1	Sending.....	91
7.5.6.1.2	Receiving.....	92
7.5.6.2	PP send and receive loudness ratings	94
7.5.6.2.1	Nominal values.....	94
7.5.6.2.2	User-controlled volume control in PP	95
7.5.6.2.3	PP adaptive volume control.....	95
7.5.6.3	Sidetone.....	95
7.5.6.3.1	Talker sidetone	95
7.5.6.3.2	D Factor	96
7.5.6.3.3	Sidetone delay	96
7.5.6.4	Terminal coupling loss.....	96
7.5.6.4.1	Weighted Terminal Coupling Loss (TCL _w).....	96
7.5.6.4.2	Stability loss	96
7.5.6.5	Distortion	97
7.5.6.5.1	Sending Distortion.....	97
7.5.6.5.2	Receiving Distortion.....	97
7.5.6.6	Noise	97
7.5.6.6.1	Sending.....	97
7.5.6.6.2	Receiving.....	98
7.5.6.7	Acoustic shock.....	98
7.5.6.7.1	Continuous signal.....	98
7.5.6.7.2	Peak signal.....	98
7.5.6.8	Delay.....	98
7.5.6.9	Variation of gain with input level-sending.....	98
7.5.6.10	Double talk Performance.....	99
7.5.6.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	99
7.5.6.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	100
7.5.6.10.3	Detection of Echo Components during Double Talk.....	100
7.5.6.10.4	Minimum activation level and sensitivity of double talk detection.....	100
7.5.6.11	Switching characteristics.....	100
7.5.6.11.1	Activation in Sending Direction	101
7.5.6.11.2	Activation in Receiving Direction.....	101
7.5.6.11.3	Silence Suppression and Comfort Noise Generation.....	101
7.5.6.11.4	Performance in Sending in the Presence of Background Noise.....	101
7.5.6.11.5	Speech Quality in the Presence of Background Noise.....	102
7.5.6.11.6	Quality of Background Noise Transmission (with Far End Speech).....	102
7.5.6.11.7	Quality of background noise transmission (with Near End Speech)	102
7.5.6.12	Quality of echo cancellation.....	102
7.5.6.12.1	Temporal echo effects	102
7.5.6.12.2	Spectral Echo Attenuation.....	103
7.5.7	Transmission characteristics for PP types 4a and 4b (HATS Tested wideband loudspeaking and handsfree devices).....	103
7.5.7.1	Sending sensitivity/frequency response	103
7.5.7.2	Receive sensitivity/frequency response.....	104

7.5.7.3	Sending loudness rating	107
7.5.7.4	Receive loudness rating.....	107
7.5.7.5	Sending distortion	108
7.5.7.6	Receiving distortion	108
7.5.7.7	Out-of-band signals in sending direction	109
7.5.7.8	Out-of-band signals in receiving direction	109
7.5.7.9	Sending noise	109
7.5.7.10	Receiving noise	109
7.5.7.11	Terminal Coupling Loss.....	110
7.5.7.12	Stability Loss.....	110
7.5.7.13	Double Talk Performance	110
7.5.7.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	111
7.5.7.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	111
7.5.7.13.3	Detection of Echo Components during Double Talk.....	111
7.5.7.13.4	Minimum activation level and sensitivity of double talk detection	112
7.5.7.14	Switching characteristics.....	112
7.5.7.14.1	Activation in Sending Direction	112
7.5.7.14.2	Activation in Receiving Direction	112
7.5.7.14.3	Silence Suppression and Comfort Noise Generation.....	113
7.5.7.14.4	Performance in sending direction in the presence of background noise	113
7.5.7.14.5	Speech Quality in the Presence of Background Noise.....	113
7.5.7.14.6	Quality of Background Noise Transmission (with Far End Speech).....	113
7.5.7.14.7	Quality of background noise transmission (with Near End Speech)	113
7.5.7.15	Quality of echo cancellation.....	114
7.5.7.15.1	Temporal echo effects	114
7.5.7.15.2	Spectral Echo Attenuation.....	114
7.6	Transmission characteristics for Fixed Parts	114
7.6.1	Transmission characteristics for FP type 1a ("Classic" Fixed Part with ISDN Network interface, 3,1 kHz service)	114
7.6.1.1	Reduction of echo from PP	114
7.6.1.2	FP Network echo control	115
7.6.1.3	FP adaptive volume control	116
7.6.1.4	FP Delay.....	116
7.6.2	Transmission characteristics for FP type 1b ("new" Fixed Part with ISDN Network interface, 3,1 kHz service)	116
7.6.2.1	FP Network echo control	116
7.6.2.2	FP adaptive volume control	116
7.6.2.3	FP Delay.....	117
7.6.3	Transmission characteristics for FP type 2 (Fixed Part with analog 2-wire interface, 3,1 kHz service)... ..	117
7.6.3.1	FP adaptive volume control	117
7.6.3.2	Network echo control	117
7.6.3.3	Additional requirements for DECT FP provided with a 2-wire PSTN interface.....	118
7.6.3.3.1	General	118
7.6.3.3.2	Speech performance characteristics.....	118
7.6.3.4	FP Delay.....	119
7.6.4	Transmission characteristics for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service)	119
7.6.4.1	Send delay	119
7.6.4.2	Receive delay	119
7.6.4.3	Adaptive volume control.....	120
7.6.5	Transmission characteristics for FP type 4 (Fixed Part with ISDN network interface, wideband service).....	120
7.6.5.1	FP adaptive volume control	120
7.6.5.2	FP Delay.....	120
7.6.6	Transmission characteristics for FP type 5 (Fixed Part with VoIP interface, wideband service)	120
7.6.6.1	Send Delay	120
7.6.6.2	Receive delay	121
7.6.6.3	FP adaptive volume control	121
8	Additional features	121
8.1	Loudspeaking hands-free and headset facilities	121
8.1.1	Loudspeaking hands-free facility.....	121
8.1.2	Headset facility	121

8.2	Tandem with mobile radio network.....	121
8.2.1	Tandem with GSM	122
8.2.1.1	Network echo control.....	122
8.2.1.2	Terminal coupling loss.....	122
8.2.1.3	The GSM mobile transmitter operates in continuous mode.....	122
8.2.1.4	The GSM mobile transmitter operates in discontinuous mode, DTX.....	122
8.3	DECT connected to the GSM fixed network.....	122
8.3.1	Network echo control.....	123
8.3.2	Terminal coupling loss.....	123
8.4	Wireless Relay Stations (WRS).....	123
8.4.1	Modified FP network echo control requirements for implementation of 2 and 3 CRFP links in cascade.....	124
Annex A (informative): Description of "reference" echo control devices.....		125
A.1	Handset echo	125
A.1.1	Overview	125
A.1.1.1	Connection to the PSTN/ISDN.....	125
A.1.1.1.1	Local and national calls.....	125
A.1.1.1.2	Long distance connections with echo control devices in the PSTN/ISDN, e.g. calls via satellites.....	125
A.1.1.2	Connection to the GSM network	126
A.1.2	Implementation of the FP echo control function	126
A.1.2.1	Suppression threshold.....	127
A.1.2.2	Static characteristics of activation control	127
A.1.2.3	Dynamic characteristics of activation control.....	127
A.2	Network echo	127
A.2.1	Soft suppressor implementation of requirement 2.....	128
A.2.1.1	Static characteristics	129
A.2.1.2	Dynamic characteristics.....	129
A.2.2	Additional echo control for a 2-wire interface of requirement 1.....	129
A.2.3	Echo canceller used for both requirements 1 and 2.....	130
Annex B (informative): Local loop application.....		131
B.1	DECT tethered local loop replacement with 2-wire PP end system.....	131
B.1.1	TCLw requirements.....	131
B.1.2	Network echo	132
Annex C (informative): GSM Discontinuous Transmission (DTX), and Voice Activity Detection (VAD).....		133
Annex D (informative): Speech levels in relation to ambient room noise and examples of adaptive volume control settings		134
Annex E (informative): Echo related topics.....		135
E.1	Summary table on echo parameters for PPs and FPs	135
E.2	General information about Delay-Echo interaction for DECT terminals.....	141
Annex F (informative): Guidelines on specific requirements.....		144
F.1	Delay requirements for FPs with VoIP interface	144
F.1.1	Delay requirements for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service).....	144
F.1.1.1	Send delay.....	144
F.1.1.2	Receive delay.....	145
F.1.2	Delay requirements for FP type 5 (Fixed Part with VoIP interface, wideband service).....	146
F.1.2.1	Send Delay.....	146
F.1.2.2	Receive delay.....	147
Annex G (informative): Bibliography.....		149
Annex H (informative): Change history		150
History		151

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 8 of a multi-part deliverable ([1] to [7]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.6] and ETR 043 [i.7].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document is one of the parts of the specification of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI) [1] to [7].

This part of the DECT CI specifies the speech and audio coding and transmission requirements.

In order to ensure satisfactory interworking of different portable and fixed units, it is necessary to specify the transmission performance of the analog information over the digital link. This requires not only use of a common speech algorithm, but also standardization of frequency responses, reference speech levels (or loudness) at the air interface and various other parameters.

The present document applies to DECT equipment which includes all the necessary functions to provide real-time two-way speech conversation. Several speech services are defined in the present document, including conventional 3,1 kHz telephony, wideband 7 kHz voice transmission and super-wideband 14 kHz service. DECT Fixed part providing such services may be connected to the public circuit switched (PSTN/ISDN) network, to private networks or to the Internet.

Tethered fixed point local loop applications are not required to comply with the requirements of the present document.

For the DECT systems which connect to the Public Switched Telephone Network (PSTN) via an analog interface, the additional requirements, which are implemented in the FP, have as much as possible been aligned with TBR 038 [29].

A summary of the control and the use of the DECT echo control functions, to guide on need for options to manufacturers and installers, is found in annex A.

Information concerning test methods can be found in EN 300 176-1 [9] and EN 300 176-2 [10] (previously covered by TBR 010 [i.5]). The test methods take into account that DECT is a digital system.

The present document includes New Generation DECT, a further development of the DECT standard introducing wideband speech, improved data services, new slot types and other technical enhancements.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".

- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [8] Void.
- [9] ETSI EN 300 176-1: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio".
- [10] ETSI EN 300 176-2: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech".
- [11] Recommendation ITU-T G.701: "Vocabulary of digital transmission and multiplexing, and pulse code modulation (PCM) terms".
- [12] Recommendation ITU-T G.726: "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
- [13] Recommendation ITU-T G.711 (1988): "Pulse Code Modulation (PCM) of voice frequencies".
- [14] Recommendation ITU-T G.722 (2012): "7 kHz audio-coding within 64 kbit/s".
- [15] Void.
- [16] Void.
- [17] Recommendation ITU-T G.729.1 (2006): "G.729-based Embedded Variable bit-rate coder: An 8-32 kbit/s scalable wideband coder bitstream interoperable with G.729".
- [18] Void.
- [19] ISO/IEC 14496-3:2009: "Information Technology - Coding of audio-visual objects - Part 3: Audio" ISO/IEC JTC1/SC29/WG11 (MPEG).
- [20] Recommendation ITU-T P.311 (2011): "Transmission characteristics for wideband digital handset and headset telephones".
- [21] Recommendation ITU-T P.10: "Vocabulary for performance and quality of service".
- [22] Recommendation ITU-T P.340: "Transmission characteristics and speech quality parameters of hands-free terminals".
- [23] Recommendation ITU-T P.58: "Head and torso simulator for telephony".
- [24] Recommendation ITU-T G.111: "Loudness Ratings (LRs) in an international connection".
- [25] Recommendation ITU-T G.1020: "Performance parameter definitions for quality of speech and other voiceband applications utilizing IP networks".
- [26] Recommendation ITU-T P.57: "Artificial ears".
- [27] Recommendation ITU-T P.502: "Objective test methods for speech communication systems using complex test signals".
- [28] Recommendation ITU-T P.51: "Artificial mouth".
- [29] ETSI TBR 038: "Public Switched Telephone Network (PSTN); Attachment requirements for a terminal equipment incorporating an analogue handset function capable of supporting the justified case service when connected to the analogue interface of the PSTN in Europe".
- [30] Recommendation ITU-T G.131: "Talker echo and its control".