

SLOVENSKI STANDARD
oSIST prEN 300 328 V1.8.2:2014
01-junij-2014

Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) - Širokopasovni prenosni sistemi - Oprema za prenos podatkov v frekvenčnem pasu 2,4 GHz ISM, ki uporablja širokopasovne modulacijske tehnike - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2 direktive R&TTE

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Wideband transmission systems - Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques - Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

[SIST EN 300 328 V1.9.1:2015](https://standards.iteh.ai/catalog/standards/sist/c801f35f-adff-4d3e-9f1e-2ae96aafe4a7/sist-en-300-328-v1-9-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/c801f35f-adff-4d3e-9f1e-2ae96aafe4a7/sist-en-300-328-v1-9-1-2015>

Ta slovenski standard je istoveten z: EN 300 328 Version 1.8.2

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

oSIST prEN 300 328 V1.8.2:2014 **en**

Draft ETSI EN 300 328 V1.8.2 (2014-04)



Harmonized European Standard

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Wideband transmission systems;
Data transmission equipment operating
in the 2,4 GHz ISM band and
using wide band modulation techniques;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

Reference

REN/ERM-TG11-010

Keywords

data, ISM, LAN, mobile, radio, regulation, spread spectrum, SRD, testing, transmission, UHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 328 V1.9.1:2015

[https://standards.iteh.ai/catalog/standards/sist/5f-adff-4d3e-9f1e-2ae96aafe4a7/sist-](https://standards.iteh.ai/catalog/standards/sist/5f-adff-4d3e-9f1e-2ae96aafe4a7/sist-en-300-328-v1-9-1-2015)

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. 3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Introduction	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references	10
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols	13
3.3 Abbreviations	13
4 Technical specifications	14
4.1 Environmental profile.....	14
4.2 Equipment types	14
4.2.1 Modulation types	14
4.2.2 Adaptive and non-adaptive equipment	14
4.3 Technical requirements	15
4.3.1 Technical requirements for Frequency Hopping equipment	15
4.3.1.1 Introduction	15
4.3.1.2 RF output power.....	15
4.3.1.2.1 Applicability	15
4.3.1.2.2 Definition.....	15
4.3.1.2.3 Limit	15
4.3.1.2.4 Conformance	15
4.3.1.3 Duty Cycle, Tx-sequence, Tx-gap.....	15
4.3.1.3.1 Applicability	15
4.3.1.3.2 Definition.....	15
4.3.1.3.3 Limit	16
4.3.1.3.4 Conformance	16
4.3.1.4 Accumulated Transmit Time, Frequency Occupation and Hopping Sequence.....	16
4.3.1.4.1 Applicability	16
4.3.1.4.2 Definition.....	16
4.3.1.4.3 Limit	16
4.3.1.4.4 Other Requirements	17
4.3.1.4.5 Conformance	17
4.3.1.5 Hopping Frequency Separation.....	17
4.3.1.5.1 Applicability	17
4.3.1.5.2 Definition.....	17
4.3.1.5.3 Limit	18
4.3.1.5.4 Conformance	18
4.3.1.6 Medium Utilization (MU) factor	18
4.3.1.6.1 Applicability	18
4.3.1.6.2 Definition.....	18
4.3.1.6.3 Limit	18
4.3.1.6.4 Conformance	19
4.3.1.7 Adaptivity (Adaptive Frequency Hopping).....	19
4.3.1.7.1 Applicability	19
4.3.1.7.2 Adaptive Frequency Hopping using LBT based DAA	19
4.3.1.7.3 Adaptive Frequency Hopping using other forms of DAA (non-LBT based)	20
4.3.1.7.4 Short Control Signalling Transmissions	21
4.3.1.8 Occupied Channel Bandwidth.....	21
4.3.1.8.1 Applicability	21
4.3.1.8.2 Definition.....	21

4.3.1.8.3	Limits	21
4.3.1.8.4	Conformance	21
4.3.1.9	Transmitter unwanted emissions in the out-of-band domain	22
4.3.1.9.1	Applicability	22
4.3.1.9.2	Definition.....	22
4.3.1.9.3	Limit	22
4.3.1.9.4	Conformance	22
4.3.1.10	Transmitter unwanted emissions in the spurious domain.....	22
4.3.1.10.1	Applicability	22
4.3.1.10.2	Definition.....	22
4.3.1.10.3	Limit	23
4.3.1.10.4	Conformance	23
4.3.1.11	Receiver spurious emissions	23
4.3.1.11.1	Applicability	23
4.3.1.11.2	Definition.....	23
4.3.1.11.3	Limit	23
4.3.1.11.4	Conformance	23
4.3.1.12	Receiver Blocking.....	24
4.3.1.12.1	Applicability	24
4.3.1.12.2	Definition.....	24
4.3.1.12.3	Limits	24
4.3.1.12.4	Conformance	24
4.3.2	Technical requirements for other types of Wide Band modulation	24
4.3.2.1	Introduction.....	24
4.3.2.2	RF output power.....	24
4.3.2.2.1	Applicability	24
4.3.2.2.2	Definition.....	25
4.3.2.2.3	Limit	25
4.3.2.2.4	Conformance	25
4.3.2.3	Power Spectral Density	25
4.3.2.3.1	Applicability	25
4.3.2.3.2	Definition.....	25
4.3.2.3.3	Limit	25
4.3.2.3.4	Conformance	25
4.3.2.4	Duty Cycle, Tx-sequence, Tx-gap.....	25
4.3.2.4.1	Applicability	25
4.3.2.4.2	Definition.....	25
4.3.2.4.3	Limit	26
4.3.2.4.4	Conformance	26
4.3.2.5	Medium Utilization (MU) factor.....	26
4.3.2.5.1	Applicability	26
4.3.2.5.2	Definition.....	26
4.3.2.5.3	Limit	26
4.3.2.5.4	Conformance	26
4.3.2.6	Adaptivity (adaptive equipment using modulations other than FHSS).....	26
4.3.2.6.1	Applicability	26
4.3.2.6.2	Non-LBT based Detect and Avoid	27
4.3.2.6.3	LBT based Detect and Avoid	27
4.3.2.6.4	Short Control Signalling Transmissions.....	29
4.3.2.7	Occupied Channel Bandwidth.....	30
4.3.2.7.1	Applicability	30
4.3.2.7.2	Definition.....	30
4.3.2.7.3	Limits	30
4.3.2.7.4	Conformance	30
4.3.2.8	Transmitter unwanted emissions in the out-of-band domain	30
4.3.2.8.1	Applicability	30
4.3.2.8.2	Definition.....	30
4.3.2.8.3	Limit	30
4.3.2.8.4	Conformance	31
4.3.2.9	Transmitter unwanted emissions in the spurious domain.....	31
4.3.2.9.1	Applicability	31
4.3.2.9.2	Definition.....	31

4.3.2.9.3	Limit	31
4.3.2.9.4	Conformance	31
4.3.2.10	Receiver spurious emissions	32
4.3.2.10.1	Applicability	32
4.3.2.10.2	Definition.....	32
4.3.2.10.3	Limit	32
4.3.2.10.4	Conformance	32
4.3.2.11	Receiver Blocking.....	32
4.3.2.11.1	Applicability	32
4.3.2.11.2	Definition.....	32
4.3.2.11.3	Limits	32
4.3.2.11.4	Conformance	33
5	Essential radio test suites.....	33
5.1	Conditions for testing.....	33
5.1.1	Normal and extreme test conditions.....	33
5.1.1.1	Introduction.....	33
5.1.1.2	Normal test conditions	33
5.1.1.2.1	Normal temperature and humidity.....	33
5.1.1.2.2	Normal power source	33
5.1.1.3	Extreme test conditions	33
5.1.1.3.1	Extreme temperatures	33
5.1.1.3.2	Extreme power source voltages.....	33
5.1.2	Test mode.....	34
5.1.3	Antennas and transmit operating modes	34
5.1.3.1	Integrated and dedicated antennas.....	34
5.1.3.2	Smart antenna systems and related operating modes	34
5.1.3.2.1	Introduction	34
5.1.3.2.2	Operating mode 1 (single antenna).....	34
5.1.3.2.3	Operating mode 2 (multiple antennas, no beamforming)	35
5.1.3.2.4	Operating mode 3 (multiple antennas, with beamforming)	35
5.1.3.3	Output power setting	35
5.1.4	Adaptive and Non-adaptive equipment	35
5.1.5	Presentation of equipment	35
5.1.5.1	Testing of stand-alone equipment	35
5.1.5.2	Testing of host connected equipment and plug-in radio equipment.....	35
5.1.5.2.1	Introduction	35
5.1.5.2.2	The use of a host or test jig for testing Plug-In radio equipment.....	35
5.1.5.2.3	Testing of combinations	36
5.1.6	Test Fixture	36
5.2	Interpretation of the measurement results	37
5.3	Test procedures for essential radio test suites.....	37
5.3.1	Product Information.....	37
5.3.2	RF output power, Duty Cycle, Tx-sequence, Tx-gap, Medium Utilization	38
5.3.2.1	Test conditions	38
5.3.2.2	Test method.....	39
5.3.2.2.1	Conducted measurements	39
5.3.2.2.2	Radiated measurements	41
5.3.3	Power Spectral Density.....	41
5.3.3.1	Test conditions	41
5.3.3.2	Test method.....	41
5.3.3.2.1	Conducted measurement.....	41
5.3.3.2.2	Radiated measurement.....	43
5.3.4	Accumulated Transmit Time, Frequency Occupation and Hopping Sequence	43
5.3.4.1	Test conditions	43
5.3.4.2	Test method.....	43
5.3.4.2.1	Conducted measurements	43
5.3.4.2.2	Radiated measurements	45
5.3.5	Hopping Frequency Separation.....	45
5.3.5.1	Test conditions	45
5.3.5.2	Test method.....	45
5.3.5.2.1	Conducted measurements	45

5.3.5.2.2	Radiated measurements	47
5.3.6	Void	47
5.3.7	Adaptivity (Channel access mechanism)	47
5.3.7.1	Test conditions	47
5.3.7.2	Test Method	48
5.3.7.2.1	Conducted measurements	48
5.3.7.2.2	Radiated measurements	55
5.3.8	Occupied Channel Bandwidth	55
5.3.8.1	Test conditions	55
5.3.8.2	Test method.....	56
5.3.8.2.1	Conducted measurement.....	56
5.3.8.2.2	Radiated measurement.....	56
5.3.9	Transmitter unwanted emissions in the out-of-band domain	56
5.3.9.1	Test conditions	56
5.3.9.2	Test method.....	57
5.3.9.2.1	Conducted measurement.....	57
5.3.9.2.2	Radiated measurement.....	58
5.3.10	Transmitter unwanted emissions in the spurious domain	59
5.3.10.1	Test conditions	59
5.3.10.2	Test method.....	59
5.3.10.2.1	Conducted measurement.....	59
5.3.10.2.2	Radiated measurement.....	61
5.3.11	Receiver spurious emissions	62
5.3.11.1	Test conditions	62
5.3.11.2	Test method.....	62
5.3.11.2.1	Conducted measurement.....	62
5.3.11.2.2	Radiated measurement.....	64
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	65
Annex B (normative):	Test sites and arrangements for radiated measurement	68
B.1	Radiation test sites.....	68
B.1.1	Open Area Test Site (OATS)	68
B.1.2	Semi Anechoic Room.....	69
B.1.3	Fully Anechoic Room (FAR)	70
B.1.4	Measurement Distance	71
B.2	Antennas.....	72
B.2.1	Measurement antenna.....	72
B.2.2	Substitution antenna	72
B.3	Test fixture	72
B.3.1	Conducted measurements and use of test fixture	72
B.3.2	Description of the test fixture.....	72
B.3.3	Using the test fixture for relative measurements	73
B.4	Guidance on the use of radiation test sites	73
B.4.1	Power supplies for a battery-only powered UUT	73
B.4.2	Site preparation	73
B.5	Coupling of signals.....	74
B.6	Interference Signal used for Adaptivity Tests	74
Annex C (normative):	Measurement procedures for radiated measurement	75
C.1	Radiated measurements in an OATS or SAR.....	75
C.2	Radiated measurements in a FAR	75
C.3	Substitution measurement	76
C.4	Guidance for testing technical requirements	76
C.4.1	Essential radio test suites and corresponding test sites.....	76

C.4.2	Guidance for testing Adaptivity (Channel Access Mechanism).....	77
C.4.2.1	Measurement Set-up	77
C.4.2.2	Calibration of the measurement Set-up.....	77
C.4.2.3	Test method	78
Annex D (informative): Guidance for testing IEEE 802.11™ Equipment.....		79
D.1	Introduction	79
D.2	Possible Modulations	79
D.2.1	Guidance for Testing	79
D.2.1.1	Modulation Used for Conformance Testing	79
D.3	Possible Operating Modes.....	80
D.3.1	Guidance for Testing.....	80
Annex E (informative): Application form for testing.....		82
E.1	Information as required by EN 300 328 V1.9.1, clause 5.3.1	82
E.2	Combination for testing (see clause 5.1.3.3 of EN 300 328 V1.9.1).....	87
E.3	Additional information provided by the applicant	87
E.3.1	Modulation	87
E.3.2	Duty Cycle.....	87
E.3.3	About the UUT.....	87
E.3.4	Additional items and/or supporting equipment provided	87
History		89

iTeH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 328 V1.9.1:2015

<https://standards.iteh.ai/catalog/standards/sist/c801f35f-adff-4d3e-9f1e-2ae96aafe4a7/sist-en-300-328-v1-9-1-2015>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been produced by ETSI in response to mandate M/284 issued from the European Commission under Directive 98/34/EC [i.12] as amended by Directive 98/48/EC [i.5].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.1].

See article 5.1 of Directive 1999/5/EC [i.1] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.1] are summarized in annex A.

https://standards.iteh.ai/ Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.2].

1 Scope

The present document applies to Wide Band Data Transmission equipment.

The present document also describes spectrum access requirements to facilitate spectrum sharing with other equipment.

Wide Band Data Transmission equipment covered by the present document is operated in accordance with the ERC Recommendation 70-03 [i.6], annex 3 or Commission Decision 2006/771/EC [i.7] (and its amendments).

Examples of Wide Band Data Transmission equipment are equipments such as IEEE 802.11™ RLANs [i.3], Bluetooth® wireless technologies, Zigbee™, etc.

This equipment can be used in fixed, mobile or nomadic applications, e.g.:

- stand-alone radio equipment with or without their own control provisions;
- plug-in radio devices intended for use with or within a variety of host systems, e.g. personal computers, hand-held terminals, etc.;
- plug-in radio devices intended for use within combined equipment, e.g. cable modems, set-top boxes, access points, etc.;
- combined equipment or a combination of a plug-in radio device and a specific type of host equipment.

This radio equipment is capable of operating in the band 2,4 GHz to 2,4835 GHz.

Applications using Ultra Wide Band (UWB) technology are not covered by the present document.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive) article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

SIST EN 300 328 V1.9.1:2015

<http://standards.iteh.ai/catalog/standards/sist/c801c35f-4d66-443e-9f1e-2ae96aaf24e7/sist>

en-300-328-v1-9-1-2015

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [2] ETSI TS 103 051 (V1.1.1) (08-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Expanded measurement uncertainty for the measurement of radiated electromagnetic fields".
- [3] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] ETSI EG 201 399 (V2.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.3] IEEE Std. 802.11™-2012: "IEEE Standard for Information Technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements. Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [i.4] IEEE Std. 802.15.4™-2011: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements. Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (WPANs)".
- [i.5] Directive 98/48/EC of the European parliament and of the council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.6] CEPT ERC Recommendation 70-03 (1997): "Relating to the use of Short Range Devices (SRD)".
- [i.7] Commission Decision 2006/771/EC of 9 November 2006 on harmonisation of the radio spectrum for use by short-range devices.
- [i.8] ETSI TR 102 273-2 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.9] ETSI TR 102 273-3 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.10] ETSI TR 102 273-4 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.11] ETSI TR 100 028-2 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.12] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations and of rules on Information Society services.
- [i.13] Council Directive 93/42/EEC of 14 June 1993 concerning medical devices (Medical Devices Directive).

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1], the Medical Devices Directive [i.13] and the following apply:

adaptive equipment: equipment operating in an adaptive mode

adaptive frequency hopping: mechanism that allows a frequency hopping equipment to adapt to its radio environment by identifying channels that are being used and excluding them from the list of available channels

adaptive mode: mechanism by which equipment can adapt to its radio environment by identifying other transmissions present in the band

adjacent hopping frequency: neighbouring hopping frequency which is separated by the minimum hopping frequency separation

antenna assembly: combination of the antenna (integral or dedicated), its feeder (e.g. coaxial cable) and if applicable, its antenna connector and associated switching components

NOTE: The gain of an antenna assembly (G) in dBi, does not include the additional gain that may result out of beamforming. This term (antenna assembly) refers to an antenna connected to one transmit chain.

beamforming gain: additional (antenna) gain realized by using beamforming techniques in smart antenna systems

NOTE: Beamforming gain as used in the present document, does not include the gain of the antenna assembly.

clear channel assessment: mechanism used by an equipment to identify other transmissions in the channel

combined equipment: any combination of non-radio equipment that requires a plug-in radio equipment to offer full functionality

dedicated antenna: antenna external to the equipment using an antenna connector, with or without a cable, which has been designed or developed for one or more specific types of equipment

NOTE: It is the combination of dedicated antenna and radio equipment that is expected to be compliant with the regulations.

detect and avoid: mechanism which mitigates interference potential by avoiding use of frequencies upon detection of other transmissions on those frequencies

direct sequence spread spectrum: form of modulation where a combination of data to be transmitted and a known code sequence (chip sequence) is used to directly modulate a carrier, e.g. by phase shift keying

NOTE: The transmitted bandwidth is determined by the chip rate and the modulation scheme.

dwelt time: time between frequency changes for Frequency Hopping equipment

NOTE: The Dwell Time might comprise transmit, receive and idle phases of the equipment.

energy detect: mechanism used by an LBT based adaptive equipment to determine the presence of other devices operating on the channel based on detecting the signal level of that other device

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

frame based equipment: equipment where the transmit/receive structure is not directly demand-driven, i.e. it may be altered by configuration changes but there is always a minimum Idle Period following a transmit period

frequency hopping spread spectrum: spread spectrum technique in which the equipment occupies a number of frequencies in time, each for some period of time, referred to as the dwell time

NOTE: Transmitter and receiver follow the same frequency hop pattern. The frequency range is determined by the lowest and highest hop positions and the bandwidth per hop position.

hopping frequency: any of the (centre) frequencies defined within the hopping sequence of a FHSS system

host equipment: any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

idle period: period in time following a transmission sequence during which the equipment does not transmit

integral antenna: antenna designed as a fixed part of the equipment, without the use of an external connector and which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable may be used.

Listen Before Talk (LBT): mechanism by which an equipment first applies CCA before using the channel

load based equipment: equipment where, opposite to a frame based equipment, the transmit/receive structure is demand-driven

multi-radio equipment: radio, host or combined equipment using more than one radio transceiver

necessary bandwidth: width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

nominal channel bandwidth: band of frequencies assigned to a single channel

NOTE: The Nominal Channel Bandwidth is declared by the manufacturer as outlined in clause 5.3.1.

operating frequency: nominal frequency at which the equipment can be operated; this is also referred to as the operating centre frequency

NOTE: Equipment may be adjustable for operation at more than one operating frequency.

out-of-band emission: emission on a frequency or frequencies immediately outside the necessary bandwidth which results from the modulation process, but excluding emissions in the spurious domain

plug-in radio equipment: radio equipment module intended to be used with or within host, combined or multi-radio equipment, using their control functions and power supply

power envelope: RF power versus frequency contour

power spectral density: the mean power in a given reference bandwidth

receive chain: receiver circuit with an associated antenna assembly

NOTE: Two or more receive chains are combined in a smart antenna assembly.

smart antenna systems: equipment that combines multiple transmit and/or receive chains with a signal processing function to increase the throughput and/or to optimize its radiation and/or reception capabilities

NOTE: These are techniques such as spatial multiplexing, beamforming, cyclic delay diversity, MIMO, etc.

spurious emissions: emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

stand-alone radio equipment: equipment that is intended primarily as communications equipment and that is normally used on a stand-alone basis

supplier: person or entity submitting the equipment for testing

transmission burst: the period in time during a transmission during which the transmitter is continuously on

transmit chain: transmitter circuit with an associated antenna assembly

NOTE: Two or more transmit chains are combined in a smart antenna system.

ultra wide band technology: technology for short-range radiocommunication, involving the intentional generation and transmission of radio-frequency energy that spreads over a very large frequency range, which may overlap several frequency bands allocated to radiocommunication services

wide band modulation: wide band modulation is considered to include FHSS, DSSS, OFDM, etc. that meet the emission requirements as defined in the present document

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{ch}	number of active transmit chains
BW_{CHAN}	Channel Bandwidth
dBm	dB relative to 1 milliwatt
dB _r	dB relative to peak power
dBW	dB relative to 1 Watt
F_{HS}	Hopping Frequency Separation
GHz	GigaHertz
Hz	Hertz
kHz	kiloHertz
MHz	MegaHertz
mW	milliWatt
ms	millisecond
MS/s	Mega Samples per second
N	Number of hopping frequencies
P _{out}	Output Power
TxOff	Transmitter Off
TxOn	Transmitter On

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
AC/DC	Alternating Current/Direct Current
ACK	Acknowledgement
AFH	Adaptive Frequency Hopping
BW	BandWidth
CCA	Clear Channel Assessment
CE	Conformité Européenne
CSD	Cyclic Shift Diversity
CW	Continuous Wave
DAA	Detect And Avoid
DC	Duty Cycle
DSSS	Direct Sequence Spread Spectrum
e.i.r.p.	equivalent isotropically radiated power
e.r.p.	effective radiated power
EMC	ElectroMagnetic Compatibility
FAR	Fully Anechoic Room
FFT	Fast Fourier Transformation
FHSS	Frequency Hopping Spread Spectrum
HT	High Throughput
ISM	Industrial, Scientific and Medical
LBT	Listen Before Talk
LPDA	Logarithmic Periodic Dipole Antenna
MCS	Modulation and Coding Scheme
MS/s	Mega-Samples per second
MU	Medium Utilization
NACK	Not Acknowledged
OATS	Open Air Test Site
OFDM	Orthogonal Frequency Division Multiplexing
OOB	Out Of Band
R&TTE	Radio and Telecommunications Terminal Equipment
RBW	Resolution BandWidth
RF	Radio Frequency
RMS	Root Mean Square
SAR	Semi Anechoic Room
TL	Threshold Level