
**Earth-moving machinery —
Determination of emission sound
pressure level at operator's position —
Dynamic test conditions**

*Engins de terrassement — Détermination du niveau de pression
acoustique d'émission au poste de conduite — Conditions d'essai
dynamique*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 6396:2008

<https://standards.iteh.ai/catalog/standards/sist/ed53149b-c30b-482c-95c3-6e48bbc1ad38/iso-6396-2008>



Reference number
ISO 6396:2008(E)

© ISO 2008

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 6396:2008

<https://standards.iteh.ai/catalog/standards/sist/ed53149b-c30b-482c-95c3-6e48bbc1ad38/iso-6396-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Instrumentation.....	2
5 Test environment.....	2
6 Measurement of time-averaged A-weighted sound pressure levels	2
6.1 Operator stature	2
6.2 Operator presence	2
6.3 Microphone.....	2
7 Set-up and operation of machine, and operator's position set-up.....	3
7.1 Set-up and operation of machine	3
7.2 Setting-up operator's position for machines with cab	4
8 Acoustic measurements	4
8.1 Measurement procedure	4
8.2 Determination of measurement result	4
9 Information to be recorded	4
10 Information to be reported	5
10.1 Information	5
10.2 Declaration of sound emission data and uncertainty	6
Annex A (normative) Declaration of sound emission data and uncertainty	7
Bibliography	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6396 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 2, *Safety requirements and human factors*, in collaboration with Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO 6396:1992), which has been technically revised.

ISO 6396:2008
<https://standards.iteh.ai/catalog/standards/sist/ed53149b-c30b-482c-95c3-6e48bbc1ad38/iso-6396-2008>

Introduction

This International Standard is a specific test code for earth-moving machinery as defined in ISO 6165.

A simulated dynamic test condition, rather than an actual work cycle, is used. Simulated dynamic test conditions provide noise emission data which are repeatable and representative. Actual work cycle tests are complex and repeatability can be a problem.

Specific procedures are described in this International Standard to enable the time-averaged A-weighted emission sound pressure level in dynamic test conditions to be determined in a manner which is repeatable. Attachments (bucket, dozer, etc.) for the manufacturer's production version are intended to be fitted since this is the configuration most likely to exist when the machine is in actual use.

This International Standard enables compliance with noise limits to be determined, if applicable. It can also be used for evaluation purposes in noise reduction investigations.

A complementary test code is given in ISO 6395. This other specific test code is intended to be used to determine the noise emitted by earth-moving machinery in terms of the A-weighted sound power level, with the machine under dynamic test conditions.

Corresponding measurements of noise emitted to the environment and noise at the operator's position under stationary test conditions are described in ISO 6393 and ISO 6394, respectively.

ISO 6396:2008
<https://standards.iteh.ai/catalog/standards/sist/ed53149b-c30b-482c-95c3-6e48bbc1ad38/iso-6396-2008>

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 6396:2008

<https://standards.iteh.ai/catalog/standards/sist/ed53149b-c30b-482c-95c3-6e48bbc1ad38/iso-6396-2008>

Earth-moving machinery — Determination of emission sound pressure level at operator's position — Dynamic test conditions

1 Scope

This International Standard specifies a method for determining the emission sound pressure level of earth-moving machinery at the operator's position, measured in terms of the time-averaged A-weighted emission sound pressure level while the machine is operating under dynamic test conditions.

It is applicable to earth-moving machinery as defined in ISO 6165 and as specified in ISO 6395:2008, Annex A.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3411, *Earth-moving machinery — Physical dimensions of operators and minimum operator space envelope*

ISO 6396:2008

ISO 6165, *Earth-moving machinery — Basic types — Identification and terms and definitions*

ISO 6395:2008, *Earth-moving machinery — Determination of sound power level — Dynamic test conditions*

ISO 9249, *Earth-moving machinery — Engine test code — Net power*

ISO 11201, *Acoustics — Noise emitted by machinery and equipment — Measurement of emission sound pressure levels at a work station and at other specified positions — Engineering method in an essentially free field over a reflecting plane*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11201, ISO 6165 and the following apply.

3.1

time-averaged A-weighted sound pressure level

$L_{pA,T}$

A-weighted sound pressure level averaged on an energy basis over the whole measurement period, T

4 Instrumentation

The instrumentation shall be capable of being used to carry out measurements as described in Clause 8. The preferred instrumentation system for acquiring the data is an integrating-averaging sound level meter complying with the requirements of IEC 61672-1 for a class 1 instrument.

5 Test environment

For the purposes of this International Standard, the test environment specified in ISO 6395 applies.

6 Measurement of time-averaged A-weighted sound pressure levels

6.1 Operator stature

The operator shall have a stature between that of the small operator and the large operator as defined in ISO 3411. See also 6.2.2.2.

6.2 Operator presence

6.2.1 Ride-on machines

6.2.1.1 Operator's position

The operator shall be in the driving position and observers shall not be in close proximity or in the cab during sound measurement. The operator shall wear neither abnormally sound-absorptive clothing nor any hat or scarf (other than a protective helmet used for safety reasons, or a helmet or frame used to support a microphone) which might influence the noise measurement.

6.2.1.2 Seat adjustment

The seat shall be set at, or as near as possible to, the midpoint of its horizontal and vertical adjustment. Any seat suspension shall be adjusted to the operator's weight.

6.2.2 Pedestrian-controlled machines

6.2.2.1 Operator's position

The operator shall be in the usual working position specified by the manufacturer and observers shall not be in close proximity to the operator during sound measurement. The operator shall wear neither abnormally sound-absorptive clothing nor any hat or scarf (other than a protective helmet used for safety reasons, or a helmet or frame used to support a microphone) which might influence the noise measurement.

6.2.2.2 Standing operator

The standing operator shall have a stature of $1\,715\text{ mm} \pm 50\text{ mm}$.

6.3 Microphone

6.3.1 Microphone orientation

The microphone shall be oriented horizontally, with its reference direction — as specified by the microphone manufacturer — pointing in the direction in which a person occupying the operator's position would normally look.

6.3.2 Microphone position

As a preliminary sound pressure level data check point, the microphone shall be located $200 \text{ mm} \pm 20 \text{ mm}$ from the median plane of the head of the operator and in line with the eyes, on the left side and on the right side of the head of the operator, during the maximum governor engine speed (high idle) condition and with the machine in a static mode, as a preliminary sound pressure level data check point. Whichever side yields the highest reading shall be used for the dynamic check. If both initial sound pressure level checks are the same, the right side location shall be used.

6.3.3 Microphone mounting

The microphone can conveniently be mounted on a frame or on the helmet, or on a shoulder harness worn by the operator.

6.3.4 Microphone vibration precautions

Care shall be taken to isolate the microphone from vibrations which could affect the measurements. If the microphone is moved during the measurements, care shall be exercised to avoid introducing acoustical noise (for example, noise due to the microphone rubbing against the operator's clothing) or electrical noise (for example, due to a flexing cable) that could interfere with the measurements.

6.3.5 Precautions against microphone-reflected noise

6.3.5.1 Care shall be taken to minimize the effect of reflected noise which could affect microphone measurements. The recommendations given in 6.3.5.2 and 6.3.5.3 will minimize the effect of reflected noise.

6.3.5.2 Once the microphone location has been determined, a positional tolerance should be maintained of $\pm 50 \text{ mm}$ from this location in any direction during the test.

6.3.5.3 The microphone should be placed a minimum of 100 mm from the side of the head and a minimum of 50 mm above the clothing on the shoulder during the test.

7 Set-up and operation of machine, and operator's position set-up

7.1 Set-up and operation of machine

The set-up and operation of the machine shall be as specified in ISO 6395:2008, Clause 7.

Based on the type of machine, measurements are made in

- a travel mode,
- a stationary work cycle mode, or
- a combination of travel/stationary work cycle modes.

The positioning of the machine and travel length shall be as specified in ISO 6395:2008, 6.1 and 6.3. The machine operation and travel path shall be as specified in ISO 6395:2008, Annexes B to L.