
Tool holders with cylindrical shank —
Part 1:
Cylindrical shank, location bore —
Technical delivery conditions

Porte-outil à queue cylindrique —
Partie 1: Queue cylindrique, alésage de réception — Conditions
techniques de livraison

[ISO 10889-1:2004](https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-bd20ceb8c2e0/iso-10889-1-2004)

[https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-
bd20ceb8c2e0/iso-10889-1-2004](https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-bd20ceb8c2e0/iso-10889-1-2004)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 10889-1:2004](https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-bd20ceb8c2e0/iso-10889-1-2004)

<https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-bd20ceb8c2e0/iso-10889-1-2004>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10889-1 was prepared by Technical Committee ISO/TC 29, *Small tools*.

This second edition cancels and replaces the first edition (ISO 10889-1:1997), Table 2 of which has been technically revised.

ISO 10889 consists of the following parts, under the general title *Tool holders with cylindrical shank*:

- *Part 1: Cylindrical shank, location bore — Technical delivery conditions*
ISO 10889-1:2004
<https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-bd20ceb8e2e0/iso-10889-1-2004>
- *Part 2: Type A, shanks for tool holders of special designs*
- *Part 3: Type B with rectangular radial seat*
- *Part 4: Type C with rectangular axial seat*
- *Part 5: Type D with more than one rectangular seat*
- *Part 6: Type E with cylindrical seat*
- *Part 7: Type F with taper seat*
- *Part 8: Type Z, accessories*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10889-1:2004

<https://standards.iteh.ai/catalog/standards/sist/2858cc40-1686-48a5-9826-bd20ceb8c2e0/iso-10889-1-2004>

Tool holders with cylindrical shank —

Part 1: Cylindrical shank, location bore — Technical delivery conditions

1 Scope

ISO 10889 is applicable to tool holders with cylindrical shank for machine tools with non-rotating tools, preferably for turning machines.

This part of ISO 10889 specifies the interchangeability dimensions of the cylindrical shank and location bore, and the dimensions related to data medium. It also specifies the technical delivery conditions of the tool holders.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1629, *Rubber and latices — Nomenclature*

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 13715, *Technical drawings — Edges of undefined shape — Vocabulary and indications*

3 Cylindrical shank


3.1 Dimensions

The dimensions of the cylindrical shank are shown in Figure 1 and given in Table 1, the geometrical tolerances are shown in Figure 2.

Unspecified details shall be chosen appropriately.

General tolerances: ISO 2768-m.

Dimensions in millimetres,
surface roughness in micrometres



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10889-1:2004
<https://standards.iteh.ai/catalog/standards/sist/2858cc00-1686-48a5-9826-bd20ceb8c2e0/iso-10889-1-2004>

Key

- 1 measuring roll, tolerance $\pm 0,01$ mm
- a See 6.3.2.

Figure 1 — Cylindrical shank of tool holder


Table 1 — Dimensions of cylindrical shank

Dimensions in millimetres

d_1	l_1	d_2		d_3	d_6	f	g	h_1	h_2	h_3	l_2
h6	$\pm 0,3$	nom.	tol.		$\begin{matrix} 0 \\ -0,1 \end{matrix}$			max.	$\pm 0,1$	$\pm 0,1$	$\pm 0,05$
16	32	8	H6	40	15,4	2	1,7	12	15	16,92	12,7
20	40	10		50	19,1	2,4	2	16	18	19,92	21,7
25	48	10		58	24,1	2,4	2	16	23,5	25,42	21,7
30	55	14	H8	68	29,1	2,4	2	20	27	28,92	29,7
40	63	14		83	38,7	3,7	2,8	25	36	37,92	29,7
50	78	16		98	48,7	3,7	2,8	32	45	46,92	35,7
60	94	16		123	58,7	4,3	3,7	32	55	56,92	43,7
80	124	20		158	78,7	4,3	3,7	40	72	73,92	59,7

d_1	l_3	l_4	l_7	r_1	r_2	O-ring
h6	min.	$\begin{matrix} +1 \\ 0 \end{matrix}$		$\pm 0,02$		
16	16	2	3,5	14,5	0,6	15 × 1,5
20	24	2	7	18	0,8	18,77 × 1,78
25	24	2	7	21	0,8	23,52 × 1,78
30	40	2	7	25	0,8	28,3 × 1,78
40	40	3	7	32	1,2	37,77 × 2,62
50	48	3	8	37	1,2	47,29 × 2,62
60	56	4	10	48	1,6	56,74 × 3,53
80	80	4	10	65	1,6	75,79 × 3,53

Dimensions in millimetres



^a Non-convex.

Figure 2 — Cylindrical shank — Geometrical tolerances

3.2 Designation

A cylindrical shank in accordance with this part of ISO 10889 shall be designated by

- a) "Cylindrical shank",
- b) reference to this part of ISO 10889, i.e. ISO 10889-1,
- c) nominal diameter, d_1 , in millimetres,
- d) nominal length, l_1 , in millimetres.

EXAMPLE A cylindrical shank with a nominal diameter $d_1 = 40$ mm and a nominal length $l_1 = 63$ mm is designated as follows:

Cylindrical shank ISO 10889-1 - 40 × 63

4 Location bore


4.1 Dimensions

The dimensions of the location bore are shown in Figure 3 and given in Table 2, the geometrical tolerances are shown in Figure 4.

Unspecified details shall be chosen appropriately.

General tolerances: ISO 2768-m.

iTech STANDARD PREVIEW
(standards.itech.ai)



- a Contact surface.
- b Clearance.

Figure 3 — Location bore

Table 2 — Dimensions of the location bore

Dimensions in millimetres

d_1	d_4		d_5	l_5	l_6	l_8	r_1
H6	nom.	tol.	min.	$\pm 0,05$			$\pm 0,02$
16	8	f6	42	13	32	2,1	14,5
20	10		52	22	40	2,5	18
25	10		60	22	48	2,5	21
30	13,95	$\pm 0,02$	70	30	55	2,5	25
40	13,95		85	30	63	4	32
50	15,9		100	36	78	4	37
60	15,9		125	44	94	6	48
80	19,9		160	60	124	6	65

Dimensions in millimetres




Figure 4 — Location bore — Geometrical tolerances

4.2 Designation

A location bore in accordance with this part of ISO 10889 shall be designated by

- “Location bore”,
- reference to this part of ISO 10889, i.e. ISO 10889-1,
- nominal diameter, d_1 , in millimetres.

EXAMPLE A location bore with a nominal diameter $d_1 = 40$ mm is designated as follows:

Location bore ISO 10889-1 - 40