

SLOVENSKI STANDARD SIST ISO 16220:2005

01-september-2005

Magnezij in magnezijeve zlitine – Ingoti magnezijevih zlitin in ulitki

Magnesium and magnesium alloys -- Magnesium alloy ingots and castings

iTeh STANDARD PREVIEW

Magnésium et alliages de magnésium - Lingots et pièces moulées en alliage de magnésium

SIST ISO 16220:2005

Ta slovenski standard je istoveten z: C4513de3209/sist-150-16220:2005

<u>ICS:</u>

77.120.20 Magnezij in magnezijeve zlitine

Magnesium and magnesium alloys

SIST ISO 16220:2005

en

SIST ISO 16220:2005

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 16220:2005</u> https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02ec4515de3209/sist-iso-16220-2005



INTERNATIONAL STANDARD

ISO 16220

Second edition 2005-03-01

Magnesium and magnesium alloys — Magnesium alloy ingots and castings

Magnésium et alliages de magnésium — Lingots et pièces moulées en alliage de magnésium

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 16220:2005</u> https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02ec4515de3209/sist-iso-16220-2005



Reference number ISO 16220:2005(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 16220:2005</u> https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02ec4515de3209/sist-iso-16220-2005

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forewo	ord iv	'
Introdu	ction	,
1	Scope1	
2	Normative references1	
3	Designation1	
4	Requirements	
5	Sampling	6
6	Test pieces for mechanical properties	6
7	Test methods4	ŀ
8	Retests	ŀ
9	Rounding of numbers4	ŀ
Annex	A (informative) List of European, national and former national European designations corresponding, but not necessarily identical to, the former ISO designations)
Annex	B (informative) Additional information regarding the manganese and iron content	I
Annex	C (informative) Additional information regarding maximum content of alloying elements and impurities in ingots and castings	
Bibliog	SISTISO 16220:2005 raphyhttps://standards.itch.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02	1

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16220 was prepared by Technical Committee ISO/TC 79, *Light metals and their alloys*, Subcommittee SC 5, *Magnesium and alloys of cast or wrought magnesium*.

This second edition cancels and replaces the first edition (ISO 16220:2000), which has been technically revised. (standards.iteh.ai)

<u>SIST ISO 16220:2005</u> https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02ec4515de3209/sist-iso-16220-2005

Introduction

This International Standard classifies the commercially available magnesium alloys into a number of grades suitable for the applications to which they might be put.

Some of the alloys referenced in this International Standard can be the subject of a patent or of patent applications and their listing herein is not to be construed in any way as the granting of a license under such patent rights.

This International Standard is technically identical with European Standard EN 1753, except for some minor deviation in Ni content, Mn content and Fe/Mn ratio. Grade designation also differs slightly; the correlation is given in Annex A.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 16220:2005 https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02ec4515de3209/sist-iso-16220-2005 SIST ISO 16220:2005

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 16220:2005 https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02ec4515de3209/sist-iso-16220-2005

Magnesium and magnesium alloys — Magnesium alloy ingots and castings

1 Scope

This International Standard specifies the chemical composition of magnesium alloy ingots. It also specifies the chemical composition of magnesium alloy castings and the mechanical properties of separately cast samples of these alloys (see Clause 6). By agreement, this International Standard also specifies the mechanical properties of magnesium alloy castings determined from samples cut from a casting.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 31-0, Quantities and units — Part 0: General principles **PRVIE**

ISO 6506-1, Metallic materials — Brinell hardness test — Part 1: Test method

ISO 6892, Metallic materials — Tensile testing at ambient temperature

SIST ISO 16220:2005

EN 1559-5, Founding_{1ps}//Technical_condition_of_delivery_b_5Rart 5; Additional_requirements for magnesium alloy castings ec4515de3209/sist-iso-16220-2005

3 Designation

3.1 Material

The material shall be designated by symbols as given in Tables 1 to 5.

NOTE 1 The material symbol designations are in accordance with ISO 2092:1981¹). The material number designations are identical to those used in EN 1753.

NOTE 2 A list of European designations, national and former national European designations corresponding to those specified in this International Standard is given in Annex A.

3.2 Temper designation

The following symbols for temper designation shall be used:

 F: as-cast; applies to products that acquire some temper from casting processes not having special control over the amount of thermal treatment;

¹⁾ Withdrawn in 2002.

- T4: solution heat-treated and naturally aged; applies to products that have no further treatment after solution heat treatment;
- T5: as-cast and artificially aged; applies to products that are cooled from the casting process, and then artificially aged to improve mechanical properties or dimensions;
- T6: solution heat-treated and artificially aged; applies to products that are solution heat treated followed by artificially ageing.

3.3 Casting process designation

The following symbols shall be used for the designation of the different casting processes:

- S: sand casting;
- K: permanent-mould casting;
- D: pressure-die casting;
- L: investment casting.

3.4 Designation for ordering

The designation used for ordering shall include, in the following order, the number of castings, a mention of this International Standard, the ISO alloy designation, the designation for the heat treatment process (temper), and the designation for the casting process.

(standards.iteh.ai)

EXAMPLE An order for 20 castings conforming to this International Standard, of magnesium alloy ISO-MC21120, delivered in as-cast (F temper) and made by sand casting (S), is as follows:

https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02-20 castings – ISO 16220 – ISO-MgAl9Zn1(A) for ISO-MC21120)-F-Z 0 castings – ISO 16220 – ISO-MgAl9Zn1(A) for ISO-MC2120-F-Z

4 Requirements

4.1 Chemical composition

The chemical composition of magnesium alloy ingots shall conform to the requirements for the appropriate material given in Table 1.

The chemical composition of magnesium alloy castings shall conform to the requirements for the appropriate material given in Table 2.

Conformance shall be determined by the manufacturer by analysing samples taken at the time the ingots or castings are produced.

NOTE For additional information regarding the manganese and iron contents, see Annex B.

4.2 Mechanical properties of castings

The mechanical properties obtained from test pieces prepared from separately cast samples for sand castings and permanent-mould castings shall meet the requirements given in Tables 3 and 4. As appropriate, the tests shall be carried out in accordance with Clause 7.

NOTE 1 Mechanical properties obtained from test pieces prepared from separately cast samples for investment castings are not specified, as experience is limited. As a general rule they are similar to those for permanent mould castings.

NOTE 2 The values obtained from test pieces cut from castings can differ from the minimum values specified in the tables because of variation in structure arising from differences in section thickness and soundness.

NOTE 3 The mechanical properties obtained from test pieces prepared from separately cast samples, especially for pressure-die castings, are very dependent upon injection and process parameters; therefore, the properties given in Table 5 are for guidance only.

The Brinell hardness test shall be carried out on sound areas of castings or on a test piece which has not been stressed.

4.3 Frequency of testing

The frequency of testing shall be in accordance with EN 1559-5.

4.4 General condition of the product

The product shall have a clean surface according to agreement between the manufacturer and the purchaser, and shall be commercially free from visible and internal defects to a standard also agreed between the manufacturer and the purchaser.

5 Sampling

Conditions for sampling, formation of batches and frequency of verification shall be as specified in EN 1559-5.

iTeh STANDARD PREVIEW

6 Test pieces for mechanical properties.iteh.ai)

6.1 Design

SIST ISO 16220:2005

https://standards.iteh.ai/catalog/standards/sist/9b95deaf-15b4-4591-8b02-

The design of test pieces shall be subject to agreement between the manufacturer and the purchaser.

6.2 Test pieces obtained from separately cast samples

6.2.1 Sand-cast samples

Test pieces may be in the machined or unmachined condition.

The following conditions shall apply:

- samples shall be cast in sand moulds and without artificial chilling;
- the minimum diameter of the test piece shall be 12 mm;
- the gauge length and the parallel length shall conform to ISO 6892.

6.2.2 Permanent-mould cast samples

Test pieces may be in the machined or unmachined condition.

The following conditions shall apply:

- the minimum diameter of the test piece shall be 12 mm;
- the gauge length and parallel length shall conform to ISO 6892.