



**SLOVENSKI STANDARD**  
**SIST EN 301 598 V1.1.1:2014**  
**01-julij-2014**

---

**Naprave za kanalske presledke (WSD) - Brezžični dostopovni sistemi, ki delujejo v frekvenčnem pasu od 470 MHz do 790 MHz - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2 direktive R&TTE**

White Space Devices (WSD) - Wireless Access Systems operating in the 470 MHz to 790 MHz frequency band - Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 598 V1.1.1:2014  
https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50fbfa5fe/sist-en-301-598-v1-1-1-2014](https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50fbfa5fe/sist-en-301-598-v1-1-1-2014)

**Ta slovenski standard je istoveten z: EN 301 598 Version 1.1.1**

---

**ICS:**

33.040.99	Druga oprema za telekomunikacijske sisteme	Other equipment for telecommunication systems
-----------	--	---

**SIST EN 301 598 V1.1.1:2014**                      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 598 V1.1.1:2014](https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50bfa5fe/sist-en-301-598-v1-1-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50bfa5fe/sist-en-301-598-v1-1-1-2014>

# ETSI EN 301 598 V1.1.1 (2014-04)



**White Space Devices (WSD);  
Wireless Access Systems operating in the 470 MHz to 790 MHz  
TV broadcast band;  
Harmonized EN covering the essential requirements  
of article 3.2 of the R&TTE Directive**

---

Reference

DEN/BRAN-0060010

---

Keywordsaccess, broadband, CRS, FWA, LAN, M2M,  
mobile, radio**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 598 V1.1.1:2014

<https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50fbf-9d3d-4771-98c1-1-1-2014>  
**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Introduction .....	7
1 Scope .....	8
2 References .....	8
2.1 Normative references .....	8
2.2 Informative references .....	9
3 Definitions, symbols and abbreviations .....	9
3.1 Definitions .....	9
3.2 Symbols .....	11
3.3 Abbreviations .....	12
4 Technical requirements specifications .....	12
4.1 Environmental profile.....	12
4.2 Conformance requirements .....	12
4.2.1 Equipment types .....	13
4.2.1.1 Equipment Type A .....	13
4.2.1.2 Equipment Type B .....	13
4.2.2 Nominal Channel Bandwidth and Total Nominal Channel Bandwidth .....	13
4.2.2.1 Definition .....	13
4.2.2.2 Requirements .....	13
4.2.2.3 Conformance .....	14
4.2.3 RF power and RF power spectral density .....	14
4.2.3.1 Definitions .....	14
4.2.3.1.1 RF power .....	14
4.2.3.1.2 RF power spectral density .....	14
4.2.3.2 Limits .....	14
4.2.3.3 Conformance .....	14
4.2.4 Transmitter unwanted emissions .....	14
4.2.4.1 Transmitter unwanted emissions outside the 470 MHz to 790 MHz band.....	14
4.2.4.1.1 Definition.....	14
4.2.4.1.2 Limits .....	14
4.2.4.1.3 Conformance .....	15
4.2.4.2 Transmitter unwanted emissions within the 470 MHz to 790 MHz band .....	15
4.2.4.2.1 Definition.....	15
4.2.4.2.2 Limits .....	15
4.2.4.2.3 Conformance .....	15
4.2.5 Transmitter Reverse Intermodulation Attenuation.....	15
4.2.5.1 Definition .....	15
4.2.5.2 Limits .....	16
4.2.5.3 Conformance .....	16
4.2.6 Control and monitoring .....	16
4.2.6.1 TVWSDB identification.....	16
4.2.6.1.1 Definition.....	16
4.2.6.1.2 Applicability .....	17
4.2.6.1.3 Requirements .....	17
4.2.6.1.4 Conformance .....	17
4.2.6.2 Data exchange and compliance with parameters.....	17
4.2.6.2.1 Definitions .....	17
4.2.6.2.2 Transmission in compliance with parameters.....	20
4.2.6.2.3 Reporting of device parameters .....	21
4.2.6.2.4 Reporting of channel usage parameters .....	21
4.2.6.2.5 Functionality of a master TVWSD to support slave TVWSDs .....	21
4.2.6.2.6 Conformance .....	22

4.2.6.3	Master TVWSD update.....	22
4.2.6.3.1	Definition.....	22
4.2.6.3.2	Requirements.....	22
4.2.6.3.3	Conformance.....	23
4.2.6.4	Slave TVWSD update.....	23
4.2.6.4.1	Definition.....	23
4.2.6.4.2	Requirements.....	23
4.2.6.4.3	Conformance.....	23
4.2.7	Receiver spurious emissions.....	23
4.2.7.1	Definition.....	23
4.2.7.2	Limits.....	23
4.2.7.3	Conformance.....	24
4.2.8	Geo-Location capability.....	24
4.2.8.1	Definition.....	24
4.2.8.2	Applicability.....	24
4.2.8.3	Requirements.....	24
4.2.8.4	Conformance.....	24
4.2.9	Software, Firmware and User Access Restrictions.....	25
4.2.9.1	Definition.....	25
4.2.9.2	Requirement.....	25
4.2.9.3	Conformance.....	25
4.2.10	Security.....	25
4.2.10.1	Definition.....	25
4.2.10.2	Requirements.....	25
4.2.10.3	Conformance.....	26
5	Testing for compliance with technical requirements.....	26
5.1	Conditions for testing.....	26
5.1.1	Normal and extreme test conditions.....	26
5.1.2	Antennas.....	26
5.1.3	Transmit operating modes.....	27
5.1.4	Requirements for the test modulation.....	27
5.1.5	Communication between test TVWSDB, master and slave UUT.....	27
5.1.6	Operational Parameter set.....	28
5.2	Interpretation of measurement results.....	28
5.3	Essential test suites.....	29
5.3.1	Product Information.....	29
5.3.2	RF output power.....	30
5.3.2.1	Test conditions.....	30
5.3.2.2	Test method.....	30
5.3.2.2.1	Conducted measurements.....	30
5.3.2.2.2	Radiated measurements.....	31
5.3.3	Power Spectral Density and Transmitter unwanted emissions within the 470 MHz to 790 MHz band.....	32
5.3.3.1	Test conditions.....	32
5.3.3.2	Test method.....	32
5.3.3.2.1	Conducted measurement.....	32
5.3.3.2.2	Radiated measurement.....	34
5.3.4	Transmitter unwanted emissions outside the 470 MHz to 790 MHz bands.....	34
5.3.4.1	Test conditions.....	35
5.3.4.2	Test method.....	35
5.3.4.2.1	Conducted measurements.....	35
5.3.4.2.2	Radiated measurements.....	37
5.3.5	Transmitter Intermodulation.....	37
5.3.5.1	Measurement Arrangement.....	37
5.3.5.2	Test Method.....	37
5.3.6	Master TVWSD update.....	37
5.3.6.1	Test conditions.....	38
5.3.6.2	Test method.....	38
5.3.7	Lost connection between the master TVWSD and the TVWSDB.....	39
5.3.7.1	Test conditions.....	39
5.3.7.2	Test method.....	40
5.3.8	Slave TVWSD update - specific parameters invalidated.....	40

5.3.8.1	Test conditions .....	40
5.3.8.2	Test method.....	40
5.3.9	Slave TVWSD update - loss of communication with master TVWSD .....	41
5.3.9.1	Test conditions .....	41
5.3.9.2	Test method.....	41
5.3.10	Receiver spurious emission .....	41
5.3.10.1	Test conditions .....	41
5.3.10.2	Test method.....	42
5.3.10.2.1	Conducted measurements .....	42
5.3.10.2.2	Radiated measurements .....	43
5.3.11	Control and monitoring functions.....	43
5.3.11.1	TVWSDB identification.....	43
5.3.11.1.1	Test condition .....	43
5.3.11.1.2	Test method 1 .....	44
5.3.11.1.3	Test method 2 .....	44
5.3.11.1.4	Test method 3 .....	45
5.3.11.1.5	Test method 4 .....	45
5.3.11.1.6	Test method 5 .....	46
5.3.11.2	Transmission in compliance with parameters, provision of device parameters, provision of channel usage parameters and master TVWSD functionality in support of slave TVWSDs.....	46
5.3.11.2.1	Test condition .....	46
5.3.11.2.2	Test method 1 .....	47
5.3.11.2.3	Test method 2 .....	47
5.3.11.2.4	Test method 3 .....	48
5.3.11.2.5	Test method 4 .....	48
5.3.11.2.6	Test method 5 .....	49
5.3.11.2.7	Test method 6.....	49
5.3.12	Geo-location capability.....	50
5.3.12.1	Test conditions .....	50
5.3.12.2	Test method.....	51
<b>Annex A (normative):</b>	<b>HS Requirements and Conformance Test specifications Table</b>	
	<a href="https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50fba5fe/sist-en-301-598-v1-1-1-2014">https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50fba5fe/sist-en-301-598-v1-1-1-2014</a>	
	<b>(HS-RTT).....</b>	<b>52</b>
<b>Annex B (normative):</b>	<b>Test sites and arrangements for radiated measurement .....</b>	<b>55</b>
B.1	Radiation test sites.....	55
B.1.1	Open Area Test Site (OATS) .....	55
B.1.2	Semi Anechoic Room.....	56
B.1.3	Fully Anechoic Room (FAR) .....	57
B.1.4	Measurement Distance .....	58
B.2	Antennas.....	59
B.2.1	Measurement antenna.....	59
B.2.2	Substitution antenna .....	59
B.3	Test fixture .....	60
B.3.1	Conducted measurements and use of test fixture .....	60
B.3.2	Description of the test fixture .....	60
B.3.3	Using the test fixture for relative measurements .....	60
B.4	Guidance on the use of radiation test sites .....	60
B.4.1	Power supplies for the battery powered UUT .....	61
B.4.2	Site preparation .....	61
B.5	Coupling of signals.....	61
B.5.1	General .....	61
B.5.2	Data Signals.....	61
<b>Annex C (normative):</b>	<b>General description of measurement .....</b>	<b>62</b>
C.1	Conducted measurements.....	62
C.2	Radiated measurements.....	62

C.3	Substitution measurement .....	63
<b>Annex D:</b>	<b>Void .....</b>	<b>64</b>
<b>Annex E (informative):</b>	<b>Nominal Channel Bandwidth and Total Bandwidth .....</b>	<b>65</b>
<b>Annex F (informative):</b>	<b>Application form for testing.....</b>	<b>67</b>
F.1	Information as required by EN 301 598 V1.1.1, clause 5.3.1 .....	67
<b>Annex G (informative):</b>	<b>Bibliography.....</b>	<b>71</b>
History .....		72

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 598 V1.1.1:2014](https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50bfa5fe/sist-en-301-598-v1-1-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50bfa5fe/sist-en-301-598-v1-1-1-2014>



## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN).

The present document has been produced by ETSI in response to mandates M/284 and M/512 issued from the European Commission under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.2].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.3].

See article 5.1 of Directive 1999/5/EC [i.3] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.3] are summarized in annex A.

SIST EN 301 598 V1.1.1:2014

<https://standards.iteh.ai/catalog/standards/sist-en-301-598-v1-1-1-2014>  
**National transposition dates**  
<https://standards.iteh.ai/catalog/standards/sist-en-301-598-v1-1-1-2014>

Date of adoption of this EN:	21 April 2014
Date of latest announcement of this EN (doa):	31 July 2014
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2015
Date of withdrawal of any conflicting National Standard (dow):	31 January 2016

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.3]. The modular structure is shown in EG 201 399 [i.4].

The methods and principles used in the present document for the operation of TV White Space devices in the band 470 MHz to 790 MHz are taken from the ECC Report 186 [i.5], which explains the regulatory principles under which it is envisaged such devices will be permitted to operate in Europe. This approach is also explained in further detail in Chapter 9 of "Dynamic White Space Spectrum Access" [i.11].

A requirement to facilitate coexistence between TVWSDs is not considered essential with respect to compliance with Article 3.2 of Directive 1999/5/EC [i.3] and therefore is not included in the current version of the present document. This may change in the future, resulting in the inclusion of mitigation techniques in a revision of the present document, to improve the coexistence among TVWSDs, if considered essential in order to comply with Article 3.2 of Directive 1999/5/EC [i.3].

---

# 1 Scope

The present document applies to TV white space devices (TVWSDs) controlled by a TV white space database (TVWSDB) and which operate in the TV broadcast band 470 MHz to 790 MHz.

The present document applies to the following radio equipment types:

- 1) Master TV white space device (TVWSD)
- 2) Slave TV white space device (TVWSD)

The present document applies to TVWSDs with integral, dedicated or external antennas, where TVWSDs using external antennas are intended only for fixed use. The present document is intended to cover the provisions of Directive 1999/5/EC [i.3] (R&TTE Directive), Article 3.2, which states that "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

---

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] NIMA Technical Report TR8350.2 (1984, including amendment 1 of 03 January 2000 and amendment 2 of 23 June 2004): "Department of Defense World Geodetic System 1984. Its Definition and Relationships with Local Geodetic Systems".

NOTE: Available at <http://earth-info.nga.mil/GandG/publications/tr8350.2/wgs84fin.pdf>.

- [2] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [3] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [4] IETF RFC 4122 (05-2007): "A Universally Unique IDentifier (UUID) URN Namespace".

NOTE: Available at <http://www.ietf.org/rfc/rfc4122.txt>.

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations and of rules on Information Society services.
- [i.2] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.3] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.4] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.5] ECC Report 186: "Technical and operational requirements for the operation of white space devices under geo-location approach", January 2013.
- [i.6] ETSI TR 102 273-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.7] ETSI TR 102 273-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.8] ETSI TR 102 273-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.9] ETSI TR 103 231: "White Space Devices (WSD); Wireless Access Systems operating in the 470 MHz to 790 MHz TV broadcast band; Information on weblisting of TV White Space Databases (TVWSDBs)".
- [i.10] ECC Report 159: "Technical and operational requirements for the possible operation of cognitive radio systems in the "white spaces" of the frequency band 470-790 MHz", January 2011.
- [i.11] Dynamic White Space Spectrum Access; By William Webb and contributors.

NOTE: Available at <http://www.webbsearch.co.uk/publications/>.

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in ECC Report 159 [i.10] and the following apply:

**Adjacent Channel Leakage Ratio (ACLR):** ratio of the in-band transmit power measured in an 8 MHz TV channel, to the out-of-band emission measured in 100 kHz in an adjacent TV channel

**altitude:** height above the reference level defined by WGS84

**association:** process whereby a slave TVWSD provides its device parameters to a master TVWSD and initially identifies itself to its serving master TVWSD

**Authentication:** ability to verify the identity of a server, and that a message was truly sent by the asserted sender

**channel usage parameters:** parameters sent by a TVWSD to inform the TVWSDB of the actual radio resources that will be used by both the master and the slave TVWSDs

**dedicated antenna:** removable antenna supplied and assessed with the radio equipment, designed as an indispensable part of the equipment

**device emission class:** classification declared by the manufacturer that identifies the level of ACLR for the device

**device parameters:** parameters that specify the technical characteristics of an individual TVWSD, and its location

**Digital Terrestrial Television (DTT):** platform for the delivery of digital TV content via terrestrial broadcasting

**DTT channel:** 8 MHz channel in accordance with the European harmonized DTT channel raster

**external antenna:** removable antenna which is designed for use with a broad range of radio equipment and has not been designed for use with a specific product

NOTE: An external antenna is not assessed together with the equipment against the requirements of the present document.

**generic operational parameters:** transmission parameters communicated by a master TVWSD to any slave TVWSD within the coverage area of that master TVWSD to allow the slave TVWSD to operate as required

**geographic validity:** geographic area within which the operational parameters for a geo-located TVWSD are valid

**geo-location capability:** capability of a TVWSD to determine and report the latitude, longitude and altitude coordinates of its antenna

**geo-location uncertainty:** 3D position error defined by the difference in metres between the point reported by the TVWSD device to the TVWSDB and the actual position of the TVWSD antenna

**horizontal geo-location capability:** capability of a TVWSD to determine and report the latitude and longitude coordinates of its antenna

**in-block emissions:** intended emissions that fall within a single or multiple DTT channel(s)

**integral antenna:** antenna designed as a fixed part of the equipment, without the use of an external connector, which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable can be used.

**Integrity:** capability to protect messages against accidental or malicious changes during transit

**master operational parameters:** transmission parameters communicated from a TVWSDB to a master TVWSD to allow the master TVWSD to operate as required

**master TVWSD:** geo-located TVWSD that is able to communicate directly with a TVWSDB and with TVWSDs

**out-of-block emissions:** unwanted emissions that fall within the 470 MHz to 790 MHz band

**regulatory domains:** geographical area where a set of regulatory rules applies

NOTE: This is normally a country.

**reverse intermodulation attenuation:** measure of the capability of the transmitter to inhibit the generation of intermodulation signals in its non-linear components caused by the presence of the transmitter wanted signal and an unwanted signal reaching the transmitter via the antenna

**reverse intermodulation attenuation improvement:** measure of the improvement in reverse intermodulation attenuation beyond the minimum value required, as a function of in-block transmitter power

**slave operational parameters:** transmission parameters communicated from a TVWSDB via a master TVWSD to enable a slave TVWSD to operate as required

**slave TVWSD:** TVWSD that is only able to communicate with other TVWSDs, when under the control of a master TVWSD

**sleep mode:** mode of operation for which the TVWSD is inactive but is not powered-down

**specific operation parameters:** transmission parameters communicated from a TVWSDB to a specific TVWSD (master or slave), taking account of the device parameters of that specific TVWSD

**test equipment:** equipment that provides the means to operate and control a UUT for the purposes of testing against the requirements contained in the present document

**test master TVWSD:** test equipment that emulates the functionalities of a master TVWSD for the purposes of testing a slave TVWSD against the requirements contained in the present document

**test slave TVWSD:** test equipment that emulates the functionalities of a slave TVWSD for the purposes of testing a master TVWSD against the requirements contained in the present document

**test white space database:** test equipment that emulates the functionalities of a TVWSDB for the purposes of testing a TVWSD against the requirements contained in the present document

**time validity:** period of time when a set of operational parameters is valid, determined by the  $T_{ValStart}$  and  $T_{ValEnd}$  parameters contained in the said operational parameter set

**TV white spaces:** frequencies within the 470 MHz to 790 MHz band which have been identified by a TVWSDB for use by a TVWSD

**TV White Space Database (TVWSDB):** database system approved by the relevant national regulatory authority which can communicate with TVWSDs and provide information on TV white space availability

**TV White Space Device (TVWSD):** TVWSD controlled by a TVWSDB and which operates in TV white spaces

**UHF TV band:** 470 MHz to 790 MHz band

NOTE: This corresponds to DTT channels 21 to 60.

**vertical geo-location capability:** capability of a TVWSD to determine and report the altitude of its antenna

**weblisting:** publically available Internet listing of approved TVWSDB(s) relevant to a regulatory domain, and which is hosted by, or on behalf of the national regulatory authority for that regulatory domain

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$A_{ch}$	Number of active transmit chains
dB	decibel
dBc	decibel relative to carrier
dBm	decibel relative to 1 milliwatt
$f$	Frequency of measurement
$f_c$	Centre frequency of the assigned channel
$f_{l,i}$	Frequency at the lower edge of the $i^{th}$ channel
$f_{u,i}$	Frequency at the upper edge of the $i^{th}$ channel
$f_{un}$	Centre frequency of the unwanted signal
$f_w$	Centre frequency of the wanted signal
$P_{0,i}$	Maximum mean EIRP in a given ( $i^{th}$ ) 100 kHz channel
$P_{1,i}$	Maximum mean EIRP in a given ( $i^{th}$ ) 8 MHz channel
$P_{IB}$	Measured in block EIRP spectral density over 8 MHz
$P_{IBk}$	An intermediate ( $k^{th}$ ) value of $P_{IB}$
$P_{IBMax}$	Maximum value of $P_{IB}$
PIM3	Power of the third order intermodulation product at frequency $(2 \times f_w - f_{un})$ , measured in a 100 kHz bandwidth
$P_{OOB}$	Mean out of block EIRP spectral density
$P_{0,i}$	In-block EIRP spectral density (dBm/100 kHz) which a TVWSD intends to use within each DTT channel
$P_{1,i}$	In-block EIRP which a TVWSD intends to use within each (8 MHz) DTT channel
RIM3	third order reverse intermodulation attenuation
$\Delta RIM3$	Improvement in the third order reverse intermodulation attenuation (RIM3)

T <sub>Dur</sub>	Time duration of the operational parameters
T <sub>ValEnd</sub>	Absolute time of the end of the period of validity of the operational parameters
T <sub>ValStart</sub>	Absolute time of the start of the period of validity of the operational parameters

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
ACLR	Adjacent Channel Leakage Ratio
BW	Bandwidth
DC	Direct Current
DHCP	Dynamic Host Configuration Protocol
DNS	Domain Name System
DTT	Digital Terrestrial Television
EIRP	Equivalent Isotropically Radiated Power
FAR	Fully Anechoic Room
GHz	GigaHertz
GNSS	Global Navigation Satellite System
IEEE	Institute of Electrical and Electronics Engineers
IETF	Internet Engineering Task Force
IP	Internet Protocol
LPDA	Logarithmic Periodic Dipole Antenna
MAC	Media Access Control
MHz	MegaHertz
OATS	Open Area Test Site
OUI	Organizationally Unique Identifier
R&TTE	Radio equipment and Telecommunications Terminal Equipment
RBW	Resolution Bandwidth
RF	Radio Frequency
RMS	Root Mean Square
SAR	Semi Anechoic Room <a href="#">SIST EN 301 598 V1.1.1:2014</a>
TE	Test Equipment <a href="#">standards.iteh.ai/catalog/standards/sist/58610dd9-18dd-4991-b90f-dda50fba5fe/sist-en-301-598-v1-1-1-2014</a>
TV	Television <a href="#">dda50fba5fe/sist-en-301-598-v1-1-1-2014</a>
TVWSD	TV White Space Device
TVWSDB	TV White Space Database
UE	User Equipment
UHF	Ultra High Frequency
UUID	Universally Unique Identifier
UUT	Unit Under Test
VSWR	Voltage Standing Wave Ratio

---

## 4 Technical requirements specifications

### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared normal and extreme operating conditions.

### 4.2 Conformance requirements

To meet the essential requirements under article 3.2 of the R&TTE Directive [i.3] the essential parameters have been identified. Table A.1 provides a cross reference between these essential parameters and the corresponding technical requirements for equipment within the scope of the present document. To fulfil an essential parameter the compliance with all the corresponding technical requirements in table A.1 shall be verified.

Where the technical requirements in the present document do not contain values for the operating limits, these values will be supplied individually by the TVWSDB according to national regulations.

## 4.2.1 Equipment types

For the purpose of the present document, two equipment types have been defined.

NOTE: It is envisaged that a TVWSD which is not fixed, will operate with an integral or dedicated antenna.

### 4.2.1.1 Equipment Type A

A Type A TVWSD is a device that is intended for fixed use only. This type of equipment can have integral, dedicated or external antennas.

### 4.2.1.2 Equipment Type B

A Type B TVWSD is a device that is not intended for fixed use and which has an integral antenna or a dedicated antenna.

The equipment and the antenna shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

In the case of dedicated antennas, the manufacturer has to specify the antennas that have been assessed together with the equipment against the requirements of the present document. That information shall be included in the user documentation. The use of other antennas is prohibited.

## 4.2.2 Nominal Channel Bandwidth and Total Nominal Channel Bandwidth

### 4.2.2.1 Definition

A Nominal Channel is defined as one or more contiguous DTT channels that are used by a TVWSD for its wanted transmissions.

The Nominal Channel Bandwidth is the bandwidth of a Nominal Channel. The Nominal Channel Bandwidth is a multiple of 8 MHz.

The Total Nominal Channel Bandwidth is the sum of all of the Nominal Channel Bandwidths used simultaneously by a TVWSD.

NOTE: A TVWSD may operate in a single DTT channel, or it may operate simultaneously in a group of contiguous DTT channels, multiple non-contiguous DTT channels, or a mixture of contiguous and non-contiguous DTT channels. See the examples in annex E.

### 4.2.2.2 Requirements

The lower and upper edge frequencies of a nominal channel shall coincide with the European harmonized DTT channel raster shown in figure 1.

<b>DTT channel raster (MHz)</b>	470 to 478	478 to 486	486 to 494	...	766 to 774	774 to 782	782 to 790
<b>DTT channel numbers</b>	21	22	23	...	58	59	60

**Figure 1: European harmonized DTT channel raster**

The Nominal Channel Bandwidth used by a TVWSD shall not exceed the Maximum Nominal Channel Bandwidth specified by the TVWSDB (see clause 4.2.6.2.1.2).

The Total Nominal Channel Bandwidth used by a TVWSD shall not exceed the Maximum Total Nominal Channel Bandwidth specified by the TVWSDB (see clause 4.2.6.2.1.2).