# INTERNATIONAL STANDARD



First edition 2004-05-15

# Information technology — Participant identifiers

Technologies de l'information — Identificateurs de participant

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/IEC 24703:2004</u> https://standards.iteh.ai/catalog/standards/sist/2238066a-e56b-41d6-ab34-0332e4c4961d/iso-iec-24703-2004



Reference number ISO/IEC 24703:2004(E)

#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/IEC 24703:2004</u> https://standards.iteh.ai/catalog/standards/sist/2238066a-e56b-41d6-ab34-0332e4c4961d/iso-iec-24703-2004

© ISO/IEC 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

### Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 24703 was prepared by Joint Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee SC 36, Information technology for learning, education and training.

### (standards.iteh.ai)

<u>ISO/IEC 24703:2004</u> https://standards.iteh.ai/catalog/standards/sist/2238066a-e56b-41d6-ab34-0332e4c4961d/iso-iec-24703-2004

### Introduction

The purpose of this International Standard is to define the datatype of an identifier for the purposes of identifying participants in learning, education and training. Participants may be users, teachers, agents, groups, organizations, institutions, etc.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/IEC 24703:2004</u> https://standards.iteh.ai/catalog/standards/sist/2238066a-e56b-41d6-ab34-0332e4c4961d/iso-iec-24703-2004

### Information technology — Participant identifiers

#### 1 Scope

This International Standard specifies the datatype of participant identifiers in learning, education and training. Security and protection of personal data associated with the use of a participant identifier is not addressed in this standard. The naming policy, registration, and authentication of participant identifiers are outside the scope of this International Standard.

NOTE There is a risk of improper access and misuse of personal and private data facilitated by the use of a participant identifier. It is the responsibility of the implementer to ensure proper use of a participant identifier.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 2382-1, Information technology Docabulary Dealt 1. Fundamental terms

ISO/IEC 10646-1, Information technology <u>ISO Universal Mult</u>iple-Octet Coded Character Set (UCS) — Part 1: Architecture and Basic Multilingual Plane talog/standards/sist/2238066a-e56b-41d6-ab34-

0332e4c4961d/iso-iec-24703-2004

ISO/IEC TR 10176, Information technology — Guidelines for the preparation of programming language standards

ISO/IEC 11404, Information technology — Programming languages, their environments and system software interfaces — Language-independent datatypes

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 2382-1 and the following apply.

#### 3.1

#### abstract character

character of the ISO/IEC 10646-1 repertoire (UCS) that is independent of encoding

#### 3.2

binding

application or mapping from one framework or specification to another

#### 3.3

#### datatype

set of distinct values, characterized by properties of those values and by operations on those values

#### 3.4

encoding

bit and byte format and representation of information

#### 3.5

#### implementation-defined behaviour

unspecified behaviour where each implementation documents how the choice is made

#### 3.6

#### participant identifier

designation associated with a participant

NOTE A participant may have more than one participant identifier — a non-singular identifier. The policy of singularity or non-singularity of identifiers is outside the scope of this International Standard.

#### 3.7

#### participant information

data that is primarily associated with, tracked by, tracked for, and about participants in information technology systems

#### 3.8

smallest permitted maximum SPM

smallest maximum value for a requirement provision

EXAMPLE The smallest permitted maximum length of field X shall be 25.

#### 3.9

UCS

universal character set character set defined by ISO/IEC 10646-1 (standards.iteh.ai)

#### 3.10

#### unspecified behaviour

implementation behaviour for which a standard provides two or more possibilities and imposes no further requirements on which possibility is chosen in any instance ds/sist/2238066a-e56b-41d6-ab34-0332e4c4961d/iso-iec-24703-2004

#### 4 Conformance

A conforming participant identifier shall conform to the requirements specified in: Clause 5, Clause 6, Clause 7, at least one binding of Clause 8 and Clause 9.

#### 5 Functionality

A participant identifier shall represent a designator.

NOTE More than one participant identifier may be associated with an individual participant.

A participant identifier shall be a printable text string that should facilitate transcription by humans.

EXAMPLE A 10-character string of digits is easier to transcribe than a 256-character string of mixed-case Latin characters.

#### 6 Conceptual model

A participant identifier is a string of abstract characters that is associated with a participant. Conceptually, the participant identifier is "opaque" in that the string contains no information itself, e.g., "35267901" has no particular meaning. Some implementations and administrators may choose participant identifiers that convey information, e.g., "doe.john", and some participant identifiers may contain even more information, e.g., "building2--doe.john".

A participant identifier may be used in several contexts, such as being embedded into filenames, URLs, or E-mail addresses. Within information technology systems that manage participant information, participant identifiers may be used to link repositories to provide common and/or consolidated identification methods.

#### 7 Semantics

#### 7.1 Components of a participant identifier

A participant identifier shall consist of identifier segments separated by segment separators. An identifier segment shall consist of identifier characters from the abstract character set. A segment separator shall be implementation-defined, but the period character "." is recommended.

#### 7.2 ISO/IEC 11404 datatype definition

The following datatype, given in ISO/IEC 11404 notation, defines the participant identifier:

```
characterstring(ISO/IEC-10646-1)
```

The smallest permitted maximum length of a participant identifier shall be 50 abstract characters.

NOTE The parameter "ISO/IEC-10646-1" identifies that abstract character repertoire, not its encoding.

## 7.3 Allowable abstract characters NDARD PREVIEW

The abstract characters of a participant identifier shall be limited to the following set. The characters are named by their 16-bit hexadecimal name within the Basic Multilingual Plane of UCS. This subset of abstract characters is based on ISO/IEC TR 10176.

#### ISO/IEC 24703:2004

7.3.1 Identifier characters dards.iteh.ai/catalog/standards/sist/2238066a-e56b-41d6-ab34-

0332e4c4961d/iso-iec-24703-2004

The following are non-digit, non-special abstract characters:

- Latin: 0041-005A, 0061-007A, 00AA, 00BA, 00C0-00D6, 00D8-00F6, 00F8-01F5, 01FA-0217, 0250-02A8, 1E00-1E9B, 1EA0-1EF9, 207F
- Greek: 0386, 0388-038A, 038C, 038E-03A1, 03A3-03CE, 03D0-03D6, 03DA, 03DC, 03DE, 03E0, 03E2-03F3, 1F00-1F15, 1F18-1F1D, 1F20-1F45, 1F48-1F4D, 1F50-1F57, 1F59, 1F5B, 1F5D, 1F5F-1F7D, 1F80-1FB4, 1FB6-1FBC, 1FC2-1FC4, 1FC6-1FCC, 1FD0-1FD3, 1FD6-1FDB, 1FE0-1FEC, 1FF2-1FF4, 1FF6-1FFC
- Cyrillic: 0401-040C, 040E-044F, 0451-045C, 045E-0481, 0490-04C4, 04C7-04C8, 04CB-04CC, 04D0-04EB, 04EE-04F5, 04F8-04F9
- Armenian: 0531-0556, 0561-0587
- Hebrew: 05B0-05B9, 05BB-05BD, 05BF, 05C1-05C2, 05D0-05EA, 05F0-05F2
- Arabic: 0621-063A, 0640-0652, 0670-06B7, 06BA-06BE, 06C0-06CE, 06D0-06DC, 06E5-06E8, 06EA-06ED
- Devanagari: 0901-0903, 0905-0939, 093E-094D, 0950-0952, 0958-0963
- Bengali: 0981-0983, 0985-098C, 098F-0990, 0993-09A8, 09AA-09B0, 09B2, 09B6-09B9, 09BE-09C4, 09C7-09C8, 09CB-09CD, 09DC-09DD, 09DF-09E3, 09F0-09F1

- Gurmukhi: 0A02, 0A05-0A0A, 0A0F-0A10, 0A13-0A28, 0A2A-0A30, 0A32-0A33, 0A35-0A36, 0A38-0A39, 0A3E-0A42, 0A47-0A48, 0A4B-0A4D, 0A59-0A5C, 0A5E, 0A74
- Gujarati: 0A81-0A83, 0A85-0A8B, 0A8D, 0A8F-0A91, 0A93-0AA8, 0AAA-0AB0, 0AB2-0AB3, 0AB5-0AB9, 0ABD-0AC5, 0AC7-0AC9, 0ACB-0ACD, 0AD0, 0AE0
- Oriya: 0B01-0B03, 0B05-0B0C, 0B0F-0B10, 0B13-0B28, 0B2A-0B30, 0B32-0B33, 0B36-0B39, 0B3E-0B43, 0B47-0B48, 0B4B-0B4D, 0B5C-0B5D, 0B5F-0B61
- Tamil: 0B82-0B83, 0B85-0B8A, 0B8E-0B90, 0B92-0B95, 0B99-0B9A, 0B9C, 0B9E-0B9F, 0BA3-0BA4, 0BA8-0BAA, 0BAE-0BB5, 0BB7-0BB9, 0BBE-0BC2, 0BC6-0BC8, 0BCA-0BCD
- Telugu: 0C01-0C03, 0C05-0C0C, 0C0E-0C10, 0C12-0C28, 0C2A-0C33, 0C35-0C39, 0C3E-0C44, 0C46-0C48, 0C4A-0C4D, 0C60-0C61
- Kannada: 0C82-0C83, 0C85-0C8C, 0C8E-0C90, 0C92-0CA8, 0CAA-0CB3, 0CB5-0CB9, 0CBE-0CC4, 0CC6-0CC8, 0CCA-0CCD, 0CDE, 0CE0-0CE1
- Malayalam: 0D02-0D03, 0D05-0D0C, 0D0E-0D10, 0D12-0D28, 0D2A-0D39, 0D3E-0D43, 0D46-0D48, 0D4A-0D4D, 0D60-0D61
- Thai: 0E01-0E3A, 0E40-0E5B
- Lao: 0E81-0E82, 0E84, 0E87-0E88, 0E8A, 0E8D, 0E94-0E97, 0E99-0E9F, 0EA1-0EA3, 0EA5, 0EA7, 0EAA-0EAB, 0EAD-0EAE, 0EB0-0EB9, 0EBB-0EBD, 0EC0-0EC4, 0EC6, 0EC8-0ECD, 0EDC-0EDD
- Tibetan: 0F00, 0F18-0F19, 0F35, 0F37, 0F39, 0F3E-0F47, 0F49-0F69, 0F71-0F84, 0F86-0F8B, 0F90-0F95, 0F97, 0F99-0FAD, 0FB1-0FB7, 0FB9
- Georgian: 10A0-10C5, 10D0-10F6
  ISO/IEC 24703:2004
  https://standards.iteh.ai/catalog/standards/sist/2238066a-e56b-41d6-ab34 Uiragapa: 2041 2003 200P 200C
  0332e4c4961d/iso-iec-24703-2004
- Hiragana: 3041-3093, 309B-309C
- Katakana: 30A1-30F6, 30FB-30FC
- Bopomofo: 3105-312C
- CJK Unified Ideographs: 4E00-9FA5
- Hangul: AC00-D7A3

#### 7.3.2 Identifier digits

The following are digit characters:

Digits: 0030-0039, 0660-0669, 06F0-06F9, 0966-096F, 09E6-09EF, 0A66-0A6F, 0AE6-0AEF, 0B66-0B6F, 0BE7-0BEF, 0C66-0C6F, 0CE6-0CEF, 0D66-0D6F, 0E50-0E59, 0ED0-0ED9, 0F20-0F33

#### 7.3.3 Identifier special characters

The following are special characters:

Special characters: 005F, 00B5, 00B7, 02B0-02B8, 02BB, 02BD-02C1, 02D0-02D1, 02E0-02E4, 037A, 0559, 093D, 0B3D, 1FBE, 203F-2040, 2102, 2107, 210A-2113, 2115, 2118-211D, 2124, 2126, 2128, 212A-2131, 2133-2138, 2160-2182, 3005-3007, 3021-3029

#### 7.4 Encoding characters

The following characters define the set of encoding characters.

NOTE 1 The selection of characters is intended to be harmonized with IETF RFC 2396.

NOTE 2 The percent character "%" is used in the encoding of a participant identifier, but it is not part of the "encoding character set".

#### 8 Bindings

#### 8.1 Data instance

An instance of a participant identifier shall be encoded as an array of octets.

#### 8.2 C, C++ binding

### iTeh STANDARD PREVIEW

Applications and environments that claim conformance within a C/C++ language translation system shall use the "char" base type (or compatible) for structures, pointers, arrays, and function parameters that store a participant identifier.

NOTE If the 7-bit encoding is used for the C/C++ translation environment, the smallest permitted maximum requirement implies that the participant identifier must be at least 501 chars long: ("%0" + 8 hex digits) \* 50 + 1 terminating null character.

An instance of a participant identifier shall be encoded as an array of octets.

#### 8.3 Java binding

Applications and environments that claim conformance within a Java language translation system shall use the "string" type (or compatible) for classes, arrays, and method parameters that store a participant identifier.

#### 8.4 ECMAScript (JavaScript) binding

Applications and environments that claim conformance within an ECMAScript (JavaScript) language translation system shall use the "string" type (or compatible) for arrays and function parameters that store a participant identifier.

#### 9 Encodings

All bindings shall use the encodings specified in this clause.

NOTE 1 Applications and user interfaces may allow entry and display of these participant identifiers in forms that are more natural to humans, e.g., a login screen for a Japanese user might only show Kanji characters, meanwhile the application converts these Kanji characters to/from the participant identifier encoding format.