



SLOVENSKI STANDARD
SIST EN 14052:2012+A1:2012
01-december-2012

Industrijske čelade z visoko stopnjo zaščite

High performance industrial helmets

Hochleistungs-Industrieschutzhelme

Casques de protection à haute performance pour l'industrie

Ta slovenski standard je istoveten z: EN 14052:2012+A1:2012

[SIST EN 14052:2012+A1:2012](https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012)

<https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012>

ICS:

13.340.20 Varovalna oprema za glavo Head protective equipment

SIST EN 14052:2012+A1:2012 en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 14052:2012+A1:2012](https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012)

<https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 14052:2012+A1

October 2012

ICS 13.340.20

Supersedes EN 14052:2012

English Version

High performance industrial helmets

Casques de protection à haute performance pour l'industrie

Hochleistungs-Industrieschutzhelme

This European Standard was approved by CEN on 17 December 2011 and includes Amendment 1 approved by CEN on 19 July 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

(standards.iteh.ai)

[SIST EN 14052:2012+A1:2012](https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012)

<https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Physical requirements	7
4.1 General.....	7
4.2 Materials and construction	7
4.2.2 Visual inspection	8
4.3 Chin strap	8
5 Performance requirements	8
5.1 General.....	8
5.2 Mandatory requirements	8
5.2.1 Shock absorption.....	8
5.2.2 Resistance to penetration	8
5.2.3 Retention system release	9
5.2.4 Retention system effectiveness	9
5.2.5 Flame resistance.....	9
5.2.6 Label.....	9
5.3 Optional requirements	9
5.3.1 Performance at lower temperatures	9
5.3.2 Performance at higher temperature	9
5.3.3 Resistance to radiant heat	9
5.3.4 Electrical properties	10
5.3.5 Molten metal splash	10
6 Testing	10
6.1 Samples	10
6.2 Conditions and conditioning for testing	11
6.2.1 General.....	11
6.2.2 Low temperature	12
6.2.3 High temperature	12
6.2.4 Water immersion.....	12
6.2.5 Artificial ageing	12
6.2.6 Lower temperature.....	12
6.2.7 Higher temperature.....	12
6.2.8 Radiant heat	14
6.3 Headforms	14
6.3.1 Construction.....	14
6.3.2 Selection of size.....	14
6.4 Shock absorption.....	14
6.5 Resistance to penetration	15
6.6 Retention system release	16
6.7 Retention system effectiveness	16
6.8 Resistance to flame	16
6.9 Resistance to radiant heat	16
6.10 Electrical properties	17
6.11 Molten metal splash	17
6.11.1 Principle.....	17

6.11.2	Apparatus	17
6.11.3	Procedure	17
7	Marking and information to be supplied by the manufacturer	17
7.1	Markings on the helmet	17
7.2	Additional information supplied by the manufacturer	18
7.2.1	Information to be supplied on a label.....	18
7.2.2	Additional information	18
Annex A	(informative) Comfort.....	20
Annex B	(informative) Test results, uncertainty of measurement	21
B.1	Uncertainty of measurement.....	21
B.2	Interpretation of results	21
B.3	Calculation of uncertainty of measurement	22
Annex C	(informative) Significant technical changes between this European Standard and EN 14052:2005	23
Annex ZA	(informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC Personal Protective Equipment.....	24
Bibliography	25

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 14052:2012+A1:2012](https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012)

[https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-
da45d84d5771/sist-en-14052-2012a1-2012](https://standards.iteh.ai/catalog/standards/sist/e54c6d8b-adda-435c-a524-da45d84d5771/sist-en-14052-2012a1-2012)

EN 14052:2012+A1:2012 (E)**Foreword**



This document (EN 14052:2012+A1:2012) has been prepared by Technical Committee CEN/TC 158 “Head protection”, the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2013, and conflicting national standards shall be withdrawn at the latest by April 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 19 July 2012.

This document supersedes  EN 14052:2012 .

The start and finish of text introduced or altered by amendment is indicated in the text by tags  .

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

Annex C provides details of significant technical changes between this European Standard and the previous edition.

[SIST EN 14052:2012+A1:2012](http://standards.iteh.ai/catalog/standards/sist/e54c6d8b-9dda-435c-a524-da45d84d5771/sist-en-14052-2012-a1-2012)

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Advances in materials and design methods have allowed helmets to be developed that have a higher performance than other types of general industrial helmets.

Helmets complying with European Standards offer a suite of head protection devices for general industrial use:

- the industrial bump cap meeting the requirements of EN 812,
- the industrial safety helmet meeting the requirements of EN 397, and
- the high performance industrial helmet meeting the requirements of EN 14052.

Industrial bump caps are intended to provide protection to the wearer against the effects of striking his head against hard, stationary objects with sufficient severity to cause lacerations or other superficial injuries. They are not intended to provide protection against the effects of falling or thrown objects, or moving or suspended loads. In addition to the mandatory requirements the caps may have shock absorption properties at low temperatures, be flame resistant and have electrical properties.

Industrial safety helmets are intended primarily to provide protection to the wearer against falling objects and are not intended to provide protection against off crown impacts. The mandatory requirements for the helmets includes for them to have flame resistant properties. In addition to the mandatory requirements the helmets may have shock absorption properties at very low temperatures and very high temperatures, have electrical insulation properties, have lateral deformation properties, and provide protection against molten metal splash.

The high performance industrial helmet offers greater protection from falling objects, protection from off crown impacts and protection from penetration by a flat blade striker. It also includes a retention system that meets mandatory requirements for system release and system effectiveness properties. The helmet has the same flame resistant properties as the industrial safety helmet and offers the same optional protection against other risks with the exception of lateral deformation.

The technical committee, which has prepared this European Standard, realizes that mechanical rigidity is of importance for the wearer's safety. At the time, the standard was prepared no valid test method was recognized. For that reason, no requirements concerning mechanical rigidity have been introduced.

Designers are encouraged to accommodate ear, eye, and respiratory protection into the helmet design where required. When possible the design and performance of such additional protective functions should be in accordance with the relevant European Standard for these products. When this is not possible, the manufacturer will draw attention to any compromises by means of information supplied with the helmet.

The wearing of a helmet meeting the requirements of this European Standard will reduce, but not eliminate, the likelihood of head injury. There are limits to the amount of protection that can be provided. In the workplace, it remains the responsibility of the employer to judge the helmet's suitability for their particular purpose.

EN 14052:2012+A1:2012 (E)**1 Scope**

This European Standard specifies physical, performance, test and marking requirements for high performance industrial helmets.

High performance industrial helmets, as specified in this European Standard, are intended to provide to the wearer protection against falling objects and off crown impacts and the consequential brain injury, skull fracture and neck injury.

This European Standard includes mandatory requirements that apply to all high performance industrial helmets and additional, optional, performance requirements that apply only where specifically claimed by the helmet manufacturer.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 960:2006, *Headforms for use in the testing of protective helmets*

EN 13087-1, *Protective helmets — Test methods — Part 1: Conditions and conditioning*

EN 13087-2, *Protective helmets — Test methods — Part 2: Shock absorption*

EN 13087-3, *Protective helmets — Test methods — Part 3: Resistance to penetration*

EN 13087-5:2012, *Protective helmets — Test methods — Part 5: Retention system strength*

EN 13087-7, *Protective helmets — Test methods — Part 7: Flame resistance*

EN 13087-8, *Protective helmets — Test methods — Part 8: Electrical properties*

EN 13087-10, *Protective helmets — Test methods — Part 10: Resistance to radiant heat*

EN ISO 472, *Plastics — Vocabulary (ISO 472:1999)*

EN ISO 9185:2007, *Protective clothing — Assessment of resistance of materials to molten metal splash (ISO 9185:2007)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1**high performance industrial helmet**

head protector, hereinafter referred to as 'helmet', primarily intended to provide the wearer with protection against falling objects and of crown impacts

Note 1 to entry: The helmet may incorporate additional protective functions.

3.2**retention system**

complete assembly by means of which the helmet is maintained in position on the head, including any devices for adjusting the system or enhancing the wearer's comfort

A1 Note 1 to entry: **A1** The retention system may include a chin strap.

3.3

chin strap

part of the retention system, consisting of a strap which fits under the chin to help secure the helmet on the head

3.4

crown

area on the upper outside surface of the helmet which lies within a 30° included solid angle from point G (as defined in EN 960:2006, 2.12) on the central vertical axis through the headform to which the helmet is fitted

3.5

integral additional protective function

part(s) of the helmet, intended by the helmet manufacturer not to be removed by the user, except for maintenance purposes, and which provide protection to the wearer, other than as provided for by this European Standard

3.6

non-integral additional protective function

additional protective device(s) which may be attached to the helmet and are intended to be removable by the user, but are not specifically required in order for the helmet to satisfy this European Standard

3.7

helmet accessory

additional device(s) which may be attached to the helmet and are intended to be removable by the user, but which provide no protective function to the wearer

3.8

helmet type

category of helmets which does not differ in such essential respects as the materials, dimensions or construction of the helmet or the retention system

4 Physical requirements

4.1 General

Unless otherwise specified, the values stated in this European Standard are expressed as nominal values. Except for temperature limits, values that are not stated as maxima or minima shall be subject to a tolerance of $\pm 5\%$. Unless otherwise specified, the temperature values shall be in accordance with EN 13087-1.

4.2 Materials and construction

4.2.1 Innocuousness

For those parts of the helmet that come into contact with the skin, materials shall not be used which are known to be likely to cause skin irritation or any adverse effect on health.

Substances recommended for cleaning, maintenance or disinfection shall have no adverse effect on the helmet and shall be known not to be likely to have any adverse effect upon the wearer, when applied in accordance with the helmet manufacturer's instructions. See 7.2.2 f).

Information claiming that the product is innocuous shall be checked.

The following are examples of documents that shall be examined:

EN 14052:2012+A1:2012 (E)

- a) materials specifications;
- b) safety data sheets relating to the materials;
- c) information relating to the suitability of the materials for use with food, in medical devices, or other relevant applications;
- d) information relating to toxicological, allergenic, carcinogenic, toxic to reproduction, or mutagenic investigations on the materials.

4.2.2 Visual inspection

There shall be no sharp edges, roughness or projection on any parts of the helmet which are in contact, or potential contact, with the wearer, when the helmet is worn, such as is likely to cause injury to the wearer.

Any part of the helmet that can be adjusted, or removed by the wearer for the purpose of replacement (in accordance with the helmet manufacturer's instructions, see 7.2), shall be so designed and manufactured as to facilitate adjustment, removal and attachment without the use of tools.

Any adjustment system incorporated within the helmet shall be so designed and manufactured as not to become incorrectly adjusted without the wearer's knowledge under the foreseeable conditions of use.

NOTE Recommendations regarding wearer comfort are given in Annex A.

4.3 Chin strap

Any chin strap supplied with the helmet shall be no less than 10 mm wide when un-tensioned.

NOTE A chin strap can be an essential part of the helmet, required to retain the helmet on the head. This will be specified by the helmet manufacturer and indicated by the markings on the helmet and in the manufacturer's information (see Clause 7).

5 Performance requirements**5.1 General**

Helmets shall be tested with all integral additional protective functions (3.5) fitted. When non-integral additional protective functions (3.6) or helmet accessories (3.7) are submitted with the helmet for test, the helmet shall satisfy the requirements of this European Standard with and without these items fitted.

5.2 Mandatory requirements**5.2.1 Shock absorption**

When a helmet is tested in accordance with 6.4, the force transmitted to the headform shall not exceed 5,0 kN for an impact to the crown and the deceleration of the striker shall not exceed 300 g for off-crown impacts.

5.2.2 Resistance to penetration

When a helmet is tested in accordance with 6.5, the point of the striker shall not contact the headform, nor shall the force transmitted to the headform exceed 5,0 kN for an impact to the crown or 15,0 kN for off-crown impacts.

5.2.3 Retention system release

If the helmet is fitted with a chin strap, it shall be tested in accordance with 6.6 and the artificial jaw shall be released at a force of no less than 150 N and no more than 250 N.

5.2.4 Retention system effectiveness

The helmet shall not become removed from the headform during the shock absorption and resistance to penetration tests (6.4 and 6.5).

When tested in accordance with 6.7, the helmet shall not fall off the head of more than two test subjects.

5.2.5 Flame resistance

When tested in accordance with 6.8, the materials tested shall not burn with the emission of flame after a period of 5 s has elapsed after removal of the flame.

5.2.6 Label

The label(s) which may be attached to the helmet in accordance with 7.1.2, shall remain attached and legible on each sample helmet, following the appropriate conditioning in accordance with 6.2.2 or where applicable 6.2.6, 6.2.3 or where applicable 6.2.7, 6.2.4, 6.2.5, and where applicable 6.2.8.

5.3 Optional requirements

5.3.1 Performance at lower temperatures

When tested for shock absorption in accordance with 6.4, the requirement given in 5.2.1 shall be satisfied by two helmets which have been conditioned in accordance with 6.2.6.

When tested for penetration in accordance with 6.5, the requirement given in 5.2.2 shall be satisfied by two helmets which have been conditioned in accordance with 6.2.6.

Helmets claimed to meet this requirement shall state this fact on the label attached to the helmet in accordance with 7.1.2.

5.3.2 Performance at higher temperature

When tested for shock absorption in accordance with 6.4, the requirement given in 5.2.1 shall be satisfied by two helmets which have been conditioned in accordance with 6.2.7.

When tested for penetration in accordance with 6.5, the requirement given in 5.2.2 shall be satisfied by two helmets which have been conditioned in accordance with 6.2.7.

Helmets claimed to meet this requirement shall state this fact on the label attached to the helmet in accordance with 7.1.2.

5.3.3 Resistance to radiant heat

When tested for shock absorption in accordance with 6.4, the requirement given in 5.2.1 shall be satisfied by two helmets which have been conditioned in accordance with 6.2.8.

When tested for penetration in accordance with 6.5, the requirement given in 5.2.2 shall be satisfied by two helmets which have been conditioned in accordance with 6.2.8.