

SLOVENSKI STANDARD oSIST prEN 14791:2015

01-januar-2015

Emisije nepremičnih virov - Določevanje masne koncentracije žveplovih dioksidov - Standardna referenčna metoda

Stationary source emissions - Determination of mass concentration of sulphur oxides - Standard reference method

Emissionen aus stationären Quellen - Bestimmung der Massenkonzentration von Schwefeloxiden - Standardreferenzverfahren

Emissions de sources fixes - Détermination de la concentration massique des oxydes de soufre - Méthode de référence normalisée

Ta slovenski standard je istoveten z: prEN 14791

https://standards.iteh.ai/catalog/standards/sist/f5ebf720-489f-4396-8ebd-039eb67f1974/sist-en-14791-2017

ICS:

13.040.40 Emisije nepremičnih virov

Stationary source emissions

oSIST prEN 14791:2015

en,fr,de



iTeh Standards (https://standards.iteh.ai) Document Preview

<u>SIST EN 14791:2017</u> https://standards.iteh.ai/catalog/standards/sist/f5ebf720-489f-4396-8ebd-039eb67f1974/sist-en-14791-2017



EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

DRAFT prEN 14791

October 2014

ICS 13.040.40

Will supersede EN 14791:2005

English Version

Stationary source emissions - Determination of mass concentration of sulphur oxides - Standard reference method

Emissions de sources fixes - Détermination de la concentration massique des oxydes de soufre - Méthode de référence normalisée Emissionen aus stationären Quellen - Bestimmung der Massenkonzentration von Schwefeloxiden -Standardreferenzverfahren

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 264.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.

https://standards.iteh.ai/catalog/standards/sist/f5ebf720-489f-4396-8ebd-039eb67f1974/sist-en-14791-2017



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2014 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. prEN 14791:2014 E

oSIST prEN 14791:2015

prEN 14791:2014 (E)

Contents

Forewo	ord	3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Symbols and abbreviated terms	9
5	Measuring principle	10
6	Description of measuring equipment	11
7	Performance characteristics of the SRM	16
8	Sampling procedure	19
9	Analytical procedure	22
10	Expression of results	26
11	Equivalence of Thorin and ion chromatography methods	28
12	Equivalence with an alternative method	28
13	Test report iTeh Standards	29
Annex Annex	A (informative) Type of sampling equipment B (informative) Examples of absorbers	30 31
Annex	C (informative) Evaluation of the method in the field	32
Annex	D (informative) Example of assessment of compliance or reference method for SO ₂ with requirements on emission measurements	39
Annex	E (informative) Test of equivalency of Thorin method and ion chromatography	46
Annex	F (informative) Calculation of the uncertainty associated with a concentration expressed on dry gas and at a oxygen reference concentration	52
Annex	G (informative) Significant technical changes	56
Bibliog	Jraphy	57

Foreword

This document (prEN 14791:2014) has been prepared by Technical Committee CEN/TC 264 "Air quality", the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 14791:2005.

Annex G provides details of significant technical changes between this document and the previous edition.

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>SIST EN 14791:2017</u> https://standards.iteh.ai/catalog/standards/sist/f5ebf720-489f-4396-8ebd-039eb67f1974/sist-en-14791-2017

1 Scope

This European Standard specifies the standard reference method (SRM) for the determination of the sulphuric oxide SO_2 in flue gases emitted to the atmosphere from ducts and stacks. It is based on a sampling system and two analytical principles: ion chromatography and the Thorin method.

This European Standard specifies the performance characteristics to be determined and the performance criteria to be fulfilled by measuring systems based on the measurement method. It applies to periodic monitoring and to the calibration or control of automatic measuring systems (AMS) permanently installed on a stack, for regulatory or other purposes.

This European Standard specifies criteria for demonstration of equivalence of an alternative method to the SRM by application of prEN 14793.

This European Standard has been evaluated during field tests on waste incineration, co-incineration and large combustion installations. It has been validated for sampling periods of 30 min in the range of 0.5 mg/m^3 to 2 000 mg/m³ of SO₂ for an ion-chromatography variant and 5 mg/m³ to 2 000 mg/m³ of SO₂ for the Thorin method according to emission limit values laid down in the Directive 2010/75/EC.

The limit values of EU Directives are expressed in units of mg/m^3 of SO₂ on dry basis and at standard conditions of 273 K and 101,3 kPa.

NOTE The characteristics of installations, the conditions during field tests and the values of repeatability and reproducibility in the field are given in Annex E.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

prEN 14793:2014, Stationary source emission – Demonstration of equivalence of an alternative method with a reference method

EN 15259:2007, Air quality – Measurement of stationary source emissions – Requirements for measurement sections and sites and for the measurement objective, plan and report

EN ISO 14956:2002, Air quality – Evaluation of the suitability of a measurement procedure by comparison with a required measurement uncertainty (ISO 14956:2002)

ISO/IEC Guide 98-3:2008, Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

absorber

device in which sulphur oxide is absorbed into an absorption liquid

3.2 absorption efficiency

ε

ratio of quantity of the analyte q_1 collected in the first absorber divided by the quantity of the analyte collected in the first and the second absorber ($q_1 + q_2$)

 $\varepsilon = q_1 / (q_1 + q_2)$

3.3 automated measuring system AMS

measuring system permanently installed on site for continuous monitoring of emissions or measurement of peripheral parameters

Note 1 to entry: An AMS is a method which is traceable to a reference method.

Note 2 to entry: Apart from the analyser, an AMS includes facilities for taking samples (e.g. probe, sample gas lines, flow meters, regulators, delivery pumps) and for sample conditioning (e.g. dust filter, moisture removal devices, converters, diluters). This definition also includes testing and adjusting devices that are required for regular functional checks.

[SOURCE: FprEN 14181:2014]

3.4

calibration of an AMS

establishment of the statistical relationship between values of the measurand indicated by the automated measuring system (AMS) and the corresponding values given by the standard reference method (SRM) used during the same period of time and giving a representative measurement on the same measurement plane

Note 1 to entry: The result of calibration permits to establish the relationship between the values of the SRM and the AMS (calibration function).

Note 2 to entry: Calibration should not be confused with adjustment of a measuring system.

3.5

calibration of the SRM

set of operations that establish, under specified conditions, the relationship between values of quantities indicated by a measuring instrument or measuring system, and the corresponding values realized by standard reference method implemented in the state of the art in order to provide representative results.

3.6

chemical blank value

sulphate ion content of an unexposed sample of the absorption solution, plus reagents that are added to the solution before analysis if necessary

3.7

emission limit value

ELV

emission limit value according to EU Directives on the basis of 30 min, 1 h or 1 day

3.8

field blank

value determined by a specific procedure used to ensure that no significant contamination has occurred during all steps of the measurement and to check that the operator can achieve a quantification level adapted to the task

[SOURCE: CEN/TS 15675]

3.9

influence quantity

quantity that is not the measurand but that affects the result of the measurement

Note 1 to entry: Influence quantities are e.g. ambient temperature, atmospheric pressure, presence of interfering gases in the flue gas matrix or pressure of the gas sample.

3.10

measurand

quantity intended to be measured

[SOURCE: JCGM 200:2012]

3.11

measurement series

several successive measurements carried out on the same measurement plane and at the same process operating conditions

3.12

measurement plane

plane normal to the centreline of the duct at the sampling position

Note 1 to entry: Measurement plane is also known as sampling plane.

[SOURCE: EN 15259:2007]

3.13

measurement point

position in the measurement plane at which the sample stream is extracted or the measurement data are obtained directly

Note 1 to entry: Measurement point is also known as sampling point.

[SOURCE: EN 15259:2007]

3.14

measurement site

<u>SIST EN 14791:2017</u>

place on the waste gas duct in the area of the measurement plane(s) consisting of structures and technical equipment, for example working platforms, measurement ports, energy supply

Note 1 to entry: Measurement site is also known as sampling site.

[SOURCE: EN 15259:2007]

3.15

measuring system

complete set of measuring instruments and other equipment assembled to carry out specified measurements

[VIM 3.2]

3.16

performance characteristic

one of the quantities (described by values, tolerances, range, ...) assigned to equipment in order to define its performance

3.17 reference method RM

measurement method taken as a reference by convention, which gives the accepted reference value of the measurand

Note 1 to entry: A reference method is fully described.

Note 2 to entry: A reference method can be a manual or an automated method.

Note 3 to entry: Alternative methods can be used if equivalence to the reference method has been demonstrated.

[SOURCE: EN 15259:2007]

3.18 standard reference method SRM

reference method prescribed by European or national legislation

[SOURCE: EN 15259:2007]

3.19

repeatability in the laboratory

closeness of the agreement between the results of successive measurements of the same measurand carried out under the same conditions of measurement

Note 1 to entry: These conditions include:

- same measurement procedure;

same laboratory;

same sampling equipment, used under the same conditions;

- same location;
- repetition over a short period of time. <u>SIST EN 14791</u>:

Note 2 to entry: Repeatability may be expressed quantitatively in terms of the dispersion characteristics of the results.

Note 3 to entry: In this European Standard the repeatability is expressed as a value with a level of confidence of 95 %.

3.20

repeatability in the field

closeness of the agreement between the results of simultaneous measurements of the same measurand carried out with two equipments under the same conditions of measurement

Note 1 to entry: These conditions include:

- same measurement procedure;
- two equipments, the performances of which are fulfilling the requirements of the reference method, used under the same conditions;
- same location;
- implemented by the same laboratory;
- typically calculated on short periods of time in order to avoid the effect of changes of influence parameters (e.g. 30 min).

oSIST prEN 14791:2015

prEN 14791:2014 (E)

Note 2 to entry: Repeatability may be expressed quantitatively in terms of the dispersion characteristics of the results.

Note 3 to entry: In this European Standard the repeatability under field conditions is expressed as a value with a level of confidence of 95 %.

3.21

reproducibility in the field

closeness of the agreement between the results of simultaneous measurements of the same measurand carried out with several sets of equipment under the same conditions of measurement

Note 1 to entry: These conditions are called field reproducibility conditions and include:

- same measurement procedure;
- several sets of equipment, the performance of which fulfils the requirements of the reference method, used under the same conditions;
- same location;
- implemented by several laboratories.

Note 2 to entry: Reproducibility may be expressed quantitatively in terms of the dispersion characteristics of the results.

Note 3 to entry: In this European Standard the reproducibility under field conditions is expressed as a value with a level of confidence of 95 %.

3.22

uncertainty

parameter associated with the result of a measurement, that characterises the dispersion of the values that could reasonably be attributed to the measurand

3.23

standard uncertainty

и

uncertainty of the result of a measurement expressed as a standard deviation

3.24

<u>IST EN 14791:2017</u>

combined uncertainty hai/catalog/standards/sist/f5ebf720-489f-4396-8ebd-039eb67f1974/sist-en-14791-2017 u_{c}

standard uncertainty attached to the measurement result calculated by combination of several standard uncertainties according to the principles laid down in ISO/IEC Guide 98-3 (GUM)

3.25

expanded uncertainty

U

quantity defining a level of confidence about the result of a measurement that may be expected to encompass a specific fraction of the distribution of values that could reasonably be attributed to a measurand

 $U = k \times u$

Note 1 to entry: In this European Standard, the expanded uncertainty is calculated with a coverage factor of k = 2, and with a level of confidence of 95 %.

Note 2 to entry: The expression overall uncertainty is sometimes used to express the expanded uncertainty.

3.26

uncertainty budget

calculation table combining all the sources of uncertainty according to EN ISO 14956 or ISO/IEC Guide 98-3 in order to calculate the combined uncertainty of the method at a specified value

4 Symbols and abbreviated terms

4.1 Symbols

For the purposes of this document, the following symbols apply.

C_m	mass concentration of sulphur dioxide in the sample gas, in milligrams per cubic metre (of gas)
f_a	equivalent mass of sulphur dioxide of 1 mm of titration solution (barium perchlorate standard volumetric solution) used for titration in Thorin method, in milligrams per millilitre
f_{v}	ratio of the volume of the pre-treated sample solution (sample absorption solution pre-treated before analyse) to the volume of the aliquot taken for the titration in Thorin method
L_{Q}	limit of quantification, in milligrams per litre of SO_4^2
m _s	weight of the sample solution (absorption solution used for sampling + rinsing solution), in grams
P _m	absolute pressure at the gas volume meter, in kilopascals
P_{std}	standard pressure: 101,3 kPa
P _{sat (Tm)}	saturation vapour pressure of water at volume gas meter temperature, in kilopascals
q_{s}	mass concentration of sulphate in sample absorption solution, in milligrams per litre (of solution)
q_{cb}	mass concentration of sulphate in chemical blank solution, in milligrams per litre (of solution)
r	repeatability, in milligrams per cubic metre or percentage
R	reproducibility, in milligrams per cubic metre or percentage
R _s ttps://standar	peak resolution S_s : volume of titration solution used for titration of sample absorption solution, in millilitre catalog/standards/sist/f5ebf720-489f-4396-8ebd-039eb67f1974/sist-en-14791-2017
$S_{\sf cb}$	volume of titration solution used for titration of chemical blank solution, in millilitre
S _r	repeatability standard deviation, in milligrams per cubic metre or percentage
S _R	reproducibility standard deviation, in milligrams per cubic metre or percentage
S _{r, limit}	maximum allowable repeatability standard deviation, in milligrams per cubic metre
S_s	volume of titration solution used for the titration of the aliquot of the pre-treated sample solution, in millilitres
t ₁	retention time of the first peak, in seconds
<i>t</i> ₂	retention time of the second peak, in seconds
T_j	temperature at the gas meter, in Kelvin
T_m	mean temperature at the gas volume meter, in Kelvin

oSIST prEN 14791:2015

prEN 14791:2014 (E)

T_{std} standard temperature, 273 K

\mathbf{I}	reading at the gas volume motor at the beginning of the compling paris	vd in aubia matroa
V 4		Ju. III cubic metres
· .		.,

- *V*₂ reading at the gas volume meter at the end of the sampling period, in cubic metres
- *V*_{m (std)} dry gas volume measured, corrected to standard conditions, in cubic metres
- *V*_s volume of the sample solution (absorption solution used for sampling + rinsing solution), in litres
- w_1 peak width, on the time axis, of the first peak, in seconds
- *w*₂ peak width on the time axis, of the second peak, in seconds
- ε absorption efficiency, in percentage
- σ conductivity, in micro-siemens per metre
- ρ_{20}^{4} density of a liquid at 20 °C compared to water's at 4 °C, in kilograms per litre
- χ volume content, in percentage

4.2 Abbreviated terms

For the purposes of this document, the following abbreviated terms apply.

PE Polyethene

PTFE Polytetrafluoroethene

5 Measuring principle

5.1 General

<u>SIST EN 14791:2017</u>

https://standards.iteh.ai/catalog/standards/sist/5ebf720-4896-4396-8ebd-039eb6711974/sist-en-14791-2017 This European Standard describes the standard reference method (SRM) based on two alternative analytical techniques for determining sulphur dioxide (SO₂) content emitted to atmosphere from ducts and stacks. The specific components and the requirements for the measuring system are described in Clauses 6 to Clause 8. A number of performance characteristics with associated performance criteria are specified for the measuring system (see Tables 1 and 2). The expanded uncertainty of the method shall meet the specifications given in this European Standard. Requirements and recommendations for quality assurance and quality control are given for measurements in the field (see Clause 6 and Clause 8).

5.2 Measuring principle

A sample of gas is extracted via a heated temperature-controlled probe. The sample is filtered and drawn through hydrogen peroxide absorber solutions for a specified time and at a controlled flow rate. The sulphur dioxide in the sampled gas is absorbed and oxidised to sulphate ion. The mass concentration of sulphate in the absorption solutions is subsequently determined using ion chromatography or by titration with a barium perchlorate solution using Thorin as indicator. SO_3 is also absorbed and transformed in sulphate ion and is therefore an interferent.

This European Standard has been validated with a $0,3 \% H_2O_2$ absorption solution for concentrations lower than 1 000 mg/m³ and with a $3,0 \% H_2O_2$ absorption solution for higher concentrations but lower than 2 000 mg/m³. Typical concentration of the absorption solution is $0,3 \% H_2O_2$. However, for concentrations higher than 1 000 mg/m³ it is recommended, in case of a bad efficiency either to decrease the flow or to increase the H₂O₂concentration.

6 Description of measuring equipment

6.1 Reagents

6.1.1 General

During the analysis, use only reagents of recognised analytical grade.

Normal, accepted laboratory safety practices and cleaning procedures for glassware should be followed during reagent preparation.

WARNING — Use the reagents in accordance with the appropriate health and safety regulations.

6.1.2 Hydrogen peroxide

Commercially available solution of H₂O₂; mass content 30 %, ρ_{20}^{4} = 1,11 kg/l.

6.1.3 Water

H₂O; ultra pure water with conductivity σ < 10 μ S m⁻¹.

6.1.4 Absorption solution, H_2O_2 (Standards.iteh.ai)

The absorption solution is a hydrogen peroxide solution (6.1.2) diluted to a mass concentration of $0,3 \ \text{M}_2\text{O}_2$ in water (6.1.3). For flue-gas concentrations higher than 1 000 mg/m³, it is suggested, in case of a bad efficiency, either to decrease the flow, or to increase the concentration of the absorption solution.

For the preparation of the mass concentration of 0,3 % H₂O₂ in water, thoroughly mix about 10 ml of 30 % of H₂O₂ (6.1.2) with 500 ml of water (5.1.3) and make up to 1 000 ml with water (6.1.3). Store the solution in a glass or PE bottle in a dark place and for no longer than one week.

WARNING — Decomposition of the solution may occur and may lead to the explosion of the storage bottle. It is recommended that the lid of this bottle is not closed too tightly or to use a security cap.

NOTE Cleanliness of the glassware is important to avoid a possible decomposition of hydrogen peroxide.

6.1.5 Reagents for chromatographic analysis

6.1.5.1 Eluent solution

The choice of eluent depends on the manufacturer's separator column and detector. For the exact composition of the eluent, use a validated solvent for the method and/or refer to the instructions given by the manufacturer.

NOTE For an ion chromatograph using the suppressor technique, a typical eluent is a solution of $1,7 \times 10^{-3}$ mol/l of NaHCO₃ and $1,8 \times 10^{-3}$ mol/l of Na₂CO₃.

6.1.5.2 Standard sulphate stock solution, $10,4 \times 10^{-3}$ mol/l of SO₄²⁻

Use a commercially available sulphate stock solution of 1 000 mg/l sulphate (10.4×10^{-3} mol/l) with a minimum content of 99,0 %. As an alternative prepare the standard solution as follows:

Dissolve 1,814 g of analytical grade potassium sulphate (K_2SO_4) in water (6.1.3) and dilute to a 1 000 ml volumetric flask. 1 ml of stock solution corresponds to 1 mg of $SO_4^{2^2}$.

NOTE Calibration standards are prepared by diluting the standard stock solution with the absorption solution as specified in 9.2.3.2.

6.1.5.3 Regeneration solution for suppressor

For the exact composition of the suppressor regeneration solution, refer to the instructions given by the manufacturer of the suppressor.

NOTE An example is a solution of $12,5 \times 10^{-3}$ mol/l of H₂SO₄.

6.1.6 Reagent for Thorin analysis

6.1.6.1 2-propanol [CH₃CH(OH)CH₃]

Use commercially available 2-propanol [CH₃CH(OH)CH₃] in analytical grade (minimum content 99,8 %).

6.1.6.2 Barium perchlorate, standard volumetric solution, [Ba(CIO₄)₂] = 0,005 mol/l

Use a commercially available barium perchlorate solution (80 % 2-propanol/20 % water) with concentration of 0,005 mol/l Ba(CIO_4)₂, or prepare the standard solution as follows:

Dissolve 1,7 g of anhydrous barium perchlorate $[Ba(CIO_4)_2]$ in about 200 ml of water in a 1 000 ml one-mark volumetric flask. Make up to the mark with 2-propanol (5.1.6.1) and mix well.

Titrate the solution accurately against a 0,005 mol/l standard volumetric sulphuric acid solution.

1 ml of exactly 0,005 mol/l barium perchlorate solution is equivalent to a mass of sulphur dioxide of 0,320 mg; $(f_a = 0,320 \text{ mg/ml})$.

6.1.6.3 Potassium hydroxide, standard volumetric solution, [KOH] = 0,1 mol/l

Use a commercially available solution of 0,1 mol/l KOH in water.

NOTE This reagent is only necessary if the sampling gas contains high concentration of acid components (e.g. $SO_2 > 100 \text{ mg/m}^3$ or HCl > 200 mg/m³ or NO₂ > 400 mg/m³).

6.1.6.4 Perchloric acid, standard volumetric solution, [HCIO₄] = 0,1 mol/l

Prepare an approximate 1 % solution of perchloric acid by mixing 16 ml of a commercially available solution of 60 % perchloric acid in water (6.1.3) and make up to 1 000 ml with water. Store this solution in a glass or PE bottle.

NOTE This reagent is only necessary if the sampling gas contents high concentrations of alkali components (e.g. $NH_3 > 50 \text{ mg/m}^3$).