
**Conveyor belts — Determination of
minimum transition distance on three
idler rollers**

*Courroies transporteuses — Détermination de la distance minimale de
transition d'auge à trois rouleaux égaux*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 5293:2004](https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004)

[https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-
e2671652b1c5/iso-5293-2004](https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 5293:2004](#)

<https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Calculation of minimum transition distance	1
4 Application of the formula for transition distance	2
4.1 General	2
4.2 Values of elastic modulus, M, of belt	2
4.3 Values of vertical distance, h, which the belt edge raises or lowers	2
4.4 Values of ΔT	4
Annex A (normative) Derivation of the formula for transition distance	6
Annex B (normative) Derivation of values of ΔT	8
Bibliography	11

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 5293:2004](https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004)

<https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5293 was prepared by Technical Committee ISO/TC 41, *Pulleys and belts (including veebelts)*, Subcommittee SC 3, *Conveyor belts*.

This second edition cancels and replaces ISO 5293:1981 and ISO/TR 10357:1989, which have been technically revised.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 5293:2004
<https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004>

Conveyor belts — Determination of minimum transition distance on three idler rollers

1 Scope

This International Standard specifies the formula for calculating conveyor belt transition distances and details its application and derivation.

This International Standard is not suitable or valid for light conveyor belts as described in ISO 21183-1^[1].

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1537, *Continuous mechanical handling equipment for loose bulk materials — Troughed belt conveyors (other than portable conveyors) — Idlers*

ISO 9856, *Conveyor belts — Determination of elastic and permanent elongation and calculation of elastic modulus*

<https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004>

3 Calculation of minimum transition distance

The formula for calculating the transition distance, the derivation of which is given in Annex A, is as follows:

$$L_1 = \frac{h}{\sin \lambda} \left[\frac{M}{\Delta T} (1 - \cos \lambda) \right]^{0,5}$$

where

- L_1 is the transition distance, expressed in metres;
- h is the vertical distance, expressed in metres, the belt edge raises or lowers in the transition (see Figure 1);
- λ is the idler trough angle;
- M is the elastic modulus, expressed in newtons per millimetre, measured under tension T_R ;
- T_R is the maximum recommended belt-to-belt joint tension (RMBT), expressed in newtons per millimetre, for a steady-state condition of the conveyor;
- ΔT is the induced belt edge stress, expressed in newtons per millimetre, in the transition.




Figure 1 — Transition distance

4 Application of the formula for transition distance

4.1 General

Calculate the transition distance by using appropriate values of M , h and ΔT as described in 4.2 to 4.4, as appropriate.

4.2 Values of elastic modulus, M , of belt

Determine the values in accordance with ISO 9856.

4.3 Values of vertical distance, h , which the belt edge raises or lowers

4.3.1 General

Calculate the values from the idler trough angle λ (see Figure 1) and the position of the terminal pulley with respect to the centre idler roller. Four common situations are described in 4.3.2 and 4.3.3.

4.3.2 Three equal length roller

4.3.2.1 The pulley is on a line with the top centre idler roller (see Figure 2).

$$h = \frac{b \sin \lambda}{3}$$

where

h is the vertical distance, expressed in metres, that the belt edge raises or lowers in the transition (see Figure 1);

b is the width, expressed in metres, of the belt;

λ is the idler trough angle.




Figure 2 — Pulley on line with top centre idler roller

4.3.2.2 The pulley is elevated by 1/3 of the trough depth above the line of centre idler roller (see Figure 3).

h is then equal to 2/3 full trough depth, i.e.

$$h = \frac{2}{3} \times \frac{b \sin \lambda}{3} = \frac{b \sin \lambda}{4,5}$$

where

h is the vertical distance, expressed in metres, the belt edge raises or lowers in the transition (see Figure 1);

b is the width, expressed in metres, of the belt;

λ is the idler trough angle.




Figure 3 — Pulley elevated by 1/3 of trough depth above line of centre idler roller

4.3.3 Long centre roller

4.3.3.1 The pulley is on a line with the top centre idler roller (see Figure 4).

$$h = b_1 \times \sin \lambda$$

where

h is the vertical distance, expressed in metres, the belt edge raises or lowers in the transition (see Figure 1);

b_1 is the amount of belt width, expressed in metres, on one of the outer rollers, i.e. ($b = 2b_1 + b_2$);

λ is the idler trough angle.




Figure 4 — Pulley on line with top centre idler roller

4.3.3.2 The pulley is elevated by 1/3 of the trough depth above the line of centre idler roller (see Figure 5).

h is then equal to 2/3 full trough depth, i.e.

$$h = \frac{2}{3} \times b_1 \times \sin \lambda$$

where

h is the vertical distance, expressed in metres, the belt edge raises or lowers in the transition (see Figure 1);

b_1 is the amount of belt width, expressed in metres, on one of the outer rollers, i.e. ($b = 2b_1 + b_2$);

λ is the idler trough angle.




Figure 5 — Pulley elevated by 1/3 of trough depth above line of centre idler roller

4.4 Values of ΔT

4.4.1 Calculate the average belt tension at the transition and express it as a fraction of the maximum recommended belt tension for a steady operating condition, T_R , taking the strength of the belt joints into account. Values of belt tension at transition higher than $1 T_R$ take into account peak belt loadings which can occur in short-time non-steady operating conditions, for example when starting and stopping the conveyor belt.

In agreement with the belt manufacturer, select a maximum belt edge tension of $F\%$ related to the steady operating condition (100%), provided that the gap (or overlap) between the rollers complies with the requirements of ISO 1537.

4.4.2 The values of ΔT selected (calculated in accordance with Annex B) will

- a) prevent edge tension not only in the steady operating conditions but also in the temporary non-steady conditions from exceeding the maximum recommended tension of the belt or the belt joints in the steady conditions by F %;
- b) keep the tension in the belt centre adequate and always positive to prevent the centre of the belt from buckling.

NOTE Further information regarding F % is given in Clause B.1.

4.4.3 The additional tensions induced at the troughing transition will normally also be equalized beyond the transition distance. For this reason the actual existing edge stress will be lower. For determining the maximum transition distances a higher value of ΔT can be agreed with the belt manufacturer, if necessary.

4.4.4 Unless otherwise specified by the belt manufacturer, the values below can be allowed for belt edge tensions in short-time non-steady operating conditions:

$F \leq 1,8T_R$ or 180 % max. for textile belts; and

$F \leq 2,0T_R$ or 200 % max. for steel cord belts.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 5293:2004](#)

<https://standards.iteh.ai/catalog/standards/sist/6627acf5-e90f-4128-9342-e2671652b1c5/iso-5293-2004>