
**Animal feeding stuffs — Determination of
nitrogen content and calculation of crude
protein content —**

**Part 1:
Kjeldahl method**

*Aliments des animaux — Détermination de la teneur en azote et calcul
de la teneur en protéines brutes —
Partie 1. Méthode Kjeldahl*

[ISO 5983-1:2005](https://standards.iso.org/iso-5983-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/93796a4c-9f81-4dcc-8b7a-2f00fd835d30/iso-5983-1-2005>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 5983-1:2005](https://standards.iteh.ai/catalog/standards/sist/93796a4c-9f81-4dcc-8b7a-2f00fd835d30/iso-5983-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/93796a4c-9f81-4dcc-8b7a-2f00fd835d30/iso-5983-1-2005>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope	1
2 Normative references	1
3 Principle	1
4 Reagents and materials	1
5 Apparatus	2
6 Sampling	2
7 Preparation of test sample.....	3
8 Procedure	3
9 Calculation and expression of results.....	5
10 Precision.....	6
11 Test report	7
Annex A (informative) Results of interlaboratory test.....	8
Bibliography	10

iTech STANDARD PREVIEW
<https://standards.iteh.ai/catalog/standards/sist/93796a4c-9f81-4dcc-8b7a-2f00fd835d30/iso-5983-1-2005>
 (standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5983-1 was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 10, *Animal feeding stuffs*.

This first edition of ISO 5983-1, together with ISO 5983-2:2005, cancels and replaces ISO 5983:1997, which has been technically revised.

ISO 5983 consists of the following parts, under the general title *Animal feeding stuffs — Determination of nitrogen content and calculation of crude protein content*:

- Part 1: Kjeldahl method
- Part 2: Block digestion/steam distillation method

iTeh STANDARD PREVIEW
(standards.iteh.ai)
ISO 5983-1:2005
<https://standards.iteh.ai/catalog/standards/sist/93796a4c-9f81-4dcc-8b7a-2f00fd835d30/iso-5983-1-2005>

Animal feeding stuffs — Determination of nitrogen content and calculation of crude protein content —

Part 1: Kjeldahl method

1 Scope

This part of ISO 5983 specifies a method for the determination of the nitrogen content of animal feeding stuffs by the Kjeldahl process, and a method for the calculation of the crude protein content.

The method does not measure oxidized forms of nitrogen or heterocyclic nitrogen compounds.

This method does not distinguish between protein nitrogen and non-protein nitrogen. If it is important to determine the content of non-protein nitrogen, an appropriate method should be used.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6498, *Animal feeding stuffs — Preparation of test samples*

3 Principle

The organic matter is digested by sulfuric acid in the presence of a catalyst. The reaction product is rendered alkaline, then the liberated ammonia is distilled and titrated. The nitrogen content is calculated and the result is multiplied by the conventional factor to obtain the crude protein content.

4 Reagents and materials

Use only reagents of recognized analytical grade, unless otherwise specified, and distilled or deionized water or water of equivalent purity.

The reagents [except the standard materials (4.6)] shall be practically free from nitrogenous compounds.

4.1 Potassium sulfate.

4.2 Catalyst, either 4.2.1 or 4.2.2.

4.2.1 Copper(II) oxide (CuO).

4.2.2 Copper(II) sulfate pentahydrate (CuSO₄·5H₂O).

4.3 Sulfuric acid, $c(\text{H}_2\text{SO}_4) = 18 \text{ mol/l}$, $\rho_{20}(\text{H}_2\text{SO}_4) = 1,84 \text{ g/ml}$.

4.4 Paraffin wax.

4.5 Saccharose.

4.6 Standard materials, either 4.6.1 or 4.6.2.

4.6.1 Acetanilide, with melting point 114 °C; nitrogen (N) content 103,6 g/kg.

4.6.2 Tryptophan, with melting point 282 °C; nitrogen (N) content 137,2 g/kg.

Dry before use.

4.7 Sodium hydroxide solution, $w(\text{NaOH}) = 33\%$ (mass fraction).

4.8 Collecting liquid, either 4.8.1 or 4.8.2.

4.8.1 Sulfuric acid, standard volumetric solution, $c(\text{H}_2\text{SO}_4) = 0,05\text{ mol/l}$ or $c(\text{H}_2\text{SO}_4) = 0,125\text{ mol/l}$.

4.8.2 Boric acid, $\rho(\text{H}_3\text{BO}_3) = 40\text{ g/l}$.

4.9 Solutions for titration.

4.9.1 Sodium hydroxide, standard volumetric solution, $c(\text{NaOH}) 0,1\text{ mol/l}$ or $c(\text{NaOH}) = 0,25\text{ mol/l}$.

4.9.2 Sulfuric acid, standard volumetric solution, $c(\text{H}_2\text{SO}_4) = 0,05\text{ mol/l}$ or $c(\text{H}_2\text{SO}_4) = 0,125\text{ mol/l}$.

The molarity of standard volumetric solutions should be known to the fourth decimal point.

4.10 Mixed indicator, neutral point at pH 4,4 to 5,8.

Dissolve 2 g of methyl red and 1 g of methylene blue in 1.000 ml of ethanol [$\varphi(\text{C}_2\text{H}_5\text{OH}) = 95\%$ (volume fraction)].

4.11 pH indicator paper.

4.12 Boiling aids, such as granulated pumice stone, or glass beads of diameter 5 mm to 7 mm, or carborundum chips, washed in hydrochloric acid and in distilled water, and ashed.

5 Apparatus

Usual laboratory apparatus and, in particular, the following.

5.1 Analytical balance.

5.2 Digestion, distillation and titration apparatus.

6 Sampling

A representative sample should have been sent to the laboratory. It should not have been damaged or changed during transport or storage.

Sampling is not part of the method specified in this part of ISO 5893. A recommended sampling method is given in ISO 6497.

Store the sample in such a way that deterioration and change in its composition are prevented.

7 Preparation of test sample

Prepare the test sample in accordance with ISO 6498.

8 Procedure

WARNING — The operations described in 8.3.1 and 8.3.2 should be carried out under a well-ventilated hood or in a fume cupboard which is resistant to sulfuric acid.

8.1 General

For general directions on the application of the Kjeldahl method, see ISO 1871.

8.2 Test portion

Weigh, to the nearest 1 mg, a mass of the test sample chosen according to the expected nitrogen content so that the test portion contains between 0,005 g and 0,2 g of nitrogen and, preferably, more than 0,02 g.

The mass of the test portion of homogeneous air-dry samples should be between 0,5 g and 2,0 g. The mass of the test portion of wet and/or inhomogeneous samples should be between 2,5 g and 5,0 g.

8.3 Determination

8.3.1 Digestion of organic matter

Transfer the test portion quantitatively into a Kjeldahl digestion flask of suitable size (usually 800 ml).

Add 15 g of potassium sulfate (4.1). <https://standards.iteh.ai/catalog/standards/sist/93796a4c-9f81-4dcc-8b7a-2f00fd835d30/iso-5983-1-2005>

Add an appropriate quantity of catalyst as follows: 0,3 g of copper(II) oxide (4.2.1) or 0,9 g to 1,2 g of copper(II) sulfate pentahydrate (4.2.2).

Add 25 ml of sulfuric acid (4.3) for the first gram of dry matter of the test portion and 6 ml to 12 ml for each additional gram of dry matter. Mix thoroughly, ensuring complete wetting of the test portion.

Support the flask so that its axis is inclined at an angle of 30° to 45° to the vertical. Maintain the flask in this position throughout heating.

Heat the flask moderately at first to prevent foam from rising into the neck of the flask or escaping from the flask.

NOTE 1 It may be advisable to add an anti-foaming agent such as paraffin wax (4.4).

Heat moderately, swirling from time to time, until the mass has carbonized and the foam has disappeared. Then heat more intensively until the liquid is boiling steadily.

NOTE 2 Heating is adequate if the boiling acid condenses towards the middle of the neck of the Kjeldahl flask.

Avoid overheating of the walls of the flask not in contact with liquid.

NOTE 3 If a naked flame is used, such overheating can be prevented by placing the flask on a sheet of heat-resistant material with an aperture of diameter slightly less than that of the flask at the liquid level.

After the liquid has become clear with a light green-blue colour, heat for another 2 h.

Leave to cool. If the digest starts to solidify, add some water and mix by swirling.

8.3.2 Distillation of ammonia

8.3.2.1 Carefully add 250 ml to 350 ml of water to dissolve the sulfates completely. If necessary, facilitate dissolving by heating the flask in warm water. Mix by swirling and allow to cool.

Add a few boiling aids (4.12).

For some specific samples, the sulfates may not completely dissolve in the added water. In that case, it is recommended to repeat the digestion with a reduced mass of potassium sulfate (4.1).

8.3.2.2 Pipette, into the collecting flask of the distillation apparatus, 25 ml of the sulfuric acid (4.8.1), choosing the concentration according to the expected nitrogen content of the test portion. Add 100 ml to 150 ml of water. Add a few drops of the mixed indicator (4.10). Proceed in accordance with 8.3.2.4.

8.3.2.3 Alternatively, transfer into the collecting flask 100 ml to 250 ml of boric acid (4.8.2). Add a few drops of mixed indicator (4.10).

Simultaneous titration of the ammonia (see 8.3.3.3) during distillation is recommended since it facilitates verification of the end of distillation.

8.3.2.4 Immerse the end of the condenser in the liquid contained in the collecting flask, to a depth of at least 1 cm.

Slowly pour 100 ml of sodium hydroxide solution (4.7) into the digestion flask along the wall.

Immediately connect the flask to the distillation apparatus.

Heat the flask in such a manner that approximately 150 ml of distillate is collected in 30 min. At the end of this time, check the pH of the distillate at the tip of the condenser using litmus paper (4.11). If the reaction is alkaline, continue distillation.

IMPORTANT — Lift the condenser from the liquid just before the end of the distillation, to prevent backflow.

If, during distillation using sulfuric acid as collecting liquid, the contents of the collecting flask become alkaline, recommence the determination, making appropriate adjustments.

8.3.3 Titration

8.3.3.1 Titration with automatic endpoint indication using a pH-meter is recommended. Otherwise, the endpoint is indicated by the change in colour of the mixed indicator (4.10) added in 8.3.2.

8.3.3.2 If sulfuric acid is used as the collecting liquid, titrate, in the collecting flask, the excess sulfuric acid with sodium hydroxide solution (4.9.1), $c(\text{NaOH}) = 0,1 \text{ mol/l}$ or $c(\text{NaOH}) = 0,25 \text{ mol/l}$ as appropriate, until the endpoint is indicated by the pH-meter or until the colour changes from violet to green.

8.3.3.3 If boric acid is used as the collecting liquid, titrate the ammonia with sulfuric acid (4.9.2), $c(\text{H}_2\text{SO}_4) = 0,05 \text{ mol/l}$ or $c(\text{H}_2\text{SO}_4) = 0,125 \text{ mol/l}$ as appropriate, until the endpoint is indicated by the pH-meter or the colour changes from green to violet.

If simultaneous titration is not possible (see 8.3.2.3), the titration should be carried out as soon as possible after the distillation is complete, ensuring that the temperature of the distillate does not exceed 25 °C. Under these conditions, losses of ammonia are avoided.

8.4 Blank test

Perform a blank test using about 1 g of saccharose (4.5) in place of the test portion.

8.5 Check test

Perform a check test by determining the nitrogen content of acetanilide (4.6.1) or tryptophan (4.6.2) after addition of 1 g of saccharose (4.5).

The choice of the substance for the check test should be related to the digestibility of the samples to be analysed. Acetanilide is easily digested, whereas the digestion of tryptophan is more difficult.

The recovery of nitrogen from acetanilide or tryptophan should be at least 99,5 % for acetanilide and at least 99,0 % for tryptophan.

9 Calculation and expression of results

9.1 Calculation of nitrogen content

9.1.1 Distillate collected in sulfuric acid

Provided that the volumes of sulfuric acid used to collect the ammonia for the determination (8.3) and for the blank test (8.4) are equal, calculate the nitrogen content, w_{n1} , in grams per kilogram of the test sample, by the following equation:

$$w_{n1} = \frac{(V_0 - V_1) \times c_1 \times M}{m}$$

where

V_0 is the volume, in millilitres, of the sodium hydroxide solution (4.9.1) required for the blank test;

V_1 is the volume, in millilitres, of the sodium hydroxide solution (4.9.1) required for the determination;

c_1 is the concentration, in moles per litre, of the sodium hydroxide solution (4.9.1) used for the titrations;

M is the molar mass, in grams per mole, of nitrogen ($M = 14$ g/mol);

m is the mass, in grams, of the test portion.

Report the result to the nearest 0,01 g/kg.

9.1.2 Distillate collected in boric acid

Calculate the nitrogen content of the test sample by the equation:

$$w_{n2} = \frac{2(V_3 - V_2) \times c_2 \times M}{m}$$

where

w_{n2} is the nitrogen content, in grams per kilogram, of the test sample;

V_2 is the volume, in millilitres, of the sulfuric acid (4.9.2) required for the blank test;

V_3 is the volume, in millilitres, of the sulfuric acid (4.9.2) required for the determination;

M is the molar mass, in grams per mole, of nitrogen ($M = 14$ g/mol);

c_2 is the concentration, in moles per litre, of the sulfuric acid (4.9.2) used for the titrations;

m is the mass, in grams, of the test portion.

Report the result to the nearest 0,01 g/kg.