
**Pneumatic fluid power — Assessment of
component reliability by testing —**

**Part 1:
General procedures**

*Transmissions pneumatiques — Évaluation par essais de la fiabilité des
composants*

iTeh STANDARD PREVIEW
Partie 1: Procédures générales
(standards.iteh.ai)

ISO 19973-1:2007

<https://standards.iteh.ai/catalog/standards/sist/07dabeca-8e4b-46c8-bf9e-d037c951572e/iso-19973-1-2007>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 19973-1:2007](https://standards.iteh.ai/catalog/standards/sist/07dabeca-8e4b-46c8-bf9e-d037c951572e/iso-19973-1-2007)

<https://standards.iteh.ai/catalog/standards/sist/07dabeca-8e4b-46c8-bf9e-d037c951572e/iso-19973-1-2007>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols and units of measurement	3
5 Concept of reliability	3
6 Strategies for conducting testing	4
6.1 Accelerated life testing.....	4
6.2 Test stand and measurement of parameters	4
6.3 Test planning.....	4
7 Statistical analysis.....	4
8 Test conditions	4
9 Sample size and selection criteria	5
10 End of test	5
10.1 Minimum number of failures required	5
10.2 Termination cycle count	6
10.3 Suspended test unit.....	6
10.4 Censored test	6
11 Evaluation of reliability characteristics from the test data	6
12 Test report	8
13 Identification statement (reference to this part of ISO 19973).....	8
Annex A (informative) Calculation procedures for censored data without suspensions.....	9
Annex B (informative) Calculation procedures for censored data with suspensions	14
Annex C (informative) Verification of minimum life at a specified reliability and one-sided confidence level	21
Annex D (informative) Dealing with outliers in test data.....	26
Bibliography	31

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19973-1 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*.

ISO 19973 consists of the following parts, under the general title *Pneumatic fluid power — Assessment of component reliability by testing*:

— *Part 1: General procedures*

— *Part 2: Directional control valves*

— *Part 3: Cylinders with piston rod*

— *Part 4: Pressure regulators*

ITEH STANDARD PREVIEW

(standards.iteh.ai)

[ISO 19973-1:2007](https://standards.iteh.ai/catalog/standards/sist/07dabeca-8e4b-46c8-bf9e-d037c951572e/iso-19973-1-2007)

<https://standards.iteh.ai/catalog/standards/sist/07dabeca-8e4b-46c8-bf9e-d037c951572e/iso-19973-1-2007>

Introduction

In pneumatic fluid power systems, power is transmitted and controlled through a gas under pressure within a circuit. Pneumatic fluid power systems are composed of components and are an integral part of various types of machines and equipment. Efficient and economical production requires highly reliable machines and equipment.

It is necessary that machine producers know the reliability of the components that make up their machine's pneumatic fluid power system. Knowing the reliability characteristic of the component, which can be determined from laboratory testing, the producers can model the system and make decisions on service intervals, spare parts inventory and areas for future improvements.

There are three primary levels in the determination of component reliability:

- a) preliminary design analysis: finite element analysis (FEA), failure mode and effect analysis (FMEA);
- b) laboratory testing and reliability modelling: physics of failure, reliability prediction, pre-production evaluation;
- c) collection of field data: maintenance reports, warranty analysis.

Each level has its application during the life of a component. A preliminary design analysis is useful to identify possible failure modes and eliminate them or reduce their effect on reliability. When prototypes are available, in-house laboratory reliability tests are run and initial reliability can be determined. Reliability testing is often continued into the initial production run and throughout the production lifetime as a continuing evaluation of the component. Collection of field data is possible when products are operating and data on their failures are available.

Specific component test procedures and exclusions are provided in ISO 19973-2, ISO 19973-3 and ISO 19973-4.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 19973-1:2007

<https://standards.iteh.ai/catalog/standards/sist/07dabeca-8e4b-46c8-bf9e-d037c951572e/iso-19973-1-2007>

Pneumatic fluid power — Assessment of component reliability by testing —

Part 1: General procedures

1 Scope

This part of ISO 19973 provides general procedures, the calculation method for assessing the reliability of pneumatic fluid power components and the methods of reporting. These procedures are independent of the kinds of components and of their design.

This part of ISO 19973 also provides general test conditions and a method for data evaluation.

NOTE Because the service life of any component is subject to variations, a statistical evaluation assists the interpretation of the test results.

The methods specified in this part of ISO 19973 apply to the first failure without repairs (see IEC 60300-3-5) [4], but exclude outliers; however, because outliers can be highly significant, information about how to deal with them is given in Annex D.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1000, *SI units and recommendations for the use of their multiples and of certain other units*

ISO 3534-1, *Statistics — Vocabulary and symbols — Part 1: General statistical terms and terms used in probability*

ISO 5598, *Fluid power systems and components — Vocabulary*

IEC 60050-191, *International Electrotechnical Vocabulary, chapter 191: Dependability and quality of service*

IEC 61649, *Goodness-of-fit tests, confidence intervals and lower confidence limits for Weibull distributed data*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3534-1, ISO 5598 and IEC 60050-191 and the following apply.

3.1

catastrophic failure

sudden failure of an item that results in its complete inability to perform all required functions

[IEC 60050-191]

3.2
confidence coefficient
confidence level

value $(1 - \alpha)$ of the probability associated with a confidence interval or a statistical coverage interval

NOTE 1 See also 3.6.

NOTE 2 See ISO 3534-1 for notes related to this term and definition.

3.3
confidence limit

either of the limits, T_1 or T_2 , of the two-sided confidence interval, or the limit, T , of the one-sided confidence interval

NOTE See ISO 3534-1 for notes related to this term and definition.

3.4
failure

termination of the ability of an item to perform a required function

[IEC 60050-191]

NOTE In the ISO 19973 (all parts), the reaching of a threshold level for statistical calculation is also considered a failure.

3.5
mean time to failure
MTTF

expectation of the time to failure

[IEC 60050-191]

NOTE In ISO 19973-2 to ISO 19973-4, the concept of time is expressed as either cycles or distance.

3.6
one-sided confidence interval

T
interval estimator for a population, θ , comprised of the interval from the smallest possible value of the population, θ , up to T or the interval from T up to the largest possible value of θ , where the probability $p(T \geq \theta)$ or $p(T \leq \theta)$ is at least equal to $(1 - \alpha)$, where $(1 - \alpha)$ is a fixed number, positive and less than 1

NOTE See ISO 3534-1 for notes related to this term and definition.

3.7
relevant failure

failure that should be included in interpreting test or operational results or in calculating the value of a reliability performance measure

[IEC 60050-191]

3.8
reliability

probability that an item can perform a required function under given conditions for a given time interval

[IEC 60050-191]

3.9
sample

one or more test units taken from a population and intended to provide information on the population

NOTE A sample can serve as a basis for a decision on the population or on the process that produced it.

3.10**sample size**

number of test units in the sample

NOTE In a multi-stage sample, the sample size is the total number of test units at the conclusion of the final stage of sampling.

3.11**threshold level**

value of a performance characteristic (for example, leakage, flow rate, current, etc.) against which the component's test data is compared

NOTE This is an arbitrary value defined by the experts as the critical value for performance comparisons, but is not necessarily indicative of a component failure.

4 Symbols and units of measurement

4.1 The symbols used in this part of ISO 19973 are given in Table 1.

Table 1 — Symbol list

Symbol ^a	Definition
B_{10}	Expected time at which 10 % of the population fails (10 % fractile of the lifetime)
η	Scale parameter (characteristic life) of the Weibull distribution
$F(t)$	Probability of failure, expressed in percent
β	Shape parameter (slope) of the Weibull distribution
$R(t)$	Reliability value of the entire sample; cumulative reliability
^a	Other symbols can be used in other documents and software.

4.2 Units of measurement are in accordance with ISO 1000.

5 Concept of reliability

For the purposes of this part of ISO 19973, reliability is the probability that a component does not have a relevant failure for a specified interval of time, number of cycles or distance when it operates under stated conditions.

A relevant failure occurs when a component

- exceeds any of its defined threshold levels, or
- experiences a catastrophic failure (burst, fatigue or functional failure, etc.).

Threshold levels of the components covered by ISO 19973 (all parts) are specified in the component-specific parts of this International Standard.

This probability can be determined by analysing the results of a series of tests and describing the population failure by statistical methods. There are many different statistical distributions that describe the population of failures that result from testing.

NOTE See Annex C for information about verifying the minimum life of a component at a specified reliability and one-sided confidence level.

6 Strategies for conducting testing

6.1 Accelerated life testing

One of the major difficulties encountered in specifying a reliability test is the time it takes to reach the threshold levels without accelerating the test. Accelerated testing, in which a component is subjected to environmental conditions more severe than those for which the component is rated, is sometimes necessary in order to keep the test time at a reasonable length. The degree and amount of accelerated testing specified in ISO 19973 (all parts) reflect the best judgement of, and agreement among, those who developed these International Standards. The primary criterion for determining test acceleration factors is that the failure mode or failure mechanism should not change or be different from that expected from a non-accelerated test.

6.2 Test stand and measurement of parameters

Two other important factors are the test stand and measurement of parameters. The test stand shall be designed to operate reliably within the planned environmental conditions. Its configuration shall not affect the results of the test being run on the component. Evaluation and maintenance of the test stand during the reliability test program is critical. The accuracy of parameter measurement and control of parameter values shall be within the specified tolerances to assure accurate and repeatable test results.

6.3 Test planning

Proper test planning is essential in order to produce results that accurately predict the component's reliability under specified conditions. The goals and objectives of the test program shall be clearly defined if a supplier and user agree to apply ISO 19973 (all parts).

STANDARD PREVIEW
(standards.iteh.ai)

7 Statistical analysis

ISO 19973-1:2007

The resulting test data shall be evaluated for calculating an assessment of the reliability. One of the most commonly used methods is the Weibull analysis because of its versatility in modelling various statistical distributions. This method shall be used for the analysis of the test data to ensure comparability of the results. Examples of applying Weibull analysis are given in Annex A.

NOTE Commercial software can be helpful for this purpose.

8 Test conditions

8.1 Testing shall be carried out in accordance with the provisions defined in the part of ISO 19973 that relates to the component tested, including the test parameters that are measured and threshold levels specified for each test parameter.

8.2 No repairs are permitted on the samples during the reliability test.

8.3 Unless otherwise specified in the relevant part of ISO 19973 that relates to the component being tested, or when agreed between the user and supplier, all tests shall be carried out under the conditions specified in Table 2.

Table 2 — General test conditions

Parameter	Value	
Working pressure	630 kPa \pm 30 kPa (6,3 bar \pm 0,3 bar)	
Ambient temperature	23 °C \pm 10 °C	
Temperature of the medium	23 °C \pm 10 °C	
Air quality	Filtration: nominal filtration rating	5 μ m
	Dryer: maximum pressure dew point	+3 °C
	Lubrication	None

8.4 During the endurance test, the test operator shall determine the measuring intervals in relation to the total number of cycles expected. Perform measurements more frequently at the beginning of the test until confidence with the operation is assured. It is up to the experience and judgement of the people in the test laboratory to determine effective measuring intervals; test intervals that are too long can reduce the statistically-determined lifetime of the test unit (see 10.2); measuring intervals that are too short increase the cost of testing. The first measurement shall be done within 10 % of the expected lifetime of the test unit. Test units shall be operated continuously and checked periodically for proper functioning.

9 Sample size and selection criteria

9.1 The samples shall be representative of the population and shall be selected randomly.

9.2 The minimum sample size shall be seven units.

NOTE It is important to have at least seven samples in order that the first data point on the Weibull graph is below the 10 % cumulative-failure point. This allows a more accurate projection of the lower confidence limit lines to intersect the 10 % cumulative-failure point and determine a B_{10} life.

9.3 For a product series with the same design principle, it is not necessary to test all types or sizes. However, the test program shall include the type with the most critical conditions, for example, highest velocity.

10 End of test

10.1 Minimum number of failures required

The minimum number of test units that are required to fail (e.g. reach a threshold level) is described in Table 3. This number does not include suspensions, which are not considered failures.

NOTE It is desirable to achieve at least 10 failures in accordance with IEC 61649. Fewer failures result in a wider confidence interval and a shorter B_{10} life at the lower confidence limit.

Table 3 — Minimum number of failures for evaluation of the characteristic life

Sample size	7	8	9	10	> 10
Minimum numbers of failures	5	6	7	7	70 % of the sample size, truncated ^a
^a For example, if the sample size is 11, the minimum number of failures is 7.					

10.2 Termination cycle count

When a test unit fails between consecutive observations, the data collected is referred to as left-censored interval data; in this case, both the last cycle count at which the test unit was operating properly and the cycle count at which the test unit failed shall be recorded. In some cases, when a more precise determination of a failure point is desired, it can be necessary to continuously monitor the performance of a test unit by using limit switches or other suitable means to detect failures when they occur.

10.3 Suspended test unit

Testing on an individual test unit may be stopped before a relevant failure occurs. This is known as a suspension. Some examples of suspensions include

- a unit which has been disassembled for inspection, or
- a unit which has been accidentally crushed.

However, these units had achieved a number of cycles until the point of suspension and these data have a positive influence on the calculation of the statistical parameters.

10.4 Censored test

If the test is stopped after the minimum number of failures specified in Table 3 is reached but the remaining samples are still operating, the test shall be considered censored. If the censored test does not include any suspensions, the method specified in Annex A shall be used to calculate the statistical parameters. If the censored test includes one or more suspensions, the method specified in Annex B shall be used to calculate the statistical parameters.

11 Evaluation of reliability characteristics from the test data

11.1 To improve the interpretation of the calculation results, the failure mode shall be specified and recorded.

11.2 Calculations shall be made from the test data to determine

- characteristic life, η : relative location of the straight line in the Weibull plot relative to the x-axis (time or scale parameter);
- Weibull shape parameter, β : slope of the straight line in the Weibull plot.

11.3 Calculate B_{10} life at the median ranks (see Figure 1, footnote a).

NOTE See Annex B for information on how to deal with censored data with suspensions.

11.4 Calculate the confidence limit of the B_{10} life at the one-sided 95 % confidence level using Fisher Matrix (see Figure 1, footnote a).