
**Petroleum and natural gas industries —
Downhole equipment — Lock mandrels
and landing nipples**

*Industries du pétrole et du gaz naturel — Équipement de fond de
trou — Mandrins à clé d'ancrage et sièges d'ancrage*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 16070:2005

[https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-
f50227c48d53/iso-16070-2005](https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-f50227c48d53/iso-16070-2005)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 16070:2005

<https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-f50227c48d53/iso-16070-2005>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	3
4 Abbreviated terms	4
5 Functional specification.....	5
5.1 General.....	5
5.2 Functional characteristics of lock mandrels and landing nipples	5
5.3 Well parameters	5
5.4 Operational parameters	5
5.5 Environmental compatibility.....	6
5.6 Compatibility with the related well equipment	6
5.7 Quality documentation.....	6
5.8 Design validation.....	6
6 Technical specification	7
6.1 General.....	7
6.2 Technical characteristics of lock mandrels and landing nipples	7
6.3 Design criteria	7
6.4 Design verification.....	9
6.5 Design validation	10
6.6 Design changes	12
6.7 Functional test parameters.....	12
7 Supplier/manufacturer requirements.....	12
7.1 Documentation and data control.....	12
7.2 User/purchaser documentation.....	13
7.3 Product identification	14
7.4 Quality control.....	14
7.5 Functional testing	21
8 Repair	22
Annex A (informative) Example of landing nipple validation test dimensional check sheet	23
Bibliography	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16070 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 4, *Drilling and production equipment*.

iTeh STANDARD PREVIEW

This second edition cancels and replaces the first edition (ISO 16070:2001), which has been technically revised.

[ISO 16070:2005](https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-f50227c48d53/iso-16070-2005)

<https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-f50227c48d53/iso-16070-2005>

Introduction

This International Standard has been developed by users/purchasers and suppliers/manufacturers of lock mandrels and landing nipples intended for use in the petroleum and natural gas industry worldwide. This International Standard is intended to give requirements and information to both parties in the selection, manufacture, testing and use of lock mandrels and landing nipples. Furthermore, this International Standard addresses the minimum requirements with which the supplier/manufacturer is to comply so as to claim conformity to this International Standard.

This International Standard has been structured to allow for grades of increased requirements in quality documentation and design validation. These variations allow the user/purchaser to select the grade required for a specific application.

There are two quality documentation grades which provide the user/purchaser the choice of requirements to meet specific preference or application. Quality documentation grade Q2 is the minimum grade of documentation offered by this International Standard. Grade Q1 provides additional material documentation.

There are three design validation grades which provide the user/purchaser the choice of requirements to meet specific preference or application. Design validation grade V3 is the minimum grade and represents equipment where the validation method has been defined by the supplier/manufacturer. The complexity and severity of the validation testing increases as the grade number decreases.

Users of this International Standard should be aware that requirements above those outlined in this International Standard may be needed for individual applications. This International Standard is not intended to inhibit a supplier/manufacturer from offering, or the user/purchaser from accepting, alternative equipment or engineering solutions. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the supplier/manufacturer should identify any variations from this International Standard and provide details.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 16070:2005

<https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-f50227c48d53/iso-16070-2005>

Petroleum and natural gas industries — Downhole equipment — Lock mandrels and landing nipples

1 Scope

This International Standard provides the requirements for lock mandrels and landing nipples within the production/injection conduit for the installation of flow control or other equipment used in the petroleum and natural gas industries. It includes the interface connections to the flow control or other equipment, but does not cover the connections to the well conduit.

2 Normative references

The following referenced documents are indispensable for the application of this document. The way in which these referenced documents are cited determines the extent (in whole or part) to which they apply. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2859-1, *Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

ISO 3601-1, *Fluid power systems — O-rings — Part 1: Inside diameters, cross-sections, tolerances and size identification code*

ISO 3601-3, *Fluid power systems — O-rings — Part 3: Quality acceptance criteria*

ISO 6506-1, *Metallic materials — Brinell hardness test — Part 1: Test method*

ISO 6507-1, *Metallic materials — Vickers hardness test — Part 1: Test method*

ISO 6508-1, *Metallic materials — Rockwell hardness test — Part 1: Test method (scales A, B, C, D, E, F, G, H, K, N, T)*

ISO 6892, *Metallic materials — Tensile testing at ambient temperature*

ISO 9712, *Non-destructive testing — Qualification and certification of personnel*

ISO 13628-3, *Petroleum and natural gas industries — Design and operation of subsea production systems — Part 3: Through flowline (TFL) systems*

ISO 13665, *Seamless and welded steel tubes for pressure purposes — Magnetic particle inspection of the tube body for the detection of surface imperfections*

ISO 15156-1, *Petroleum and natural gas industries — Materials for use in H₂S-containing environments in oil and gas production — Part 1: General principles for selection of cracking-resistant materials*

ISO 15156-2, *Petroleum and natural gas industries — Materials for use in H₂S-containing environments in oil and gas production — Part 2: Cracking-resistant carbon and low alloy steels, and the use of cast irons*

ISO 16070:2005(E)

ISO 15156-3, *Petroleum and natural gas industries — Materials for use in H₂S-containing environments in oil and gas production — Part 3: Cracking-resistant CRAs (corrosion-resistant alloys) and other alloys*

API Spec 5B¹⁾, *Specification for threading, gauging, and thread inspection of casing, tubing, and line pipe threads*

ASME Boiler and Pressure Vessel Code:2004²⁾, Section V, *Non-destructive examination*

ASME Boiler and Pressure Vessel Code:2004, Section VIII, Division 1, *Rules for construction of pressure vessels*

ASME Boiler and Pressure Vessel Code:2004, Section IX, *Welding and brazing qualifications*

ASTM A 388/A 388M³⁾, *Standard practice for ultrasonic examination of heavy steel forgings*

ASTM A 609/A 609M, *Standard practice for castings, carbon, low-alloy, and martensitic stainless steel, ultrasonic examination thereof*

ASTM D 395, *Standard test methods for rubber property — Compression set*

ASTM D 412, *Standard test methods for vulcanized rubber and thermoplastic rubbers and thermoplastic elastomers — Tension*

ASTM D 638, *Standard test method for tensile properties of plastics*

ASTM D 1414, *Standard test methods for rubber O-rings*

ASTM D 1415, *Standard test method for rubber property — International hardness*

ASTM D 2240, *Standard test methods for rubber property — Durometer hardness*

ASTM E 94, *Standard guide for radiographic examination*

ASTM E 140, *Standard hardness conversion tables for metals (relationship among Brinell hardness, Vickers hardness, Rockwell hardness, Rockwell superficial hardness, Knoop hardness, and scleroscope hardness)*

ASTM E 165, *Standard test method for liquid penetrant examination*

ASTM E 186, *Standard reference radiographs for heavy-walled [2 to 4 ½-in. (51 to 114-mm)] steel castings*

ASTM E 280, *Standard reference radiographs for heavy-walled [4 ½ to 12-in. (114 to 305-mm)] steel castings*

ASTM E 428, *Standard practice for fabrication and control of steel reference blocks used in ultrasonic examination*

ASTM E 446, *Standard reference radiographs for steel castings up to 2 in. (51 mm) in thickness*

BS 2M 54:1991⁴⁾, *Specification for temperature control in the heat treatment of metals*

SAE-AMS-H-6875:1998⁵⁾, *Heat treatment of steel raw materials*

1) American Petroleum Institute, 1220 L Street NW, Washington, DC 20005-4070, USA.

2) American Society of Mechanical Engineers, Three Park Avenue, New York, NY 10016-5990, USA.

3) American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, USA.

4) BSI, Customer Services, 389 Chiswick High Road, London W4 4AL, UK.

5) SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, USA.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE For quality system terms used in the text of this International Standard but not defined below, see ISO 9000.

3.1

ambient temperature

prevailing temperature at test site

3.2

critical component

part that is pressure containing and/or load bearing

3.3

design acceptance criteria

defined limits placed on characteristics of materials, products, or services established by the organization, customer, and/or applicable specifications to achieve conformity to the product design

[ISO/TS 29001:2003]

3.4

design validation

process of proving a design by testing to demonstrate conformity of the product to design requirements

[ISO/TS 29001:2003]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.5

design verification

process of examining the result of a given design or development activity to determine conformity with specified requirements

[ISO/TS 29001:2003]

<https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-f50227c48d53/iso-16070-2005>

3.6

full life cycle

expected period of time in which the product is specified to function according to the supplier's/manufacture's specifications

3.7

landing nipple

receptacle containing a profile designed for the installation of a lock mandrel

3.8

lock mandrel

retention device used for flow control equipment or other equipment

3.9

manufacturing

process and action performed by an equipment supplier/manufacture that are necessary to provide finished component(s), assembly(ies) and related documentation, that fulfil the requests of the user/purchaser and meet the standards of the supplier/manufacture

NOTE Manufacturing begins when the supplier/manufacture receives the order and is completed at the moment the component(s), assembly(ies) and related documentation are surrendered to a transportation provider.

**3.10
model**

lock mandrel or landing nipple equipment with unique components and operating characteristics which differentiate it from other lock mandrel or landing nipple equipment of the same type

**3.11
operating environment**

set of conditions to which the product is exposed during its full life cycle

**3.12
production/injection conduit**

tubulars and equipment which provide the flow path between the reservoir and the christmas tree, including the riser for subsea applications

**3.13
profile**

feature designed to receive the lock mandrel's locking mechanism

**3.14
sealing device**

device preventing passage (i.e. communication) of liquid and/or gas across the interface between the lock mandrel and the landing nipple

**3.15
size**

relevant dimensional characteristics of the equipment as defined by the supplier/manufacturer

**3.16
test pressure**

pressure at which the equipment is tested based upon all relevant design criteria

NOTE See 6.5.1 for test pressure requirements.

<https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47-150227c48d53/iso-16070-2005>

**3.17
test temperature**

temperature at which the equipment is tested based upon all relevant design criteria

**3.18
type**

lock mandrel or landing nipple equipment with unique characteristics which differentiate it from other functionally similar lock mandrel or landing nipple equipment

**3.19
rated working pressure**

landing nipple internal pressure design limit or lock mandrel differential pressure design limit from above and/or below, as established by the supplier/manufacturer

4 Abbreviated terms

- AQL Acceptance quality limit
- NDE Non-destructive examination
- TFL Through flowline

5 Functional specification

5.1 General

The user/purchaser shall prepare a functional specification for ordering products conforming to this International Standard and specify the following requirements and operating conditions, as applicable, and/or identify the supplier's/manufacturer's specific product. These requirements and operating conditions may be conveyed by means of a dimensional drawing, data sheet or other suitable documentation.

5.2 Functional characteristics of lock mandrels and landing nipples

The following functional characteristics shall be specified, as applicable, for lock mandrels and landing nipples:

- a) conveyance method;
- b) locking mechanism;
- c) no-go;
- d) selectivity;
- e) sealing device;
- f) dimensions;
- g) passage of lines (electrical and/or hydraulic) in the annulus (for landing nipples only).

5.3 Well parameters

ISO 16070:2005

<https://standards.iteh.ai/catalog/standards/sist/46db2e3e-242b-4726-ba47->

The following well parameters shall be specified, as applicable, for the lock mandrel and landing nipple:

- a) size, mass, material and grade of the casing and tubing;

NOTE The term "weight" is often incorrectly used to mean mass, but this practice is deprecated.
- b) well depth and angle from the vertical to the installed position;
- c) casing and tubing architecture, deviations, and restrictions through which the lock mandrel and/or landing nipple pass;
- d) anticipated loading conditions which might be applied to the lock mandrel and landing nipple.

5.4 Operational parameters

The following operational parameters shall be specified, as applicable, for the lock mandrel and landing nipple:

- a) acidizing, including the acid composition, pressure, temperature, velocity, exposure time and any other chemicals used during the stimulation;
- b) fracturing, including proppant description, fracture fluid velocity and proppant-to-fluid ratio;
- c) sand consolidation operations;
- d) type of well intervention, including service equipment such as electric line, slick line, braided line, coiled tubing, or snubbing equipment.

5.5 Environmental compatibility

The following shall be identified, as applicable, for the lock mandrel and landing nipple to ensure environmental compatibility:

- a) production/injection fluid composition, mass, chemical and/or physical composition, and the condition of the fluid and/or its components [i.e. solid (sand production, scale, etc.), liquid and/or gaseous], to which the lock mandrel and landing nipple is exposed during its full life cycle;
- b) both the minimum and the maximum anticipated values of the production/injection pressures, pressure differentials, temperatures and flow rates;
- c) in cases where the user/purchaser has access to corrosion property historical data and/or research which is applicable to the functional specification, the user/purchaser should state to the supplier/manufacturer which material(s) has the ability to perform as required within the corrosion environment.

5.6 Compatibility with the related well equipment

5.6.1 Lock mandrels

The following information shall be specified, as applicable, to ensure the compatibility of the lock mandrel with the related well equipment:

- a) size and/or type of the lock mandrel required to position the flow control equipment in the landing nipple;
- b) landing nipple size, model and type into which the lock mandrel is to be installed;
- c) size, type, material, configuration and interface dimensions of the connection between the flow control equipment and the lock mandrel;
- d) size, type and configuration of other products to be used with the lock mandrel.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 16070:2005

<https://standards.iteh.ai/catalog/standards/sist/46db7e3e-242b-4736-ba47-150227c48d53/iso-16070-2005>

5.6.2 Landing nipples

The following information shall be specified, as applicable, to ensure the compatibility of the landing nipples with the related well equipment:

- a) top and bottom tubular connection(s), the material and dimensions of the landing nipple which is connected to the tubing;
- b) internal receptacle profile(s), sealing bore dimension(s), outside diameter, inside diameter and their respective locations;
- c) size, type and configuration of lock mandrels or other products to be used with the landing nipple.

5.7 Quality documentation

The quality documentation grade (i.e. Q1 or Q2 as given in 7.4) shall be specified by the user/purchaser.

5.8 Design validation

The design validation grade (i.e. V1, V2 or V3 as given in 6.5) shall be specified by the user/purchaser.