
**Road vehicles — Cleanliness of
components of fluid circuits —**

Part 3:

**Method of extraction of contaminants by
pressure rinsing**

iTeh STANDARD PREVIEW
Véhicules routiers — Propreté des composants des circuits de fluide —
(standards.iteh.ai) **Partie 3: Méthode d'extraction des contaminants par aspersion**

[ISO 16232-3:2007](https://standards.iteh.ai/catalog/standards/sist/07ddd571-9914-4e8b-b138-614a5d50b4e9/iso-16232-3-2007)

[https://standards.iteh.ai/catalog/standards/sist/07ddd571-9914-4e8b-
b138-614a5d50b4e9/iso-16232-3-2007](https://standards.iteh.ai/catalog/standards/sist/07ddd571-9914-4e8b-b138-614a5d50b4e9/iso-16232-3-2007)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 16232-3:2007

<https://standards.iteh.ai/catalog/standards/sist/07ddd571-9914-4e8b-b138-614a5d50b4e9/iso-16232-3-2007>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Principle	2
5 Equipment	2
5.1 General.....	2
5.2 Test liquid	2
5.3 Test component container.....	2
5.4 Pressure rinsing liquid dispenser.....	2
5.5 Clean-up filter	2
5.6 Vacuum suction system.....	2
5.7 Collection equipment	2
5.8 Sampling containers.....	3
5.9 Environmental conditions.....	3
5.10 Health and safety	3
6 Procedure	3
6.1 Handling and storage	3
6.2 Extraction procedure set-up and validation.....	3
6.3 Blank test.....	6
6.3.1 Sources of blank contamination.....	6
6.3.2 System blank test	7
6.3.3 Blank value	7
6.4 Component routine test	8
7 Analysis of the extraction liquid	8
8 Presentation of results	9
Annex A (informative) Synopsis of the extraction procedure set-up and validation	10
Annex B (informative) Example of data sheet for the extraction procedure by pressure rinsing	11
Annex C (informative) Synopsis of the routine test procedure	14
Bibliography	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16232-3 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 5, *Engine tests*.

ISO 16232 consists of the following parts, under the general title *Road vehicles — Cleanliness of components of fluid circuits*:

iTeh STANDARD PREVIEW
(standards.iteh.ai)

- *Part 1: Vocabulary*
- *Part 2: Method of extraction of contaminants by agitation*
- *Part 3: Method of extraction of contaminants by pressure rinsing*
- *Part 4: Method of extraction of contaminants by ultrasonic techniques*
- *Part 5: Method of extraction of contaminants on functional test bench*
- *Part 6: Particle mass determination by gravimetric analysis*
- *Part 7: Particle sizing and counting by microscopic analysis*
- *Part 8: Particle nature determination by microscopic analysis*
- *Part 9: Particle sizing and counting by automatic light extinction particle counter*
- *Part 10: Expression of results*

Introduction

The presence of particulate contamination in a fluid system is acknowledged to be a major factor governing the life and reliability of that system. The presence of particles residual from the manufacturing and assembly processes will cause a substantial increase in the wear rates of the system during the initial run-up and early life, and may even cause catastrophic failures.

In order to achieve reliable performance of components and systems, control over the amount of particles introduced during the build phase is necessary, and measurement of particulate contaminants is the basis of control.

The ISO 16232 series has been drafted to fulfil the requirements of the automotive industry, since the function and performance of modern automotive fluid components and systems are sensitive to the presence of a single or a few critically sized particles. Consequently, ISO 16232 requires the analysis of the total volume of extraction liquid and of all contaminants collected using an approved extraction method.

The ISO 16232 series has been based on existing ISO International Standards such as those developed by ISO/TC 131/SC6. These International Standards have been extended, modified and new ones have been developed to produce a comprehensive suite of International Standards to measure and report the cleanliness levels of parts and components fitted to automotive fluid circuits.

This part of ISO 16232 defines procedures for the removal and collection of contaminants from components by rinsing with a jet of test liquid so that their cleanliness can be evaluated.

The cleanliness level of a component, as determined according to this method, depends to a large extent on the test parameters (e.g. rinsing pressure, volume of liquid, type of jet). All parameters should be included in the cleanliness specification and in the inspection document and should be rigorously followed by the test staff.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 16232-3:2007

<https://standards.iteh.ai/catalog/standards/sist/07ddd571-9914-4e8b-b138-614a5d50b4e9/iso-16232-3-2007>

Road vehicles — Cleanliness of components of fluid circuits —

Part 3: Method of extraction of contaminants by pressure rinsing

1 Scope

This part of ISO 16232 describes the principles of extraction of contaminants from a component by pressure rinsing. It is preferably applied to components of which the surface to be examined is accessible by a jet of test liquid.

This method can be employed on its own or in association with other methods of extraction described in the ISO 16232 series.

Unless otherwise specified, this part of ISO 16232 deals with particulate contamination only. It does not, therefore, cover appearance defects or contamination by liquid or gaseous materials. It covers the amount and the nature of residual particles resulting from manufacturing processes and from the environment.

(standards.iteh.ai)

2 Normative references

ISO 16232-3:2007

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16232-1, *Road vehicles — Cleanliness of components of fluid circuits — Part 1: Vocabulary*

ISO 16232-2, *Road vehicles — Cleanliness of components of fluid circuits — Part 2: Method of extraction of contaminants by agitation*

ISO 16232-4, *Road vehicles — Cleanliness of components of fluid circuits — Part 4: Method of extraction of contaminants by ultrasonic techniques*

ISO 16232-5, *Road vehicles — Cleanliness of components of fluid circuits — Part 5: Method of extraction of contaminants on functional test bench*

ISO 16232-6, *Road vehicles — Cleanliness of components of fluid circuits — Part 6: Particle mass determination by gravimetric analysis*

ISO 16232-7, *Road vehicles — Cleanliness of components of fluid circuits — Part 7: Particle sizing and counting by microscopic analysis*

ISO 16232-8, *Road vehicles — Cleanliness of components of fluid circuits — Part 8: Particle nature determination by microscopic analysis*

ISO 16232-9, *Road vehicles — Cleanliness of components of fluid circuits — Part 9: Particle sizing and counting by automatic light extinction particle counter*

ISO 16232-10:2007, *Road vehicles — Cleanliness of components of fluid circuits — Part 10: Expression of results*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16232-1 apply.

4 Principle

The contaminants are extracted from the controlled surface of the component by pressure rinsing with a jet of test liquid which carries away the particles for subsequent analysis.

5 Equipment

5.1 General

The equipment used shall neither alter nor modify the size distribution of the extracted particles.

5.2 Test liquid

The test liquid shall be compatible with all the materials in the component, with the liquid used in the final system and with the test equipment, including seals, membrane filter and clean-up filter. A test liquid of low viscosity ($\leq 5 \text{ mm}^2/\text{s}$) and having the capability of removing (or dissolving) oil and grease is recommended. It should be filtered to attain the requirements of 6.3.3.

SAFETY PRECAUTIONS — In case a tested component will be reclaimed for final use, application of incompatible test liquid may cause hazardous damage.

5.3 Test component container

A closed container should be used for the transfer of the component from the place of sampling to the place of particle extraction. This container shall be appropriate to the shape of the component and made of material compatible with the test liquid. Its degree of cleanliness shall comply with the blank requirements specified in 6.3.3.

5.4 Pressure rinsing liquid dispenser

The pressure liquid dispenser is a device that provides clean test liquid specified in 5.2 at a pressure and flow rate capable of extracting the contaminants in an effective manner. The dispenser can also be used to rinse the test equipment and all other items.

5.5 Clean-up filter

If used, a clean-up filter of the test liquid shall achieve the blank level specified and have a retention capacity such that it does not require replacement too often in order to not introduce particles.

5.6 Vacuum suction system

If necessary, use an assembly consisting of a source of vacuum, a vacuum flask previously cleaned and a flexible tube of suitable dimensions and shape for recovery of the extraction liquid and the contaminants accumulated in the component under examination.

5.7 Collection equipment

The collection equipment shall allow effective draining of particles. A conical base is preferred.

The collection equipment shall be cleaned to achieve the requirement of 6.3.3.

It is possible for contaminants remaining on the equipment to be transferred to the sample and thus be erroneously included as part of the particles removed from the component. All collection equipment shall be cleaned and covered before use in order to limit contamination from the environment.

5.8 Sampling containers

The sampling containers (glassware, etc.) required for transferring the extraction liquid from the collection equipment to the analysis equipment shall be cleaned to achieve the requirements of 6.3.3.

5.9 Environmental conditions

The cleanliness of the environment where the extraction is performed shall be consistent with the presumed cleanliness of the component to test. This requirement may result in the test being carried out in a laboratory or controlled workplace. The suitability of the environment is validated when performing the blank test.

5.10 Health and safety

5.10.1 Local Health and Safety procedures shall be followed at all times, any equipment shall be operated in accordance with the manufacturer's instruction and personal protection equipment used where appropriate.

5.10.2 Chemicals used in the procedures can be harmful, toxic or flammable. Good laboratory practices shall be observed in the preparation and use of these chemicals. Care shall be taken to ensure compatibility of the chemicals with the materials used (refer to each Material Safety Data Sheet [MSDS]). Follow the precautions for safe handling and usage as described in the MSDS available from the supplier.

5.10.3 Volatile liquids; care shall be taken with flammable liquids to ensure that they are used in accordance with the MSDS, at temperatures below the stated flash point and away from potential sources of ignition. Appropriate precautions should be taken to avoid inhalation of fumes from these solvents. Always use suitable protective equipment.

5.10.4 Electrical; appropriate care should be applied in the use of electrical power.

5.10.5 Disposal; all liquids and substances shall be disposed of in accordance with local environmental procedures. In the event of spillage it shall be cleaned-up in the manner detailed in the MSDS.

6 Procedure

6.1 Handling and storage

6.1.1 During handling and storage of test components, it shall be ensured that no contaminants are deposited on or removed from controlled surfaces.

6.1.2 To prevent loss from particles during transport it may be necessary to seal openings of the test components, e.g. with suitable plugs.

6.2 Extraction procedure set-up and validation

6.2.1 The number of components to be analysed shall be chosen so as to measure a significant number of contaminants, so that it complies with the requirements for a blank (see 6.2.18 NOTE 3).

6.2.2 If the break-in of the component is part of its manufacturing process the extraction procedure should be agreed between parties and included in the inspection document because break-in may alter the component's initial cleanliness level.

6.2.3 For active components, it may be necessary to operate them in order to pass the test liquid through during the extraction procedure. In this case, the initial contamination level may be altered. The extraction conditions should be agreed upon between parties and included in the inspection document.

6.2.4 If the particles detached during transportation of the test component and particles from the packaging shall be included in the cleanliness inspection, they shall be collected using the appropriate extraction method (e.g. low pressure rinsing) as agreed upon between parties and included in the inspection document.

6.2.5 The effectiveness of pressure rinsing depends on the following, non-exhaustive list of parameters: pressure, flow rate, distance, angle, size and shape of the nozzle (flat, circular, etc.), sequence/procedure, how the components are treated, time/liquid volume per unit area. A synopsis of the operations to perform is given in Annex A. The detailed description of operating conditions and equipment used in application of this standard to rinse and empty the component constitutes the extraction procedure. This procedure shall be established for each component and shall be both agreed between parties and included in the inspection document. Details of the procedure shall be reported on a suitable data sheet (for an example of an extraction procedure data sheet see Annex B).

6.2.6 If needed for reporting results and if not specified, determine the controlled volume and/or controlled surface area of the component under examination (see Annex B of ISO 16232-10:2007). Report and/or specify their values in the inspection document.

6.2.7 Before starting to set up or validate any extraction protocol/equipment, it is necessary to perform an initial blank test to know the cleanliness of the equipment. This is performed after cleaning the equipment and the initial blank shall exhibit values stated in 6.3.3.

NOTE Conditioning and cleaning serves the purpose of obtaining a suitable cleanliness level of the inspection set-up. It is recommended that a basic procedure for conditioning the inspection set up be defined. For example, by performing a cleanliness analysis of a defined volume of liquid after the cleaning procedure of the set-up, it can be determined whether the inspection environment is in suitable conditions and acceptable for carrying out a validation procedure. The initial blank shall exhibit values stated in 6.3.3.

6.2.8 If necessary, demagnetise the component and/or clean those external surfaces which are not involved in the cleanliness inspection. The external surface should be cleaned in a physically different place from where extraction is to be carried out. Ensure that no particles are deposited on or removed from controlled surfaces. For example, if the component is of large size (like a tank), clean only those external surfaces which might contribute to contamination during the extraction process.

6.2.9 If necessary, remove all covers and other plugs fitted for transport of the component. If the component contains a shipment liquid, empty it out, measure its volume and analyse its contaminants according to Clause 7.

NOTE Dismantling or removal of plugs might generate particles to contribute to the original contamination.

6.2.10 Place the component over the clean collection equipment as specified in 5.7.

When components are heavy or large, they should be manipulated and moved to a suitable position with appropriate supports (e.g. a sling, a frame or a pulley block). This position shall enable the extraction liquid to flow easily into a collection equipment or sampling container. For components which are difficult to empty, such as tanks, it is possible to use a vacuum suction system to collect the whole extraction liquid.

6.2.11 If dismantling is necessary to obtain access to all the surfaces to be inspected, do so with care.

NOTE Any operation of dismantling might generate particles which could be added to or lost from the original amount of particles.

6.2.12 Equip the test liquid dispenser with one or more spray nozzle(s), suitable for the surfaces to be pressure rinsed.

6.2.13 Adjust the pressure of the test liquid to obtain a jet of sufficient power to remove and transport the particles from the controlled surfaces without degrading or dissolving the surface material of the component.

6.2.14 Rinse the controlled surfaces carefully with test liquid sprayed on through the nozzle, ensuring that the whole controlled surface has been swept by the jet in order to extract the particles from the component(s). Depending on the presumed amount of particles or extraction liquid volume, collect the extraction liquid in either a single or several sampling containers or, if appropriate, by using the vacuum suction system.

6.2.15 Collect all recovered extraction liquids and particles. Carefully rinse the collection equipment and collect all of the accumulated particles in a clean sampling container. Identify the sampling container.

NOTE 1 As a function of the level of particle observed in the extraction liquid, it may be necessary to divide the total volume among several sampling containers to facilitate their subsequent analysis, to avoid either clogging of the membrane filter during filtration, the saturation of an APC or overlapping particles in the case of microscopic analysis.

NOTE 2 Instead of collecting in a container, the liquid samples may also be directed through a membrane filter directly connected to the outlet of the collection equipment.

6.2.16 Analyse the extraction liquid in accordance with Clause 7 and label the result obtained as S_1 .

6.2.17 Repeat 6.2.14 to 6.2.16 twice more on the same component, using, when necessary, a different container for each extraction liquid volume and label the result obtained as S_2 and S_3 .

NOTE The extractions should be made directly the one after the other.

6.2.18 Validate the contamination extraction procedure to ensure its efficacy as follows:

- a) for each of the three samples analysed in 6.2.16 and 6.2.17, establish the total mass of contaminants and/or the total number of particles. For the particle count, this is applicable to the total number of particles larger than the smallest particle size specified in the inspection document. This particle size shall be chosen to enable counting significant numbers of particles;
- b) divide the result of the last sample (S_3) by the sum of all the values obtained in 6.2.18 a);
- c) if the value obtained is less than or equal to 10 %, the end-point is reached and the extraction is completed.

NOTE 1 This procedure enables the extraction curve to be drawn and the end-point ($\leq 0,10$) to be demonstrated (see Figure 1).

NOTE 2 The cleanliness level of the component is the sum of the extractions.

NOTE 3 In some cases (for example: a very low contamination level, difficulties in extracting particles, inappropriate blank level, etc.) the extraction curve may not be of the form seen in Figure 1. If this is the case, it is ensured that all extraction parameters have been properly investigated.

- d) If the value obtained is $> 0,10$, a further extraction is necessary. Repeat stages 6.2.14 to 6.2.18 until the last sample (S_n) produces a result $\leq 0,10$ of the total of the whole samples ($S_n \leq \frac{10}{100} \sum_{i=1}^n S_i$).

6.2.19 If six extractions have been performed without reaching a value $\leq 0,10$, then the extraction parameters are not suitable and shall be modified. Then repeat operations 6.2.14 to 6.2.18 with new parameters on a new component.

6.2.20 If this criterion is not fulfilled, set up a new extraction protocol and validate it according to 6.2 or apply another extraction method as defined in ISO 16232-2, ISO 16232-4 and ISO 16232-5.