

Designation: D5360 - 05

Standard Practice for Design and Construction of Bituminous Surface Treatments¹

This standard is issued under the fixed designation D5360; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This practice covers the design and construction of bituminous surface treatments. It is a guide and should be used as such. End-use specifications should be adopted to conform to job and user requirements.
- 1.2 The values given in inch-pound units are to be regarded as the standard.
- 1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. For specific precautions see Section 9.

2. Referenced Documents

2.1 ASTM Standards:²

D448 Classification for Sizes of Aggregate for Road and Bridge Construction

D490 Specification for Road Tar

D946 Specification for Penetration-Graded Asphalt Cement for Use in Pavement Construction

D977 Specification for Emulsified Asphalt

D1139 Specification for Aggregate for Single or Multiple Bituminous Surface Treatments

D1369 Practice for Quantities of Materials for Bituminous Surface Treatments

D2027 Specification for Cutback Asphalt (Medium-Curing Type)

D2028 Specification for Cutback Asphalt (Rapid-Curing Type)

D2397 Specification for Cationic Emulsified Asphalt

D2399 Practice for Selection of Cutback Asphalts

¹ This practice is under the jurisdiction of ASTM Committee D04 on Road and Paving Materials and is the direct responsibility of Subcommittee D04.24 on Bituminous Surface Treatments.

Current edition approved Feb. 1, 2005. Published February 2005. Originally approved in 1998. Last previous edition approved in 1998 as D5360 - 98. DOI: 10.1520/D5360-05.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D2995 Practice for Estimating Application Rate of Bituminous Distributors

D3381 Specification for Viscosity-Graded Asphalt Cement for Use in Pavement Construction

D3628 Practice for Selection and Use of Emulsified Asphalts

D5624 Test Method for Determining the Transverse-Aggregate Spread Rate for Surface Treatment Applications

3. Terminology

- 3.1 Definitions of Terms Specific to This Standard:
- 3.1.1 *multiple surface treatment*—the bituminous surface produced by the repeat application of bitumen and aggregate a second or even a third time, with the aggregate size usually becoming smaller with each application. Each layer is immediately rolled, preferably with a pneumatic-tired roller.
- 3.1.2 *single surface treatment*—the bituminous surface produced by the application of bitumen to a prepared surface followed at once by an aggregate cover. The surface is immediately rolled, preferably with a pneumatic-tired roller.
- 3.1.3 *surface treatment*—an application of bituminous material followed by a layer of mineral aggregate. Multiple applications of bituminous material and mineral aggregate may be used.

4. Significance and Use

4.1 This practice is to be used as a guide and not a specification.

5. Ordering Information

- 5.1 Orders for seal coat and surface treatment materials under this guide shall include the following information:
- 5.1.1 Type of bitumen (asphalt cement, emulsified asphalt, cutback asphalt, road tar) specification designation,
 - 5.1.2 Grade of bitumen,
 - 5.1.3 Quantity of bitumen required,
- 5.1.4 Type of aggregate (crushed stone, crushed gravel, crushed slag, gravel, slag) specification designation,
 - 5.1.5 Size or sizes of aggregate to be furnished,
 - 5.1.6 Quantity of aggregate required, and
 - 5.1.7 Special requirements.