

ETSI EN 300 176-1 V2.2.1 (2015-10)



Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio

iTeh STANDARD PREVIEW
(standard.it-eh.com)
Full standard available on iTeh.com
https://standards.it-eh.com/catalog/standards/sls/08822015-2015-10-4baa-ae63-7b263224b840/etsi-en-300-176-1-v2-2-1-2015-10

ReferenceREN/DECT-000303

KeywordsDECT, radio, regulation, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
Modal verbs terminology.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	13
3.1 Definitions.....	13
3.2 Symbols.....	15
3.3 Abbreviations	15
4 General	16
4.1 Document layout	16
4.1.1 Test suites	16
4.1.2 Test groups.....	17
4.1.3 Test cases.....	18
4.2 Presentation of equipment for testing purposes.....	18
4.2.0 General.....	18
4.2.1 Choice of model for testing (if applicable).....	18
4.2.2 Description of equipment.....	18
4.2.2.0 General	18
4.2.2.1 Protocol Implementation Conformance Statement (PICS).....	18
4.2.2.2 Protocol Implementation Extra Information for Testing (PIXIT).....	19
4.2.2.3 Environmental test conditions.....	19
4.2.3 Host connected equipment.....	19
4.2.4 Applicants' declaration.....	19
4.3 Applicability of tests	19
4.3.0 General.....	19
4.3.1 Equipment that includes only a DECT RF receiver.....	19
4.3.2 Equipment that includes a radio transmitter	19
4.3.3 CTAs.....	20
4.3.4 Equipment with a synchronization port	20
4.3.5 Equipment incorporating the IPEI (PPs only).....	20
4.3.6 All FP equipment.....	20
4.3.7 PPs with direct PP to PP communication option	20
4.3.8 Installation related issues	20
4.3.9 Equipment with combined FT and PT functionality.....	20
4.3.9.0 General	20
4.3.9.1 Wireless Relay Station	20
4.3.9.2 Direct PP to PP communication	21
4.3.9.3 Distributed communications	21
4.3.10 Provision of 4 Mbit/s services. Equipment that is capable of using 4-level, 8-level, 16-level and/or 64-level modulation	21
4.3.11 Equipment supporting additional carriers	21
4.4 Interpretation of the measurement results	21
5 General test requirements	22
5.1 Test philosophy	22
5.2 Test site	23
5.2.1 Open air test site	23
5.2.1.1 Description	23
5.2.1.2 Calibration.....	23
5.2.2 Anechoic chamber	24
5.2.2.1 General	24
5.2.2.2 Description	24

5.2.2.3	Influence of parasitic reflections	27
5.2.2.4	Calibration and mode of use.....	27
5.2.3	Stripline coupler.....	27
5.2.3.0	General	27
5.2.3.1	Description	27
5.2.3.2	Calibration.....	27
5.2.3.3	Mode of use.....	27
5.3	Standard position.....	28
5.4	Test antenna of the LT.....	28
5.5	Substitution antenna	28
5.6	Test fixture	28
5.6.1	Description.....	28
5.6.1.0	General	28
5.6.1.1	Calibration of the test fixture for the measurement of transmitter characteristics.....	29
5.6.1.2	Calibration of the test fixture for the measurement of receiver characteristics	29
5.6.1.3	Mode of use.....	30
5.6.2	Equipment with a temporary or internal permanent antenna connector.....	30
5.6.2.0	General	30
5.6.2.1	Equipment with a temporary antenna connector	30
5.7	Indoor test site	31
5.7.0	General.....	31
5.7.1	Description.....	31
5.7.2	Test for parasitic reflections.....	32
5.7.3	Calibration and mode of use	32
5.8	Lower Tester (LT).....	32
5.8.1	Description.....	32
5.8.2	Connections between the EUT and the LT	32
5.8.3	Functions and abilities	33
5.8.4	Signal generation uncertainty	33
5.8.4.0	General	33
5.8.4.1	Modulated DECT-like carrier.....	33
5.8.4.2	CW interferers.....	33
5.8.4.3	DECT RF signal.....	33
5.8.4.4	Test modulation signals.....	33
5.8.5	Measurement uncertainty.....	34
5.9	Upper Tester (UT).....	34
5.9.1	Description of the UT	34
5.9.2	The test standby mode	34
5.9.3	Test messages	34
5.9.4	Dummy setting when EUT is a RFP and it is in test stand-by mode	35
5.10	Description of the lower tester FT and PT	35
5.11	General test methods	35
5.11.1	General.....	35
5.11.2	Sampling the RF signal.....	35
5.11.2.1	Introduction	35
5.11.2.2	Sampling method	35
5.11.3	Determining the reference position.....	36
5.11.3.0	General	36
5.11.3.1	Case 1: EUTs that cannot transmit.....	36
5.11.3.2	Case 2: EUTs that can transmit.....	36
5.11.4	Bit Error Rate (BER) and Frame Error Ratio (FER) measurements.....	36
5.12	Test setup.....	36
5.12.0	General.....	36
5.12.1	Test setup 1	37
5.12.2	Test setup 2	37
5.12.3	Test setup 3	37
5.12.4	Test setup 4.....	38
5.12.5	Test setup 5.....	38
5.13	Test arrangements for intermodulation measurements.....	39
5.13.1	PT to PT arrangement	39
5.13.2	FT to FT arrangement.....	39
5.13.3	FT to PT arrangement.....	40

6	Test conditions, power sources and ambient temperatures	40
6.1	General	40
6.2	Nominal test conditions	41
6.3	Extreme test conditions	41
6.4	Test power source - general requirements	42
6.5	Nominal test power source	43
6.5.1	Mains voltage.....	43
6.5.2	Regulated lead acid battery power sources	43
6.5.3	Nickel cadmium battery	43
6.5.4	Other power sources	43
6.6	Extreme test power source.....	43
6.6.1	Mains voltage.....	43
6.6.2	Regulated lead acid battery power sources	43
6.6.3	Nickel cadmium battery	43
6.6.4	Other power sources	43
6.7	Testing of host connected equipment and plug-in cards.....	43
6.7.0	Approaches	43
6.7.1	Alternative A: composite equipment	44
6.7.2	Alternative B: use of a test jig and three hosts.....	44
7	Accuracy and stability of RF carriers	44
7.0	Requirements.....	44
7.1	Definition	44
7.2	Test environment.....	45
7.3	Method of measurement	45
7.4	Verdict criteria when the EUT is a RFP	45
7.5	Verdict criteria when the EUT is a PP.....	46
8	Accuracy and stability of timing parameters	46
8.0	Requirements.....	46
8.1	Slot structure definitions	46
8.2	Definition of the position of p0	48
8.3	Measurement of packet timing jitter	48
8.3.1	Test environment	48
8.3.2	Method of measurement	48
8.3.3	Verdict criteria	48
8.4	Measurement of the reference timing accuracy of a RFP.....	48
8.4.1	Test environment	48
8.4.2	Method of measurement	49
8.4.3	Verdict criteria	49
8.5	Measurement of packet transmission accuracy of a PP	49
8.5.1	Test environment	49
8.5.2	Method of measurement	49
8.5.3	Verdict criteria	50
9	Transmission burst	50
9.0	Requirements.....	50
9.1	Definitions	50
9.1.1	Physical packets.....	50
9.1.2	Transmitted power	50
9.1.3	Normal Transmitted Power (NTP).....	50
9.1.4	Transmitter attack time	50
9.1.5	Transmitter release time.....	50
9.1.6	Minimum power	51
9.1.7	Maximum power.....	51
9.1.8	Maintenance of transmission after packet end	51
9.1.9	Transmitter idle power output.....	51
9.2	Test environment.....	51
9.3	Method of measurement	51
9.4	Verdict criteria.....	52
10	Transmitted power.....	52
10.0	Requirements.....	52

10.1	Definitions	52
10.1.1	PP and RFP with an integral antenna	52
10.1.2	PP and RFP with external connections for all antennas	52
10.1.3	PP and RFP with both integral and external antennas	52
10.2	PP and RFP with an integral antenna	53
10.2.1	Test environment	53
10.2.2	Method of measurement	53
10.2.2.0	General	53
10.2.2.1	Measurement of NTP	53
10.2.2.2	Measurement of antenna gain	53
10.2.2.3	Determination of EIRP	54
10.2.3	Verdict criteria for all EUTs	54
10.3	PP and RFP with external antenna connection(s)	54
10.3.1	Test environment	54
10.3.2	Method of measurement	54
10.3.3	Verdict criteria for all EUTs	54
11	RF carrier modulation	55
11.0	Requirements	55
11.1	Test environment	55
11.2	Method of measurement, parts 1 and 2	55
11.2.0	General	55
11.2.1	Part 1	55
11.2.2	Part 2	55
11.3	Method of measurement, parts 3 and 4	56
11.3.0	General	56
11.3.1	Part 3	56
11.3.2	Part 4	56
11.4	Verdict criteria for part 1	57
11.5	Verdict criteria for part 2	57
11.6	Verdict criteria for part 3	57
11.7	Verdict criteria for part 4	57
12	Unwanted RF power radiation	58
12.1	General test conditions	58
12.2	Emissions due to modulation	58
12.2.0	Requirements	58
12.2.1	Definition	58
12.2.2	Test environment	58
12.2.3	Method of measurement	59
12.2.4	Verdict criteria	59
12.3	Emissions due to transmitter transients	60
12.3.0	Requirements	60
12.3.1	Definition	60
12.3.2	Test environment	60
12.3.3	Method of measurement	60
12.3.4	Verdict criteria	61
12.4	Emissions due to intermodulation	61
12.4.0	Requirements	61
12.4.1	Definition	61
12.4.2	Test environment	61
12.4.3	Method of measurement	61
12.4.4	Verdict criteria	62
12.5	Spurious emissions when allocated a transmit channel	62
12.5.0	Requirements	62
12.5.1	Definition	62
12.5.2	Radiated emissions	63
12.5.2.1	Test environment	63
12.5.2.2	Method of measurement	63
12.5.2.3	Verdict criteria	64
12.5.3	Conducted spurious emissions when the EUT has a permanent external antenna connector	64
12.5.3.1	Test environment	64

12.5.3.2	Method of measurement.....	64
12.5.3.3	Verdict criteria	64
13	Radio receiver testing.....	65
13.1	Radio receiver sensitivity	65
13.1.0	Requirements	65
13.1.1	Definition.....	65
13.1.2	Test environment	65
13.1.3	Method of measurement	65
13.1.4	Verdict criteria.....	65
13.2	Radio receiver reference BER and FER	66
13.2.0	Requirements	66
13.2.1	Definition.....	66
13.2.2	Test environment	66
13.2.3	Method of measurement	66
13.2.4	Verdict criteria	66
13.3	Radio receiver interference performance.....	66
13.3.0	Requirements	66
13.3.1	Definition.....	66
13.3.2	Test environment	66
13.3.3	Method of measurement	67
13.3.4	Verdict criteria.....	67
13.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	67
13.4.0	Requirements	67
13.4.1	Definition.....	67
13.4.2	Test environment	67
13.4.3	Method of measurement	68
13.4.4	Verdict criteria.....	69
13.5	Radio receiver blocking case 2: owing to signals occurring at a different time	69
13.5.0	Requirements	69
13.5.1	Definition.....	69
13.5.2	Test environment	69
13.5.3	Method of measurement	69
13.5.4	Verdict criteria.....	70
13.6	Receiver intermodulation performance	70
13.6.0	Requirements	70
13.6.1	Definition.....	70
13.6.2	Test environment	70
13.6.3	Method of measurement	70
13.6.4	Verdict criteria.....	71
13.7	Spurious emissions when the PP has no allocated transmit channel	71
13.7.0	Requirements	71
13.7.1	Definition.....	71
13.7.2	Test environment	71
13.7.3	Method of measurement	71
13.7.4	Verdict criteria (outside the DECT band).....	71
13.7.5	Verdict criteria (inside the DECT band).....	72
14	Intersystem synchronization (FP only).....	72
14.0	Requirements.....	72
14.1	Description	72
14.2	Test environment.....	72
14.3	Wired synchronization ports.....	72
14.3.1	FP as a master	72
14.3.1.1	Method of measurement.....	72
14.3.1.2	Verdict criteria	73
14.3.2	FP as a slave.....	73
14.3.2.1	Method of measurement.....	73
14.3.2.2	Verdict criteria	73
14.4	GPS synchronization	74
14.4.1	FP with integrated Global Positioning System (GPS) synchronization	74
14.4.1.1	Method of measurement.....	74

14.4.1.2	Verdict criteria	74
14.4.2	External GPS synchronization device.....	74
14.4.2.1	Method of measurement.....	74
14.4.2.2	Verdict criteria	74
15	EMC	75
16	Equipment identity testing.....	75
16.1	PP	75
16.2	FP	75
17	Efficient use of the radio spectrum.....	75
17.1	Channel selection	75
17.2	Channel confirmation	75
17.2.1	For the PT	75
17.2.2	For the FT	76
17.3	Channel release	76
17.4	General	76
17.5	Channel selection and confirmation for DECT ULE	76
17.5.1	General.....	76
17.5.2	For the PT	77
17.5.3	For the FT	77
18	WRS testing.....	77
18.0	General	77
18.1	Testing as a PP	77
18.2	Testing as an RFP.....	77
18.3	Applicants declarations	78
19	Requirements for PPs with direct PP to PP communication mode	78
19.0	General	78
19.1	Setting the EUT in direct communications mode.....	78
19.2	When the EUT has not initiated a call.....	79
19.3	When the EUT initiates a call.....	79
19.4	Applicants declarations	79
20	Distributed communications.....	79
20.0	General	79
20.1	Testing as a PP	80
20.2	Testing as an RFP.....	80
20.3	Applicants declaration.....	80
21	Higher level modulation options.....	81
21.0	General	81
21.1	Activation of higher level modulations when EUT is in test stand-by mode	81
21.2	Applicants declaration.....	82
Annex A (normative):	Procedures for test fixture calibration and for measurement of radiated spurious emissions	83
A.1	Calibration of test fixture for receiver measurements	83
A.1.0	General	83
A.1.1	Method of measurement.....	83
A.2	Radiated measurements.....	84
A.2.1	General	84
A.2.2	Radiated spurious emissions.....	85
A.2.2.1	Definition.....	85
A.2.2.2	Method of measurement	85
A.2.3	Cabinet radiation	87
A.2.3.1	Definition.....	87
A.2.3.2	Method of measurement	87
Annex B (normative):	Procedure for measurement of conducted spurious emissions.....	88
B.1	Conducted spurious emissions	88

B.1.1	Definition	88
B.1.2	Method of measurement	88
Annex C (normative):	Test Support Profile (TSP).....	89
C.1	Introduction	89
C.2	Standardized symbols for the status column	89
C.3	Capabilities of PP (EUT) under test	90
C.3.1	Services	90
C.3.2	Messages	90
C.3.3	Message parameters	92
C.3.4	Procedure support.....	96
C.3.5	CSF multiplexing functions.....	96
C.3.6	Timer and counter support.....	97
C.4	Capabilities of FP (EUT) under test	98
C.4.1	Services	98
C.4.2	Messages	98
C.4.3	Message parameters	100
C.4.4	Procedure support.....	104
C.4.5	CSF multiplexing functions.....	104
C.4.6	Timer and counter support.....	105
Annex D (normative):	Measurement of BER and FER.....	106
Annex E (informative):	Procedures for the measurement of synchronization loss at the EUT by the LT	107
E.1	Description	107
E.2	Method	107
Annex F (informative):	Guide lines for installation related issues	108
F.0	General	108
F.1	Antennas with directivity	108
F.2	DECT frame synchronization.....	108
F.2.0	General	108
F.2.1	Guidance for installation of frame synchronized DECT systems.....	109
F.2.1.1	GPS synchronization.....	109
F.2.1.2	Wired synch port synchronization	109
F.2.1.3	Requirements for DECT air synchronization.....	110
History	111

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document contains text pertaining to testing of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface [1] to [4] and [i.11] to [i.14]. Such text should be considered as guidance to approval (or licensing) authorities.

Details of the DECT Common Interface may be found in ETSI EN 300 175 [1] to [4] and [i.11] to [i.14]. Further details of the DECT system may be found in ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2].

The present document is part 1 of a multi-part deliverable covering the test specification for Digital Enhanced Cordless Telecommunications (DECT), as identified below:

Part 1: "Radio";

Part 2: "Audio and speech".

National transposition dates

Date of adoption of this EN:	13 October 2015
Date of latest announcement of this EN (doa):	31 January 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2016
Date of withdrawal of any conflicting National Standard (dow):	31 July 2016

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document (part 1) specifies tests applicable to all Digital Enhanced Cordless Telecommunications (DECT) equipment accessing the DECT frequency band 1 880 MHz to 1 900 MHz (including provisions for testing other or extended frequency bands as described in ETSI EN 300 175-1 [i.11] and ETSI EN 300 175-2 [1]). Part 2 of the present multi-part deliverable [i.15] specifies tests applicable to DECT speech and audio transmission using a collection of speech codecs, including Recommendation ITU-T G.726 [i.7] ADPCM codec, Recommendation ITU-T G.722 [i.8] "7 kHz codec", "MPEG-4 codec" [i.10] and others.

The aims of the present document are to ensure:

- efficient use of frequency spectrum;
- no harm done to any connected network and its services;
- no harm done to other radio networks and services;
- no harm done to other DECT equipment or its services;
- interworking of terminal equipment via the public network.

The tests of ETSI EN 300 176 are split into two parts:

- the present document (part 1) covers testing of radio frequency parameters, security elements and those DECT protocols that facilitate the radio frequency tests and efficient use of frequency spectrum;
- part 2 [i.15] describes testing of speech and audio requirements between network interface and DECT PT, or between a DECT CI air interface and alternatively a DECT PT or FT. Part 2 is not applicable to terminal equipment specially designed for the disabled (e.g. with amplification of received speech as an aid for the hard-of-hearing).

DECT terminal equipment consists of the following elements:

- a) Fixed Part (FP);
- b) Portable Part (PP);
- c) Cordless Terminal Adapter (CTA);
- d) Wireless Relay Station (WRS) (FP and PP combined);
- e) Hybrid Part (HyP) (a PP with capability to act as a FP to provide PP to PP communication).

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".

- [2] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [3] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [4] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [5] Recommendation ITU-T V.11: "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [6] Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [7] ETSI EN 300 700: "Digital Enhanced Cordless Telecommunications (DECT); Wireless Relay Station (WRS)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 178: "Digital Enhanced Cordless Telecommunications (DECT); A High Level Guide to the DECT Standardization".
- [i.2] ETSI ETR 043: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Services and facilities requirements specification".
- [i.3] ETSI EN 301 649: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)".
- [i.4] ETSI TS 102 527-1: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 1: Wideband speech".
- [i.5] ETSI TS 102 527-2: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 2: Support of transparent IP packet data".
- [i.6] ETSI TS 102 527-3: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 3: Extended Wideband speech services".
- [i.7] Recommendation ITU-T G.726 (1990): "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
- [i.8] Recommendation ITU-T G.722: "7 kHz audio - coding within 64 kbit/s".
- [i.9] Void.
- [i.10] ISO/IEC JTC1/SC29/WG11 (MPEG): International Standard ISO/IEC 14496-3:2005/AMD 1:2007: "Information Technology - Coding of audio-visual objects - Part 3: Audio; AMENDMENT 1: Low Delay AAC profile".
- [i.11] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [i.12] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".

- [i.13] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [i.14] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [i.15] ETSI EN 300 176-2: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech".
- [i.16] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- NOTE: See also ITU-T Recommendation X.290.
- [i.17] Void.
- [i.18] Council Directive 2004/108/EC of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC.
- [i.19] ETSI EN 301 406: "Digital Enhanced Cordless Telecommunications (DECT); Harmonized EN for Digital Enhanced Cordless Telecommunications (DECT) covering the essential requirements under article 3.2 of the Radio Equipment Directive; Generic radio".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

antenna diversity: feature that implies that the Radio Fixed Part (RFP) is able to select for each bearer independently different antenna properties such as gain, polarization, coverage patterns, and other features that may affect the practical coverage

NOTE: A typical example is space diversity, provided by two vertically polarized antennas separated by 10 cm to 20 cm.

bearer handover: internal handover process provided by the Medium Access Control (MAC) layer, whereby one MAC connection can modify its underlying bearers while maintaining the service provided to the Data Link Control (DLC) layer

NOTE: Bearer handover is slot based.

cell: domain served by a single antenna system (including a leaky feeder) of one FP

NOTE: A cell may include more than one source of radiated Radio Frequency energy (i.e. more than one Radio End Point).

central control fixed part: physical grouping that contains the central control elements of one or several FPs

NOTE: An FP may be split in the control part (CCFP) and the Radio part (RFP). A CCFP may control one or more RFPs.

conducted measurements: measurements which are made using a direct connection to the equipment under test

cordless terminal adapter: physical grouping that contains a DECT portable termination and a line interface

DECT Distributed communications: communication capability of a DECT Local Network that allows a number of DECT terminals (a FP and number of PPs) to co-exists and directly communicate one with another

DECT-like carrier: modulated RF DECT carrier used for interference testing which conforms to the requirements in ETSI EN 300 175-2 [1] in terms of frequency and timing and uses a pseudo-random sequence for modulation

double slot: one-12th of a Time Division Multiple Access (TDMA) frame which is used to support one high-capacity physical channel