



**VHF air-ground and air-air Digital Link (VDL)  
Mode 4 radio equipment;  
Technical characteristics and methods of measurement  
for aeronautical mobile (airborne) equipment;  
Part 1: Physical layer**

---

Reference

REN/AERO-00019-1

---

Keywords

aeronautical, digital, radio, testing, VHF

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD  
(Standards.iteh.org)  
Full standard:  
<http://standards.iteh.org/catalog/standards/sist/etsi-en-302-842-1-v1.3.1-2015-04>

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaircor/ETSI\\_support.asp](http://portal.etsi.org/chaircor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction .....	7
1    Scope .....	8
2    References .....	9
2.1    Normative references .....	9
2.2    Informative references.....	10
3    Definitions and abbreviations.....	11
3.1    Definitions .....	11
3.1.1    Basic reference model definitions.....	11
3.1.2    Service conventions definitions .....	11
3.1.3    General definitions.....	11
3.2    Abbreviations .....	15
4    General description and architecture of VDL Mode 4.....	16
4.1    General .....	16
5    VDL mode 4 physical layer functional specifications.....	16
5.1    Overview .....	16
5.1.1    Functions .....	17
5.1.2    Data reception.....	17
5.1.3    Data transmission.....	17
5.2    Modulation scheme .....	17
6    VDL Mode 4 equipment requirements.....	17
6.1    Receiver requirements .....	17
6.1.1    Receiver operating range .....	17
6.1.2    BER requirement .....	18
6.1.3    Reference signal level.....	18
6.1.4    Sensitivity .....	18
6.1.5    Adjacent channel rejection.....	18
6.1.6    Receiver performance in the presence of strong signals inside the VHF aeronautical band.....	19
6.1.7    Receiver performance in the presence of strong signals outside the VHF aeronautical band.....	19
6.1.8    Desired signal dynamic range.....	20
6.1.9    Symbol rate capture range .....	20
6.1.10    Frequency capture range .....	20
6.1.11    Doppler rate .....	20
6.1.12    Co-channel interference.....	20
6.1.13    Conducted spurious emission .....	21
6.1.14    FM broadcast intermodulation.....	21
6.1.14.1    Radio frequencies in the band 112,000 MHz to 137,000 MHz .....	21
6.1.15    In-band intermodulation .....	21
6.2    Transmitter requirements .....	22
6.2.1    Transmitter operating range.....	22
6.2.2    Channel bit rate.....	22
6.2.3    Manufacturer's declared output power.....	22
6.2.4    RF power rise time.....	22
6.2.5    RF power release time .....	23
6.2.6    Spurious emissions .....	23
6.2.7    Adjacent channel power.....	24
6.2.8    Wide-band noise .....	24
6.2.9    Load VSWR capability .....	25
6.2.10    Adjacent channel transient power.....	25

6.2.11	Frequency tolerance .....	25
6.2.12	Start of transmission .....	25
6.2.13	Structure of bursts .....	25
6.3	Transceiver requirements .....	26
6.3.1	Automatic transmitter shut-down .....	26
6.3.2	Tuning time.....	26
6.3.3	Receiver to transmitter turnaround time .....	26
6.3.4	Transmitter to receiver turnaround time .....	26
6.3.5	Short power interrupt.....	27
6.3.6	Demodulator action.....	27
6.3.7	System timing requirements .....	27
6.3.8	Reservation table stored in memory .....	27
6.3.9	Failure of associated equipment.....	27
6.3.10	Simultaneous reception.....	27
7	General design requirements .....	27
7.1	Controls and indicators.....	27
7.2	Class of emission and modulation characteristics .....	28
7.3	Warm up.....	28
7.4	Airworthiness .....	28
7.5	Intended function.....	28
7.6	Fire protection .....	28
7.7	Operation of controls.....	28
7.8	Accessibility of controls .....	28
7.9	Effects of tests .....	28
7.10	Failure of VDL Mode 4 equipment .....	28
7.11	Software management .....	29
7.12	Transceiver configuration.....	29
7.13	Provision for multiple redundant VDL4 transceivers.....	29
7.14	Reception capability .....	29
7.15	Transmission capability.....	29
7.16	Monitoring of proper operation .....	30
7.17	Power-up self test .....	30
8	Environmental test requirements .....	30
8.1	Introduction .....	30
8.2	Receiver.....	32
8.3	Transmitter .....	34
9	Detailed test procedures for the physical layer.....	36
9.1	General requirements .....	36
9.1.1	Test conditions.....	36
9.1.2	Alignment, adjustment and calibration prior to test.....	36
9.1.3	Recording of test results .....	36
9.1.4	Connected load .....	36
9.1.5	Test instrument precautions .....	36
9.1.6	Simultaneous application of two signals to the receiver input.....	37
9.1.7	Test frequencies .....	37
9.1.8	Equipment configuration .....	37
9.1.9	Detailed physical and MAC layer test procedures .....	37
9.2	Receiver.....	37
9.2.1	BER test .....	37
9.2.2	Sensitivity .....	39
9.2.3	Adjacent Channel Rejection (ACR).....	40
9.2.4	Rejection of signals in the VHF aeronautical band .....	40
9.2.5	Rejection of signals outside the VHF aeronautical band .....	41
9.2.6	Desired signal dynamic range .....	42
9.2.7	Symbol rate capture range .....	42
9.2.8	Frequency capture range .....	43
9.2.9	Doppler rate .....	43
9.2.10	Co-channel interference .....	44
9.2.11	Conducted spurious emission .....	44
9.2.12	FM broadcast intermodulation .....	45

9.2.13	In-band intermodulation .....	46
9.3	Transmitter .....	47
9.3.1	Channel bit rate .....	47
9.3.2	Manufacturer's declared output power .....	47
9.3.3	RF power rise time .....	48
9.3.4	RF power release time .....	48
9.3.5	Spurious emissions .....	49
9.3.6	Adjacent channel power .....	49
9.3.6.1	Method of measurement for the first adjacent channel .....	49
9.3.6.2	Method of measurement for the second adjacent channel .....	50
9.3.6.3	Method of measurement for the fourth adjacent channel .....	51
9.3.6.4	Alternative measurement procedure for Adjacent Channel Power (ACP) .....	52
9.3.7	Wideband noise .....	53
9.3.8	Load VSWR capability .....	54
9.3.9	Adjacent channel transient power .....	55
9.3.10	Frequency tolerance .....	56
9.4	Transceiver .....	56
9.4.1	Tuning time .....	56
9.4.2	Receiver to transmitter turn-around time .....	56
9.4.3	Transmitter to receiver turn-around time .....	57
10	Installed equipment requirements .....	57
10.1	Introduction .....	57
10.2	Equipment installation .....	57
10.2.1	Aircraft environment .....	57
10.2.2	Failure protection .....	57
10.2.3	Aircraft power source .....	58
10.3	Installed equipment performance requirements .....	58
10.3.1	Dynamic response .....	58
10.3.2	Interference effects .....	58
10.3.3	Regular maintenance .....	58
10.4	Conditions of test .....	58
10.4.1	Power input .....	58
10.4.2	Associated equipment or systems .....	58
10.4.3	Environment .....	58
10.5	Test procedures for installed equipment performance .....	59
10.5.1	Ground test procedures .....	59
10.5.1.1	Conformity inspection .....	59
10.5.1.2	Interference tests .....	59
10.5.1.3	Power supply fluctuation test .....	59
10.5.1.4	Reception .....	59
10.5.1.5	Transmission .....	59
10.5.1.6	Functional behaviour tests .....	60
10.5.1.7	Interface conformance tests .....	60
10.5.2	Flight test procedures .....	60
10.5.2.1	Interference effects .....	60
10.5.2.2	System performance .....	61
<b>Annex A (informative):</b>	<b>Cross reference matrix .....</b>	<b>62</b>
<b>Annex B (informative):</b>	<b>VDL Mode 4 link budget .....</b>	<b>65</b>
<b>Annex C (informative):</b>	<b>Bibliography .....</b>	<b>73</b>
History .....	74	

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Aeronautics (AERO), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 1 of a multi-part deliverable covering the VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment, as identified below:

**Part 1: "Physical layer";**

Part 2: "General description and data link layer";

Part 3: "Additional broadcast aspects";

Part 4: "Point-to-point functions".

The present document is accompanied by an equivalent ground-based standard, ETSI EN 301 842 [i.7] parts 1 to 5, covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment.

**NOTE:** Minimum Operational Performance Specifications (MOPS) are also being developed for VDL Mode 4. EUROCAE have previously published Interim MOPS for VDL Mode 4 [i.2] which are a sub set of ETSI EN 302 842-1 (the present document), ETSI EN 302 842- 2 [7], ETSI EN 302 842-3 [8] and ETSI EN 302 842-4 [9]. ETSI EN 302 842-1 (the present document), ETSI EN 302 842-2 [7], ETSI EN 302 842-3 [8] and ETSI EN 302 842-4 [9] comply with the requirements of CEC Mandate M/318 [i.3].

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 112,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [2].

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it may be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority.

iTeh STANDARD PREVIEW  
(Standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/1e9209f4-c567-4b5e-ab67-fad8437035c2/etsi-en-302-842-1-v1.3.1-2015-04>

---

# 1 Scope

The present document applies to the following radio equipment types:

- Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 112,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [2].

The present technical document provides part 1 of the technical specifications.

The present document is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VDL SARPs [2] and ICAO VDL4 Technical Manual [1].

Manufacturers should note that in future the tuning range for the transmitter and receiver may cover any 25 kHz channel from 108,000 MHz to 111,975 MHz.

The present document applies to "aeronautical mobile (airborne and in some cases ground vehicles)" equipment which will hereinafter be referred to as "mobile" equipment.

The scope of the present document is limited to mobile stations. The equivalent specification for ground stations is ETSI EN 301 842 [i.7].

The VDL Mode 4 system provides digital communication exchanges between aircraft and ground-based systems and other aircraft supporting surveillance and communication applications. The supported modes of communication include:

- broadcast and point-to-point communication;
- broadcast services including Automatic Dependent Surveillance - Broadcast (ADS-B), Traffic Information Service - Broadcast (TIS-B) and Flight Information Service - Broadcast (FIS-B) capabilities;
- air-air and ground-air services;
- operation without ground infrastructure.

The present document is derived from the specifications:

- ICAO VDL4 Technical Manual [1] and ICAO VDL SARPs [2] produced under the auspices of the International Civil Aviation Organization (ICAO).
- Other relevant standards as defined in clause 2.

It is envisaged that manufacturers may provide equipment supporting:

- broadcast services only;
- point-to-point services only;
- both broadcast and point-to-point services.

The present document deals with tests of the physical layer necessary to support all types of equipment.

The present document is organized as follows:

- clause 2 provides references to relevant documents;
- clause 3 provides general definitions, abbreviations and symbols used;
- clause 4 provides a general description and architecture of VDL Mode 4;
- clause 5 provides functional specifications applicable to the physical layer including transmitter/receiver requirements and the modulation scheme;

- clause 6 provides VDL Mode 4 equipment requirements;
- clause 7 provides general design requirements;
- clause 8 provides environmental test requirements;
- clause 9 provides detailed test procedures for the physical layer;
- clause 10 provides installed equipment requirements;
- annex A provides a detailed cross-reference to the relevant requirements contained in reference [1];
- annex B provides an assessment of VDL Mode 4 Link Budget;
- annex C provides a Bibliography;

The full physical layer tests are provided which correspond closely to the standard set of tests used for other VDL systems.

NOTE: Flight tests are defined in ETSI EN 302 842-2 [7].

#### **Mandating and recommendation phrases**

- a) "Shall"
  - The use of the word "Shall" indicates a mandated criterion; e.g. compliance with the particular procedure or specification is mandatory and no alternative may be applied.
- b) "Should"
  - The use of the word "Should" (and phrases such as "It is recommended that...", etc.) indicate that though the procedure or criterion is regarded as the preferred option, alternative procedures, specifications or criteria may be applied, provided that the manufacturer, installer or tester can provide information or data to adequately support and justify the alternative.

---

## **2 References**

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### **2.1 Normative references**

The following referenced documents are necessary for the application of the present document.

- [1] ICAO Doc 9816 (First Edition 2004): "Manual on VHF Digital Link (VDL) Mode 4, Part 2: Detailed Technical Specifications".
- [2] ICAO Annex 10 to the Convention on International Civil Aviation: "Aeronautical Telecommunications, Volume III: Communication Systems, Part I: Digital Data Communication Systems, chapter 6", including Amendment 88 (applicable 14/11/13).
- [3] ISO/IEC 7498-1 (1994): "Information technology -- Open Systems Interconnection -- Basic Reference Model: The Basic Model".
- [4] ISO/IEC 10731 (1994): "Information technology -- Open Systems Interconnection -- Basic Reference Model -- Conventions for the definition of OSI services".

- [5] EUROCAE ED-12C/RTCA DO-178C: "Software Considerations in Airborne Systems and Equipment Certification", January 2012.
- [6] EUROCAE ED-14G/RTCA DO-160G: "Environmental Conditions and Test Procedures for Airborne Equipment", May 2011.
- [7] ETSI EN 302 842-2 (V1.4.0): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 2: General Description and data link layer".
- [8] ETSI EN 302 842-3 (V1.4.0): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 3: Additional broadcast aspects".
- [9] ETSI EN 302 842-4 (V1.3.0): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 4: Point-to-point functions".

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- [i.2] EUROCAE ED-108A: "MOPS for VDL Mode 4 Aircraft Transceiver for ADS-B", October 2005.
- [i.3] CEC Mandate M/318: "Mandate to CEN/CENELEC/ETSI for standardisation in the field of air traffic management systems and Galileo local components".
- [i.4] EASA CS-25: "Large Aeroplanes" Appendix F (previously Joint Airworthiness Requirements (JAR), Part 25).
- [i.5] EUROCAE ED-23C: "MOPS for airborne VHF receiver - transmitter operating in the frequency range 117.975-137.000 MHz".
- [i.6] RTCA DO-224C: "Signal-in-Space Minimum Aviation System Performance Standards (MASPS) for Advanced VHF Digital Data Communications Including Compatibility with Digital Voice Techniques".
- [i.7] ETSI EN 301 842 (all parts): "VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment".
- [i.8] ITU Radio Regulations. (2012).
- [i.9] Agilent Application Note (AN 1303): "Spectrum Analyser Measurements and Noise", 11th February 2003.
- [i.10] TIA/EIA/TSB-88-A (1999): "Performance in Noise and Interference-Limited Situations - Recommended Methods for Technology-Independent Modeling, Simulation, and Verification".

## 3 Definitions and abbreviations

### 3.1 Definitions

#### 3.1.1 Basic reference model definitions

The present document is based on the concepts developed in the open systems interconnect basic reference model and makes use of the following terms defined in ISO/IEC 7498-1 [3]:

- layer;
- sublayer;
- entity;
- service;
- service access point;
- service data unit;
- physical layer;
- data link layer.

#### 3.1.2 Service conventions definitions

The present document makes use of the following terms defined in ISO/IEC 10731 [4]:

- service provider;
- service user;
- service primitive;
- request;
- indication;
- confirm.

#### 3.1.3 General definitions

For the purposes of the present document, the following terms and definitions apply:

**adjacent channel power:** amount of the modulated rf signal power which falls within a given adjacent channel

NOTE: Adjacent channel power includes discrete spurious, signal sidebands, and noise density (including phase noise) at the transmitter output.

**Adjacent Channel Rejection (ACR):** receiver's ability to demodulate the desired signal and meet the BER requirement in the presence of an interfering signal in an adjacent channel

NOTE: The ratio (in dB) between the adjacent interfering signal level and the desired signal level necessary to achieve the specified minimum BER, is the adjacent channel rejection (ACR) ratio.

**Aeronautical Mobile Service (AMS):** mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

**Aeronautical Telecommunication Network (ATN):** internetwork architecture that allows ground, air/ground, and aircraft data subnetworks to interoperate by adopting common interface services and protocols based on the International Organization for Standardization Open Systems Interconnection Reference Model

**aircraft address:** unique combination of 24 bits available for assignment to an aircraft for the purpose of communications, navigation and surveillance

NOTE: An aircraft may choose not to use this unique address and can use instead a non-unique address.

**Automatic Dependent Surveillance-Broadcast (ADS-B):** surveillance application transmitting parameters, such as position, track and ground speed, via a broadcast mode digital link for use by any air and ground users requiring it

NOTE: ADS-B is a surveillance service based on aircraft self-determination of position/velocity/time and automatic, periodic or random, broadcast of this information along with auxiliary data such as aircraft identity (ID), communications control parameters, etc. ADS-B is intended to support multiple high-level applications and associated services such as cockpit display of traffic information, traffic alert and collision avoidance functionality, enhanced traffic management in the air and on the ground, search and rescue support and others.

**autotune function:** function, performed by the Link Management Entity, that allows a ground VDL Mode 4 station to command an aircraft to change the operating characteristics of synchronization burst transmissions

**Bit Error Rate (BER):** ratio between the number of erroneous bits received and the total number of bits transmitted

**burst length:** number of slots across which the VDL Mode 4 burst is transmitted

**Co-Channel Interference (CCI):** capability of a receiver to demodulate the desired signal and achieve the minimum specified BER performance in the presence of an unwanted signal at the same assigned frequency

NOTE: The ratio (in dB) between the wanted signal level and the unwanted signal level is the co-channel interference ratio. The co-channel interference ratio has a major impact on frequency re-use planning criteria.

**conducted measurements:** measurements which are made using a direct rf connection to the equipment under test

**current slot:** slot in which a received transmission begins

**Data Link Entity (DLE):** protocol state machine capable of setting up and managing a single data link connection

**Data Link Service (DLS) sublayer:** sublayer that resides above the VDL Mode 4 Specific Services (VSS) and the MAC sublayers

NOTE: The data link service (DLS) manages the transmit queue, creates and destroys data link entities (DLEs) for connection-oriented communications, provides facilities for the link management entity (LME) to manage the DLS, and provides facilities for connection-less communications.

**data rate:** Mode 4 nominal data rate is 19 200 bits/s

**delayed burst:** VDL Mode 4 burst that begins sufficiently after the beginning of a slot so that the transmitting VDL Mode 4 station is confident that no other VDL Mode 4 station that it could receive from and is within the guard range is transmitting in the slot

NOTE: The delayed VDL Mode 4 burst terminates by the end of the slot in which it began (its length is shortened to ensure completion by the nominal time).

**DLS system:** VDL system that implements the DLS and subnetwork protocols to carry Aeronautical Telecommunication Network (ATN) or other packets

**frame:** link layer frame is composed of a sequence of address, control, information and FCS fields, bracketed by opening and closing flag sequences

NOTE: A valid frame is at least 11 octets in length and contains an address field (8 octets), a link control field (1 octet) and a frame check sequence (2 octets). A frame may or may not include a variable-length information field.

**Global Signalling Channel (GSC):** channel available on a world wide basis which provides for communication control

**ground base station:** aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

**ground station coordination:** coordination of transmissions from two or more ground stations uses the UTC-minute time frame

**hand held:** radio equipment with integral batteries, designed to be hand portable and operated hand held

NOTE: Provisions may be made for external connections and temporary installation into vehicles.

**integral antenna equipment:** radio communications equipment with an antenna integrated into the equipment without the use of an external connector and considered to be part of the equipment

NOTE: An integral antenna may be internal or external to the equipment. In equipment of this type, a  $50\ \Omega$  rf connection point should be provided for test purposes.

**link:** connects a mobile DLE and a ground DLE and is uniquely specified by the combination of mobile DLS address and the ground DLS address

NOTE: A different subnetwork entity resides above every link endpoint.

**link establishment:** process by which an aircraft and a ground LME discover each other, determine to communicate with each other, decide upon the communication parameters, create a link and initialize its state before beginning communications

**link handoff:** process by which peer LMEs, already in communication with each other, create a link between an aircraft and a new ground station before disconnecting the old link between the aircraft and the current ground station

**link layer:** layer that lies immediately above the physical layer in the Open Systems Interconnection protocol model

NOTE: The link layer provides for the reliable transfer of information across the physical media. It is subdivided into the data link sublayer and the media access control sublayer.

**Link Management Entity (LME):** protocol state machine capable of acquiring, establishing, and maintaining a connection to a single peer system

NOTE: An LME establishes data link and subnetwork connections, "hands-off" those connections, and manages the media access control sublayer and physical layer. An aircraft LME tracks how well it can communicate with the ground stations of a single ground system. An aircraft VDL management entity (VME) instantiates an LME for each ground station that it monitors. Similarly, the ground VME instantiates an LME for each aircraft that it monitors. An LME is deleted when communication with the peer system is no longer viable.

**Media Access Control (MAC):** sublayer that acquires the data path and controls the movement of bits over the data path

**mobile:** radio equipment designed for installation into vehicles

**non-integral antenna equipment:** radio communications equipment with a connector intended for connection to an antenna

**physical layer:** lowest level layer in the Open Systems Interconnection (OSI) protocol model

NOTE: The physical layer is concerned with only the transmission of binary information over the physical medium (e.g. VHF radio).

**primary time source:** normal operation timing mode in which a VDL Mode 4 station maintains time synchronization to Universal Coordinated Time (UTC) second to within a two-sigma value of 400 ns

**private parameters:** parameters that are contained in CTRL and UCTRL DLPDUs and that are unique to the VHF digital link environment

**radiated measurements:** measurements which involve the measurement of a radiated field

**reference bit sequence:** sequence of bits used in the transmitter performance specifications

**reference signal level:** signal level used in the receiver performance specifications except otherwise stated